



**HEARINGS EXAMINER MEETING AGENDA**  
**Thursday, October 18, 2018, 5:00 PM**  
**City Hall, 616 NE 4th Avenue**

---

**I. CALL TO ORDER**

**II. INTRODUCTION AND INSTRUCTIONS**

**III. HEARING ITEM**

Valley View Estates Subdivision Preliminary Plat Application Public Hearing (File No. SUB18-02)

Presenter: Lauren Hollenbeck, Senior Planner

- 
- [1-Application](#)
  - [2-Narrative](#)
  - [3-Preliminary Plans May 18, 2018](#)
  - [4-Updated Preliminary Development Plans June 25, 2018](#)
  - [5-GIS Packet with Vicinity Map](#)
  - [6-Notice of Development Sign](#)
  - [7-SEPA Checklist](#)
  - [8-300 Foot Assessors Map, Mailing List and Labels](#)
  - [9-Pre-Application Report](#)
  - [10-Breckenridge Trail](#)
  - [11-Stormwater Plan](#)
  - [12-Stormwater Report](#)
  - [13-Geotechnical Report](#)
  - [14-Revised Geotechnical Report](#)
  - [15-EEI Geotechnical Peer Review #1](#)
  - [16-EEI Geotechnical Peer Review #2](#)
  - [17-Traffic Study](#)
  - [18-Environmental Report](#)
  - [19-Tribal Certified Mailings](#)
  - [20-Notice of Application](#)
  - [21-Incompleteness Review Letter](#)
  - [22-Completeness Review Letter](#)
  - [23-City Review Letter](#)
  - [24-Notice of Public Hearing](#)
  - [25-MDNS Cover Letter SEPA18-15](#)
  - [26-MDNS Determination SEPA18-15](#)
  - [27-Wetland Determination Report October 18, 2007](#)
  - [28-Revised Preliminary Plat October 9, 2018](#)
  - [29-Valley View Estates Subdivision Staff Report SUB18-02](#)
  - [30-Kris Good Comment Letter](#)
  - [Index of Exhibits](#)

#### **IV. ADJOURNMENT**

#### **V. LAND USE DECISION**

NOTE: The City of Camas welcomes and encourages the participation of all of its citizens in the public meeting process. A special effort will be made to ensure that persons with special needs have opportunities to participate. For more information, please call the City Clerk's Office at 360.817.1591.



Community Development Department | Planning  
 616 NE Fourth Avenue | Camas, WA 98607  
 (360) 817-1568  
[communitydevelopment@cityofcamas.us](mailto:communitydevelopment@cityofcamas.us)

General Application Form

Case Number:

Applicant Information

Applicant/Contact: Sterling Design, Inc./Joel Stirling Phone: ( 360 ) 759-1794  
 Address: 2208 E. Evergreen Blvd. Mail@SterlingDesign.biz  
Street Address E-mail Address  
Vancouver WA 98661  
City State ZIP Code

Property Information

Property Address: 20109 SE 40th Street 125646-000 & 125635-000  
Street Address County Assessor # / Parcel #  
Camas WA 98666  
City State ZIP Code  
 Zoning District R-7.5 Site Size 9.26 acres

Description of Project

Brief description: Preliminary Subdivision application to subdivide 9.26 acres into 36 residential lots.

Are you requesting a consolidated review per CMC 18.55.020(B)? YES  NO   
 Permits Requested:  Type I  Type II  Type III  Type IV, BOA, Other

Property Owner or Contract Purchaser

Owner's Name: Firestone Stan Phone: ( 360 ) 772-3445  
Last First  
 Address: PO Box 61928  
Street Address Apartment/Unit #  
 E mail Address: Vancouver WA 98666  
City State Zip

Signature

I authorize the applicant to make this application. Further, I grant permission for city staff to conduct site inspections of the property.

Signature:  Date: 5/17/2018

Note: If multiple property owners are party to the application, an additional application form must be signed by each owner. If it is impractical to obtain a property owner signature, then a letter of authorization from the owner is required.

Date Submitted: <u>5/18/18</u>	Pre-Application Date:	Paid ✓ 5/18/18 \$17,714.00 AB Validation of Fees
Staff:	Related Cases #	
		<input type="checkbox"/> Electronic Copy Submitted

### Project Narrative:

The "Valley View Estates" Subdivision proposal is to subdivide two parcels of land, serial number(s): 125646-000 and 125635-00, located in the NE ¼ quarter of Section 8, Township 1 North, Range 3 East of the Willamette Meridian, Clark County, Washington into 36 single family residential lots utilizing the R-7.5 zone development standards with the Density Transfer design subsection. The site area is approximately 9.2 acres and currently has one (1) single family home on it. The single-family home will be removed as part of the development process. The property topography slopes moderately from the Northeastern property corner down to the Southwestern property corner and currently has field grass with black berry bushes.

The site is zoned R-7.5 and the comprehensive plan designation for the site is SFM. There are no sensitive lands located on the property and none were located within 100' from the property on adjacent properties as was field verified by Ecological Land Services, Inc.

CMC18.09.040 - Table 2 shows the Lot Requirements for properties within the R1-7.5 zoning district:

18.09.040 Table 2—Density and dimensions—Single-family residential zones.

#### Density and Dimensions for Single-family Residential Zones<sup>1</sup>

	R-5	R-6	R-7.5	R-10	R-12	R-15	R-20
<b>A. Standard New Lots</b>							
Maximum density (dwelling units/gross acre)	8.7	7.2	5.8	4.3	3.6	2.9	2.1
Average lot area (square feet) <sup>5</sup>	5,000	6,000	7,500	10,000	12,000	15,000	20,000
Minimum lot size (square feet)	4,000	4,800	6,000	8,000	9,600	12,000	16,000
Maximum lot size (square feet) <sup>4</sup>	6,000	7,200	9,000	12,000	14,400	18,000	24,000
Minimum lot width (feet)	50	60	70	80	90	100	100
Minimum lot depth (feet)	80	90	90	100	100	100	100
Maximum building lot coverage	45%	40%	40%	35%	30%	30%	30%
Maximum building height (feet) <sup>3</sup>	35	35	35	35	35	35	35
<b>B. Density Transfer Lots<sup>1</sup></b>							
Maximum density (dwelling units/gross acre)	8.7	7.2	5.8	4.3	3.6	2.9	2.1
Minimum lot size (square feet)	3,500	4,200	5,250	7,000	8,400	10,500	14,000
Maximum lot size (square feet) <sup>4</sup>	6,000	7,200	9,000	12,000	14,400	18,000	24,000

Minimum lot width (feet) <sup>1</sup>	40	50	60	60	70	80	90
Minimum lot depth (feet) <sup>1</sup>	80	80	80	90	90	100	100
Maximum building lot coverage	45%	40%	40%	40%	35%	35%	30%
Maximum building height (feet) <sup>3</sup>	35	35	35	35	35	35	35
<b>C. Setbacks based on average lot sizes (not zone specific)<sup>2</sup></b>	Up to 4,999 sq. ft.	5,000 to 7,499 sq. ft.	7,500 to 9,999 sq. ft.	10,000 to 11,999 sq. ft.	12,000 to 14,999 sq. ft.	15,000 to 19,999 sq. ft.	20,000 or more sq. ft.
Minimum front yard (feet)	15	20	20	20	25	30	30
Minimum side yard and corner lot rear yard (feet)	5	5	5	5	10	15	15
Minimum side yard flanking a street (feet)	15	20	20	20	25	30	30
Minimum rear yard (feet)	20	25	25	25	30	35	35
Minimum lot frontage on a cul-de-sac or curve (feet)	25	30	30				

**The proposed plat has been designed in accordance with CMC18.09.040 Table 2(B.) Density Transfer Lots, as allowed within CMC18.09.080(B.) due to the requirement for a Public Trail (T-21) to be extended through the Project.**

The proposed lots all exceed the minimum requirements of the R-7.5 zone, utilizing CMC18.09.040 Table 2(B.). The minimum lot size is 5,900 sq.ft.; the maximum lot size is 9,000 sq.ft. and the average lot area is 7,087 sq.ft. The total property area is 9.2 acres and the maximum density allowed for the property at 5.8 units/acre is 53 lots.

The site is located to the north of the recently constructed "Breckenridge" subdivision near the intersection of SE 202nd Avenue with NW 18th Street. The project is bordered to the East by the existing "Knight Point At Prune Hill" subdivision, to the West by the existing "Winchester Hills Phase 1" subdivision, to the South by the "Breckenridge" subdivision and to the North by SE 40th Street, a public road.

During the preparation of the Type 3 Subdivision Application materials several site studies were performed on the property to assure that the project is feasible and the reports from these studies are included within the application packet. A site geotechnical study was performed by Rapid Soil Solutions, a traffic study was performed by H. Lee and Associates, a wetland determination was performed by Ecological Land Services, Inc. and an archaeological predetermination was performed by Archaeological Services of Clark County. As mentioned previously, all reports are included within the application packet.

**CMC17.11.030.D (1 – 10):**

Criteria for Preliminary Plat Approval. The hearings examiner decision on an application for preliminary plat approval shall be based on the following criteria:

1. The proposed subdivision is in conformance with the Camas comprehensive plan, parks and open space comprehensive plan, neighborhood traffic management plan, and any other city adopted plans;

***The proposed Valley View Estates Subdivision is in substantial conformance with the Camas Comprehensive Plans, Parks and Open Space Comprehensive Plan, Neighborhood Traffic Management Plan, and all other City Adopted Plans.***

2. Provisions have been made for water, storm drainage, erosion control and sanitary sewage disposal for the subdivision that are consistent with current standards and plans as adopted in the Camas Design Standard Manual;

***Provisions have been made for water, storm drainage, erosion control and sanitary sewage disposal for the subdivision and they are consistent with the current standards and plans as adopted in the Camas Design Standard Manual.***

3. Provisions have been made for road, utilities, street lighting, street trees and other improvements that are consistent with the six-year street plan, the Camas Design Standard Manual and other state adopted standards and plans;

***Roads, Utilities, Street Lighting, Street Trees and other required project improvements are consistent with the six-year street plan, the Camas Design Standard Manual and other State Adopted Standards and Plans are included herein.***

4. Provisions have been made for dedications, easements and reservations;

***Dedications and easements are designed into the project as required.***

5. The design, shape and orientation of the proposed lots are appropriate to the proposed use;

***The design, shape and orientation of the proposed lots are appropriate to the proposed use.***

6. The subdivision complies with the relevant requirements of the Camas land development and zoning codes, and all other relevant local regulations;

***The subdivision complies with the relevant requirements of the Camas land development and zoning codes, and all other relevant local regulations.***

7. Appropriate provisions are made to address all impacts identified by the transportation impact study;

***There are no offsite improvements proposed as part of the project since none were identified as needed within the Transportation Impact Study.***

8. Appropriate provisions for maintenance of commonly owned private facilities have been made;

***All commonly owned private facilities will be owned and maintained by a Home Owners Association (HOA) that will be formed and put in place to assure perpetual ownership and maintenance of all private facilities within the project.***

9. Appropriate provisions, in accordance with RCW 58.17.110, are made for:
  - a. The public health, safety, and general welfare and for such open spaces, drainage ways, streets, or roads, alleys or other public ways, transit stops, potable water supplies, sanitary wastes, parks and recreation, playgrounds, schools and school grounds and all other relevant facts, including sidewalks and other planning features that assure safe conditions at schools bus shelter/stops, and for students who walk to and from school, and
  - b. The public use and interest will be served by the platting of such subdivision and dedication;

***Provisions are made for public health, safety, and general welfare for open spaces, drainage ways, streets, roads, potable water supplies, sanitary wastes, parks and recreations, including sidewalks and other planning features that assure safe conditions at school bus shelter/stops, and for students who walk to and from school. The public use and interest will be served by the platting of such subdivision and dedication.***

10. The application and plans shall be consistent with the applicable regulations of the adopted comprehensive plans, shoreline master plan, state and local environmental acts and ordinances in accordance with RCW 36.70B.030.

***The Valley View Estates Subdivision has been designed to be consistent with the applicable regulations of the comprehensive plans, shoreline master plan, state and local environmental acts and ordinances in accordance with RCW 36.70B.030.***

A pre-application conference was held for the project on January 18, 2018 to review the proposed development and the report issued by the City of Camas is included herein. The specific issues discussed in the conference are addressed further on within this document.

**STERLING DESIGN, INC.** has prepared a Preliminary Plat for the project along with a Preliminary Utility Plan, Grading & Erosion Control Plan, Preliminary Transportation Plan, and a Preliminary Stormwater Plan with Technical Information Report demonstrating that the project is feasible. Water Quantity and Quality control for the new drainage from the required infrastructure and future home sites will be managed onsite within privately owned and maintained stormwater facilities that will be constructed at the time of infrastructure installation. As part of the recent infrastructure improvements that were installed with the "Breckenridge" subdivision, two (2) 18" storm conveyance systems were extended to the Southern property line of the Valley View Estates property. All stormwater from the project will be conveyed to these conveyance systems following water quality and water quantity control as required by City of Camas development code CMC14.02 and the SMMWW standards from Washington Department of Ecology.

The site currently has public road access from NW 18th Street on the Northern boundary and to SE 202nd Avenue from the South. There is a project that is being constructed to the south and west of the property that will be extending a Public Road to the southwest corner for extension. All roads accessing the property are a minimum of 20' wide paved roads and there are no offsite road improvements needed to serve the project. New Public Roads will be extended through the project to connect SE 202nd Avenue to SE 40th Street and to provide access the proposed single-family lots. Sight distance has been verified at all proposed intersections.

Public sanitary sewer facilities were extended to the property as part of the "Breckenridge" subdivision and each new lot will be provided via a 4" sanitary sewer lateral that is connected into the Public Sanitary Sewer system owned and operated by the City of Camas.

Public water facilities are available on both the Northern and Southern property boundaries. Public water will be provided to each new lot via a water service connection to the Public Water system owned and operated by City of Camas

There are fire hydrants near the property both on the Northern and Southern boundaries, however, new hydrants will be installed as required to meet the spacing requirements of the City of Camas Fire Marshall. Since the project is proposing to utilize a 28-foot-wide paved Public Road section for access to the future home sites, all new homes will utilize residential fire suppressant sprinkler systems.

All newly constructed homes located on the site will be required to pay park, school and traffic impact fees at the time of building permit issuance. These fees are collected to ensure that adequate facilities are available to serve new growth and development; promote orderly growth and development by requiring that new development pay a proportionate share of the cost of new established procedures and criteria so that specific developments do not pay arbitrary fees or duplicate fees for the same impact.

The development of this site into 36 single family home sites that meet the dimensional and area requirements of the Density Transfer Section of the R-7.5 zone, will aid in meeting the zoning and comprehensive plan goals for the area. The development of this site will improve public road and utility access to the area. The full build out of this development will provide housing consistent with the goals of the Growth Management Act and will provide housing that is compatible with the existing housing types located in the vicinity.

### **Specific Items as addressed in the Pre-Application Conference Report:**

#### **Planning:**

- (1.) The required application fee has been paid for the project application.
- (2.) A SEPA Checklist has been prepared for the project and is included herein.
- (3.) Land Use Application materials have been prepared utilizing the requirements found in the City of Camas Development Code along with the specific comments from the Pre-Application Conference Report.



- (4.) A Vicinity Map Showing the Location of the Site is included herein.
- (5.) There are a few small scraggly trees scattered on the property but no Significant Trees are located on the property as defined in CMC 18.31.080.
- (6.) Existing conditions are shown within the Preliminary Development Plans.
- (7.) A Preliminary Grading Plan is included within the Preliminary Development Plans.
- (8.) A Preliminary Stormwater Plan and Report are included within the Application Materials.
- (9.) A Geotechnical Report is included within the Land Use Application Materials.
- (10.) A Clark County Assessor's Map of Properties within 300 feet is included.
- (11.) Mailing Labels as required by CMC 18.55.110 are provided.
- (12.) A Traffic Study is included within the Land Use Application Materials.
- (13.) All Open Spaces and Tract's will be owned and maintained by the HOA.
- (14.) The required Development Sign has been ordered for installation.
- (15.) 3 Copies and an Electronic Copy of the Land Use Application is provided.

**Preliminary Plat Review**

- (1.) The T-21 Trail will be set aside within a tract as required for Density Transfer.
- (2.) A 10-foot-wide Landscape Tract has been placed along the northerly edge of Lot(s) 1 - 4 as required to address "double frontage" Lot(s).
- (3.) All Lot(s) will accommodate a minimum 40' x 40' Building Envelope. Building Envelopes are shown for all Lot(s) but only the smallest Lot(s) show the 40' x 40' Footprint.
- (4.) All Lot Frontages on a curve are a minimum of 30 feet.
- (5.) All Lot areas have been adjusted as required by the Pre-application Conference Report.
- (6.) As required, eight (8) "off street" parking spaces are provided as shown.
- (7.) A Circulation Plan is included within the Land Use Application Materials as required.
- (8.) Future Retaining Walls are shown on the Preliminary Grading Plan as required.

**Engineering:**

- (1.) Construction Plans will be prepared by a licensed Washington State Engineer.
- (2.) Plan review and inspection fees will be paid at the time of Final Construction Plan Submittal.
- (3.) Construction of project infrastructure will be completed per CMC 17.19.020.
- (4.) Final Platting will be completed as required by City of Camas Development Code.
- (5.) All existing wells and septic systems will be abandoned as required.
- (6.) Street improvements to NW 18<sup>th</sup> Street are designed to the ST5 Standard, including a center turn lane.
- (7.) Street rights-of-way meet the criteria of CMC 17.19.040(B.), Table 17.19.040-2(C.).
- (8.) Sidewalk and fencing along NW 18<sup>th</sup> meets the Camas Design Standards.
- (9.) All improvements will blend with the Camas School District PBL Project at the time of construction. It is anticipated that both projects will construct the NW 18<sup>th</sup> Road improvements during the summer of 2018.
- (10.) As stated in number 8, sidewalk and fencing along NW 18<sup>th</sup> meets the Camas Design Standards. It is impossible to have both a sidewalk and a multi-mobile access in the same location.
- (11.) Tracts for home access meet the Minimum Private Street Standards.
- (12.) A Traffic Study is included within the Land Use Application Materials.
- (13.) This is no longer applicable now that all lots access from the internal street network.
- (14.) The proposed intersection with NW 18<sup>th</sup> Street is designed to meet the intersection spacing standards and is 333 feet from the intersection to the west.
- (15.) NW 18<sup>th</sup> Street is designed with a center turn lane instead of a raised median which will allow for left turn movements into the proposed Valley View Estates Development.
- (16.) Uniform fencing and landscaping will be installed along NW 18<sup>th</sup>.
- (17.) ADA compliant street crossings will be installed as required.
- (18.) A right deceleration lane is not needed based on the Traffic Study.

- (19.) Traffic signs, street names, pavement markings and street lighting will be installed as required by City of Camas Standards.
- (20.) A utility plan will be provided as required prior to approval of the infrastructure construction drawings.
- (21.) A road connection is being provided to the southwesterly corner of the project to connect to the Vancouver Riverview Gateway Subarea.
- (22.) Streets will be named to reflect Camas addresses.
- (23.) Stormwater Management is in accordance with the Western Washington and City of Camas Stormwater Design Standards Manual.
- (24.) Stormwater facilities will be located and landscaped as required.
- (25.) Stormwater facilities are designed as required by City of Camas standards.
- (26.) Stormwater facilities will be Privately Owned and Maintained by the future HOA.
- (27.) All contributing stormwater will be collected and conveyed through the project as required. Flow calculations will be provided to assure that flow rates following installation of the stormwater facilities will be equal to, or less than, pre-developed flow rates.
- (28.) Public water system will be extended through the project.
- (29.) Public sanitary sewer system will be extended through the project.
- (30.) The existing 8" STEF sanitary sewer system will be utilized.
- (31.) A sewer basin analysis will be completed prior to approval of the infrastructure construction drawings.
- (32.) Community mailboxes will be coordinated with the Postmaster and City of Camas prior to installation.
- (33.) Garbage and recycling containers will be placed at the public right-of-way.

#### Building Division

All Building Division Comments will be addressed at the time of home construction

#### Fire Department

All Fire Department Comments are addressed within the Land Use Application Materials or will be completed with the future home construction.

Applications submitted for this project:



- Subdivision Type III
- SEPA Checklist
- Archeological review
- Critical area review
- Fire department review

Please review the enclosed data and contact us as soon as possible if you have any questions or need any additional data.

Thank you for your assistance,




Joel G. Stirling, P.E.  
**STERLING DESIGN, INC.**



# VALLEY VIEW ESTATES

A Preliminary Subdivision  
within in a portion of the  
NE 1/4 of Sec. 8,  
T1N., R3E., W.M.  
Clark County, Washington



VICINITY MAP (NTS)

**LEGEND**

- CURB & SIDEWALK
- PROPOSED EASEMENT
- PROPOSED LOT LINE
- - - EXISTING RIGHT-OF-WAY
- PROPOSED SANITARY SEWER LINE
- PROPOSED STORM SEWER LINE
- PROPOSED PERFORATED STORM LINE
- PROPOSED ROADWAY CENTERLINE
- EXISTING ELECTRIC
- EXISTING TELEPHONE LOCATE PAINT
- EXISTING WATER LOCATE PAINT
- EXISTING EDGE OF PAVEMENT/GRAVEL
- EXISTING SANITARY SEWER LINE
- EXISTING STORM LINE
- EXISTING FENCE
- EXISTING GROUND CONTOUR
- PROPOSED GROUND CONTOUR (1')
- DIRECTION OF STORMWATER FLOW
- EROSION CONTROL SILT FENCE
- INLET PROTECTION
- PROPOSED SANITARY CLEANOUT
- PROPOSED FIRE HYDRANT
- STD 1" WATER METER SERVICE
- PROPOSED MANHOLE
- PROPOSED DRYWELL
- PROPOSED CATCH BASIN
- PROPOSED COMBINATION CURB INLET
- PROPOSED STORMFILTER
- EXISTING POWER POLE WITH NUMBER AND DIRECTION OF OVERHEAD LINES
- EXISTING GUY ANCHOR
- EXISTING TELEPHONE PEDESTAL
- EXISTING STORM DRAIN MANHOLE
- EXISTING CATCH BASIN
- EXISTING ADA RAMP
- EXISTING ELECTRICAL SERVICE BOX
- EXISTING SANITARY MANHOLE
- EXISTING SANITARY CLEANOUT
- EXISTING FIRE HYDRANT
- EXISTING WATER SERVICE
- EXISTING WATER VALVE
- PROPOSED STREET TREES 30' O.C.
- PROPOSED STREET LIGHT 70' SPACING

**SHEET INDEX**

COVER SHEET	1
PROPOSED DEVELOPMENT PLAN	2
PRELIMINARY TOPOGRAPHIC & BOUNDARY SURVEY	3
PRELIMINARY GRADING PLAN	4
PRELIMINARY EROSION CONTROL PLAN	5
PRELIMINARY STORMWATER MANAGEMENT PLAN	6
PRELIMINARY TRANSPORTATION PLAN	7
PRELIMINARY UTILITY PLAN	8
PRELIMINARY LANDSCAPE & LIGHTING PLAN	9

**SITE DATA:**

- TAX LOT(S): 59 & 48
- SERIAL NUMBER(S): 125646-000 & 125635-000
- SITE ADDRESS: 20109 SE 40th STREET
- AREA: 9.26 ACRES
- ZONING: R-7.5
- COMPREHENSIVE PLAN: UL

STREET TREES AND STREET LIGHTING WILL BE PROVIDED AS REQUIRED BY THE CITY OF CAMAS CODE.

**CITY OF CAMAS PRE-APPLICATION NUMBER: PA18-09**

## DESIGN & DEVELOPMENT TEAM

<b>PROPERTY OWNER:</b> SIAM FIRESTONE PO BOX 61928 VANCOUVER WA, 98666 stan@firestonepacificfoods.com	<b>CIVIL ENGINEER/ LAND USE PLANNING:</b> STERLING DESIGN, INC. 401 STERLING, P.E. 2208 E. EVERGREEN BLVD. VANCOUVER, WA 98661 (360) 759-1794 FAX: (360) 759-4983 EMAIL: jpe@sterling-design.biz	<b>SURVEYOR:</b> MINISTER & GLASSER SURVEYING, INC. 2200 E. EVERGREEN BLVD. VANCOUVER WA, 98661 PHONE: (360) 694-3313 FAX: (360) 694-8410
---	---	--

**BENCH MARK:**  
W.S.D.O.T. MONUMENT "LACAMAS" @ NO. 3789  
A BRASS DISK IN CONCRETE LOCATED ON THE WESTERLY SIDEWALK OF N.E. 192nd AVE APPROXIMATELY 500 FEET NORTH OF THE INTERSECTION OF N.E. 192nd AVE AND S.E. 34th STREET. ELEVATION = 250.85', CITY OF CAMAS DATUM

**NOTE:**  
Existing utilities shown are approximate only from utility records and as visible at the site, contractor shall verify presence, location, depth & slope of any and all existing utilities prior to construction. Contact One Call Center at (800) 424-5555.

## SITE INFORMATION

<b>ALIGNMENT &amp; FIELD DATA:</b> MINISTER & GLASSER SURVEYING, INC. (360) 694-3313	<b>Scale:</b> AS SHOWN
<b>SOIL TYPE:</b> HYDROLOGIC GROUP: C	<b>ASHTO CLASSIFICATION:</b> A-4
<b>SALES LISTING BY:</b> RAPID SOIL SOLUTIONS (503) 816-3069	<b>DATE:</b> MARCH 2014
<b>SITE LOCATION:</b> CLARK COUNTY, WA	<b>APPROX. SURFACE ELEV:</b> 365'-488'
<b>SITE AREA:</b> 9.26 ACRES	<b>FILENAME:</b> 288/Preliminary.pro

PREPARED BY:  
STERLING DESIGN, INC.  
10000 150TH AVE. S.W.  
VANCOUVER, WA 98648  
TEL: (360) 759-1794  
FAX: (360) 759-4983  
www.sterlingdesign.biz


**STERLING DESIGN, INC.**

Sheet Description:  
COVER SHEET

Project:  
VALLEY VIEW ESTATES  
SUBDIVISION



Project Number: 288  
Design: JGS/BC  
Drawn:  
Drawing Date: MAY 2018  
Sheet 1 of 9 Sheet(s)



**PROPERTY BOUNDARY LEGAL DESCRIPTION(s)**

**TAX LOT 49 (ASSESSORS PARCEL NUMBER 125635-000)**  
 That parcel of land located in a portion of the Joel Knight D.L.C. No. 41 and in a portion of the Northwest Quarter of the Northwest Quarter and the Northwest Quarter of Section 8, Township 1 North, Range 3 East, Willamette Meridian, City of Camas, Clark County, Washington, described as follows:  
 BEGINNING at the Northeast corner of the Plat of "Breckenridge" as recorded in Book 311 of Plats, at Page 715, Clark County, Washington, plat records;  
 Thence South 89°29'23" East, along the North line of said Plat of "Breckenridge" for a distance of 95.97 feet;  
 Thence leaving said North line, North 04°25'46" East, parallel with the West line of the Joel Knight D.L.C. No. 41, for a distance of 62.70 feet;  
 Thence North 39°16'12" East, for a distance of 114.49 feet to the beginning of a 96.00 foot radius non-tangent curve to the left;  
 Thence along the arc of a 96.00 foot radius non-tangent curve to the right, for an arc distance of 20.15 feet, through a central angle of 12°01'29"; the radius of which bears North 39°16'12" East, the long chord of which bears North 44°43'03" West, for a chord distance of 20.11 feet;  
 Thence South 39°16'12" West, for a distance of 123.30 feet;  
 Thence North 89°29'23" West, parallel with the North line of said Plat of "Breckenridge", for a distance of 75.68 feet to the West line of the Joel Knight D.L.C. No. 41;  
 Thence South 04°25'46" West, along said West line, for a distance of 70.00 feet to the POINT OF BEGINNING;  
 CONTAINING: 9,000 square feet of land, more or less.

**TAX LOT 59 (ASSESSORS PARCEL NUMBER 125645-000)**  
 That parcel of land located in a portion of the Joel Knight D.L.C. No. 41 and in a portion of the Northwest Quarter of the Northwest Quarter and the Northwest Quarter of Section 8, Township 1 North, Range 3 East, Willamette Meridian, City of Camas, Clark County, Washington, described as follows:  
 BEGINNING at the Northeast corner of the Plat of "Breckenridge" as recorded in Book 311 of Plats, at Page 715, Clark County, Washington, plat records;  
 Thence North 89°29'23" West, along the North line of said Plat of "Breckenridge", for a distance of 335.14 feet;  
 Thence continuing along said North line, South 04°25'46" West, for a distance of 9.20 feet;  
 Thence continuing along said North line, North 89°29'23" West, for a distance of 197.07 feet;  
 Thence leaving said North line, North 04°25'46" East, for a distance of 62.70 feet;  
 Thence North 39°16'12" East, for a distance of 114.49 feet to the beginning of a 96.00 foot radius non-tangent curve to the right;  
 Thence along the arc of a 96.00 foot radius non-tangent curve to the right, for an arc distance of 20.15 feet, through a central angle of 12°01'29"; the radius of which bears North 39°16'12" East, the long chord of which bears North 44°43'03" West, for a chord distance of 20.11 feet;  
 Thence South 39°16'12" West, for a distance of 123.30 feet;  
 Thence North 89°29'23" West, for a distance of 75.68 feet to the West line of the Joel Knight D.L.C. No. 41;  
 Thence North 04°25'46" East, along the West line of said Joel Knight D.L.C. No. 41, for a distance of 659.59 feet to the South Right of Way line of SE 40th Street and the beginning of a 220.99 foot radius non-tangent curve to the left;  
 Thence leaving said West line, along said South Right of Way line, along the arc of a 220.99 foot radius non-tangent curve to the left, for an arc distance of 46.36 feet, through a central angle of 10°37'07"; the radius of which bears North 10°55'53" East, the long chord of which bears South 84°22'41" East, for a chord distance of 46.36 feet;  
 Thence continuing along said South Right of Way line, South 89°41'15" East, for a distance of 378.44 feet to the Northwest corner of Tax Lot 58, as described and recorded under Clark County, Washington, Auditor's File Number 4491958-0;  
 Thence leaving said South Right of Way line, South 04°25'46" West, along the West line of said Tax Lot 58, for a distance of 181.97 feet to the Southwest corner thereof;  
 Thence leaving said West line, South 89°41'15" East, along the South line of said Tax Lot 58, for a distance of 36.14 feet to the Northwest corner of Tax Lot 47, as described and recorded under Clark County, Washington, Auditor's File Number 4510899-0;  
 Thence leaving said South line, South 01°26'14" West, along the West line of said Tax Lot 47, for a distance of 70.01 feet to the Southwest corner thereof;  
 Thence leaving said West line, South 89°41'15" East, along the South line of said Tax Lot 47, for a distance of 128.57 feet to the Southeast

**PROPOSED DEVELOPMENT PLAN:**

**TOTAL LOTS: 36**  
**MINIMUM LOT AREA: 5,900 sq.ft.**  
**MAXIMUM LOT AREA: 9,000 sq.ft.**  
**AVERAGE LOT AREA: 7,087 sq.ft.**

TRACT PURPOSE	AREA	OWNED & MAINTAINED
TRACT 'A' - LANDSCAPE	2,268 sq ft	HOA
TRACT 'B' - ACCESS & UTILITY	1,541 sq ft	HOA
TRACT 'C' - RECREATIONAL OPEN SPACE	13,438 sq ft	CITY
TRACT 'D' - ACCESS & UTILITY	1,782 sq ft	HOA
TRACT 'E' - STORM FACILITY	22,087 sq ft	HOA
TRACT 'F' - STORM FACILITY	10,488 sq ft	HOA
TRACT 'G' - ACCESS & UTILITY	2,630 sq ft	HOA
TRACT 'H' - ACCESS & UTILITY	5,034 sq ft	HOA

**LAND INVENTORY**

TOTAL SITE AREA: 9.26 ACRES  
 TOTAL DEVELOPED ACREAGE: 7.29 ACRES  
 TOTAL LOT AREA: 5.85 ACRES  
 TOTAL INFRASTRUCTURE ACREAGE: 2.79 ACRES  
 TOTAL TRACT AREA(MINUS STORM TRACTS): 0.61 ACRES  
 TOTAL ACREAGE OF CRITICAL AREAS: NONE  
 TOTAL ACREAGE OF REC. OPENSAPCE: 0.31 ACRES

ALL PROPOSED BUILDING ENVELOPES ARE LARGE ENOUGH TO FIT A 40 FOOT x 40 FOOT BUILDING FOOT PRINT.

TABLE 18.09.040  
 MINIMUM SETBACKS:

FRONT:	20'
SIDE STREET:	20'
SIDE INTERIOR:	5'
REAR:	25'
MAX. LOT COVERAGE:	40%
MAX. BLDG. HEIGHT:	35'

**SITE INFORMATION**

ALIGNMENT & FIELD DATA: MINISTER & CLAESSER SURVEYING, INC. (360) 694-3313  
 SOIL TYPE: RAPID SOIL SOLUTIONS (603) 816-3089  
 DATE: MARCH 2014  
 SITE LOCATION: CLARK COUNTY, WA  
 SHEET: 288 / Preliminary.pro  
 Scale: AS SHOWN  
 Project Number: 288  
 Design: JGS/BC  
 Drawing Date: JUNE 2018  
 Sheet 2 of 9 Sheet(s)


NOTE:  
 Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.

PREPARED BY:  
**STERLING DESIGN, INC.**  
 10000 14TH AVENUE NW  
 SUITE 200  
 WASHINGTON, WA 98667  
 TEL: (800) 706-1784  
 FAX: (206) 706-1784  
 email: info@sterlingdesign.biz


Sheet Description:  
**PROPOSED DEVELOPMENT PLAN**

Project:  
**VALLEY VIEW ESTATES SUBDIVISION**

**TOPOGRAPHIC SURVEY**  
 OF  
 A PORTION OF THE JOEL KNIGHT D.L.C.  
 IN THE NW 1/4 OF THE NE 1/4,  
 THE SW 1/4 OF THE NE 1/4,  
 THE NE 1/4 OF THE NW 1/4  
 AND THE SE 1/4 OF THE NW 1/4  
 SECTION 8  
 T. 1 N., R. 3 E., W.M.  
 CLARK COUNTY, WASHINGTON  
 JOB NO.: 04-413 DATA COLLECT: 10-11-04, 10-12-04  
 DRAWING DATE: 04-27-18






- LEGEND:**
- INDICATES FOUND MONUMENT AS NOTED
  - ⊕ INDICATES TELEPHONE VAULT
  - ⊗ INDICATES FIRE HYDRANT
  - ⊕ INDICATES WATER VALVE
  - ⊕ INDICATES CATCH BASIN
  - ⊕ INDICATES WELL
  - ⊕ INDICATES SANITARY MANHOLE
  - - - - - INDICATES EASEMENT LINE
  - - - - - INDICATES ADJACENT LOT LINE
  - - - - - INDICATES BACK OF CURB LINE
  - - - - - INDICATES CALCULATED RIGHT-OF-WAY LINE
  - - - - - INDICATES CENTERLINE OF CREEK
  - - - - - INDICATES EDGE OF GRAVEL
  - - - - - INDICATES EDGE OF PAVEMENT
  - x - x - x INDICATES FENCE LINE
  - - - - - INDICATES GAS LINE LOCATE
  - - - - - INDICATES TELEPHONE LINE LOCATE
  - - - - - INDICATES WATER LINE LOCATE
  - - - - - INDICATES 10 FOOT INTERVAL CONTOUR
  - - - - - INDICATES 1 FOOT INTERVAL CONTOUR

  
 BASIS OF BEARING:  
 AND 85/91 WASHINGTON STATE  
 SOUTH ZONE, U.S. SURVEY FEET  
 COMBINED STATE PLACEMENT  
 1:25000 SCALE FACTOR: 1.000041831  
 SCALE 1 INCH = 50 FEET

**BENCH MARK:**  
 W.S.D.O.T. MONUMENT "LACAMAS" ID NO. 5789  
 A BRASS DISK IN CONCRETE LOCATED ON THE WESTERLY  
 SIDEWALK OF N.E. 192ND AVE APPROXIMATELY 500 FEET  
 NORTH OF THE INTERSECTION OF N.E. 192ND AVE AND S.E.  
 34TH STREET. ELEVATION = 250.85, CITY OF CAMAS DATUM

**NOTE:**  
 A UTILITY LOCATE WAS CALLED FOR ON 10-01-04 UNDER TICKET NUMBER  
 4323876. THE UNDERGROUND UTILITIES AS SHOWN ON THIS TOPOGRAPHIC  
 MAP ARE AS MARKED AT THE TIME OF THIS SURVEY. UNDERGROUND UTILITY  
 LOCATIONS SHOWN ARE APPROXIMATE ONLY. UNDERGROUND CONNECTIONS  
 ARE SHOWN AS STRAIGHT LINES BETWEEN SURFACE LOCATIONS BUT MAY  
 CONTAIN BENDS OR CURVES NOT SHOWN. SOME UNDERGROUND LOCATIONS  
 HEREON MAY HAVE BEEN TAKEN FROM PUBLIC RECORDS. M.G.S. ASSUMES NO  
 LIABILITY FOR THE ACCURACY OF PUBLIC RECORDS.





PREPARED BY:  
STERLING DESIGN, INC.  
1500 W. 10TH AVENUE  
WABOYCE, WA 98005  
TEL: (360) 798-1784  
FAX: (360) 798-1784  
mailto:sterlingdesign.biz

# STERLING DESIGN, INC.

Sheet Description:  
**PRELIMINARY GRADING PLAN**

Project:  
**VALLEY VIEW ESTATES  
SUBDIVISION**





## SITE INFORMATION

ALIGNMENT & FIELD DATA: MINISTER & CLAESSER SURVEYING, INC. (360) 694-3313 Rich, PAIS & FROD	Scale: AS SHOWN
SOL TYPE: HYDROLOGIC GROUP: C ASHTO CLASSIFICATION: A-4	Project Number: 286
DATE: MARCH 2014	Design: JGS/BC
SOLS TESTING BY: RAPID SOIL SOLUTIONS (360) 816-3069	Drawn:
SITE LOCATION: CLARK COUNTY, WA	APPROX. SURFACE ELEV.: 365'-488'
SITE AREA: 9.28 ACRES	FILENAME: 286/Preliminary.pro
	Sheet 4 of 9 Sheet(s)

NOTE:  
Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.





UNDESIGNED:

1. ALL GRADING SHALL CONFORM TO THE MOST RECENTLY ADOPTED EDITION OF THE F.S.D. OF 2. (MAY BE SUBJECT TO CHANGE) FOR PUBLIC, PRIVATE, AND MUNICIPAL LANDS WITHIN THE CITY OF LANSING (MAY BE SUBJECT TO CHANGE)
2. THE LIMIT OF CLEARING SHALL BE PLACED PRIOR TO CLEARING AND SURROUNDING OF THE SITE.
3. ANY EXISTING TREES TO REMAIN WITHIN THE CLEARING LIMITS SHALL BE MARKED AND PROTECTED FROM DAMAGE.
4. PRIOR TO AND DURING PLACEMENT, ALL AREAS WHICH WILL BE UNDER STRUCTURAL FILL SHALL BE EXCAVATED TO FIRM, NON-SATURATED, UNDESIGNED NATIVE SOILS. THE EXCAVATED AREAS SHALL BE PROTECTED AND MAINTAINED BY THE SUPERVISOR, ENGINEER AND THE CITY OF LANSING AS REQUIRED.
5. ALL ERT FILLS SHALL BEET 20% OF AND TO 1:1.50 COMPACTED.
6. ALL EXPOSED SOIL SURFACES SHALL BE COVERED WITHIN 14-DAY OF COMPLETION.
7. FILL SHALL BE 2% TO 4% IN ALL AREAS WITH ANY EXCESSIVE SLOPES OR INCREASED AND SHALL BE COMPACTED TO REQUIRED DENSITIES.
8. FILLS PLACED ON SLOPES EXCEEDING 3:1 SHALL BE KEPT AND BENDED, GEOTECHNICAL APPROVAL REQUIRED PRIOR TO ANY FILL PLACEMENT.
9. ALL SURFACES SHALL BE GRADED SMOOTH AND BE FREE OF IRREGULARITIES THAT MIGHT ACCUMULATE SURFACE WATER.
10. ALL CUT AND FILL SLOPES SHALL NOT EXCEED 2:1 SLOPES.
11. ANY EXPOSED SOILS SHALL BE PROTECTED FROM THE WIND BY PLANTING TREES OR 10' TALL FENCE OR ALL FTS FROM THE SITE TO 2' CONSTRUCTOR PROVIDED WAS THE SITE IS VISIBLE TO THE CITY OF LANSING, A SIGNAGE SHALL BE REQUIRED.
12. ALL EXPOSED AND UNCOVERED SOILS SHALL BE STABILIZED BY SUITABLE APPLICATION OF EROSION CONTROL MATS.
13. ALL SURFACES EXHIBITING VERTICULAR CRACKS SHALL BE REWORKED PRIOR TO SETBACK OF 10' SHORT PERPENDICULAR TO SURFACE FLOW TO REDUCE EROSION AND WEIL REGULATION.
14. FINAL EROSION CONTROL MEASURES SHALL BE SUBMITTED PRIOR TO SETBACK OF 10' SHORT PERPENDICULAR TO SURFACE FLOW TO REDUCE EROSION AND WEIL REGULATION.
15. FINAL EROSION CONTROL MEASURES SHALL BE SUBMITTED UPON COMPLETION OF SITE GRADING WORK.

PREPARED BY:  
STERLING DESIGN, INC.  
10000 WOODWARD AVE. SUITE 100  
ANN ARBOR, MI 48106  
TEL: (800) 798-1794  
WWW.STERLINGDESIGN.COM

STERLING DESIGN, INC.

PRELIMINARY PLAN  
EROSION CONTROL PLAN


Project: VALLEY VIEW ESTATES SUBDIVISION



SITE INFORMATION

ALIGNMENT & FIELD DATA: MINISTER & CLAASSEN SURVEYING, INC. (360) 694-3313	Scale: AS SHOWN
SOIL TYPE(S): Rapid Soil Solutions (603) 816-3888	Project Number: 286
DATE: MARCH 2014	Design: JGS/BC
SITE LOCATION: CLARK COUNTY, WA	Drawn
APPROX. SURFACE ELEV.: 365'-488'	Drawing Date: MAY 2018
SITE AREA: 9.28 ACRES	Sheet 5 of 9 Sheet(s)

NOTE:  
Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.






**STORM FACILITIES ARE DESIGNED TO PROVIDE WATER QUALITY AND QUANTITY CONTROL AS REQUIRED BY CITY OF CAMAS CODE CMC 14.02 AND MEET MINIMUM REQUIREMENTS 1-10 IN ACCORDANCE WITH THE 2006 STORMWATER MANAGEMENT MANUAL FOR WESTERN WASHINGTON**

**SITE DEVELOPMENT WILL NOT INCREASE THE AMOUNT OF IMPERVIOUS SURFACES ON NW 15th STREET. ALL DRAINAGE WILL FLOW TO THE EXISTING FLOW ROUTES**

**STORMWATER FACILITIES WILL BE PRIVATELY OWNED AND MAINTAINED**

- STORM CONSTRUCTION NOTES:**
- ALL trench excavation and pipe installation shall conform to the most recently adopted edition of the M.S.D.J.T. STANDARD SPECIFICATIONS SECTION 7-08.01 AND SECTION 7-08.02. ALL EXCESS MATERIAL FROM THE TRENCH EXCAVATION SHALL BE DISPOSED OF ON AN APPROVED SITE.
  - PIPE bedding, pipe stone material and trench bedding shall be an approved granular material of stone bedding specified by the city and shall be properly compacted.
  - TRENCH CONNECTION SHALL BE PER THE MOST RECENTLY ADOPTED EDITION OF THE M.S.D.J.T. STANDARD SPECIFICATIONS SECTION 7-08.02. CONNECTION TO EXISTING PIPE SHALL BE COMPLETED TO A MINIMUM OF 25 PERCENT OF THE MAXIMUM DENSITY AS DETERMINED BY THE A.C.S.T. 1.700 TEST METHOD.
  - SETTLEMENT OF THE FINISHED SURFACE WITHIN THE WARRANTY PERIOD SHALL BE EXPEDITED TO BE A RESULT OF UNPROPER CONSTRUCTION AND SHALL BE PROMPTLY REPAIRED BY THE CONTRACTOR AT HIS EXPENSE TO THE CITY.
  - ALL STORM PIPE SHALL BE PVC OR HDPE WITH DOUBLE BELLED COUPLINGS WITH 0-RING TYPE JOINTS OF APPROVED EQUAL.
  - ALL STORM PIPE LATERALS TO BE A MINIMUM 10 INCHES DIAMETER WITH A MINIMUM SLOPE OF 3/8 INCH PER FOOT UNLESS SPECIFIED OTHERWISE IN THE PLAN.
  - ALL MANHOLES LOCATED IN UNIMPROVED AREAS AND RIGHT OF WAYS SHALL BE PROVIDED WITH TAMPER PROOF LIDS AND SHALL BE SET 4 INCHES ABOVE FINISHED GRADE.
  - ALL USED IMPROVED LIDS AND REPAIRS MAY BE REQUIRED AT THE CITY'S DISCRETION. MANHOLE TESTING MAY BE REQUIRED AT THE CITY'S DISCRETION.



**SITE INFORMATION**

ALIGNMENT & FIELD DATA:	MINISTER & CLAASBER SURVEYING, INC. (360) 694-3313	Scale:	AS SHOWN
SOL TYPE/DATE:	HYDROLOGIC GROUP: C	ASHTO CLASSIFICATION:	A - 4
SOLS TESTING BY:	RAPID SOIL SOLUTIONS (503) 816-3089	DATE:	MARCH 2014
SITE LOCATION:	CLARK COUNTY, WA	APPROX. SURFACE ELEVATION:	365'-488'
SITE AREA:	9.28 ACRES	PLANS:	288 / Preliminary.pro

**NOTE:**  
Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth & slope any and all existing utilities prior to construction. Contact One Call Concepts at (800) 474-5555.

PREPARED BY:  
STERLING DESIGN, INC.  
10000 15th Street NW  
Washouak, WA 98671  
TEL: (360) 798-1784  
FAX: (360) 798-1784  
mailto:stddesign@sterlingdesign.biz


**STERLING DESIGN, INC.**

Sheet Description:  
**PRELIMINARY STORMWATER MANAGEMENT PLAN**


Project:  
**VALLEY VIEW ESTATES SUBDIVISION**



Project Number: 288  
Design: JGS/BC  
Drawn:  
Drawing Date: MAY 2018  
Sheet 6 of 9 Sheet(s)




- STREET CONSTRUCTION NOTES:**
- ENGINEERED FILL SHALL BE PLACED AND COMPACTED IN ACCORDANCE WITH THE MOST RECENTLY ADOPTED EDITION OF THE STANDARD SPECIFICATIONS SECTION 7-2.3.1.5 (A) FOR FILL AREAS WITH REINFORCED MATS OF FIBER SHALL BE USED FOR FILL AREAS OUTSIDE OF REINFORCED MATS. ALL FILL PLACED SHALL BE MONITORED BY GEOTECHNICAL TESTING. TEST RESULTS SHALL BE FORWARDED TO THE CITY OF CHANDLER PROJECT ENGINEER.
  - MATERIALS IN SPOT SPOTS WITHIN THE ROADWAY SHALL BE REMOVED TO THE DEPTH REQUIRED TO PROVIDE A FIRM FOUNDATION AND SHALL BE BACKFILLED WITH 1-1/2 MIN MAX CRUSHED ROCK.
  - ALL SURFACES TO BE PROOF ROLLED AND APPROVED BY THE CITY INSPECTOR OR BY A GEOTECHNICAL CONSULTANT WITH EMPLOY OF THE CITY ENGINEER. SURFACE TILLS ARE TO BE TESTED USING THE AASHTO T-190 TEST METHOD.
  - ALL TRENCH LINES, FILL AREAS AND BASE COURSE LOCATED IN THE RIGHT-OF-WAY SHALL BE APPROVED BEFORE CONSTRUCTION AND SHALL MEET THE AASHTO T-190 COMPLETION. TRENCH LINES LOCATED WITHIN AN EXISTING ROADWAY SHALL BE PLACED ON EXISTING MATERIALS UNLESS OTHERWISE SPECIFIED. OTHERWISE, TILLS SHALL HAVE A MINIMUM OF 18" TYPICAL.
  - THE CONTRACTOR SHALL NOTIFY THE CITY INSPECTOR A MINIMUM OF 24 HOURS PRIOR TO SURFACE PROOF ROLL OR GRADE CHECK INSPECTIONS.
  - THE ADDRESS BY ROAD BASE SHALL BE COMPACTED IN ACCORDANCE WITH THE MOST RECENTLY ADOPTED EDITION OF THE STANDARD SPECIFICATIONS SECTION 7-2.3.1.5 (A) THE CURBING OF SHALL BE TESTED TO THE STANDARD OF THE CITY INSPECTOR. MINIMUM DENSITY (98%) AS DETERMINED BY AASHTO T-190 TEST METHOD.
  - ASPHALT CONCRETE PAVEMENT MAY BE DESIGNED FROM A MIX FORMULA APPROVED BY RESULTS FOR MATERIALS USED. CONTRACTOR TO PROVIDE THE CITY WITH CERTIFICATE OF COMPLIANCE FROM THE ASPHALT PAVEMENT PLANT, UNLESS OTHERWISE INDICATED.
  - THE ASPHALT CONCRETE PAVEMENT SHALL BE COMPACTED IN ACCORDANCE WITH THE MOST RECENTLY ADOPTED EDITION OF THE STANDARD SPECIFICATIONS SECTION 7-2.3.1.5 (A) CONTRACTOR SHALL NOTIFY TEST RESULTS TO THE ENGINEER AND THE CITY INSPECTOR.
  - ALL STORM SYSTEM IMPROVEMENTS AND STORMWATER DETENTION AND TREATMENT FACILITIES SHALL BE CONSTRUCTED AND PROPERLY FUNCTIONING PRIOR TO ANY FINISH.
  - IN ALL STREET IMPROVEMENTS SHALL INCLUDE AN ANALYSIS OF THE EXISTING STRUCTURAL SECTION DUE TO CONSTRUCTION OF THE ROADWAY. THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE A GEOTECHNICAL ANALYSIS OF THE EXISTING STRUCTURAL SECTION TO DETERMINE THE MAXIMUM DENSITY OF A STRUCTURAL COURSE A COMPLETE STREET SECTION DETERMINED BY A GEOTECHNICAL ANALYSIS AND AS APPROVED BY THE CITY ENGINEER.



**CENTERLINE CURVE DATA**

① R=70.001' Ch=95.381' A=104.531' T=65.141' E=25.621' A=95° 50' 59"	④ R=70.001' Ch=100.351' A=112.151' T=65.141' E=30.581' A=95° 47' 34"
② R=70.001' Ch=95.381' A=104.531' T=65.141' E=25.621' A=95° 50' 59"	⑤ R=70.001' Ch=97.431' A=101.771' T=67.841' E=27.481' A=95° 15' 26"
③ R=70.001' Ch=100.351' A=114.701' T=74.561' E=32.501' A=93° 50' 09"	⑦ R=275.001' Ch=94.171' A=94.041' T=47.791' E=14.791' A=119° 43' 02"



PREPARED BY:  
STERLING DESIGN, INC.  
1000 W. WASHINGTON, SUITE 100  
MILWAUKEE, WI 53233  
TEL: (800) 706-1784  
WWW.STERLINGDESIGN.COM

**STERLING DESIGN, INC.**

Sheet Description:  
PRELIMINARY TRANSPORTATION PLAN


Project:  
VALLEY VIEW ESTATES SUBDIVISION

Scale: AS SHOWN  
Project Number: 286  
Design: JGS/BC  
Drawn:  
Drawing Date: MAY 2018  
Sheet 7 of 9 Sheet(s)

**SITE INFORMATION**

ALIGNMENT & FIELD DATA: MINISTER & CLAESSER SURVEYING, INC. (360) 694-3313 SOL TYPE: HYDROLOGIC GROUP: C Rch, Pch & Pch	Scale: AS SHOWN Project Number: 286 Design: JGS/BC Drawn: Drawing Date: MAY 2018
SOILS TESTING BY: RAPID SOIL SOLUTIONS (603) 816-3888 SITE LOCATION: CLARK COUNTY, WA	DATE: MARCH 2014 APPROX. SURFACE ELEV: 365'-488'
SITE AREA: 9.28 ACRES	PLANS: 286/Preliminary.pro Sheet 7 of 9 Sheet(s)


**NOTE:**  
Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.



**UTILITY NOTE:**  
**ALL LOTS WILL BE PROVIDED WITH PUBLIC WATER & SANITARY SEWER LATERAL.**  
**EXISTING WELLS, SEPTIC TANKS AND DRAIN FIELDS SHALL BE ABANDONED IN ACCORDANCE TO STATE GUIDELINES.**

**UTILITY NOTE:**  
**ALL UTILITIES FOR LOT 38 ARE EXISTING AND INSTALLED.**

**NOTE:**  
 Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth & slope of any one of all existing utilities prior to construction. Contact One Call concepts at (800) 424-3555.



**WATER CONSTRUCTION NOTES:**

1. ALL TRENCH EXCAVATION AND PIPE INSTALLATION SHALL CONFORM TO THE MOST CURRENT A.W.A.A. STANDARDS AND ALL TRENCH EXCAVATION SHALL BE PROTECTED WITH SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
2. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
3. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
4. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
5. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
6. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
7. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
8. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
9. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
10. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
11. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
12. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
13. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.

**WATER CONSTRUCTION NOTES:**

1. ALL TRENCH EXCAVATION AND PIPE INSTALLATION SHALL CONFORM TO THE MOST CURRENT A.W.A.A. STANDARDS AND ALL TRENCH EXCAVATION SHALL BE PROTECTED WITH SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
2. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
3. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
4. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
5. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
6. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
7. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
8. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
9. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
10. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
11. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
12. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.
13. ALL TRENCH EXCAVATION SHALL BE PROTECTED BY SHIELDING OR SHIELDING SHALL BE PROVIDED TO PROTECT EXCAVATION SHALL BE PROTECTED BY SHIELDING.

**SITE INFORMATION**




ALIGNMENT & FIELD DATA:	MINISTER & CLAASBER SURVEYING, INC. (360) 694-3313	Scale:	AS SHOWN
SOIL TYPE:	RAPID SOIL SOLUTIONS (603) 816-3069	Project Number:	286
DATE:	MARCH 2014	Design/ JGS/ BC	
SITE LOCATION:	CLARK COUNTY, WA	Drawing Date:	MAY 2018
SITE AREA:	9.28 ACRES	Sheet:	8 of 9 Sheet(s)

PREPARED BY:  
**STERLING DESIGN, INC.**  
 1000 W. 10TH AVENUE, SUITE 100  
 WASHINGTON, WA 98601  
 TEL: (206) 706-1794  
 FAX: (206) 706-1794  
 www.sterlingdesign.com

**STERLING DESIGN, INC.**

Sheet Description:  
**PRELIMINARY UTILITY PLAN**

Project:  
**VALLEY VIEW ESTATES SUBDIVISION**



NOTE:  
Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth, & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.

**SITE INFORMATION**

ALIGNMENT & FIELD DATA: MINISTER & CLAESSER SURVEYING, INC. (360) 694-3313	Scale: AS SHOWN
SOIL TYPE(s): HYDROLOGIC GROUP: C ASHTO CLASSIFICATION: A-4	Project Number: 286
SOILS TESTING BY: RAPID SOIL SOLUTIONS (503) 816-3069	DATE: MARCH 2014
SITE LOCATION: CLARK COUNTY, WA	DESIGNER: JGS/BC
SITE AREA: 9.28 ACRES	PLANS: 286/ Preliminary.pro
	DRAWN: [Blank]
	DRAWING DATE: MAY 2018
	SHEET: 9 of 9 Sheet(s)

PREPARED BY:  
STERLING DESIGN, INC.  
10000 10TH AVENUE  
WAINWRIGHT, WA 98660  
TEL: (360) 796-1784  
WWW.STERLINGDESIGN.COM  
mailto:sterlingdesign@sterlingdesign.biz

**STERLING DESIGN, INC.**

Sheet Description:  
PRELIMINARY  
LANDSCAPE & LIGHTING  
PLAN

Project:  
VALLEY VIEW ESTATES  
SUBDIVISION



# VALLEY VIEW ESTATES



A Preliminary Subdivision within in a portion of the NE 1/4 of Sec. 8, T1N., R3E., W.M. Clark County, Washington

PREPARED BY:  
STERLING DESIGN, INC.  
2208 E. EVERGREEN BLVD  
VANCOUVER, WA 98661  
PHONE: (360) 759-1794  
FAX: (360) 759-4983  
mailto:sterlingdesign.biz

STERLING DESIGN, INC.

COVER SHEET

Project: VALLEY VIEW ESTATES SUBDIVISION



VICINITY MAP (NTS)

**SHEET INDEX**

COVER SHEET	1
PROPOSED DEVELOPMENT PLAN	2
PRELIMINARY TOPOGRAPHIC & BOUNDARY SURVEY	3
PRELIMINARY GRADING PLAN	4
PRELIMINARY EROSION CONTROL PLAN	5
PRELIMINARY STORMWATER MANAGEMENT PLAN	6
PRELIMINARY TRANSPORTATION PLAN	7
PRELIMINARY UTILITY PLAN	8
PRELIMINARY LANDSCAPE & LIGHTING PLAN	9

**SITE DATA:**

- TAX LOT(S): 59 & 48
- SERIAL NUMBER(S): 125646-000 & 125635-000
- SITE ADDRESS: 20109 SE 40th STREET
- AREA: 9.26 ACRES
- ZONING: R-7.5
- COMPREHENSIVE PLAN: UL

**LEGEND**

- CURB & SIDEWALK
- PROPOSED EASEMENT
- PROPOSED LOT LINE
- EXISTING RIGHT-OF-WAY
- PROPOSED SANITARY SEWER LINE
- PROPOSED STORM SEWER LINE
- PROPOSED PERFORATED STORM LINE
- PROPOSED ROADWAY CENTERLINE
- EXISTING ELECTRIC
- EXISTING TELEPHONE LOCATE PAINT
- EXISTING WATER LOCATE PAINT
- EXISTING EDGE OF PAVEMENT/GRAVEL
- EXISTING SANITARY SEWER LINE
- EXISTING STORM LINE
- EXISTING FENCE
- EXISTING GROUND CONTOUR
- PROPOSED GROUND CONTOUR (1')
- DIRECTION OF STORMWATER FLOW
- EROSION CONTROL SILT FENCE
- INLET PROTECTION
- PROPOSED SANITARY CLEANOUT
- PROPOSED FIRE HYDRANT
- STD 1" WATER METER SERVICE
- PROPOSED MANHOLE
- PROPOSED DRYWELL
- PROPOSED CATCH BASIN
- PROPOSED COMBINATION CURB INLET
- PROPOSED STORMFILTER
- EXISTING POWER POLE WITH NUMBER AND DIRECTION OF OVERHEAD LINES
- EXISTING GUY ANCHOR
- EXISTING TELEPHONE PEDESTAL
- EXISTING STORM DRAIN MANHOLE
- EXISTING CATCH BASIN
- EXISTING ADA RAMP
- EXISTING ELECTRICAL SERVICE BOX
- EXISTING SANITARY MANHOLE
- EXISTING SANITARY CLEANOUT
- EXISTING FIRE HYDRANT
- EXISTING WATER SERVICE
- EXISTING WATER VALVE
- PROPOSED STREET TREES 30' O.C.
- PROPOSED STREET LIGHT 70' SPACING

STREET TREES AND STREET LIGHTING WILL BE PROVIDED AS REQUIRED BY THE CITY OF CAMAS CODE.

**CITY OF CAMAS PRE-APPLICATION NUMBER: PA18-09**

**DESIGN & DEVELOPMENT TEAM**


<b>PROPERTY OWNER:</b> STAN FIRESTONE PO BOX 61928 VANCOUVER WA, 98666 (360) 695-9484 stan@firestonepacificfoods.com	<b>CIVIL ENGINEER/ LAND USE PLANNING:</b> STERLING DESIGN, INC. JOEL STIRLING, PE 2208 E. EVERGREEN BLVD. VANCOUVER, WA 98661 (360) 759-1794 FAX: (360) 759-4983 EMAIL: joel@sterling-design.biz	<b>SURVEYOR:</b> MINISTER & GLAESER SURVEYING, INC. 2200 E. EVERGREEN BLVD. VANCOUVER WA, 98661 PHONE: (360) 694-3313 FAX: (360) 694-8410
---	---	--

**BENCH MARK:**  
W.S.D.O.T. MONUMENT "LACAMAS" ID NO. 5789  
A BRASS DISK IN CONCRETE LOCATED ON THE WESTERLY SIDEWALK OF N.E. 192nd AVE APPROXIMATELY 500 FEET NORTH OF THE INTERSECTION OF N.E. 192nd AVE AND S.E. 34th STREET. ELEVATION = 250.85', CITY OF CAMAS DATUM

**NOTE:**  
Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-3555.

**SITE INFORMATION**

ALIGNMENT & FIELD DATA: MINISTER & GLAESER SURVEYING, INC. (360) 694-3313	Scale: AS SHOWN
SOIL TYPE(S): HYDROLOGIC GROUP: C AASHTO CLASSIFICATION: A-4	Project Number: 286
SOILS TESTING BY: RAPID SOIL SOLUTIONS (603) 816-3689 DATE: MARCH 2014	Design/Drawn: JGS/BC
SITE LOCATION: CLARK COUNTY, WA APPROX. SURFACE ELEV.: 385'-468'	Drawing Date: MAY 2018
SITE AREA: 9.26 ACRES	FILENAME: 286/Preliminary.pro Sheet 1 of 9 Sheet(s)



WESTON INVESTMENTS  
TAX LOT 12  
126936-000

TAX LOT 13  
986033-303  
TAX LOT 14  
986033-034

BRECKENRIDGE SUBDIVISION  
LENAR HOMES

TAX LOT 12  
986033-032  
TAX LOT 11  
986033-031

TAX LOT 10  
986033-030

YOUNG  
TAX LOT 12  
92231-050

KNIGHT POINT AT PRUNE HILL (H-594)  
THIEMAN  
TAX LOT 5  
92231-036

TRACT 'H'  
FULPS  
TAX LOT 4  
92231-034

WOODWARD  
TAX LOT 58  
125645-000

THERMO-O-LOC  
TAX LOT 47  
125634-000

TAX LOT 76  
126042-152

WINCHESTER HILLS HOMEOWNER  
TRACT 'A'  
126042-360

WINCHESTER HILLS PHASE -1 (J-502)

SE 201st AVE (PUBLIC)

NW 18th STREET (PUBLIC)

TRACT 'A'


TRACT 'B'

TRACT 'G'

TRACT 'D'

TRACT 'E'

TRACT 'F'



**PROPERTY BOUNDARY LEGAL DESCRIPTION(s)**

**TAX LOT 48 (ASSESSORS PARCEL NUMBER 125635-000):**

That parcel of land located in a portion of the Joel Knight D.L.C. No. 41 and in a portion of the Northwest Quarter of the Northeast Quarter and the Northeast Quarter of Section 8, Township 1 North, Range 3 East, Willamette Meridian, City of Camas, Clark County, Washington, described as follows:

BEGINNING at the Northwest corner of the Plat of "Breckenridge" as recorded in Book 311 of Plats, at Page 715, Clark County, Washington, plat records;

Thence South 89°29'23" East, along the North line of said Plat of "Breckenridge" for a distance of 95.97 feet;

Thence leaving said North line, North 04°25'46" East, parallel with the West line of the Joel Knight D.L.C. No. 41, for a distance of 62.70 feet;

Thence North 39°16'12" East, for a distance of 114.49 feet to the beginning of a 96.00 foot radius non-tangent curve to the left;

Thence along the arc of a 96.00 foot radius non-tangent curve to the right, for an arc distance of 20.15 feet, through a central angle of 12°01'29", the radius of which bears North 39°16'12" East, the long chord of which bears North 44°43'03" West, for a chord distance of 20.11 feet;

Thence South 39°16'12" West, for a distance of 123.30 feet;

Thence North 89°29'23" West, parallel with the North line of said Plat of "Breckenridge", for a distance of 75.68 feet to the West line of the Joel Knight D.L.C. No. 41;

Thence South 04°25'46" West, along said West line, for a distance of 70.00 feet to the POINT OF BEGINNING;

CONTAINING: 9,000 square feet of land, more or less.

**TAX LOT 59 (ASSESSORS PARCEL NUMBER 125646-000):**

That parcel of land located in a portion of the Joel Knight D.L.C. No. 41 and in a portion of the Northwest Quarter of the Northeast Quarter and the Northeast Quarter of Section 8, Township 1 North, Range 3 East, Willamette Meridian, City of Camas, Clark County, Washington, described as follows:

BEGINNING at the Northeast corner of the Plat of "Breckenridge" as recorded in Book 311 of Plats, at Page 715, Clark County, Washington, plat records;

Thence North 89°29'23" West, along the North line of said Plat of "Breckenridge", for a distance of 335.14 feet;

Thence continuing along said North line, South 04°25'46" West, for a distance of 9.20 feet;

Thence continuing along said North line, North 89°29'23" West, for a distance of 197.07 feet;

Thence leaving said North line, North 04°25'46" East, for a distance of 62.70 feet;

Thence North 39°16'12" East, for a distance of 114.49 feet to the beginning of a 96.00 foot radius non-tangent curve to the right;

Thence along the arc of a 96.00 foot radius non-tangent curve to the right, for an arc distance of 20.15 feet, through a central angle of 12°01'29", the radius of which bears North 39°16'12" East, the long chord of which bears North 44°43'03" West, for a chord distance of 20.11 feet;

Thence South 39°16'12" West, for a distance of 123.30 feet;

Thence North 89°29'23" West, for a distance of 75.68 feet to the West line of the Joel Knight D.L.C. No. 41;

Thence North 04°25'46" East, along the West line of said Joel Knight D.L.C. No. 41, for a distance of 659.58 feet to the South Right of Way line of SE 40th Street and the beginning of a 220.99 foot radius non-tangent curve to the left;

Thence leaving said West line, along said South Right of Way line, along the arc of a 220.99 foot radius non-tangent curve to the left, for an arc distance of 40.96 feet, through a central angle of 10°37'07", the radius of which bears North 10°55'53" East, the long chord of which bears South 84°22'41" East, for a chord distance of 40.90 feet;

Thence continuing along said South Right of Way line, South 89°41'15" East, for a distance of 378.44 feet to the Northwest corner of Tax Lot 58, as described and recorded under Clark County, Washington, Auditor's File Number #4919758 D;

Thence leaving said South Right of Way line, South 04°25'46" West, along the West line of said Tax Lot 58, for a distance of 181.97 feet to the Southwest corner thereof;

Thence leaving said West line, South 89°41'15" East, along the South line of said Tax Lot 58, for a distance of 36.14 feet to the Northwest corner of Tax Lot 47 as described and recorded under Clark County, Washington, Auditor's File Number #5106393 D;

Thence leaving said South line, South 01°26'14" West, along the West line of said Tax Lot 47, for a distance of 70.01 feet to the Southwest corner thereof;

Thence leaving said West line, South 89°41'15" East, along the South line of said Tax Lot 47, for a distance of 128.57 feet to the Southeast

**PROPOSED DEVELOPMENT PLAN:**  
**TOTAL LOTS: 36**  
**MINIMUM LOT AREA: 5,900 sq.ft.**  
**MAXIMUM LOT AREA: 9,000 sq.ft.**  
**AVERAGE LOT AREA: 7,087 sq.ft.**

TRACT PURPOSE	AREA	OWNED & MAINTAINED
TRACT 'A' - LANDSCAPE	2,268 sf	HOA
TRACT 'B' - ACCESS & UTILITY	1,541 sf	HOA
TRACT 'C' - RECREATIONAL OPEN SPACE	13,438 sf	CITY
TRACT 'D' - ACCESS & UTILITY	1,752 sf	HOA
TRACT 'E' - STORM FACILITY	23,887 sf	HOA
TRACT 'F' - STORM FACILITY	10,405 sf	HOA
TRACT 'G' - ACCESS & UTILITY	2,630 sf	HOA
TRACT 'H' - ACCESS & UTILITY	5,034 sf	HOA

**LAND INVENTORY**

TOTAL SITE AREA:	9.26 ACRES
TOTAL DEVELOPED ACREAGE:	7.29 ACRES
TOTAL LOT AREA:	5.85 ACRES
TOTAL INFRASTRUCTURE ACREAGE:	2.79 ACRES
TOTAL TRACT AREA(MINUS STORM TRACTS):	0.61 ACRES
TOTAL ACREAGE OF CRITICAL AREAS:	NONE
TOTAL ACREAGE OF REC. OPENSAPCE	0.31 ACRES

**TABLE 18.09.040**  
 MINIMUM SETBACKS:

FRONT:	20'
SIDE STREET:	20'
SIDE INTERIOR:	5'
REAR:	25'
MAX. LOT COVERAGE:	40%
MAX. BLDG. HEIGHT:	35'

ALL PROPOSED BUILDING ENVELOPES ARE LARGE ENOUGH TO FIT A 40 FOOT X 40 FOOT BUILDING FOOT PRINT.

**SITE INFORMATION**

ALIGNMENT & FIELD DATA:	MINISTER & GLAESER SURVEYING, INC. (360) 694-3313	Scale:	AS SHOWN
SOIL TYPE(s):	HYDROLOGIC GROUP: C AASHTO CLASSIFICATION: A-4	Project Number:	286
SOILS TESTING BY:	RAPID SOIL SOLUTIONS (603) 816-3689 DATE: MARCH 2014	Design/Drawn:	JGS/BC
SITE LOCATION:	CLARK COUNTY, WA APPROX. SURFACE ELEV.: 385'-468'	Drawing Date:	JUNE 2018
SITE AREA:	9.26 ACRES	FILENAME:	286:/Preliminary.pro

**NOTE:**  
 Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.

**PREPARED BY:**  
 STERLING DESIGN, INC.  
 2208 E EVERGREEN BLVD  
 WACONIA, WA 98601  
 PHONE: (360) 894-1044  
 FAX: (360) 758-4888  
 mail@sterlingdesign.com

**STERLING DESIGN, INC.**

**PROPOSED DEVELOPMENT PLAN**

**VALLEY VIEW ESTATES SUBDIVISION**




Scale: AS SHOWN  
 Project Number: 286  
 Design/Drawn: JGS/BC  
 Drawing Date: JUNE 2018  
 Sheet 2 of 9 Sheet(s)


# TOPOGRAPHIC SURVEY

OF  
 A PORTION OF THE JOEL KNIGHT D.L.C.  
 IN THE NW 1/4 OF THE NE 1/4,  
 THE SW 1/4 OF THE NE 1/4,  
 THE NE 1/4 OF THE NW 1/4  
 AND THE SE 1/4 OF THE NW 1/4  
 SECTION 8  
 T. 1 N., R. 3 E., W.M.  
 CLARK COUNTY, WASHINGTON

JOB NO.: 04-413      DATA COLLECT: 10-11-04, 10-12-04  
 DRAWING DATE: 04-27-18




- LEGEND:**
- INDICATES FOUND MONUMENT AS NOTED
  - ⊠ INDICATES TELEPHONE VAULT
  - ⊕ INDICATES FIRE HYDRANT
  - ⊕ INDICATES WATER VALVE
  - INDICATES CATCH BASIN
  - ⊙ INDICATES WELL
  - Ⓢ INDICATES SANITARY MANHOLE
  - - - - - INDICATES EASEMENT LINE
  - — — — — INDICATES ADJACENT LOT LINE
  - — — — — INDICATES BACK OF CURB LINE
  - - - - - INDICATES CALCULATED RIGHT-OF-WAY LINE
  - - - - - INDICATES CENTERLINE OF CREEK
  - - - - - INDICATES EDGE OF GRAVEL
  - - - - - INDICATES EDGE OF PAVEMENT
  - x - x - x - INDICATES FENCE LINE
  - - - - - INDICATES GAS LINE LOCATE
  - - - - - INDICATES TELEPHONE LINE LOCATE
  - - - - - INDICATES WATER LINE LOCATE
  - - - - - INDICATES 10 FOOT INTERVAL CONTOUR
  - - - - - INDICATES 1 FOOT INTERVAL CONTOUR





**BENCH MARK:**  
 W.S.D.O.T. MONUMENT "LACAMAS" ID NO. 5789  
 A BRASS DISK IN CONCRETE LOCATED ON THE WESTERLY  
 SIDEWALK OF N.E. 192ND AVE. APPROXIMATELY 500 FEET  
 NORTH OF THE INTERSECTION OF N.E. 192ND AVE AND S.E.  
 34TH STREET. ELEVATION = 250.85, CITY OF CAMAS DATUM

**NOTE:**  
 A UTILITY LOCATE WAS CALLED FOR ON 10-01-04 UNDER TICKET NUMBER  
 4323876. THE UNDERGROUND UTILITIES AS SHOWN ON THIS TOPOGRAPHIC  
 MAP ARE AS MARKED AT THE TIME OF THIS SURVEY. UNDERGROUND UTILITY  
 LOCATIONS SHOWN ARE APPROXIMATE ONLY. UNDERGROUND CONNECTIONS  
 ARE SHOWN AS STRAIGHT LINES BETWEEN SURFACE LOCATIONS BUT MAY  
 CONTAIN BENDS OR CURVES NOT SHOWN. SOME UNDERGROUND LOCATIONS  
 HEREON MAY HAVE BEEN TAKEN FROM PUBLIC RECORDS. M.G.S. ASSUMES NO  
 LIABILITY FOR THE ACCURACY OF PUBLIC RECORDS.



**MINISTER-GLAESER  
 SURVEYING INC.**  
 2200 E. EVERGREEN BLVD.  
 VANCOUVER, WA 98661  
 (360) 694-3313






PREPARED BY:  
 STERLING DESIGN, INC.  
 2208 E EVERGREEN BLVD  
 WACO, TX 76701  
 PH (800) 831-1984  
 FAX (800) 738-1983  
 mail@sterlingdesign.com

**STERLING DESIGN, INC.**

Sheet Description:  
**PRELIMINARY GRADING PLAN**


Project:  
**VALLEY VIEW ESTATES SUBDIVISION**



**SITE INFORMATION**

ALIGNMENT & FIELD DATA: MINISTER & GLAESER SURVEYING, INC. (360) 694-3313	Scale: AS SHOWN
SOIL TYPE(s): Hcb, PoB & PoD	HYDROLOGIC GROUP: C
SOILS TESTING BY: RAPID SOIL SOLUTIONS (503) 816-3889	AASHTO CLASSIFICATION: A-4
SITE LOCATION: CLARK COUNTY, WA	DATE: MARCH 2014
SITE AREA: 9.26 ACRES	APPROX. SURFACE ELEV.: 385'-468'
	FILENAME: 286/:Preliminary.pro
	Project Number: 286
	Design/Drawn: JGS/BC
	Drawing Date: MAY 2018
	Sheet 4 of 9 Sheet(s)

NOTE:  
 Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth, & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.



PREPARED BY:  
 STERLING DESIGN, INC.  
 2208 E EVERGREEN BLVD  
 WACONIA, WA 98001  
 WA 98001  
 FAX (360) 738-1808  
 mail@sterlingdesign.com

STERLING DESIGN, INC.

Sheet Description:  
 PRELIMINARY  
 EROSION CONTROL PLAN

Project:  
 VALLEY VIEW ESTATES  
 SUBDIVISION



**GRADING NOTES:**

1. ALL GRADING SHALL CONFORM TO THE MOST RECENTLY ADOPTED EDITION OF THE W.S.D.O.T. STANDARD SPECIFICATIONS FOR ROAD, BRIDGE AND MUNICIPAL CONSTRUCTION AND THE CITY OF CAMAS DESIGN STANDARDS MANUAL.
2. THE LIMITS OF CLEARING SHALL BE FLAGGED PRIOR TO CLEARING AND GRUBBING OF THE SITE.
3. ANY EXISTING TREES TO REMAIN WITHIN THE CLEARING LIMITS SHALL BE MARKED AND PROTECTED FROM DAMAGE.
4. PRIOR TO ANY FILL PLACEMENT, ALL AREAS WHICH WILL RECEIVE STRUCTURAL FILL SHALL BE EXCAVATED TO FIRM, NON-ORGANIC, UNDISTURBED NATIVE GROUND. THE STRIPPED AREAS SHALL BE OBSERVED AND ACCEPTED BY THE GEOTECHNICAL ENGINEER AND THE CITY OF CAMAS INSPECTOR.
5. ALL LOT FILLS SHALL MEET 95% OF AASHO T-99 COMPACTION.
6. ALL RIGHT-OF-WAY FILLS SHALL MEET 95% OF AASHO T-180 COMPACTION.
7. FILLS SHALL BE INSTALLED IN VERTICAL LIFTS NOT EXCEEDING 8 INCHES IN THICKNESS AND SHALL BE COMPACTED AS PREVIOUSLY NOTED.
8. FILLS PLACED ON SLOPES EXCEEDING 3:1 V SHALL BE KEED AND BENCHED, GEOTECHNICAL APPROVAL REQUIRED PRIOR TO ANY FILL PLACEMENT.
9. ALL SURFACES SHALL BE GRADED SMOOTH AND BE FREE OF IRREGULARITIES THAT MIGHT ACCUMULATE SURFACE WATER.
10. ALL CUT AND FILL SLOPES SHALL NOT EXCEED 2:1 SLOPES.
11. ANY EXCESS MATERIAL NOT REQUIRED TO MEET THE GRADES SHOWN ON THE PLANS SHALL BE HAULLED FROM THE SITE TO A CONTRACTOR PROVIDED WASTE SITE. IF WASTE SITE IS WITHIN CITY LIMITS, A GRADING PERMIT MAY BE REQUIRED.
12. ALL EXPOSED AND UNWORKED SOILS SHALL BE STABILIZED BY SUITABLE APPLICATION OF EROSION CONTROL BMP'S.
13. ALL SURFACES REQUIRING VEGETATION SHALL BE ROUGHENED PRIOR TO SEEDING (I.E. WHEEL TRACKED PERPENDICULAR TO SURFACE FLOW TO REDUCE EROSION AND HELP VEGETATION).
14. FINAL GEOTECHNICAL SUMMARY REPORT, INCLUDING ALL COMPACTION TESTING RESULTS, SHALL BE SUBMITTED UPON COMPLETION OF SITE GRADING WORK.


REV. NO.	DATE	BY	APPR.	DETAIL NO.
1	6/19/2014	JK	JK	EC1
2	1/7/2015	JK	JK	EC1

CITY OF CAMAS - EROSION CONTROL DETAIL  
 GRADING NOTES  
 DATE APPROVED BY: [Signature] DATE: 1-4-15  
 NOT TO SCALE  
 EC-ROTELENG

**NOTE:**  
 Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth, & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.

**SITE INFORMATION**


ALIGNMENT & FIELD DATA: MINISTER & GLAESER SURVEYING, INC. (360) 694-3313	Scale: AS SHOWN
SOIL TYPE(s): HYDROLOGIC GROUP: Hcb, PoB & PoD C AASHTO CLASSIFICATION: A-4	Project Number: 286
SOILS TESTING BY: RAPID SOIL SOLUTIONS (603) 816-3889 DATE: MARCH 2014	Design/Drawn: JGS/BC
SITE LOCATION: CLARK COUNTY, WA APPROX. SURFACE ELEV.: 385'-468'	Drawing Date: MAY 2018
SITE AREA: 9.26 ACRES	FILENAME: 286:/Preliminary.pro Sheet 5 of 9 Sheet(s)



CONTRACTOR SHALL UTILIZE STORM FACILITIES FOR A TEMPORARY SEDIMENT POND UNTIL SITE IS STABILIZED. PROVIDE OVERFLOW W/SEDIMENT CONTROL TO EX. FLOW ROUTES

CONTRACTOR SHALL PROTECT EXISTING STORMWATER FACILITY

PROVIDE INLET PROTECTION ON DOWNSTREAM INLETS






**STORM FACILITIES ARE DESIGNED TO PROVIDE WATER QUALITY AND QUANTITY CONTROL AS REQUIRED BY CITY OF CAMAS CODE CMC 14.02 AND MEET MINIMUM REQUIREMENTS 1-10 IN ACCORDANCE WITH THE 2005 STORMWATER MANAGEMENT MANUAL FOR WESTERN WASHINGTON**

**SITE DEVELOPMENT WILL NOT INCREASE THE AMOUNT OF IMPERVIOUS SURFACES ON NW 18th STREET. ALL DRAINAGE WILL FLOW TO THE EXISTING FLOW ROUTES**

**STORMWATER FACILITIES WILL BE PRIVATELY OWNED AND MAINTAINED**

**STORM CONSTRUCTION NOTES:**

1. ALL TRENCH EXCAVATION AND PIPE INSTALLATION SHALL CONFORM TO THE MOST RECENTLY ADOPTED EDITION OF THE W.S.D.O.T. STANDARD SPECIFICATIONS SECTION 7-08.3(1) AND SECTION 7-08.3(2). ALL EXCESS MATERIAL FROM THE TRENCH EXCAVATION SHALL BE DISPOSED OF ON AN APPROVED SITE.
2. PIPE BEDDING, PIPE ZONE MATERIAL AND TRENCH BACKFILL SHALL BE AN APPROVED GRANULAR MATERIAL OF EITHER WASHED SCREENINGS OR 5/8" INCH MINUS CRUSHED ROCK. SAND BACKFILL IS NOT ALLOWED.
3. TRENCH COMPACTION SHALL BE PER THE MOST RECENTLY ADOPTED EDITION OF THE W.S.D.O.T. STANDARD SPECIFICATIONS SECTION 7-08.3(3). CONTRACTOR TO DETERMINE THE TYPE OF EQUIPMENT AND METHOD TO USE TO ACHIEVE THE REQUIRED COMPACTION. EACH LIFT SHALL BE COMPACTED TO A MINIMUM OF 95 PERCENT OF THE MAXIMUM DENSITY AS DETERMINED BY THE A.A.S.H.T.O. T-100 TEST METHOD.
4. SETTLEMENT OF THE FINISHED SURFACE WITHIN THE WARRANTY PERIOD SHALL BE CONSIDERED TO BE A RESULT OF IMPROPER COMPACTION AND SHALL BE PROMPTLY REPAIRED BY THE CONTRACTOR AT NO EXPENSE TO THE CITY.
5. ALL STORM PIPE SHALL BE PVC OR N-12 WITH DOUBLE BELLED COUPLINGS WITH O-RING TYPE GASKETS OR APPROVED EQUAL.
6. ALL STORM PIPE LATERALS TO BE A MINIMUM 10 INCHES DIAMETER WITH A MINIMUM SLOPE OF S=0.0100 UNLESS SPECIFIED OTHERWISE IN THE PLANS.
7. ALL MANHOLES LOCATED IN UNIMPROVED EASEMENTS AND RIGHT OF WAYS SHALL BE PROVIDED WITH TAMPER PROOF LIDS AND SHALL BE SET 6 INCHES ABOVE FINISHED GRADE.
8. VIDEO INSPECTION TAPES AND REPORTS MAY BE REQUIRED AT THE CITY'S DISCRETION. MANHOLE TESTING MAY BE REQUIRED AT THE CITY'S DISCRETION.



**SITE INFORMATION**

ALIGNMENT & FIELD DATA: MINISTER & GLAESER SURVEYING, INC. (360) 694-3313	Scale: AS SHOWN
SOIL TYPE(s): Hcb, PoB & PoD	Project Number: 286
SOILS TESTING BY: RAPID SOIL SOLUTIONS (603) 816-3689	Design/Drawn: JGS/BC
SITE LOCATION: CLARK COUNTY, WA	Drawing Date: MAY 2018
SITE AREA: 9.26 ACRES	Sheet 6 of 9 Sheet(s)

**NOTE:**  
Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth, & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.

**PREPARED BY:**  
STERLING DESIGN, INC.  
2208 E. EVERGREEN BLVD  
VANCOUVER, WA 98661  
PHONE (360) 758-4804  
FAX (360) 758-4808  
mailto:sterlingdesign@gn.biz


**STERLING DESIGN, INC.**

**PRELIMINARY STORMWATER MANAGEMENT PLAN**

**VALLEY VIEW ESTATES SUBDIVISION**




05/18/18




**STREET CONSTRUCTION NOTES:**

1. ENGINEERED FILL SHALL BE PLACED AND COMPACTED IN ACCORDANCE WITH THE MOST RECENTLY ADOPTED EDITION OF THE W.S.D.O.T. STANDARD SPECIFICATIONS SECTION 2-03.3(4). FOR FILL AREAS WITHIN ROADWAYS, METHOD C OF (1)(C) SHALL BE USED. FOR FILL AREAS OUTSIDE OF ROADWAYS METHOD B SHALL BE USED. ALL FILL PLACES SHALL BE VERIFIED BY GEOTECHNICAL TESTING. TEST RESULTS SHALL BE FORWARDED TO THE CITY OF CAMAS PROJECT ENGINEER.
2. MATERIALS IN SOFT SPOTS WITHIN THE ROADWAY SHALL BE REMOVED TO THE DEPTH REQUIRED TO PROVIDE A FIRM FOUNDATION AND SHALL BE BACKFILLED WITH 1-1/2 INCH MINUS CRUSHED ROCK.
3. ALL SUBGRADE TO BE PROOF ROLLED AND APPROVED BY THE CITY INSPECTOR OR BY A GEOTECHNICAL ENGINEER WITH CONSENT OF THE CITY ENGINEER. SUBGRADE FILLS ARE TO BE TESTED USING THE A.A.S.H.T.O. T-160 TEST METHOD.
4. ALL TRENCH LINES, FILL AREAS AND BASE COURSE LOCATED IN THE RIGHT-OF-WAY SHALL BE APPROVED GRANULAR MATERIAL AND SHALL MEET 80% OF A.A.S.H.T.O. T-160 COMPACTION. TRENCH LINES LOCATED WITHIN AN EXISTING ROADWAY SHALL BE PLATED OR TOPPED WITH COLD MIX GRANULAR BACKFILL OVERNIGHT IS NOT ALLOWED. PLATES SHALL HAVE COLD MIX AROUND ALL EDGES.
5. THE CONTRACTOR SHALL NOTIFY THE CITY INSPECTOR A MINIMUM OF 24 HOURS PRIOR TO SUBGRADE PROOF ROLL OR GRADE CHECK INSPECTIONS.
6. THE AGGREGATE ROAD BASE SHALL BE COMPACTED IN ACCORDANCE WITH THE MOST RECENTLY ADOPTED EDITION OF THE W.S.D.O.T. STANDARD SPECIFICATIONS SECTION 4-04.3. THE CONTRACTOR SHALL SUBMIT TEST RESULTS TO THE ENGINEER AND CITY INSPECTOR. MAXIMUM DENSITY (95%) AS DETERMINED BY A.A.S.H.T.O. T-160 TEST METHOD.
7. ASPHALT CONCRETE PAVEMENT MIX SHALL BE DESIGNED FROM A MIX FORMULA APPROVED BY W.S.D.O.T. FOR MATERIAL USED. CONTRACTOR TO PROVIDE THE CITY WITH CERTIFICATE OF COMPLIANCE FROM THE ASPHALT PAVEMENT PLANT, UNLESS OTHERWISE INDICATED.
8. THE ASPHALT CONCRETE PAVEMENT MIX SHALL BE COMPACTED IN ACCORDANCE WITH THE MOST RECENTLY ADOPTED EDITION OF THE W.S.D.O.T. STANDARD SPECIFICATIONS SECTION 5-04.3(1). CONTRACTOR SHALL SUBMIT TEST RESULTS TO THE ENGINEER AND THE CITY INSPECTOR.
9. ALL STORM SYSTEM IMPROVEMENTS AND STORMWATER DETENTION AND TREATMENT FACILITIES SHALL BE COMPLETED AND PROPERLY FUNCTIONING PRIOR TO ANY PAVING.
10. HALF STREET IMPROVEMENTS SHALL INCLUDE AN ANALYSIS OF THE EXISTING STRUCTURAL SECTION OUT TO CENTERLINE. IF FOUND TO BE SUBSTANDARD, THE DEVELOPER SHALL BE REQUIRED TO PROVIDE AN ASSOCIATE STRUCTURAL SECTION TO CENTERLINE. THIS MAY CONSIST OF A STRUCTURAL OVERLAY OR A COMPLETE STREET RECONSTRUCTION AS DETERMINED BY A GEOTECHNICAL ANALYSIS AND AS APPROVED BY THE CITY ENGINEER.



CENTERLINE CURVE DATA			
①	R=70.00ft CH=95.38ft A=104.93ft T=65.14ft EX=25.62ft Δ=85° 52' 59"	④	R=70.00ft CH=100.53ft A=112.15ft T=72.23ft EX=30.58ft Δ=91° 47' 34"
②	R=70.00ft CH=95.38ft A=104.93ft T=65.14ft EX=25.62ft Δ=85° 52' 59"	⑥	R=70.00ft CH=97.43ft A=107.77ft T=67.94ft EX=27.48ft Δ=88° 12' 26"
③	R=70.00ft CH=102.32ft A=114.74ft T=74.96ft EX=32.56ft Δ=93° 55' 09"	⑦	R=275.00ft CH=94.17ft A=54.64ft T=47.79ft EX=4.12ft Δ=19° 43' 02"




**PREPARED BY:**  
STERLING DESIGN, INC.  
2208 E EVERGREEN BLVD  
VANCOUVER, WA 98661  
(360) 891-1800  
FAX (360) 758-4988  
mailto:sterlingdesign.biz

**STERLING DESIGN, INC.**

**Sheet Description:**  
PRELIMINARY TRANSPORTATION PLAN


**Project:**  
VALLEY VIEW ESTATES SUBDIVISION



**SITE INFORMATION**

ALIGNMENT & FIELD DATA: MINISTER & GLAESER SURVEYING, INC. (360) 694-3313	Scale: AS SHOWN
SOIL TYPE(s): Hcb, PoB & PoD	Project Number: 286
SOILS TESTING BY: RAPID SOIL SOLUTIONS (603) 816-3689	Design/Drawn: JGS/BC
SITE LOCATION: CLARK COUNTY, WA	Drawing Date: MAY 2018
SITE AREA: 9.26 ACRES	Sheet 7 of 9 Sheet(s)


**NOTE:**  
Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.



**UTILITY NOTE:**  
**ALL LOTS WILL BE PROVIDED WITH PUBLIC WATER & SANITARY SEWER LATERAL**

**EXISTING WELLS, SEPTIC TANKS AND DRAIN FIELDS SHALL BE ABANDONED IN ACCORDANCE TO STATE GUIDELINES**

**UTILITY NOTE:**  
**ALL UTILITIES FOR LOT 35 ARE EXISTING AND INSTALLED**



**SEPTIC TANK EFFLUENT FILTER (S.T.E.F.) NOTES:**

1. ALL TRENCH EXCAVATION AND PIPE INSTALLATION SHALL CONFORM TO THE MOST RECENTLY ADOPTED EDITION OF THE W.S.D.O.T. STANDARD SPECIFICATIONS SECTION 7-08.3(1) AND SECTION 7-08.3(2). ALL EXCESS MATERIAL FROM THE TRENCH EXCAVATION SHALL BE DISPOSED OF ON AN APPROVED SITE.
2. PIPE BEDDING, PIPE ZONE MATERIAL AND TRENCH BACKFILL SHALL BE AN APPROVED GRANULAR MATERIAL OF EITHER WASHED SCREENINGS OR 5/8" NO.1 MINUS CRUSHED ROCK. SAND BACKFILL IS NOT ALLOWED.
3. TRENCH COMPACTION SHALL CONFORM TO THE MOST RECENTLY ADOPTED EDITION OF THE W.S.D.O.T. STANDARD SPECIFICATIONS SECTION 7-08.3(3). CONTRACTOR TO DETERMINE THE TYPE OF EQUIPMENT AND METHOD TO USE TO ACHIEVE THE REQUIRED COMPACTION. EACH LIFT SHALL BE COMPACTED TO A MINIMUM OF 95 PERCENT OF THE MAXIMUM DENSITY AS DETERMINED BY THE A.A.S.H.T.O. T-180 TEST METHOD.
4. SETTLEMENT OF THE FINISHED SURFACE WITHIN THE WARRANTY PERIOD SHALL BE CONSIDERED TO BE A RESULT OF IMPROPER COMPACTION AND SHALL BE PROMPTLY REPAIRED BY THE CONTRACTOR AT NO EXPENSE TO THE CITY.
5. ALL PIPE AND FITTINGS SHALL BE PVC GASKETED PIPE, ASTM D2241 PRESSURE RATED FOR 200 PSI UNLESS OTHERWISE NOTED.
6. PIPE SHALL BE BEDDED WITH A MINIMUM OF 4 INCHES OF APPROVED GRANULAR MATERIAL.
7. 14 GAUGE GREEN HOPE (WMPF) INSULATED COPPER GLAD STEEL TONING WIRE SHALL BE PLACED DIRECTLY OVER ALL SEWER MAINS AND SERVICE LATERALS. THE TONING WIRE SHALL BE ACCESSIBLE AT ALL SERVICE LATERAL MARKER BOARDS, A.A.R.V.'S, RISERS, AND CLEANOUTS. ALL SPICES AND CONNECTIONS TO TONING WIRE SHALL BE PROTECTED WITH KING GEL CAPS, 3M DBY DIRECT BURY, OR OTHER APPROVED EQUAL CONNECTORS. ALL TONING WIRE CONNECTIONS SHALL BE TONE TESTED PRIOR TO INSTALLING BASE ROCK.
8. MAINLINE CLEANOUTS SHALL BE SPACED A MAXIMUM OF 400 FEET AND/OR FOR EVERY 90 DEGREES OF BENDS.
9. ALL PIPE AND FITTINGS SHALL BE AIR TESTED AT FIVE P.S.I. FOR ONE MINUTE PER EVERY 100 FEET OF MAINLINE.
10. SANITARY SERVICE LATERAL ENDS SHALL EXTEND 6 FEET PAST THE STREET RIGHT-OF-WAY LINE OR AS SHOWN ON THE PLANS AND MARKED WITH A 10 FOOT LONG 2 X 4.
11. ALL SANITARY LINES SHALL BE INSTALLED WITH A MINIMUM COVER OF 6 FEET AND A MINIMUM GRADE OF 6.4% UNLESS OTHERWISE SHOWN ON THE PLANS.
12. ALL S.T.E.F. SANITARY SEWER LATERALS SHALL BE INSTALLED IN A DEDICATED TRENCH FROM THE SERVICE CONNECTION TO THE TANK. BACKFILL SHALL BE APPROVED GRANULAR MATERIAL OR AS APPROVED BY THE WATER/SEWER DEPARTMENT.
13. ALL TANKS WITH A BURY DEPTH OVER 4'-0" MUST HAVE H-20 RATED TANK LID.

REV. NO.	DATE	BY	APPR.	DETAIL NO.
1	5/7/21	SD	JC	ST1
2	12/1/21	SD	JC	
3	10/21/24	SD	JC	

CITY OF CAMAS - SANITARY DETAIL  
 SEWER CONSTRUCTION NOTES  
 DATE: 10-21-24  
 NOT TO SCALE

**WATER CONSTRUCTION NOTES:**

1. ALL TRENCH EXCAVATION AND PIPE INSTALLATION SHALL CONFORM TO THE MOST CURRENT A.W.W.A. STANDARDS AND THE MOST RECENTLY ADOPTED EDITION OF THE W.S.D.O.T. STANDARD SPECIFICATIONS SECTION 7-08.3(1) AND SECTION 7-20.3(2). ALL EXCESS MATERIAL FROM THE TRENCH EXCAVATION SHALL BE LOADED DIRECTLY INTO A DUMP TRUCK AND DISPOSED OF AT AN APPROVED SITE.
2. PIPE BEDDING, PIPE ZONE MATERIAL, AND TRENCH BACKFILL SHALL BE AN APPROVED GRANULAR MATERIAL OF EITHER WASHED SCREENINGS OR 5/8" INCH MINUS CRUSHED ROCK. SAND BACKFILL IS NOT ALLOWED.
3. TRENCH COMPACTION SHALL CONFORM TO THE MOST RECENTLY ADOPTED EDITION OF THE W.S.D.O.T. STANDARD SPECIFICATIONS SECTION 7-08.3(3). CONTRACTOR TO DETERMINE THE TYPE OF EQUIPMENT AND METHOD USED TO ACHIEVE THE REQUIRED COMPACTION AND BE APPROVED BY THE CITY OF CAMAS. EACH LIFT SHALL BE COMPACTED TO A MINIMUM OF 95 PERCENT OF THE MAXIMUM DENSITY AS DETERMINED BY THE A.A.S.H.T.O. T-180 TEST METHOD.
4. SETTLEMENT OF THE FINISHED SURFACE WITHIN THE WARRANTY PERIOD SHALL BE CONSIDERED TO BE A RESULT OF IMPROPER COMPACTION AND SHALL BE PROMPTLY REPAIRED BY THE CONTRACTOR AT NO EXPENSE TO THE CITY.
5. ALL VALVES 10 INCHES OR LESS IN DIAMETER SHALL BE A.W.W.A. APPROVED RESILIENT WEDGE GATE VALVES, BUZZLE TRIT AT 200PSI, HANG NON-RISING STEMS, AND OPEN BY TURNING TO THE LEFT. PROVIDE A 2 INCH SQUARE NUT TO CONFORM TO A.W.W.A. C-504. ALL VALVES 12 INCHES OR LARGER IN DIAMETER SHALL BE A.W.W.A. APPROVED BUTTERFLY VALVES.
6. ALL WATER PIPE 12 INCHES OR LESS IN DIAMETER SHALL BE DUCTILE IRON CLASS 52 PIPE. ALL WATER PIPE 14 INCHES IN DIAMETER AND LARGER SHALL BE DUCTILE IRON CLASS 51 PIPE. RUBBER GASKET TYPE SHALL BE U.S. PIPE TYPON OR APPROVED EQUAL. ALL FITTINGS SHALL BE DUCTILE IRON AND SHALL CONFORM TO THE A.W.W.A. STANDARD C-110.
7. ALL TEES, FLANGES, CAPS, BENDS AND OFFSETS, AS WELL AS ALL OTHER APPURTENANCES WHICH ARE SUBJECT TO UNBALANCED THRUST, SHALL BE PROPERLY BRACED BY ONE OF THE FOLLOWING METHODS:  
 A. CONCRETE THRUST BLOCKING - AS DETAILED IN THE PLANS, SHALL BE PLACED AT BENDS, TEES, DEAD ENDS AND CROSSINGS. BLOCKING SHALL BE 2000 P.S.I. CONCRETE, PLACED IN PLACE. CONCRETE BLOCKING SHALL BE AGAINST SOLID UNDISTURBED EARTH AT THE SIDES AND BOTTOM OF THE TRENCH EXCAVATION AND SHALL BE SHAPED SO AS NOT TO OBSTRUCT ACCESS TO THE JOINTS OF THE PIPE. 6 MIL. PLASTIC SHALL BE USED TO INSULATE PIPE.  
 B. MECHANICAL JOINT RESTRAINT-USE "EIBA IRON SERIES 1100 MEGA LUG MECHANICAL JOINT THRUST RESTRAINT" OR APPROVED EQUAL. CONTRACTOR TO RESTRAIN THE MINIMUM REQUIRED PIPE LENGTH WITH "FIELD-LOCK" GASKETS OR APPROVED EQUAL.
8. ALL WATER MAINS SHALL BE TESTED AT 200PSI IN ACCORDANCE WITH SECTION 7-09.3(23) OF THE STANDARD SPECIFICATIONS. THE CITY SHALL BE NOTIFIED 48 HOURS IN ADVANCE OF ACCEPTANCE TESTING. MAXIMUM LENGTH OF PIPE TO BE TESTED AT ANY ONE TIME IS 1000 FT.
9. CHLORINATION SHALL BE PERFORMED IN ACCORDANCE WITH SECTION 7-09.3(24) OF THE STANDARD SPECIFICATIONS. CITY INSPECTOR WILL TAKE SAMPLES AND DELIVER TO LABORATORY FOR BACTERIA TESTING. NEGATIVE SAMPLE RESULTS SHALL BE CONFIRMED, PRIOR TO PRESSURE TESTING, DECHLORINATION OR DISPOSAL TO SANITARY MAIN MAY BE REQUIRED.
10. APPROPRIATE DISPOSAL AND/OR DECHLORINATION OF FLUSHED WATER DURING BLOWOFF IS THE RESPONSIBILITY OF THE CONTRACTOR. METHOD USED SHALL BE APPROVED BY CITY AND OTHER REGULATING AUTHORITIES.
11. WATER MAIN TO HAVE A MINIMUM COVER OF 30 INCHES. WATER SERVICES TO HAVE A MINIMUM 24" OF COVER.
12. ALL EXISTING VALVES TO BE OPERATED BY CITY OF CAMAS WATER/SEWER DEPARTMENT PERSONNEL ONLY.
13. NO CONNECTIONS TO EXISTING WATER MAINS SHALL BE MADE PRIOR TO SATISFACTORY PRESSURE TESTING, DISINFECTION, AND THE CONFIRMATION OF A NEGATIVE BACTERIA TEST.

REV. NO.	DATE	BY	APPR.	DETAIL NO.
1	7/17/08	SD	RES1071	W1
2	5/7/21	SD	JC	
3	12/1/21	SD	JC	

CITY OF CAMAS - WATER DETAIL  
 WATER CONSTRUCTION NOTES  
 DATE: 1-4-24  
 NOT TO SCALE

**SITE INFORMATION**

ALIGNMENT & FIELD DATA: <b>MINISTER &amp; GLAESER SURVEYING, INC. (360) 694-3313</b>	Scale: AS SHOWN
SOIL TYPE(s): HYDROLOGIC GROUP: <b>C</b> AASHTO CLASSIFICATION: <b>A-4</b>	Project Number: <b>286</b>
SOILS TESTING BY: <b>RAPID SOIL SOLUTIONS (603) 816-3689</b> DATE: <b>MARCH 2014</b>	Design/Drawn: <b>JGS/BC</b>
SITE LOCATION: <b>CLARK COUNTY, WA</b> APPROX. SURFACE ELEV.: <b>385'-468'</b>	Drawing Date: <b>MAY 2018</b>
SITE AREA: <b>9.26 ACRES</b>	FILENAME: <b>286/Preliminary.pro</b>


**NOTE:**  
 Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth, & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.

**PREPARED BY:**  
 STERLING DESIGN, INC.  
 2208 E. EVERGREEN BLVD  
 WACONAVILLE, WA 98601  
 PH: (509) 841-1000  
 FAX: (509) 758-4888  
 mail@sterlingdesign.com




**STERLING DESIGN, INC.**

**PRELIMINARY UTILITY PLAN**

**Project:**  
**VALLEY VIEW ESTATES SUBDIVISION**



05/18/18  
 Sheet 8 of 9 Sheet(s)



PREPARED BY:  
STERLING DESIGN, INC.  
2208 EVERGREEN BLVD  
MUNICIPAL, WA 98001  
PHONE (360) 738-4984  
FAX (360) 738-4983  
mailto:sterlingdesign.biz

**STERLING DESIGN, INC.**

Sheet Description:  
**PRELIMINARY  
LANDSCAPE & LIGHTING  
PLAN**

Project:  
**VALLEY VIEW ESTATES  
SUBDIVISION**



**SITE INFORMATION**

ALIGNMENT & FIELD DATA: <b>MINISTER &amp; GLAESER SURVEYING, INC. (360) 694-3313</b>	Scale: AS SHOWN
SOIL TYPE(s): HYDROLOGIC GROUP: <b>Hcb, PoB &amp; PoD</b> AASHTO CLASSIFICATION: <b>C</b>	Project Number: <b>286</b>
SOILS TESTING BY: <b>RAPID SOIL SOLUTIONS (503) 816-3889</b> DATE: <b>MARCH 2014</b>	Design/Drawn: <b>JGS/JC</b>
SITE LOCATION: <b>CLARK COUNTY, WA</b> APPROX. SURFACE ELEV.: <b>385'-468'</b>	Drawing Date: <b>MAY 2018</b>
SITE AREA: <b>9.26 ACRES</b>	FILENAME: <b>286:/Preliminary.pro</b> Sheet 9 of 9 Sheet(s)

NOTE:  
Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.

# DEVELOPER'S PACKET

## Produced By:

Clark County Geographic Information System (GIS)



## For:

Sterling Design, Inc.

## Subject Property Account Number(s):

125635000

125646000

PDF # 196986

Printed: March 26, 2018


Expires: March 26, 2019

# Table of Contents

---

General Location	1
Property Information Fact Sheet	2
Elevation Contours	3
2016 Aerial Photography	4
2016 Aerial Photography with Elevation Contours	5
Zoning Designations	6
Comprehensive Plan Designations	7
Arterials, C-Tran Bus Routes, Parks & Trails	8
Water, Sewer, and Storm Systems	9
Water Systems	10
Hydrant Fire Flow Details	11
Soil Types	12
Environmental Constraints I	13
Environmental Constraints II	14
Adjacent Development	15
Quarter Section Parcels	16





**CLARK COUNTY, WASHINGTON**

Geographic Information System

0 1,000 2,000 Feet


Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.

### General Location

Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

Location of Subject Property(s)

Printed on: March 26, 2018



# Property Information Fact Sheet

## Mailing Information:

Account No.: 125635000, 125646000  
Owner: FIRESTONE STAN  
Address: PO BOX 61928  
C/S/Z: VANCOUVER, WA 98666

**Assessed Parcel Size:** 9.26 Ac

**Property Type:** Multiple Property Types

---

## PARCEL LOCATION FINDINGS:

**Quarter Section(s):** NW 1/4,S08,T1N,R3E,  
NE 1/4,S08,T1N,R3E

**Municipal Jurisdiction:** Camas

**Urban Growth Area:** Camas

**Zoning:** R-7.5

**Zoning Overlay:** No Mapping Indicators

**Comprehensive Plan Designation:** SFM

**Trans. Impact Fee Area:** Camas: Current,  
Camas UGA: End Date Dec. 31, 2016

**Park Impact Fee District:** No Mapping Indicators

**Neighborhood Association:** No Mapping Indicators

**School District:** Camas

**Elementary School:** Prune Hill

**Junior High School:** Skyridge Middle

**Senior High School:** Camas

**Fire District:** Camas Washougal FD

**Sewer District:** Camas

**Water District:** Camas

**Wildland:** No Mapping Indicators

**Trans. Analysis Zone:** 396

**Trans. Management Zone:** 192nd\_Ave\_from\_Brady\_to\_SE\_1st\_ST

**Historic Sites:** No Mapping Indicators

---

## ENVIRONMENTAL CONSTRAINTS:

**Soil Type(s):** HcB, 17.8% of parcel  
PoB, 29.0%  
PoD, 31.6%  
PoE, 21.6%

**Hydric Soils:** Non-Hydric, 100.0% of parcel

**Flood Zone Designation:** Outside Flood Area

**Liquefaction Susceptibility:** Bedrock

**NEHRP:** B

**Slope:** 0 - 5 percent, 4.8% of parcel  
10 - 15 percent, 35.3%  
15 - 25 percent, 22.6%  
25 - 40 percent, 0.6%  
5 - 10 percent, 36.8%

**Slopes > 25% + 100 ft buffer:** No Mapping Indicators

**Unstable Slopes + 100 ft buffer:** No Mapping Indicators


**200 ft Shoreline buffer:** No Mapping Indicators

**Special Wellhead Protection Area:** No Mapping Indicators

**Habitat Conservation:** Riparian Priority Habitat

**Archeological Predictive:** Low-Moderate, 19.6% of parcel  
Moderate, 60.5%  
Moderate-High, 20.0%

**Archeological Site Buffers:** No Mapping Indicators




### Elevation Contours

Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

- Subject Property(s)
- Public Road
- Transportation or Major Utility Easement
- 10' Elevation Contours
- 2' Elevation Contours

Printed on: March 26, 2018



Geographic Information System



Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.



## 2016 Aerial Photography

Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

Printed on: March 26, 2018



Geographic Information System

0 200 400 Feet

 Subject Property(s)

13106	13105	13104
13107	13108	13109
	13117	13116

Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.



**Geographic Information System**

0 100 200 Feet

Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.


## 2016 Aerial Photography with Elevation Contours

Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

- Subject Property(s)
- 2' Elevation Contours

Printed on: March 26, 2018


13106	13105	13104
13107	///	13109
	13117	13116



### Zoning Designations


Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666



Printed on: March 26, 2018



Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.

- Subject Property(s)
- Public Road
- Transportation or Major Utility Easement
- Zoning Boundary
- Urban Holding - 10 (UH-10)
- Urban Holding - 20 (UH-20)
- Urban Holding - 40 (UH-40)
- Surface Mining Overlay District






Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.


### Comprehensive Plan Designations

Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

- Subject Property(s)
- Public Road
- Transportation or Major Utility Easement
- Comprehensive Plan Boundary
- Urban Reserve
- Industrial Reserve
- Railroad Industrial Reserve
- Mining
- Rural Center Mixed Use
- Columbia River Gorge Scenic Area

Printed on: March 26, 2018







# Arterials, C-Tran Bus Routes, Parks & Trails

Printed on: March 26, 2018


Account: 125635000, 125646000  
Owner: FIRESTONE STAN  
Address: PO BOX 61928  
C/S/Z: VANCOUVER, WA 98666



Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.

- Subject Property(s)
- Public Road
- Transportation or Major Utility Easement
- Parks
- Trail
- C-Tran Route
- Principal Arterial
- Minor Arterial
- Collector
- Rural Major Collector
- Proposed Arterial
- Scenic Highway
- Rural Minor Collector
- State Route
- Other
- Proposed Arterial
- Scenic Highway





CLARK COUNTY, WASHINGTON  
Geographic Information System

0 200 400 Feet

Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.


### Water, Sewer, and Storm Systems

Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

- Subject Property(s)
- Public Road
- Transportation or Major Utility Easement
- Water Lines
- Sewer Lines
- Storm Water Lines
- 1-year Wellhead ZOC
- 5-year Wellhead ZOC
- 10-year Wellhead ZOC
- Hydrants

Printed on: March 26, 2018

13106	13105	13104
13107	13108	13109
	13117	13116



### Water Systems


Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

Printed on: March 26, 2018

Geographic Information System

0 200 400 Feet

- Subject Property(s)
- Public Road
- Water District Boundary
- Unknown Size Water Line
- < 10" Water Line
- 10-20" Water Line
- > 20" Water Line
- No Flow Data Hydrant
- 0 - 499 GPM at 20 PSI
- 500 - 999 GPM at 20 PSI
- > 1000 - 1749 GPM at 20 PSI
- > 1750 GPM at 20 PSI
- Hydrant > 500' from parcel(s)



Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.

# Hydrant Fire Flow Details

Account No.: 125635000, 125646000  
Owner: FIRESTONE STAN  
Address: PO BOX 61928  
C/S/Z: VANCOUVER, WA 98666

---

Water District(s)	Hydrant Data Update	Project Site Provider
-------------------	---------------------	-----------------------


---

Camas (There is currently no hydrant data for this district.)

Vancouver                      January 1, 2017                      Adjacent District

## HYDRANT INFORMATION:

Hydrant ID	Hydrant Owner	Main Diameter	Flow at 20 PSI	Test Date	Distance to site
Unknown	Unknown	0.0"	No Data	None	18 ft
Unknown	Unknown	0.0"	No Data	None	134 ft
Unknown	Unknown	0.0"	No Data	None	214 ft
Unknown	Unknown	0.0"	No Data	None	355 ft
Unknown	Unknown	0.0"	No Data	None	452 ft
Unknown	Unknown	0.0"	No Data	None	470 ft
Unknown	Unknown	0.0"	No Data	None	484 ft




### Soil Types

Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

Printed on: March 26, 2018


- Subject Property(s)
- Public Road
- Transportation or Major Utility Easement
- Soil Type Boundary



Geographic Information System

0 200 400 Feet

Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.




## Environmental Constraints I

Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666


Printed on: March 26, 2018

- Subject Property(s)
- Public Road
- Transportation or Major Utility Easement
- Hydric Soils
- Wetland Inventory
- Non-Riparian Habitat or Species Area
- CARA Category 1
- 100 year Floodplains
- Floodway
- Shorelines
- Stream



Geographic Information System  
 0 200 400 Feet


Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.



## Environmental Constraints II


Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666


Printed on: March 26, 2018



Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.

- Subject Property(s)
- Public Road
- Transportation or Major Utility Easement
- Slopes > 15%
- Potentially Unstable Slope
- Historic or Active Landslide
- Severe Erosion Hazard Areas
- CCHR Historic Site
- NRHP Historic Site
- INV Historic Site





### Adjacent Development

Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

Printed on: March 26, 2018






Geographic Information System



Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.

- Subject Property(s)
- Public Road
- Transportation or Major Utility Easement
- Adjacent Development






Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.

### Quarter Section Parcels

Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

Printed on: March 26, 2018

- Subdivision Lines
- Donation Land Claim
- Section Quarters
- City Boundaries
- Subject Property(s)
- Road Right of Way - Actual Road May not Exist
- Transportation or Major Utility Easement







## Notice of Proposed Development Valley View Estates Subdivision


The Applicant is on file with the City of Camas for a review of a subdivision and SEPA to establish a residential subdivision. For information regarding this project contact:

Applicant Contact:

**Joel Stirling**  
360-759-1794

City Contact:

**Lauren Hollenbeck**  
360-817-7253



Public Hearing Schedule:

Hearing Date/Time: **10/18/18**

Hearing Location: **CITY HALL**  
**5PM**

**WAC 197-11-960 Environmental checklist.**

## ENVIRONMENTAL CHECKLIST

*Purpose of checklist:*

The State Environmental Policy Act (SEPA), chapter 43.21C RCW, requires all governmental agencies to consider the environmental impacts of a proposal before making decisions. An environmental impact statement (EIS) must be prepared for all proposals with probable significant adverse impacts on the quality of the environment. The purpose of this checklist is to provide information to help you and the agency identify impacts from your proposal (and to reduce or avoid impacts from the proposal, if it can be done) and to help the agency decide whether an EIS is required.

*Instructions for applicants:*

This environmental checklist asks you to describe some basic information about your proposal. Governmental agencies use this checklist to determine whether the environmental impacts of your proposal are significant, requiring preparation of an EIS. Answer the questions briefly, with the most precise information known, or give the best description you can.

You must answer each question accurately and carefully, to the best of your knowledge. In most cases, you should be able to answer the questions from your own observations or project plans without the need to hire experts. If you really do not know the answer, or if a question does not apply to your proposal, write "do not know" or "does not apply." Complete answers to the questions now may avoid unnecessary delays later.

Some questions ask about governmental regulations, such as zoning, shoreline, and landmark designations. Answer these questions if you can. If you have problems, the governmental agencies can assist you.

The checklist questions apply to all parts of your proposal, even if you plan to do them over a period of time or on different parcels of land. Attach any additional information that will help describe your proposal or its environmental effects. The agency to which you submit this checklist may ask you to explain your answers or provide additional information reasonably related to determining if there may be significant adverse impact.

*Use of checklist for nonproject proposals:*

Complete this checklist for nonproject proposals, even though questions may be answered "does not apply." IN ADDITION, complete the SUPPLEMENTAL SHEET FOR NONPROJECT ACTIONS (part D).

For nonproject actions, the references in the checklist to the words "project," "applicant," and "property or site" should be read as "proposal," "proposer," and "affected geographic area," respectively.

A. BACKGROUND

1. Name of proposed project, if applicable: **Valley View Estates Subdivision**

2. Name of applicant: **STERLING DESIGN, INC.**

3. Address and phone number of applicant and contact person:

**2208 E. Evergreen Blvd.**

**Vancouver, WA 98661**

**contact: Joel Stirling**

4. Date checklist prepared: **05-17-18**

5. Agency requesting checklist: **City of Camas**

6. Proposed timing or schedule (including phasing, if applicable):

**Construction in the Summer of 2019**

7. Do you have any plans for future additions, expansion, or further activity related to or connected with this proposal? If yes, explain.

**No**

8. List any environmental information you know about that has been prepared, or will be prepared, directly related to this proposal. **A Wetland Pre-determination was prepared for the property by Ecological Land Services, Inc. No wetlands were found on the property and no adjacent wetland buffers extend onto the property.**

9. Do you know whether applications are pending for governmental approvals of other proposals directly affecting the property covered by your proposal? If yes, explain. **No.**

10. List any government approvals or permits that will be needed for your proposal, if known.

**Subdivision Approval for Plat Recording and infrastructure installation construction plans will be approved by the City of Camas for the project.**

11. Give brief, complete description of your proposal, including the proposed uses and the size of the project and site. There are several questions later in this checklist that ask you to describe certain aspects of your proposal. You do not need to repeat those answers on this page.

**The Valley View Estates Subdivision is a proposal to subdivide approximately 9.26 acres of property zoned for residential development within the City of Camas R-7.5 zoning district. The property will be divided into a total of thirty two (36) new single family residential building lots. One (1) existing single family home will be removed during the subdivision infrastructure installation process.**

12. Location of the proposal. Give sufficient information for a person to understand the precise location of your proposed project, including a street address, if any, and section, township, and range, if known. If a proposal would occur over a range of area, provide the range or boundaries of the site(s). Provide a legal description, site plan, vicinity map, and topographic map, if reasonably available. While you should submit any plans required by the agency, you are not required to duplicate maps or detailed plans submitted with any permit applications related to this checklist.

**The property address is 20109 SE 40th, Camas, WA 98607 and is located the NW 1/4 of Section 8, T1N., R3E**

B. ENVIRONMENTAL ELEMENTS

1. Earth

- a. General description of the site (circle one): Flat, rolling, hilly, steep slopes, mountainous, other . . . . .
- b. What is the steepest slope on the site (approximate percent slope)? **15%**
- c. What general types of soils are found on the site (for example, clay, sand, gravel, peat, muck)? If you know the classification of agricultural soils, specify them and note any prime farmland. **Soil types on site are mapped as Hesson Clay Loam (HcB) & Powell Silt Loam(s) (PoB) & (PoD). It is unknown if the property was ever used for agriculture.**
- d. Are there surface indications or history of unstable soils in the immediate vicinity? If so, describe. **Unknown. A geotechnical study has been completed on the property and development is feasible.**
- e. Describe the purpose, type, and approximate quantities of any filling or grading proposed. Indicate source of fill. **The property will be graded as needed for roads, single family building sites, utility installation and stormwater management facilities. It is likely that up to 30,000 cu.yds. of earth will be graded, moved, cut and filled. All grading activities will be monitored by a geotechnical engineer licensed in the State of Washington and certified to be constructed as needed for future infrastructure installation.**
- f. Could erosion occur as a result of clearing, construction, or use? If so, generally describe. **Yes, prior to construction a grading and erosion control plan will be approved by the City of Camas and will be implemented during the construction process to limit the potential erosion on the project.**
- g. About what percent of the site will be covered with impervious surfaces after project construction (for example, asphalt or buildings)? **50%**
- h. Proposed measures to reduce or control erosion, or other impacts to the earth, if any:  
**Approval of a grading and erosion control plan by the City of Camas.**
- a. Air
- a. What types of emissions to the air would result from the proposal (i.e., dust, automobile, odors, industrial wood smoke) during construction and when the project is completed? If any, generally describe and give approximate quantities if known.  
**Construction vehicles will emit exhaust during the construction phase of the project and will likely create dust during dry periods. Following home construction the completed project will have typical single family home emissions from all 36 single family homes.**
- b. Are there any off-site sources of emissions or odor that may affect your proposal? If so, generally describe.  
**No**

c. Proposed measures to reduce or control emissions or other impacts to air, if any:

**None**

3. **Water**

a. Surface:

1) Is there any surface water body on or in the immediate vicinity of the site (including year-round and seasonal streams, saltwater, lakes, ponds, wetlands)? If yes, describe type and provide names. If appropriate, state what stream or river it flows into.

**No**

2) Will the project require any work over, in, or adjacent to (within 200 feet) the described waters? If yes, please describe and attach available plans.

**N/A**

3) Estimate the amount of fill and dredge material that would be placed in or removed from surface water or wetlands and indicate the area of the site that would be affected. Indicate the source of fill material.

**N/A**

4) Will the proposal require surface water withdrawals or diversions? Give general description, purpose, and approximate quantities if known.

**No**

5) Does the proposal lie within a 100-year floodplain? If so, note location on the site plan.

**No**

6) Does the proposal involve any discharges of waste materials to surface waters? If so, describe the type of waste and anticipated volume of discharge.

**No**

b. Ground:

1) Will ground water be withdrawn, or will water be discharged to ground water? Give general description, purpose, and approximate quantities if known.

**No other than natural infiltration of stormwater that will occur within the yard areas of the future home sites and limited natural infiltration of stormwater within the stormwater facilities.**

2) Describe waste material that will be discharged into the ground from septic tanks or other sources, if any (for example: Domestic sewage; industrial, containing the following chemicals. . . ; agricultural; etc.). Describe the general size of the system, the number of such systems, the number of houses to be served (if applicable), or the number of animals or humans the system(s) are expected to serve. **None**

c. Water runoff (including stormwater):

- 1) Describe the source of runoff (including storm water) and method of collection and disposal, if any (include quantities, if known). Where will this water flow? Will this water flow into other waters? If so, describe.

**Stormwater runoff from the single family homes and the new streets will be collected and conveyed to stormwater management facilities for both water quality and quantity control as required by the City of Camas and the Washington State Department of Ecology. Stormwater facilities have been designed utilizing the Western Washington Hydrology Manual and discharge from the facilities will flow south to the natural drainage routes. There is a seasonal drainage corridor located approximately 220 L.F. South of the project which will convey the controlled stormwater south where it eventually flows into the Columbia River.**

- 2) Could waste materials enter ground or surface waters? If so, generally describe.

**No. The proposed stormwater management facilities are designed to limit the potential for waste materials from the single-family residences and the public road surfaces to leave the property. Stormwater facilities will be maintained regularly as needed.**

d. Proposed measures to reduce or control surface, ground, and runoff water impacts, if any:

**Stormwater management facilities will be installed with the project and maintained in perpetuity with the completed homes.**

4. Plants

- a. Check or circle types of vegetation found on the site:

\_\_\_\_\_ deciduous tree: alder, maple, aspen, **other**  
\_\_\_\_\_ evergreen tree: **fir**, cedar, pine, other  
\_\_\_\_\_ **shrubs**  
\_\_\_\_\_ **grass**  
\_\_\_\_\_ **pasture**  
\_\_\_\_\_ crop or grain  
\_\_\_\_\_ wet soil plants: cattail, buttercup, bullrush, skunk cabbage, other  
\_\_\_\_\_ water plants: water lily, eelgrass, milfoil, other  
\_\_\_\_\_ other types of vegetation

- b. What kind and amount of vegetation will be removed or altered?

**All existing vegetation will likely be removed during the grading and infrastructure installation processes but any existing vegetation that can be retained will be utilized for erosion control measures.**

- c. List threatened or endangered species known to be on or near the site.

**None known**

- d. Proposed landscaping, use of native plants, or other measures to preserve or enhance vegetation on the site, if any: **None planned however existing vegetation will be left as much as possible during grading and infrastructure installation for erosion control.**

5. **Animals**

- a. Circle any birds and animals which have been observed on or near the site or are known to be on or near the site:

birds: hawk, heron, eagle, **songbirds**, other:

mammals: **deer**, bear, elk, beaver, other:

fish: bass, salmon, trout, herring, shellfish, other:

- b. List any threatened or endangered species known to be on or near the site. **None known**

- c. Is the site part of a migration route? If so, explain.

**It is likely that birds migrate within the vicinity of the property, as they do throughout the City of Camas region, however the site is not being utilized as a destination or nesting site for migrating birds.**

- d. Proposed measures to preserve or enhance wildlife, if any: **None**

6. **Energy and natural resources**

- a. What kinds of energy (electric, natural gas, oil, wood stove, solar) will be used to meet the completed project's energy needs? Describe whether it will be used for heating, manufacturing, etc.

**Completed single family homes will utilize electricity and natural gas for the typical energy needs of single family homes.**

- b. Would your project affect the potential use of solar energy by adjacent properties?

If so, generally describe.

**No**

- c. What kinds of energy conservation features are included in the plans of this proposal?

List other proposed measures to reduce or control energy impacts, if any:

**All single family homes will obtain building permits from the City of Camas prior to construction and will be designed to comply with all required energy codes.**

7. **Environmental health**

- a. Are there any environmental health hazards, including exposure to toxic chemicals, risk of fire and explosion, spill, or hazardous waste, that could occur as a result of this proposal?

If so, describe. **No. Project is for single family homes.**

- 1) Describe special emergency services that might be required.

**None, project will only need typical emergency services required for single family homes.**

2) Proposed measures to reduce or control environmental health hazards, if any:

**All single family homes will be connected to City of Camas water and sanitary sewer systems.**

b. Noise

1) What types of noise exist in the area which may affect your project (for example: traffic, equipment, operation, other)?

**There are public roads that serve the proposed project which generate traffic noises. There is an adjacent property to the West that is currently being developed for single family housing. During construction of the single family homes and road infrastructure there will be noise from construction equipment.**

2) What types and levels of noise would be created by or associated with the project on a short-term or a long-term basis (for example: traffic, construction, operation, other)? Indicate what hours noise would come from the site.

**During construction of the project infrastructure and single family homes there will be noise from construction. Following home build out there will be typical single family home noises which include but are not limited to traffic.**

3) Proposed measures to reduce or control noise impacts, if any:

**None**

8. Land and shoreline use

a. What is the current use of the site and adjacent properties? **The site currently has one (1) single-family home on it with a large area of underdeveloped property.**

b. Has the site been used for agriculture? If so, describe. **It is unknown if the property has ever been used for agriculture but it is not likely due to the slope of the property.**

c. Describe any structures on the site.

**There is one (1) single family home on the property.**

d. Will any structures be demolished? If so, what?

**Yes, the single family home will be removed.**

e. What is the current zoning classification of the site?

**City of Camas zoning district R-7.5**

f. What is the current comprehensive plan designation of the site?

**SFM**

g. If applicable, what is the current shoreline master program designation of the site?

**N/A**



h. Has any part of the site been classified as an "environmentally sensitive" area? If so, specify.

**No**

i. Approximately how many people would reside or work in the completed project?

**Thirty six (36) Single family homes will be constructed within the project. Based on the 2010 Census of the City of Camas the average household size was 2.91 therefore a total of approximately 104.76 people will reside within the completed project.**

j. Approximately how many people would the completed project displace?

**One (1) single family home will be destroyed as part of the project which will displace one (1) household of 2.91 people.**

k. Proposed measures to avoid or reduce displacement impacts, if any: **None**

l. Proposed measures to ensure the proposal is compatible with existing and projected land uses and plans, if any: **Approval through the City of Camas review and approval processes.**

#### 9. Housing

a. Approximately how many units would be provided, if any? Indicate whether high, middle, or low-income housing.

**Thirty six (36) middle income homes will be constructed within the completed project.**

b. Approximately how many units, if any, would be eliminated? Indicate whether high, middle, or low-income housing.

**One (1) middle income home will be removed during the project construction.**

c. Proposed measures to reduce or control housing impacts, if any: **None**

#### 10. Aesthetics

a. What is the tallest height of any proposed structure(s), not including antennas; what is the principal exterior building material(s) proposed? **City of Camas Building Code limits structures to 35' in height**

b. What views in the immediate vicinity would be altered or obstructed? **None**

c. Proposed measures to reduce or control aesthetic impacts, if any: **None**

#### 11. Light and glare

a. What type of light or glare will the proposal produce? What time of day would it mainly occur? **Street lights and vehicle lights at night along with lighting typically associated with single family uses.**

b. Could light or glare from the finished project be a safety hazard or interfere with views? **No**

c. What existing off-site sources of light or glare may affect your proposal? **Other single family homes & public streets.**

d. Proposed measures to reduce or control light and glare impacts, if any: **None**

## 12. Recreation

a. What designated and informal recreational opportunities are in the immediate vicinity?  
**City of Camas public walking trails.**

b. Would the proposed project displace any existing recreational uses? If so, describe.  
**No**

c. Proposed measures to reduce or control impacts on recreation, including recreation opportunities to be provided by the project or applicant, if any: **The project will continue a public trail through the project .**

## 13. Historic and cultural preservation

a. Are there any places or objects listed on, or proposed for, national, state, or local preservation registers known to be on or next to the site? If so, generally describe. **No**

b. Generally describe any landmarks or evidence of historic, archaeological, scientific, or cultural importance known to be on or next to the site. **None**

c. Proposed measures to reduce or control impacts, if any: **An archaeological pre-determination was completed at the property and a recommendation of "no further work needed" was sent to the Washington State Department of Archaeology and Historic Preservation (DAHP). DAHP concurred that no further work is needed at the property.**

## 14. Transportation

a. Identify public streets and highways serving the site, and describe proposed access to the existing street system. Show on site plans, if any.

**Interstate 5, NE 192nd Avenue, SE Payne Road, SE 40th Street, SE 34th Street, SE 202nd Avenue and Brady Road all can be utilized to access the property.**

b. Is site currently served by public transit? If not, what is the approximate distance to the nearest transit stop? **No. Over 500 feet away.**

c. How many parking spaces would the completed project have? How many would the project eliminate? **N/A - single family homes will provide a minimum of 2 parking spaces per single family residence.**

d. Will the proposal require any new roads or streets, or improvements to existing roads or streets, not including driveways? If so, generally describe (indicate whether public or private). **Yes, new public roads will be constructed within the proposed project to provide access to the new single family home sites. NW 18th Street, a public road, will also be improved with additional pavement, curb and sidewalk along the projects northern boundary.**

- e. Will the project use (or occur in the immediate vicinity of) water, rail, or air transportation? If so, generally describe. **No, single family residential development**
- f. How many vehicular trips per day would be generated by the completed project? If known, indicate when peak volumes would occur. **The project is expected to generate 333 new daily trips, 26 new A.M. peak hour and 35 new P.M. peak hour trips.**
- g. Proposed measures to reduce or control transportation impacts, if any: **Construction of new roads within the development and construction of improvements to NW 18<sup>th</sup> Street along the project northern boundary.**

15. Public services

- a. Would the project result in an increased need for public services (for example: fire protection, police protection, health care, schools, other)? If so, generally describe.  
**Yes, Thirty five (35) new single family households will require additional public services.**
- b. Proposed measures to reduce or control direct impacts on public services, if any.  
**Impact fees are assessed to the project to help offset immediate impacts on public services and long term taxes from the future home owner's will continue to support the impacts on public services.**

16. Utilities

- a. Circle utilities currently available at the site: electricity, natural gas, water, refuse service, telephone, sanitary sewer, septic system, other.
- b. Describe the utilities that are proposed for the project, the utility providing the service, and the general construction activities on the site or in the immediate vicinity which might be needed. **City of Camas Public Sanitary Sewer and Water will be extended to each new single family home for service, NW Natural Gas will provide natural gas, Clark Public Utilities will provide electricity and franchise utilities will be provided as available within the area.**

C. SIGNATURE

Under the penalty of perjury, the above answers are true and complete to the best of my knowledge. I understand that the lead agency is relying on them to make its decision.

Signature:  .....

Name of signee: Joel G. Stirling, PE

Position and Agency/Organization: Owner & Lead Professional Engineer/STERLING DESIGN, INC.

Date Submitted: 06/24/2018

D. SUPPLEMENTAL SHEET FOR NONPROJECT ACTIONS

(do not use this sheet for project actions)

Because these questions are very general, it may be helpful to read them in conjunction with the list of the elements of the environment.

When answering these questions, be aware of the extent the proposal, or the types of activities likely to result from the proposal, would affect the item at a greater intensity or at a faster rate than if the proposal were not implemented. Respond briefly and in general terms.

1. How would the proposal be likely to increase discharge to water; emissions to air; production, storage, or release of toxic or hazardous substances; or production of noise?

Proposed measures to avoid or reduce such increases are:

2. How would the proposal be likely to affect plants, animals, fish, or marine life?

Proposed measures to protect or conserve plants, animals, fish, or marine life are:

3. How would the proposal be likely to deplete energy or natural resources?

Proposed measures to protect or conserve energy and natural resources are:

4. How would the proposal be likely to use or affect environmentally sensitive areas or areas designated (or eligible or under study) for governmental protection; such as parks, wilderness, wild and scenic rivers, threatened or endangered species habitat, historic or cultural sites, wetlands, floodplains, or prime farmlands?

Proposed measures to protect such resources or to avoid or reduce impacts are:

5. How would the proposal be likely to affect land and shoreline use, including whether it would allow or encourage land or shoreline uses incompatible with existing plans?

Proposed measures to avoid or reduce shoreline and land use impacts are:



6. How would the proposal be likely to increase demands on transportation or public services and utilities?

Proposed measures to reduce or respond to such demand(s) are:

7. Identify, if possible, whether the proposal may conflict with local, state, or federal laws or requirements for the protection of the environment.

PID(s): 125635000,125646000 , 300 Foot Buffer

Locator



**Legend**

- Subject Property
- Buffer Selection
- Parcels
- Water Body
- Incorporated
- Urban Growth Area
- Unincorporated



Scale: 1:8,262




NOTE: This data is compiled from many sources and scales. Clark county makes this information available as a service, and accepts no responsibility for any inaccuracy, actual or implied.


GIS Order Number: 196987

Printed: 3/26/2018

Path: c:\usr\_proj\xxOrdID196987\_751054\xx\_114870\MailingListPacket.mxd




Owner Name	Mailing Address
AHSAN MUHAMMAD & AHSAN FAIZA	2424 NW IRIS CT, CAMAS, WA, 98607
ANDERSON MICHAEL B	2001 I SE 42ND ST, CAMAS, WA, 98607
BAZZAZ ALA & BAZZAZ FATMA	20017 SE 42ND ST, CAMAS, WA, 98607
CAMAS SCHOOL DISTRICT #117	841 NE 22ND AVE, CAMAS, WA, 98607
CARLSMITH DAVID SUTTON & SAULNIER VIRGINIE JEANNE	5415 NW 15TH CIR, CAMAS, WA, 98607
CHERNICHENKO VIKTOR & CHERNICHENKO VERA	4008 SE SUNRISE DRIVE, CAMAS, WA, 98607
COLUMBIA PALISADES CORP	2154 NE BROADWAY STE 200, PORTLAND, OR, 97232
COPELAND KERRY & COPELAND JACQUELINE	4039 SE 199TH AVE, CAMAS, WA, 98607
CRUZ AMOR DELA & CRUZ JOHANN	1425 NW GOODWIN ST, CAMAS, WA, 98607
DEAN NATHAN DANIEL	4001 SE SUNRISE DR, CAMAS, WA, 98607
DITTIRCH KENNETH C & DITTIRCH CAROLE	5144 NW 16TH CIR, CAMAS, WA, 98607
ELLIS JASON DANIEL & ELLIS JULIE JENNIFER	5360 NW 18TH AVE, CAMAS, WA, 98607
FEIK JOHN & FEIK MARILYN	5201 NW 17TH CIR, CAMAS, WA, 98607
FIRESTONE STAN	PO BOX 61928, VANCOUVER, WA, 98666
FISHER JARED S	20002 SE 42ND ST, CAMAS, WA, 98607
FUJIHARA PATRICIA SARAI KAIULANI & FUJIHARA BROOKS JR	5450 NW 15TH CR, CAMAS, WA, 98607
GIL KEVIN J & GIL TARA L	5215 NW 16TH CIR, CAMAS, WA, 98607
GONZALEX MIGUEL ANGEL & TRUJILLO MELINDA ELIZABETH	4005 SE SUNRISE DR, CAMAS, WA, 98607
GOOD DONALD E	4025 SE 201ST AVE, CAMAS, WA, 98607
GREAVES WESLEY C & GREAVES CYNTHIA L	1424 NW GOODWIN ST, CAMAS, WA, 98607
GREEN GAIL TRUSTEE	2927 SE VILLAGE LP #314, VANCOUVER, WA, 98683
GRIFFITH BRIAN PAUL & GRIFFITH SHELLY ANNE	4037 SE 199TH AVE, CAMAS, WA, 98607
HAMADEH SHAFIQ & HAMADEH ZHANNA	1319 NW GOODWIN ST, CAMAS, WA, 98607
HELMS JANET	124 CAMBRIA WALK, ALEXANDRIA, VA, 22304
HYLAND CURTIS S & HYLAND BRANDI F	5411 NE 15TH CIR, CAMAS, WA, 98607
JACKSON RICHARD T & JACKSON CHERYL ANN	1430 NW GOODWIN ST, CAMAS, WA, 98607
JAMISON WILLIAM C	4009 SE SUNRISE DR, CAMAS, WA, 98607
JOHNSON KRISTI L	4016 SE SUNRISE DR, CAMAS, WA, 98607
KLEINMAN GRETCHEN H	5213 NW 17TH CIR, CAMAS, WA, 98607
KOTKA GREGORY L & KOTKA JULIA M	1324 NW GOODWIN ST, CAMAS, WA, 98607
LARSON DAVID & LARSON GAIL	4120 SE 201ST AVE, CAMAS, WA, 98607
LENNAR NORTHWEST INC	11807 NE 99TH ST SUITE #1170, VANCOUVER, WA, 98682
MASONER JOHN W	4035 SE 199TH AVE, CAMAS, WA, 98607
MCCALLUM SEAN P TRUSTEE	5121 NW 17TH CIR, CAMAS, WA, 98607
MCCONNELL MARK & MCCONNELL JOEL	5440 NW 15TH CIR, CAMAS, WA, 98607
MIAN AFNAN A	4024 SE SUNRISE DR, CAMAS, WA, 98607
PIEN GENE C & PIFER-PIEN LESLIE TRUSTEES	5206 NW 16TH CIR, CAMAS, WA, 98607
PILEGGI SANTINA & PILEGGI NATHANIEL	1415 NW GOODWIN ST, CAMAS, WA, 98607
PULLEN REBECCA G	4015 SE SUNRISE DR, CAMAS, WA, 98607
PUSHKARIC SCOTT & PUSHKARIC STEPHANIE	5430 NW 15th Cir, Camas, WA, 98607
RADY DORIAN & RADY MARIE	1312 NW GOODWIN ST, CAMAS, WA, 98607
RALSTON RICHARD ANTHONY & GODFREY KELLY MARIE	5420 NW 15TH CIR, CAMAS, WA, 98607
ROSEBRAUGH FRED E & ROSEBRAUGH MARILYN	1601 NW DEERFERN ST, CAMAS, WA, 98607
SAARINEN SEPPO & SAARINEN EVA TRUSTEES	5215 NW 14TH CIRCLE, CAMAS, WA, 98607
SALTI OSAMA & ALYA SIREEN ABU	1325 NW GOODWIN ST, CAMAS, WA, 98607
SHIRA ERIC & SHIRA SHAYE	1416 NW GOODWIN ST, CAMAS, WA, 98607
SIKKEMA MARK EDWARD & SIKKEMA LISA MARIE	5120 NW 17TH CIR, CAMAS, WA, 98607
SMITH SANDRA J	4106 SE 201ST AVE, CAMAS, WA, 98607
THIEMAN LARRY & THIEMAN ARLENE ETAL	5216 NW 17TH CIR, CAMAS, WA, 98607
TSAI JAMES WEN & TSAI RINA HENDRAWAN	1421 NW GOODWIN ST, CAMAS, WA, 98607
WALES KAREN A & WALES BILLY R	1420 NW GOODWIN ST, CAMAS, WA, 98607
WILCOX AARON S & WILCOX AUBREY L	5209 NW 14TH CIR, CAMAS, WA, 98607
WINCHESTER HILLS HOMEOWNERS	16320 NE 77TH CIR, VANCOUVER, WA, 98682
WONG BENTAL H & WONG REBEKAH A	5204 NW 17TH CIR, CAMAS, WA, 98607



Owner Name	Mailing Address
WOODWARD JOHN R & YEE ELAINE M	5354 NW 18TH AVE, CAMAS, WA, 98607
WRIGHT MICHAEL B & MOORE-WRIGHT ASHLEY	5230 NW 16TH CIR, CAMAS, WA, 98607
YABLONSKIY VASILYI & YABLONSKIYA LYUDMILA	703 SE 201ST AVE, CAMAS, WA, 98607
YAN MAN PUI & YAN SUET HA ETAL	4112 SE 201ST AVE, CAMAS, WA, 98607
YING RICHARD & YING GLORIA	1635 NW DEERFERN ST, CAMAS, WA, 98607
YOUNG DAWNRAY H & YOUNG KITTY M	5220 NW 16TH CIR, CAMAS, WA, 98607
ZATTA SANDRA L	3839 LAKE KATIE WAY, SACRAMENTO, CA, 95834

**This document created by the Clark County,  
Washington Geographic Information System**

**Number of records** 61  
**Number of Pages** 2  
**Date Created** 3/26/18  
**Employee Signature**   
**Employee Name** Bob Pool



AHSAN MUHAMMAD & AHSAN FAIZA  
2424 NW IRIS CT  
CAMAS, WA 98607

DITTIRCH KENNETH C & DITTIRCH CAROLE  
5144 NW 16TH CIR  
CAMAS, WA 98607

GREEN GAIL TRUSTEE  
2927 SE VILLAGE LP #314  
VANCOUVER, WA 98683

ANDERSON MICHAEL B  
20011 SE 42ND ST  
CAMAS, WA 98607

ELLIS JASON DANIEL & ELLIS JULIE JENNIFER  
5360 NW 18TH AVE  
CAMAS, WA 98607

GRIFFITH BRIAN PAUL & GRIFFITH SHELLY  
4037 SE 199TH AVE  
CAMAS, WA 98607

BAZZAZ ALA & BAZZAZ FATMA  
20017 SE 42ND ST  
CAMAS, WA 98607

FEIK JOHN & FEIK MARILYN  
5201 NW 17TH CIR  
CAMAS, WA 98607

HAMADEH SHAFIQ & HAMADEH ZHANNA  
1319 NW GOODWIN ST  
CAMAS, WA 98607

CAMAS SCHOOL DISTRICT #117  
841 NE 22ND AVE  
CAMAS, WA 98607

FIRESTONE STAN  
PO BOX 61928  
VANCOUVER, WA 98666

HELMS JANET  
124 CAMBRIA WALK  
ALEXANDRIA, VA 22304

CARLSMITH DAVID SUTTON & SAULNIER  
5415 NW 15TH CIR  
CAMAS, WA 98607

FISHER JARED S  
20002 SE 42ND ST  
CAMAS, WA 98607

HYLAND CURTIS S & HYLAND BRANDI F  
5411 NE 15TH CIR  
CAMAS, WA 98607

CHERNICHENKO VIKTOR & CHERNICHENKO  
4008 SE SUNRISE DRIVE  
CAMAS, WA 98607

FUJIHARA PATRICIA SARAI KAIULANI &  
5450 NW 15TH CR  
CAMAS, WA 98607

JACKSON RICHARD T & JACKSON CHERYL  
1430 NW GOODWIN ST  
CAMAS, WA 98607

COLUMBIA PALISADES CORP  
2154 NE BROADWAY STE 200  
PORTLAND, OR 97232

GIL KEVIN J & GIL TARA L  
5215 NW 16TH CIR  
CAMAS, WA 98607

JAMISON WILLIAM C  
4009 SE SUNRISE DR  
CAMAS, WA 98607

COPELAND KERRY & COPELAND JACQUELINE  
4039 SE 199TH AVE  
CAMAS, WA 98607

GONZALEX MIGUEL ANGEL & TRUJILLO  
4005 SE SUNRISE DR  
CAMAS, WA 98607

JOHNSON KRISTI L  
4016 SE SUNRISE DR  
CAMAS, WA 98607

CRUZ AMOR DELA & CRUZ JOHANN  
1425 NW GOODWIN ST  
CAMAS, WA 98607

GOOD DONALD E  
4025 SE 201ST AVE  
CAMAS, WA 98607

KLEINMAN GRETCHEN H  
5213 NW 17TH CIR  
CAMAS, WA 98607

DEAN NATHAN DANIEL  
4001 SE SUNRISE DR  
CAMAS, WA 98607

GREAVES WESLEY C & GREAVES CYNTHIA L  
1424 NW GOODWIN ST  
CAMAS, WA 98607

KOTKA GREGORY L & KOTKA JULIA M  
1324 NW GOODWIN ST  
CAMAS, WA 98607

LARSON DAVID & LARSON GAIL  
4120 SE 201ST AVE  
CAMAS, WA 98607

RADY DORIAN & RADY MARIE  
1312 NW GOODWIN ST  
CAMAS, WA 98607

WALES KAREN A & WALES BILLY R  
1420 NW GOODWIN ST  
CAMAS, WA 98607

LENNAR NORTHWEST INC  
11807 NE 99TH ST SUITE #1170  
VANCOUVER, WA 98682

RALSTON RICHARD ANTHONY & GODFREY  
5420 NW 15TH CIR  
CAMAS, WA 98607

WILCOX AARON S & WILCOX AUBREY L  
5209 NW 14TH CIR  
CAMAS, WA 98607

MASONER JOHN W  
4035 SE 199TH AVE  
CAMAS, WA 98607

ROSEBRAUGH FRED E & ROSEBRAUGH  
1601 NW DEERFERN ST  
CAMAS, WA 98607

WINCHESTER HILLS HOMEOWNERS  
16320 NE 77TH CIR  
VANCOUVER, WA 98682

MCCALLUM SEAN P TRUSTEE  
5121 NW 17TH CIR  
CAMAS, WA 98607

SAARINEN SEPPO & SAARINEN EVA TRUSTEES  
5215 NW 14TH CIRCLE  
CAMAS, WA 98607

WONG BENTAL H & WONG REBEKAH A  
5204 NW 17TH CIR  
CAMAS, WA 98607

MCCONNELL MARK & MCCONNELL JOEL  
5440 NW 15TH CIR  
CAMAS, WA 98607

SALTI OSAMA & ALYA SIREEN ABU  
1325 NW GOODWIN ST  
CAMAS, WA 98607

WOODWARD JOHN R & YEE ELAINE M  
5354 NW 18TH AVE  
CAMAS, WA 98607

MIAN AFNAN A  
4024 SE SUNRISE DR  
CAMAS, WA 98607

SHIRA ERIC & SHIRA SHAYE  
1416 NW GOODWIN ST  
CAMAS, WA 98607

WRIGHT MICHAEL B & MOORE-WRIGHT  
5230 NW 16TH CIR  
CAMAS, WA 98607

PIEN GENE C & PIFER-PIEN LESLIE TRUSTEES  
5206 NW 16TH CIR  
CAMAS, WA 98607

SIKKEMA MARK EDWARD & SIKKEMA LISA  
5120 NW 17TH CIR  
CAMAS, WA 98607

YABLONSKIY VASILIIY & YABLONSKIYA  
703 SE 201ST AVE  
CAMAS, WA 98607

PILEGGI SANTINA & PILEGGI NATHANIEL  
1415 NW GOODWIN ST  
CAMAS, WA 98607

SMITH SANDRA J  
4106 SE 201ST AVE  
CAMAS, WA 98607

YAN MAN PUI & YAN SUET HA ETAL  
4112 SE 201ST AVE  
CAMAS, WA 98607

PULLEN REBECCA G  
4015 SE SUNRISE DR  
CAMAS, WA 98607

THIEMAN LARRY & THIEMAN ARLENE ETAL  
5216 NW 17TH CIR  
CAMAS, WA 98607

YING RICHARD & YING GLORIA  
1635 NW DEERFERN ST  
CAMAS, WA 98607

PUSHKARIC SCOTT & PUSHKARIC STEPHANIE  
5430 NW 15th Cir  
Camas, WA 98607

TSAI JAMES WEN & TSAI RINA HENDRAWAN  
1421 NW GOODWIN ST  
CAMAS, WA 98607

YOUNG DAWNRAY H & YOUNG KITTY M  
5220 NW 16TH CIR  
CAMAS, WA 98607

ZATTA SANDRA L  
3839 LAKE KATIE WAY  
SACRAMENTO, CA 95834



**Pre-Application Meeting  
Valley View Estates Subdivision  
20109 SE 40<sup>th</sup> Street  
#125646-000 & 125635-000  
File PA18-09**

Thursday, January 18, 2018  
3:30pm, Council Chambers  
616 NE Fourth Avenue, Camas, WA 98607

**Applicant / Contact:****Applicant:**

Sterling Design, Inc.  
Joel Stirling  
2208 E Evergreen Blvd  
Vancouver WA 98661  
Ph: (360)759-1794  
Email: [joel@sterling-design.biz](mailto:joel@sterling-design.biz)

**Contact:**

Same

**Representing City of Camas:**

Lauren Hollenbeck, Senior Planner  
Randy Miller, Fire Marshal  
Norm Wurzer, Engineer I  
Bob Cunningham, Building Official

**Location:**

20109 SE 40<sup>th</sup> Street  
Tax Account: 125646-000 and 125635-000

**Zoning:**

R-7.5

**Project Description:**

Applicant is proposing to subdivide 9.26 acres into 36 single family residential lots within the R-7.5 zone.

**NOTICE:** Notwithstanding any representation by City staff at a pre-application conference, staff is not authorized to waive any requirement of the City Code. Any omission or failure by staff to recite to an applicant all relevant applicable code requirements shall not constitute a waiver by the City of any standard or requirement. [CMC 18.55.060 (C)] This pre-application conference shall be valid for a period of 180 days from the date it is held. If no application is filed within 180 days of the conference or meeting, the applicant must schedule and attend another conference before the City will accept a permit application. [CMC 18.55.060 (D)] Any changes to the code or other applicable laws, which take effect between the pre-application conference and submittal of an application, shall be applicable. [CMC 18.55.060 (D)]. **A link to the Camas Municipal Code (CMC) can be found on the City of Camas website, <http://www.cityofcamas.us/> on the main page under “Business and Development”.**

**PLANNING DIVISION**

**LAUREN HOLLENBECK (360) 817-7253**

An application for a subdivision is considered a Type III permit. Applicable codes for preliminary plat development include Title 16 Environment, Title 17 Land Development, and Title 18 Zoning of the Camas Municipal Code (“CMC”), which can be found on the city website. Please note it remains the applicant’s responsibility to review the CMC and address all applicable provisions. The following pre-application notes are based on the application materials and site plan submitted to the City on December 22, 2017:

## Application Requirements

Your proposal will need to comply with the general application requirements per **CMC Section 18.55.110** in addition to the specific application requirements outlined in **CMC Section 17.11.030.B** for a preliminary subdivision plat. The following is an excerpt from the requirements of CMC Section 17.11.030.B (see code section for full text):

1. A completed city application form(s) and required fee(s);

Fees will be based on the adopted fees at the time of application submittal. The current fees include the following:

1. Preliminary Plat	\$6,400+\$225 per lot
2. SEPA	\$721.00
3. Critical Areas Review	\$690.00 (per type)
4. Archeological Review	\$122.00
5. Fire Department Review	\$314.00
6. Building Permit and Plan Review	based on the valuation of the project
7. Engineering Review	3% of estimated construction costs

2. A completed and signed SEPA checklist;
3. Complete applications for other required land use proposals applicable to the proposal;
4. A vicinity map showing location of the site;
5. A survey of existing significant trees as required under CMC Section 18.31.080;
6. All existing conditions shall be delineated on the site plan;
7. A preliminary grading plan as slopes are greater than ten percent;
8. Preliminary stormwater plan and report;
9. A geotechnical report consistent with CMC Chapter 16.59 as development is proposed on slopes greater than ten percent
10. A copy of the Clark County assessor's map which show the location of each property within 300 feet of the subdivision;
11. One set of mailing labels for all property owners as provided in CMC Section 18.55.110;
12. A traffic study
13. A narrative addressing ownership and maintenance of open spaces, stormwater facilities, public trails and critical areas, and the applicable approval criteria (CMC Section 17.11.030.D) and standards of the Camas Municipal Code. It should also address any proposed building conditions or restrictions.
14. A development sign must be posted on site per CMC Section 18.55.110.H (1-5).
15. Necessary drawings- three sets and an electronic copy (send as a PDF by email or on a disc). All documents and reports submitted as separate pdf copies.

## Preliminary Plat Review

The following comments are based on the site plan materials submitted with this Pre Application:

1. Density Transfer is acceptable if the T-24 trail is set aside in a tract per CMC 18.09.060.C.
2. Lots 1 and 4 are double frontage lots and shall comply with CMC 17.19.030.D.6 (a-c). Also refer to CMC Figure 17.19-1.
3. Per CMC 17.19.030.D.3, the 40x40 building envelopes should be shown on the plat. Lot 9 may not meet the 60-foot wide lot width as the front of the building envelope is measured at lot width.
4. Per CMC 18.09.040 Table 2, the minimum lot frontage on a curve shall be 30-feet. Verify if Lot 12 meets this requirement.
5. Lots 22-26 and lots 34-36 exceed the maximum lot size requirement of 9,000 square feet and should be revised.
6. Per CMC 17.19.040.B.1.c, if the average lot size is less than 7,500 square feet, one additional off-street parking space is required for every 5 units and shall be located within a common tract.

7. Per CMC 17.19.040.B.10.a, a Circulation plan is required at application that includes the subject site and properties within six hundred feet showing topography, critical areas and existing and proposed streets, trails, etc.
8. There is likelihood that retaining walls will be necessary as part of this development. Include the location and height of the retaining walls on the grading plan. Also, the elevation plans with an overlay of lot layout should be included with the submittal.

### **Trails**

The applicant shall include provisions for the T-21 trail consistent with the current City of Camas Parks, Recreation and Open Space plan. Do not remove significant trees for the location of T-21 trail. Approval is required with the Parks Ad Hoc Committee; contact Jerry Acheson with the Parks Department at 834-7092 to schedule a meeting.

### **Tree retention**

Per CMC Section 18.31.080, a tree survey is required for development; not for lands to be retained as undeveloped open space. CMC 18.31.080.B requires preservation of significant trees and integrate them into the land use design per CMC 17.19.030.A.2. Significant trees are defined as evergreen trees 8" dbh, and deciduous, other than red alder or cottonwood, 12" dbh. In addition to the tree survey, an arborist report prepared by a qualified biologist shall also be submitted.

### **SEPA**

Your proposal is not categorically exempt from the requirements of the State Environmental Policy Act (SEPA) per CMC Section 16.07.020.A.1 as the proposed subdivision is more than ten residential units.

### **Critical Areas Review**

Per city mapping and Clark County GIS, steep slopes and streams are identified within the property. Further, wetlands have been identified with the Breckenridge development to the south. Per CMC Section 16.51.130, a critical areas report prepared by a qualified professional is required if a proposed development is within or adjacent to a critical area. The general requirements for a critical areas report is found in CMC Section 16.51.140. The City's code contains additional requirements for each type of critical area:

- 1) Wetlands are addressed in CMC Section 16.53.030. If impacts to critical areas (or wetland) are anticipated, then an analysis of alternative designs must be included as a demonstration of the effort to avoid impacts per CMC Section 16.53.050.D.
- 2) Geologically Hazardous Areas are addressed in CMC Section 16.59.060 and 16.59.070. Based on the steep slopes on site, the location of some of the lots shown on the preliminary plat may not be feasible.
- 3) Fish and Wildlife Habitat Conservation Areas are addressed in CMC Section 16.61.020. If impacts to critical areas (or streams) are anticipated, then the applicant shall demonstrate that an effort has been made to avoid impacts per CMC Section 16.51.170.

### **Archeological Review**

The site is located in an area of high probability for the presence of archaeological objects. As such, an archeological predetermination will be required as per CMC Section 16.31.070.A.

### **ENGINEERING DIVISION**

**NORM WURZER (360) 817-7235**

#### General Requirements:

1. Construction plans shall be prepared by a licensed Washington State engineer in accordance with City of Camas standards.
2. A 3% plan review and inspection fee will be required. The fee will be based on an engineer's estimate or construction bid. The fee is due prior to approved construction drawings being released by the City.

3. Per CMC 17.19.020 –This includes but is not limited to: *Every developer shall be required to grade and pave streets and alleys, install curbs and gutters, sidewalks, monuments, sanitary and storm sewers, water mains, fire hydrants, street lights and street name signs, underground transmission lines, provide and install centralized mail delivery boxes as determined by the U.S. Postal Service, together with all appurtenances in accordance with specifications and standards in the Camas Design Standard Manual, the six-year street plan, and other state and local adopted standards and plans as may be applicable.*
4. Regulations for installation of public improvements, improvement agreements, bonding, final platting and final acceptance can be found at CMC 17.21.
5. Existing wells and septic tanks and septic drain fields shall be abandoned in accordance with state and county guide lines per CMC 17.19.020 (A3).

Streets:

6. Street improvements to NW 18<sup>th</sup> need to meet the requirements of Camas Street Design ST5 or an approved equivalent.
7. Street rights-of-way shall meet the criteria of CMC 17.19.040(B), Table 17.19.040-2(C).
8. Sidewalk and fencing along NW 18<sup>th</sup> shall meet the Camas Design Standards.
9. Applicant to coordinate road improvements to NW 18<sup>th</sup> with the Camas School District PBL project.
10. Applicant to maintain multi-mobile access on the south side of NW 18<sup>th</sup>.
11. Tracts for home access shall meet the requirements of Table 17.19.040-1 Minimum Private Street Standards and/or CMC 17.19.030D5 regarding Flag Lots, as applicable.
12. A traffic study will be required for this project in accordance with the City's adopted Traffic Impact Study Guidelines. The study shall include speed surveys, traffic counts, site distance evaluation, AM and PM peak volumes, trip distribution and assignment, signal warrants, turn pocket analysis, with and without project analysis for the current year and build out year. Evaluation of additional off-site intersections will be required once trip generation and distribution information is determined. Contact the City Engineer for trip distribution acceptance and the identification of specific study intersections.
13. Tract "G" will require access from the interior of the development. (Direct access from Tract "G" to NW 18<sup>th</sup> will be eliminated). Per Resolution 976 and 1260 no new residential accesses are permitted on Arterial/Collectors. Lots 58&47 were granted temporary direct access to the collector (18<sup>th</sup>) as they were otherwise land locked to public access.
14. NW 18<sup>th</sup> is designated as a collector street as such, minimum intersection access spacing of 330' is required,
15. A left turn lane intersection will be required allowing a left turn lane pocket into the proposed Valley View Estates development. *Left turn lanes required per "General Guidelines for Geometry of Roadway" listed in the City of Camas' Design Standard Manual.*
16. Uniform fencing and landscaping is required along NW 18<sup>th</sup>.
17. ADA compliant pedestrian ramps and ADA compliant street crossings are required. To provide ADA compliant pedestrian ramps and street crossings careful evaluation of street profile grades and intersection site grading will be required.
18. A right deceleration lane for NW 18<sup>th</sup> may be required based on the traffic study.
19. The applicant will be responsible for all traffic control signs, street name signs, pavement markings and street lighting per CMC 17.19.030 (I) (J).
20. The applicant will be responsible for the design and submittal of the utility plan showing the locations for underground power, telephone, gas, CATV, street lights and associated accessories.
21. The applicant will be required to comply with Vancouver's Riverview Gateway Subarea Plan that shows a roadway connection from Fisher/WSDOT Quarries to the southwest corner of the subject property. This includes but is not limited to street alignment with Columbia Palisades.
22. Streets to be named to reflect Camas addresses.

Stormwater:

23. Per CMC 14.02 stormwater treatment and runoff control, if triggered (5,000 SF of impervious surface), shall be designed in accordance with the latest Stormwater Management Manual for Western Washington and the City of Camas Stormwater Design Standards Manual.
24. Stormwater facilities shall be located and landscaped per CMC 17.19.030 (F6) and CMC 17.19.040 (C3a).
25. Stormwater facilities shall meet the requirements of Chapter 4.05 in Camas Stormwater manual. This includes but is not limited to; 10' from neighboring property lines, 50-feet from slopes 15 percent or greater unless the design meets additional requirements described in Chapter 4.05.
26. Maintenance of the storm water facilities will be the responsibility of the HOA per CMC 17.19.040 (C3).
27. The Technical Storm Water Report shall address the water conveyance from the Knights Point Subdivision and control of the downstream impacts.

Water:

28. There is a 12" DI water line available in NW 18<sup>th</sup> and an 8" DI waterline on the south side of the site on NW Goodwin. This water system will be required to be tied into NW 18<sup>th</sup> (north side), NW Goodwin (south side) and to be extended to the southwest side (for Vancouver). This site most likely will require a Pressure Relief Valve system.

Sanitary Sewer:

29. The sanitary design is required to be based on a STEF system unless otherwise approved by the City of Camas's Utility Manager.
30. There is an available 8" diameter STEF line in NW Goodwin Street that flows to the Grand Ridge sanitary pump station.
31. A sewer basin analysis will be required for the Grand Ridge Sanitary Pump Station to confirm there is adequate capacity for this proposed development.

Additional:

32. It is recommended that the applicant resolve placement of the community mailboxes with the Postmaster and the City of Camas prior to design submittal.
33. Garbage and recycling containers shall be placed at the public right-of-way.

Fees

All fees are subject to change and are paid at time of building permit issuance.

For each single family detached residential structure, the 2018 impact fees and SDC's will be as follows:

- Transportation TIF \$ 3,233.00 (South)
- School impact fee \$ 5,371.00 (Camas)
- ¾" Water Meter SDC \$ 4,778.00 (South)
- Water Connection fee \$ 380.00
- Sewer SDC \$ 2,493.00 (South)
- Parks/O.S. \$ 2,290.00
- Fire Impact Fees \$ 0.20/SF

**BUILDING DIVISION**

**BOB CUNNINGHAM (360) 817-1568**

1. A plan showing proposed development, proposed streets, lot lay out, lot numbers minus all the side notes. If possible overlay the Camas address grid on the proposed development. The Camas address grid is available on the Clark County GIS web Site.
2. Existing structures need an asbestos survey and demolition permit.
3. Decommissioning of septic tanks and drainfields through Clark County Department of Health
4. The structures will be reviewed under the most current building codes as adopted by The State of Washington.



5. The structural drawings and calculations shall be prepared and stamped by a Professional Engineer licensed by the State of Washington.
6. The placement of buildings and structures on or adjacent to slopes steeper than one unit vertical in three units horizontal shall conform to Sections R403.1.7.1 through R403.1.7.4. A geotechnical reports may be required
7. Geotechnical engineer's report required
8. The required fire distance between buildings and property line shall be in accordance with the International Building Codes.
9. The required fire suppression system shall be in accordance with IBC and other applicable codes standards and shall be reviewed by the Camas Fire Marshal's office.
10. Storm sewer disposal and connections shall identified on the approved plans.
11. All lots shall be provided a storm drain lateral at the lowest practical location.
12. Storm water from adjacent properties and existing developments should be taken into consideration.
13. System Development Charges and Impact fees shall be assessed prior to permits
14. An approved monument sign for posting addresses shall be provided at all Flag lots, the monument sign, location and design a shall be noted on the Plat.
15. Impact fees and System Development charges shall be applicable

#### **FIRE DEPARTMENT**

**RANDY MILLER (360) 834-6191**

1. Low Flow Life Safety Residential Fire Sprinklers (NFPA 13D) required in all new dwellings
2. The distance from a required fire hydrant may be doubled when Low Flow Life Safety Residential Fire Sprinklers are installed throughout a fully sprinklered subdivision. CMC 17.19.040.C.4.a.
3. Establishing Hydrant Flow Tests per NFPA 24 (National Fire Protection Association) utilizing a Washington State Licensed Fire Sprinkler Contractor may be waived when Low Flow Life Safety Residential Fire Sprinklers are installed throughout a fully sprinklered subdivision. 17.15.030.D.C
4. An approved address sign, in accordance with the Camas Municipal Code, must be posted for each residence where the flag lot leaves the public road or access tract. This sign shall be of permanence in its design/installation and shall be approved prior to installation. Contact the FMO for approval. CMC 17.19.030.D.5.d
5. Underground oil tank removal requires a permit with the fire marshal's office following IFC (International Fire Code) 3404.2.14
6. Any existing structures that are scheduled to be torn down may be considered for fire department training. Contact the FMO for further information.
7. Any blasting that may be needed for this location is required to follow the CMC Blasting Code and requires a permit with the fire marshal's office. CMC 15.40
8. Currently there is a reduction in the fire Impact Fee of .20 cents per square foot are when Low Flow Life Safety Residential Fire Sprinklers are installed.
9. Private Streets require a plan for access obstruction per CMC, 17.19.040.A.9
10. Street signs to include the 100 block designation on the sign.
11. Witnessed Hydrant Flushing required contact the FMO to schedule.
12. Underground oil/fuel tank removal requires a permit with the fire marshal's office following IFC (International Fire Code) 3404.2.14
13. Water line size installation from the meter into the house shall be determined with the fire sprinkler contractor and not the underground or plumbing contractor.

CITY OF CAMAS MAYOR APPROVED: [Signature] 1-30-14

COUNTY ASSESSOR BRECKENRIDGE SUBDIVISION PLAT NO. 162666 Peter Van Nieuwenk by Joe Utterback

COUNTY AUDITOR FILED FOR RECORD this 30th day of Jan 2014 IN BOOK 311 OF PLATS AT PAGE 715

COMMUNITY DEVELOPMENT DEPT. APPROVED: [Signature] 1-29-14

FIRE DEPARTMENT APPROVED: [Signature] 1/28/14

PUBLIC WORKS DEPARTMENT APPROVED: [Signature] 1/28/14

CITY FINANCE DIRECTOR APPROVED: [Signature] 1/28/14


LAND SURVEYOR'S CERTIFICATION ON THE BASIS OF MY KNOWLEDGE, INFORMATION AND BELIEF...

MINIMUM SETBACKS FRONT YARD 20' SIDE YARD 5' REAR YARD 25'

CORNER LOTS CORNER LOT FRONT YARD 20' CORNER LOT STREET SIDE YARD 5'


LAND INVENTORY TOTAL ACRES: 11.01 ACRES TOTAL DEVELOPED ACRES: 9.53 ACRES

BRECKENRIDGE



CURVE TABLE with columns: CURVE, DELTA ANGLE, CHORD, ARC LENGTH

CURVE TABLE (CONT.) with columns: CURVE, DELTA ANGLE, CHORD, ARC LENGTH



- LEGEND: SET 1/2" x 24" IR W/PLASTIC CAP (EOLSON ENG PL5 17886) BORING HAS SURFER...


CITY OF CAMAS REQUIRED NOTES

- 1) A HOMEOWNER'S ASSOCIATION (H.O.A.) WILL BE REQUIRED FOR THIS DEVELOPMENT...

TRACT NOTES

- TRACT A IS SET ASIDE AS OPEN SPACE AND IS TO BE OWNED AND MAINTAINED BY THE HOA OF THIS DEVELOPMENT...

ELSON LAND SURVEYORS ENGINEERING INC. 1111 BROADWAY, VANCOUVER, WA 98660



PREPARED BY:  
**STERLING DESIGN, INC.**  
 10000 15th Street NW  
 Vancouver, WA 98686  
 TEL: (360) 706-1794  
 FAX: (360) 706-1794  
 mail@sterlingdesign.biz  
 www.sterlingdesign.biz

**STERLING DESIGN, INC.**

Sheet Description:  
**PRELIMINARY STORMWATER MANAGEMENT PLAN**

Project:  
**VALLEY VIEW ESTATES SUBDIVISION**



2208 E. Evergreen Blvd., Vancouver, WA 98661  
Ph: (360) 759-1794 Fx: (360) 759-4983  
Email: [Mail@SterlingDesign.biz](mailto:Mail@SterlingDesign.biz)


**PRELIMINARY TECHNICAL INFORMATION REPORT**

**Valley View Estates Subdivision**

**June 2018**

Prepared by: Joel G. Stirling, P.E.







### General Location


Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

Printed on: March 26, 2018


 Location of Subject Property(s)



Geographic Information System



Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.



### Elevation Contours

Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

- Subject Property(s)
- Public Road
- Transportation or Major Utility Easement
- 10' Elevation Contours
- 2' Elevation Contours

Printed on: March 26, 2018


13106	13105	13104
13107	13108	13109
	13117	13116



Geographic Information System



Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.



Geographic Information System

0 200 400 Feet

Information shown on this map was collected from several sources. Clark County accepts no responsibility for any inaccuracies that may be present.

### Soil Types

Account: 125635000, 125646000  
 Owner: FIRESTONE STAN  
 Address: PO BOX 61928  
 C/S/Z: VANCOUVER, WA 98666

- Subject Property(s)
- Public Road
- Transportation or Major Utility Easement
- Soil Type Boundary

Printed on: March 26, 2018

13106	13105	13104
13107	13108	13109
		13116

## TABLE OF CONTENTS

### List of Figures:

Vicinity Map(s)  
Soils Map

### Report:

Section A – Project Overview .....	1
Section B – Minimum Requirements.....	1
Section C – Soils Evaluation .....	1
Section D – Source Control .....	2
Section E – Onsite Stormwater Management BMP’s .....	2
Section F – Runoff Treatment Analysis and Design .....	2
Section G – Flow Control Analysis and Design .....	3
Section H – Flow Control System Plan.....	3
Section I – Wetlands Protection .....	3
Section J – Other Permits .....	4
Section K – Conveyance System Analysis and Design .....	4
Section L – Offsite Analysis .....	4
Section M – Groundwater Monitoring Program .....	4
Section N – Maintenance and Operations Manual .....	5

### Technical Appendix:

I	– WWHM2012 Hydrology Calculations
II	– Perk Filter Information
III	– Geotechnical Report
IV	– Maintenance Manual

### List of References:

Stormwater Management Manual for Western Washington dated 2014.  
City of Camas Municipal Code as amended prior to March, 2014



## **Valley View Estates Subdivision**

---

### **Section A – Project Overview**

The “Valley View Estates” Subdivision proposal is to develop one existing 9.26 acre parcel of land into 36 single family building lots within the R-7.5 zoning district. The site is located at 20109 SE 40th Street in Camas, Washington; known as tax lots 59 & 48, serial number 125646-000 & 125635-000, and is located in the Northwest quarter of Section 8, Township 1 North, Range 3 East of the Willamette Meridian, Clark County, Washington.

The site topography is hilly and rolls from a gradual to a moderate slope from the Northeast corner down to the Southwest property line. Natural drainage flows from the property to a field inlet and public storm system, installed with the recently constructed "Brecken Ridge" Subdivision, which conveys it through the project to an unnamed wetland and natural seasonal drainage way to the south. There is some potential for contributing drainage from two (2) parcels of land along the Northeastern portion of the project and this area has been considered in the design of the stormwater management systems. The entire site has one (1) single family home on it with the remaining portion of the property covered with field grasses, blackberry bushes and a few undernourished trees. All existing man-made stormwater systems on the site are shown within the proposed development plans.

The existing subdivision, "Knight Point at Prune Hill", is located along the Eastern property line of the proposed Valley View Estates project which discharges stormwater from its stormwater management facilities at the Southeastern portion of the proposed project. The drainage from those facilities has been conveyed overland within a 12" ADS pipe system, to the Southern property line, for many years. As part of the proposed Valley View Estates improvements, a permanent stormwater conveyance system will be constructed to connect to the stormwater conveyance system from the Knight Point at Prune Hill stormwater management facilities, to route the drainage around the proposed stormwater management systems that will be constructed as part of the Valley View Estates Subdivision.

Construction of the Valley View Estates Subdivision will consist of grading approximately 8 acres of the site for construction of utilities, a public trail, public roads, stormwater facilities and grading building pads for the future single family home sites. The design of the stormwater management system was influenced primarily by the property topography and the location of the public storm system connection that was installed with the Breckenridge Subdivision to collect the stormwater drainage from the project. Quality control is required for this project and will be met through the use of multiple Cartridge Treatment Structures that are sized to meet the standards of the WWHM and the City of Camas stormwater management standards. Stormwater flow

rates and durations will be controlled using two (2) detention ponds located along the Southern property line of the project.

### **Section B – Minimum Requirements**

The Valley View Estates Subdivision proposal contains only one threshold discharge area (TDA) and is subject to minimum requirements 1 – 9. As required by CMC 14.02, the property is defined as follows: **Pre-developed Condition** - The native vegetation and soils that existed at a site prior to the influence of Euro-American settlement. The pre-developed condition shall be assumed to be a forested land cover unless reasonable, historic information is provided that indicates the site was prairie prior to settlement. The property currently contains a single family home and a large area of private gravel road which is not being considered within the stormwater management pre-developed flow calculations.

### **Section C – Soils Evaluation**

The “Soil Survey of Clark County, Washington” printed by the United States Department of Agriculture Soil Conservation Service (SCS), in cooperation with Washington Agriculture Experiment Station maps the soils on site as Hesson clay loam (HcB), and Powell silt loam (PoB & PoD). Both soils are listed within Soils Group (SG) 3 for WWHM calculation purposes and are also categorized as AASHO A-4 soils. Infiltration rates of 0.06-0.20 inches per hour are typical for these soil types. Although infiltration is not being considered for the primary quantity control management system, it is recognized that there is a small amount of natural infiltration that will occur throughout the project which makes the proposed stormwater management system conservative.

### **Section D – Source Control**

The development activity includes landscaping and lawn/vegetation and maintenance of stormwater drainage and treatment systems. Source control will be the responsibility of each of the new property owners within the subdivision.

### **Section E – Onsite Stormwater Management BMPs**

There are no specific applicable onsite stormwater management BMPs that apply to the proposed site improvements. All site runoff will be treated as required using multiple Treatment Cartridge Systems designed to provide water quality control to meet the

minimum stormwater quality control requirements of the SWWMM and the City of Camas. All flows from the developed project will be detained to pre-European-development runoff durations, and released to the pre-developed flow paths.

### **Section F – Runoff Treatment and Design**

Basic stormwater treatment is required for this project and will be met through the use of Stormwater Treatment Cartridge system(s) designed in compliance with City of Camas Municipal Code. Initial installation cost and the expenses associated with long-term maintenance are expected to be typical of developments of this size. There are no pollution-generating pervious surfaces (PGPS) on this project

The proposed Stormwater Treatment Cartridge System(s) have been designed according to the latest Stormwater Management Manual for Western Washington. The treatment cartridge system(s) are sized to treat at least 91% of all runoff based on the Water Quality flows calculated by the WWHM computer program.

The stormwater management facilities are design to collect and treat all proposed improvements and also include providing stormwater water quality and quantity control for the two (2) existing single-family home sites that are located at the Northeastern corner of the property. NW 18<sup>th</sup> Street is located along the Northern property line and will be improved with approximately 8' of additional pavement and a 6' wide sidewalk. The road transitions to a shed section that drains all stormwater along the Valley View Estates project to the north, making it impossible to pick up and manage. To mitigate for the small area of drainage that is able to be collected and managed onsite, the two (2) homes and driveways that are outside the project boundaries have been included within the stormwater management facilities rather than conveying the unmanaged stormwater from these offsite improvements around the proposed stormwater facilities. Another factor that is considered with this proposed area exchange is that the City of Camas is currently in the process of installing a public trail connection along NW 18<sup>th</sup> Street along the project frontage. This drainage will also flow to the North and is not be considered within the Valley View Estates stormwater management facilities which makes the proposed stormwater mitigation measures even more conservative.

### **Section G – Flow Control Analysis and Design**

Stormwater flow rates and durations will be controlled using two (2) detention pond(s) located along the southern portion of the project. The stormwater flow control analysis was done using WWHM2012 to match developed flow rate durations to pre-developed flow rate durations for all flows between ½ the 2-year discharge rate and up to the 50-year discharge rate as required by City of Camas Municipal Code. The detention pond control structures were sized utilizing the WWHM2012 computer analysis program and

will be located within each of the detention ponds. The detention ponds will have vertical walls located on all sides of the facilities as allowed by Volume III section 3.2 - Side Slopes from the 2014 SMMWW (also included herein). The section recommends that 25% of detention ponds be vegetated slope, however, gives the option to have 100% of the perimeter as vertical walls as long as:

- (a) they are constructed of reinforced concrete per Section 3.2.3, Material;**
- (b) a fence is provided along the top of the wall;**
- (c) the entire pond perimeter may be retaining walls, ....**
- (d) the design is stamped by a licensed engineer with structural expertise. If the entire pond is to be retaining walls, ladders should be provided on the walls for safety reasons.**

The detention pond walls will be designed by a licensed engineer with structural expertise and ladders will be provided on all sides of the detention pond as required. All retaining walls will comply with CMC18.17.060. A 5:1 maintenance access ramp is also proposed for access into the pond facilities and fencing with a locked access gate will also be provided on each facility.

#### **Section H – Flow Control System Plan**

See Engineering Plans.

#### **Section I – Wetlands Protection**

There are no wetlands on the property or immediately adjacent to the property.

#### **Section J – Other Permits**

Coverage under the Washington State NPDES Construction Stormwater General Permit will be obtained prior to construction.

#### **Section K – Conveyance System Analysis and Design**

See Engineering Plans for entire conveyance system design. The project is located on a property with considerable slope therefore all conveyance systems will convey the predicted 100 year flows to the proposed stormwater management facilities.

## **Section L – Offsite Analysis**

As required by Camas Municipal Code, a representative of STERLING DESIGN, INC. visited the site and followed the downstream flow route to a point in the receiving water more than ¼ of a mile from the site in order to analyze existing conditions and potential impacts of this development activity. This analysis looked for indications of excessive sedimentation, stream bank erosion, polluted discharges to ground water contributing to recharge zones, violations of water quality standards, and spills and discharges of priority pollutants as well as for potential impacts to public health and safety and private or public facilities downstream. All storm water from the site will connect to a public stormwater system that was recently installed with the Breckenridge Subdivision. The conveyance system from the Breckenridge Subdivision conveys the stormwater to a discharge point approximately 400' South of the Valley View Estates Southern property boundary. From there stormwater continues to flow south within a well vegetated natural drainage ravine along the Western boundary of the Grand Ridge Phase(s) 4 and 1. Stormwater flows from the proposed Valley View Estates Subdivision will continue to follow historical flow routes and will not be rerouted to another drainage basin. The designed stormwater system mimics the pre-developed condition by detaining to pre-development flow rates and discharging to the pre-development flow path. This project will not have a significant adverse impact on the downstream and/or upstream drainage system.

## **Section M – Groundwater Monitoring Program**

Ground water monitoring is not a requirement for single family residential developments and it is unlikely that there is any threat to ground water from the proposed Valley View Estates project.

## **Section N – Maintenance and Operations Manual**

Stormwater facilities will be privately owned and maintained per City of Camas Stormwater code CMC 14.02 and pages 7-24 and 7-25 of 2014 Stormwater Management Manual for Western Washington, Volume V.

**Appendix I: Hydrology Calculations**





Figure 1.2: New Development Flow Chart



**STORM FACILITIES ARE DESIGNED TO PROVIDE WATER QUALITY AND QUANTITY CONTROL AS REQUIRED BY CITY OF CAMAS CODE CMC 14.02 AND MEET MINIMUM REQUIREMENTS 1-10 IN ACCORDANCE WITH THE 2005 STORMWATER MANAGEMENT MANUAL FOR WESTERN WASHINGTON**

**STORMWATER FACILITIES WILL BE PRIVATELY OWNED AND MAINTAINED**

**SITE DEVELOPMENT WILL NOT INCREASE THE AMOUNT OF IMPERVIOUS SURFACES ON NW 18th STREET. ALL DRAINAGE WILL FLOW TO THE EXISTING FLOW ROUTES**

**STORM CONSTRUCTION NOTES:**

1. ALL STORM CONSTRUCTION AND PIPE INSTALLATION SHALL CONFORM TO THE MINIMUM DESIGN REQUIREMENTS SET FORTH BY THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION AND HIGHWAYS (WSDOT) DESIGN MANUAL SECTION 7-2.3.2. ALL EXCESS MATERIAL FROM THE PROJECT ESTIMATION SHALL BE DISPOSED OF BY AN APPROVED SITE.

2. PIPE DESIGN PIPE SIZE MATERIAL AND DESIGN SHALL BE AN APPROVED ORANGE HULLS ALUMINUM OR STEEL EXCEPT FOR 18" AND 24" WHICH SHALL BE GALVANNEAL.

3. EXCESS CONSTRUCTION SHALL BE FOR THE MOST RECENTLY ADAPTED SECTION OF THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION AND HIGHWAYS (WSDOT) DESIGN MANUAL SECTION 7-2.3.2.2. CONTRACTOR TO BE RESPONSIBLE FOR THE TYPE OF EXCESS AND METHOD OF EXCESS. EXCESS CONSTRUCTION SHALL BE COMPLETED TO A MINIMUM OF 50 PERCENT OF THE MINIMUM QUALITY AS DETERMINED BY THE WSDOT (7-2.3.2.2) FOR THE SITE.




4. ELEVATION OF THE PROPOSED SURFACE WITHIN THE IMPROVEMENT SHALL BE CONSIDERED TO BE A RESULT OF WINDROW CONTRACTOR AND SHALL BE PROBABLY REPORTED AT THE COMPLETION AT NO COST TO THE CITY.

5. ALL STORM PIPE SHALL BE 12" OR 18" WITH DOUBLE GULLED COUPLERS WITH 6" LONG PIPE JOINTS OF APPROVED QUALITY.

6. ALL STORM PIPE LAYERS TO BE A MINIMUM 18" DEEP COVERED WITH A MINIMUM SLOPE OF 0.5% UNLESS OTHERWISE SPECIFIED OTHERWISE AT THE PLANS.

7. ALL MANHOLES LOCATED AT UNIMPROVED ELEVATIONS AND RIGHT OF WAYS SHALL BE PROVIDED WITH FURNISH PROTECTIVE CASING AND SHALL BE SET 1" ABOVE FINISHED GRADE.

8. ALL NEW STORMWATER SYSTEMS AND IMPROVEMENTS SHALL BE REPORTED AT THE CITY'S DISCRETION. MANHOLE TESTING MAY BE REQUIRED AT THE CITY'S DISCRETION.



**SITE INFORMATION**

ALIGNMENT & FIELD DATA	MINISTERS & CLASSER SURVEYING, INC. (360) 604-5213	Scale:	AS SHOWN
SOIL TYPE:	HYDROLOGIC GROUP: C	ASHTO CLASSIFICATION:	A-4
SALES LISTING BY:	RAJPOD SONS SOLUTIONS (509) 816-3068	DATE:	MARCH 2014
SITE LOCATION:	CLATSOP COUNTY, WA	WORK NUMBER:	3667-101
SITE AREA:	8.28 ACRES	DATE:	2007/Pre/Initial/primary.ppt

**NOTES:**  
Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth & slope any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5553.

PREPARED BY:  
**STERLING DESIGN, INC.**  
STERLING DESIGN, INC.  
1000 10TH AVENUE, SUITE 100  
VANCOUVER, WA 98660  
TEL: (360) 756-1184  
WWW.STERLINGDESIGN.COM

Sheet Description:  
**PRELIMINARY STORMWATER MANAGEMENT PLAN**

Project:  
**VALLEY VIEW ESTATES SUBDIVISION**

05/18/16

Scale: AS SHOWN  
Project Number: 206  
Design: JGS/DC  
Drawn:  
Drawing Date: MAY 2016  
Sheet 6 of 8 (Sheet 6)



## Hydrologic Soil Groups for Soils in Clark County

U.S. Department of Agriculture  
Soil Conservation Service

### WATER FEATURES

Survey Area: CLARK COUNTY, WASHINGTON

Map Symbol	Soil Name	Hydrologic Group	Clark County WWHM Soils Group
BpB	BEAR PRARIE	B	2
BpC	BEAR PRARIE	B	2
CnB	CINEBAR	B	2
CnD	CINEBAR	B	2
CnE	CINEBAR	B	2
CnG	CINEBAR	B	2
CrE	CINEBAR	B	2
CrG	CINEBAR	B	2
CsF	CISPUS	B	2
CtA	CLOQUATO	B	2
CvA	COVE	D	4
CwA	COVE	D	4
DoB	DOLLAR	C	3
Fn	FILL LAND	In-situ	N/A
GeB	GEE	C	4
GeD	GEE	C	4
GeE	GEE	C	4
GeF	GEE	C	4
GuB	GUMBOOT	D	4
HcB *	HESSON *	C *	3 *
HcD	HELLSON	C	3
HcE	HESSON	C	3
HcF	HESSON	C	3
HgB	HESSON	C	3
HgD	HESSON	C	3
HhE	HESSON	C	3
HIA	HILLSBORO	B	2
HIB	HILLSBORO	B	2

Map Symbol	Soil Name	Hydrologic Group	Clark County WWHM Soils Group
NbA	NEWBERG	B	2
NbB	NEWBERG	B	2
OdB	ODNE	D	4
OeD	OLEQUA	B	3
OeE	OLEQUA	B	3
OeF	OLEQUA	B	3
OhD	OLEQUA VARIANT	C	4
OhF	OLEQUA VARIANT	C	4
OIB	OLYMPIC	B	3
OID	OLYMPIC	B	3
OIE	OLYMPIC	B	3
OIF	OLYMPIC	B	3
OmE	OLYMPIC	B	3
OmF	OLYMPIC	B	3
OpC	OLYMPIC VARIANT	C	3
OpE	OLYMPIC VARIANT	C	3
OpG	OLYMPIC VARIANT	C	3
OrC	OLYMPIC VARIANT	C	3
PhB	PILCHUCK	C	2
PoB *	POWELL *	C *	3 *
PoD *	POWELL *	C *	3 *
PoE	POWELL	C	3
PuA	PUYALLUP	B	2
Ra	RIVERWASH	D	N/A
Rc	RIVERWASH	D	N/A
Rk	ROCK LAND	D	N/A
Ro	ROUGH BROKEN LAND	A	1
SaC	SALKUM	B	2
SIB	SARA	D	4
SID	SARA	D	4
SIF	SARA	D	4
SmA	SAUVIE	B	3
SmB	SAUVIE	B	3
SnA	SAUVIE	D	3
SpB	SAUVIE	B	3

TABLE 7.—Estimated physical and chemical properties of the soils—Continued

Soil series and map symbols	Depth from surface	Classification			Percentage passing sieve—			* Permeability	Available water capacity	Re-action
		Dominant USDA texture	Unified	AASHO	No. 4 (4.76 mm.) <sup>1</sup>	No. 10 (2.0 mm.)	No. 200 (0.074 mm.)			
	<i>Inches</i>							<i>Inches per hour</i>	<i>Inches per inch of soil</i>	<i>pH</i>
Minniece: MnA, MnD.	0-48 48	Silty clay and clay - Basalt bedrock.	CH	A-7	90-95	85-95	65-75	< 0.06	0.06-0.08	6.1-7.8
MoA.	0-12 12-22 22-60	Silt loam----- Silty clay----- Very gravelly clay loam (weakly cemented).	ML CH GC	A-4 A-7 A-2	100 95-100 35-50	95-100 95-100 30-50	65-75 80-90 20-35	0.63-2.0 0.06-0.2 < 0.06	0.19-0.21 0.12-0.14 0.03-0.05	6.1-6.5 6.1-6.5 5.6-6.5
Mossyröck: MsB.	0-23 23-60 60-74	Silt loam----- Silt loam----- Loam-----	OL or OH ML ML	A-5 A-5 A-4	95-100 100 100	95-100 95-100 95-100	50-60 55-65 70-80	0.63-2.0 0.63-2.0 0.63-2.0	0.19-0.21 0.19-0.21 0.16-0.18	6.1-6.5 6.6-7.3 6.1-7.3
Newberg: NbA, NbB.	0-7 7-52 52-72	Silt loam----- Fine sandy loam and sandy loam. Sand-----	ML SM or ML SM	A-4 A-4 A-1	----- ----- -----	100 100 100	70-80 40-55 5-15	0.63-2.0 2.0-6.3 0.63-20.0	0.19-0.21 0.13-0.15 0.05-0.07	5.6-6.5 6.1-7.3 6.6-7.3
Odne: OdB.	0-50	Silt loam, silty clay loam, clay loam, and loam.	CL	A-4 or A-6	-----	100	75-85	< 0.06	0.10-0.12	5.0-6.5
Olequa: OeD, OeE, OeF.	0-17 17-90	Silt loam----- Heavy silt loam and silty clay loam.	ML CL	A-7 A-7	----- -----	100 100	75-85 80-90	0.63-2.0 0.2-0.63	0.19-0.21 0.19-0.21	6.1-6.5 4.5-6.5
OhD, OhF.	0-32 32-82	Silty clay loam----- Silty clay and clay-----	CL CH	A-7 A-7	95-100 95-100	90-95 90-95	85-95 85-95	0.2-0.63 < 0.06	0.19-0.21 0.06-0.08	5.1-6.0 5.1-6.5
Olympic: OIB, OID, OIE, OIF, OmE, OmF.	0-44 44-59 59	Clay loam and silty clay loam. Gravelly clay loam. Fractured basalt.	ML or CL GC	A-7 A-4	90-100 75-90	90-100 70-85	75-85 35-50	0.2-0.63 0.2-0.63	0.19-0.21 0.10-0.12	5.1-6.0 4.5-5.5
OpC, OpE, OpG, OrC.	0-30 30	Heavy clay loam and heavy silty clay loam. Fractured basalt.	ML or CL	A-7	90-95	90-95	75-85	0.2-0.63	0.19-0.21	5.1-6.0
Pilchuck: PhB.	0-60	Fine sand-----	SM	A-3	95-100	90-100	5-10	6.3-20.0	0.05-0.07	6.1-7.3
*Powell: PoB, PoD, PoE.	0-23 23-63	Silt loam----- Slit loam (fragipan).	ML ML	A-4 A-4	----- -----	100 100	80-90 80-90	0.63-0.20 0.06-0.20*	0.18-0.20 0.06-0.08	5.1-6.0 5.1-6.0
Puyallup: PuA.	0-27 27-60	Stratified fine sandy loam, loam, and loamy sand. Gravelly sand-----	SM SP or SW	A-4 A-1	100 70-90	95-100 65-85	35-50 0-5	2.0-6.3 6.3-20.0	0.10-0.12 0.04-0.06	5.6-6.5 6.6-7.3
Riverwash, sandy: Ra.	(?)	(?)-----	(?)	(?)	(?)	(?)	(?)	(?)	(?)	(?)
Riverwash, cobbly: Rc.	(?)	(?)-----	(?)	(?)	(?)	(?)	(?)	(?)	(?)	(?)
Rock land: Rk.	(?)	(?)-----	(?)	(?)	(?)	(?)	(?)	(?)	(?)	(?)
Rough broken land: Ro.	(?)	(?)-----	(?)	(?)	(?)	(?)	(?)	(?)	(?)	(?)

See footnotes at end of table.

**WWHM2012**  
**PROJECT REPORT**

## General Model Information

Project Name: Valley View Estates  
Site Name: Valley View Estates  
Site Address: 20109 SE 40TH ST  
City: Camas  
Report Date: 4/26/2018  
Gage: Lacamas  
Data Start: 1948/10/01  
Data End: 2008/09/30  
Timestep: 15 Minute  
Precip Scale: 1.300  
Version Date: 2017/07/05  
Version: 4.2.13

## POC Thresholds

---

Low Flow Threshold for POC1:	50 Percent of the 2 Year
High Flow Threshold for POC1:	50 Year

---

## Landuse Basin Data

### Predeveloped Land Use

#### Basin 1

Bypass: No

GroundWater: No

Pervious Land Use acre  
SG3, Forest, Steep 9.8

Pervious Total 9.8

Impervious Land Use acre  
ROADS STEEP 0.2

Impervious Total 0.2

Basin Total 10

Element Flows To:  
Surface

Interflow

Groundwater

## Mitigated Land Use

### Basin 1

Bypass: No

GroundWater: No

Pervious Land Use acre  
SG3, Lawn, Mod 2.2

Pervious Total 2.2

Impervious Land Use acre  
ROOF TOPS FLAT 1  
DRIVEWAYS FLAT 0.5

Impervious Total 1.5

Basin Total 3.7

### Element Flows To:

Surface	Interflow	Groundwater
Trapezoidal Pond 1	Trapezoidal Pond 1	

## Basin 2

Bypass:	No
GroundWater:	No
Pervious Land Use	acre
Pervious Total	0
Impervious Land Use	acre
ROADS MOD	1
Impervious Total	1
Basin Total	1

Element Flows To:		
Surface	Interflow	Groundwater
Flow Splitter 1	Flow Splitter 1	



### Basin 3

Bypass: No

GroundWater: No

Pervious Land Use acre  
SG3, Lawn, Mod 1.9

Pervious Total 1.9

Impervious Land Use acre  
ROOF TOPS FLAT 0.9  
DRIVEWAYS FLAT 0.4

Impervious Total 1.3

Basin Total 3.2

#### Element Flows To:

Surface	Interflow	Groundwater
Trapezoidal Pond 1	Trapezoidal Pond 1	

## Basin 4

Bypass:	No
GroundWater:	No
Pervious Land Use	acre
Pervious Total	0
Impervious Land Use	acre
ROADS MOD	0.2
Impervious Total	0.2
Basin Total	0.2

Element Flows To:		
Surface	Interflow	Groundwater
Trapezoidal Pond 1	Trapezoidal Pond 1	

## Basin 5

Bypass:	No
GroundWater:	No
Pervious Land Use	acre
Pervious Total	0
Impervious Land Use	acre
ROADS MOD	0.3
Impervious Total	0.3
Basin Total	0.3

### Element Flows To:

Surface	Interflow	Groundwater
Flow Splitter 2	Flow Splitter 2	

## Basin 6

Bypass: No

GroundWater: No

Pervious Land Use acre  
SG3, Lawn, Steep 0.4

Pervious Total 0.4

Impervious Land Use acre  
ROOF TOPS FLAT 0.2  
DRIVEWAYS FLAT 0.1

Impervious Total 0.3

Basin Total 0.7

### Element Flows To:

Surface	Interflow	Groundwater
Trapezoidal Pond 2	Trapezoidal Pond 2	

## Basin 7

Bypass:	No
GroundWater:	No
Pervious Land Use	acre
Pervious Total	0
Impervious Land Use	acre
ROADS STEEP	0.3
Impervious Total	0.3
Basin Total	0.3

Element Flows To:		
Surface	Interflow	Groundwater
Flow Splitter 3	Flow Splitter 3	

## Basin 8

Bypass:	No
GroundWater:	No
Pervious Land Use SG3, Lawn, Flat	acre 0.07
Pervious Total	0.07
Impervious Land Use PARKING FLAT	acre 0.03
Impervious Total	0.03
Basin Total	0.1

Element Flows To:  
Surface                      Interflow                      Groundwater  
Trapezoidal Pond 2    Trapezoidal Pond 2

## Basin 9

Bypass: Yes

GroundWater: No

Pervious Land Use acre  
SG3, Lawn, Flat 0.3

Pervious Total 0.3

Impervious Land Use acre  
ROADS FLAT 0.2

Impervious Total 0.2

Basin Total 0.5

Element Flows To:  
Surface Interflow Groundwater

*Routing Elements*  
*Predeveloped Routing*



## Mitigated Routing

### Trapezoidal Pond 1

Bottom Length: 180.00 ft.  
 Bottom Width: 90.00 ft.  
 Depth: 7 ft.  
 Volume at riser head: 2.0537 acre-feet.  
 Infiltration On  
 Infiltration rate: 0.5  
 Infiltration safety factor: 0.5  
 Total Volume Infiltrated (ac-ft.): 739.733  
 Total Volume Through Riser (ac-ft.): 459.106  
 Total Volume Through Facility (ac-ft.): 1198.839  
 Percent Infiltrated: 61.7  
 Total Precip Applied to Facility: 84.997  
 Total Evap From Facility: 15.042  
 Side slope 1: 0 To 1  
 Side slope 2: 0 To 1  
 Side slope 3: 0 To 1  
 Side slope 4: 0 To 1  
 Discharge Structure  
 Riser Height: 5.5 ft.  
 Riser Diameter: 18 in.  
 Orifice 1 Diameter: 1.9 in. Elevation:0 ft.  
 Orifice 2 Diameter: 3 in. Elevation:4 ft.  
 Element Flows To:  
 Outlet 1 Outlet 2

Pond Hydraulic Table

Stage(feet)	Area(ac.)	Volume(ac-ft.)	Discharge(cfs)	Infilt(cfs)
0.0000	0.371	0.000	0.000	0.000
0.0778	0.371	0.028	0.027	0.093
0.1556	0.371	0.057	0.038	0.093
0.2333	0.371	0.086	0.047	0.093
0.3111	0.371	0.115	0.054	0.093
0.3889	0.371	0.144	0.061	0.093
0.4667	0.371	0.173	0.066	0.093
0.5444	0.371	0.202	0.072	0.093
0.6222	0.371	0.231	0.077	0.093
0.7000	0.371	0.260	0.082	0.093
0.7778	0.371	0.289	0.086	0.093
0.8556	0.371	0.318	0.090	0.093
0.9333	0.371	0.347	0.094	0.093
1.0111	0.371	0.376	0.098	0.093
1.0889	0.371	0.405	0.102	0.093
1.1667	0.371	0.433	0.105	0.093
1.2444	0.371	0.462	0.109	0.093
1.3222	0.371	0.491	0.112	0.093
1.4000	0.371	0.520	0.115	0.093
1.4778	0.371	0.549	0.119	0.093
1.5556	0.371	0.578	0.122	0.093
1.6333	0.371	0.607	0.125	0.093
1.7111	0.371	0.636	0.128	0.093
1.7889	0.371	0.665	0.131	0.093
1.8667	0.371	0.694	0.133	0.093

1.9444	0.371	0.723	0.136	0.093
2.0222	0.371	0.752	0.139	0.093
2.1000	0.371	0.781	0.142	0.093
2.1778	0.371	0.809	0.144	0.093
2.2556	0.371	0.838	0.147	0.093
2.3333	0.371	0.867	0.149	0.093
2.4111	0.371	0.896	0.152	0.093
2.4889	0.371	0.925	0.154	0.093
2.5667	0.371	0.954	0.156	0.093
2.6444	0.371	0.983	0.159	0.093
2.7222	0.371	1.012	0.161	0.093
2.8000	0.371	1.041	0.163	0.093
2.8778	0.371	1.070	0.166	0.093
2.9556	0.371	1.099	0.168	0.093
3.0333	0.371	1.128	0.170	0.093
3.1111	0.371	1.157	0.172	0.093
3.1889	0.371	1.186	0.174	0.093
3.2667	0.371	1.214	0.177	0.093
3.3444	0.371	1.243	0.179	0.093
3.4222	0.371	1.272	0.181	0.093
3.5000	0.371	1.301	0.183	0.093
3.5778	0.371	1.330	0.185	0.093
3.6556	0.371	1.359	0.187	0.093
3.7333	0.371	1.388	0.189	0.093
3.8111	0.371	1.417	0.191	0.093
3.8889	0.371	1.446	0.193	0.093
3.9667	0.371	1.475	0.195	0.093
4.0444	0.371	1.504	0.248	0.093
4.1222	0.371	1.533	0.284	0.093
4.2000	0.371	1.562	0.310	0.093
4.2778	0.371	1.590	0.331	0.093
4.3556	0.371	1.619	0.350	0.093
4.4333	0.371	1.648	0.367	0.093
4.5111	0.371	1.677	0.382	0.093
4.5889	0.371	1.706	0.397	0.093
4.6667	0.371	1.735	0.411	0.093
4.7444	0.371	1.764	0.424	0.093
4.8222	0.371	1.793	0.436	0.093
4.9000	0.371	1.822	0.448	0.093
4.9778	0.371	1.851	0.460	0.093
5.0556	0.371	1.880	0.471	0.093
5.1333	0.371	1.909	0.482	0.093
5.2111	0.371	1.938	0.492	0.093
5.2889	0.371	1.966	0.502	0.093
5.3667	0.371	1.995	0.512	0.093
5.4444	0.371	2.024	0.522	0.093
5.5222	0.371	2.053	0.584	0.093
5.6000	0.371	2.082	1.042	0.093
5.6778	0.371	2.111	1.731	0.093
5.7556	0.371	2.140	2.558	0.093
5.8333	0.371	2.169	3.449	0.093
5.9111	0.371	2.198	4.328	0.093
5.9889	0.371	2.227	5.121	0.093
6.0667	0.371	2.256	5.771	0.093
6.1444	0.371	2.285	6.249	0.093
6.2222	0.371	2.314	6.583	0.093
6.3000	0.371	2.343	6.954	0.093
6.3778	0.371	2.371	7.263	0.093

6.4556	0.371	2.400	7.559	0.093
6.5333	0.371	2.429	7.842	0.093
6.6111	0.371	2.458	8.116	0.093
6.6889	0.371	2.487	8.380	0.093
6.7667	0.371	2.516	8.636	0.093
6.8444	0.371	2.545	8.885	0.093
6.9222	0.371	2.574	9.126	0.093
7.0000	0.371	2.603	9.361	0.093
7.0778	0.371	2.632	9.590	0.093

## Flow Splitter 1

Bottom Length: 10.00 ft.  
 Bottom Length: 10.00 ft.  
 Depth: 10 ft.  
 Side slope 1: 0 To 1  
 Side slope 2: 0 To 1  
 Side slope 3: 0 To 1  
 Side slope 4: 0 To 1  
 Control Structure Splitter Hydraulic Table

Stage(feet)	Area(ac.)	Volume(ac-ft.)	Primary(cfs)	Secondary(cfs)
0.000	0.002	0.000	0.000	0.000
0.111	0.002	0.000	5.210	0.000
0.222	0.002	0.000	7.368	0.000
0.333	0.002	0.000	9.024	0.000
0.444	0.002	0.001	10.42	0.000
0.555	0.002	0.001	11.65	0.000
0.666	0.002	0.001	12.76	0.000
0.777	0.002	0.001	13.78	0.000
0.888	0.002	0.002	14.73	0.000
1.000	0.002	0.002	15.63	0.000
1.111	0.002	0.002	16.47	0.000
1.222	0.002	0.002	17.28	0.000
1.333	0.002	0.003	18.04	0.000
1.444	0.002	0.003	18.78	0.000
1.555	0.002	0.003	19.49	0.000
1.666	0.002	0.003	20.17	0.000
1.777	0.002	0.004	20.84	0.000
1.888	0.002	0.004	21.48	0.000
2.000	0.002	0.004	22.10	0.000
2.111	0.002	0.004	22.71	0.000
2.222	0.002	0.005	23.30	0.000
2.333	0.002	0.005	23.87	0.000
2.444	0.002	0.005	24.43	0.000
2.555	0.002	0.005	24.98	0.000
2.666	0.002	0.006	25.52	0.000
2.777	0.002	0.006	26.05	0.000
2.888	0.002	0.006	26.56	0.000
3.000	0.002	0.006	27.07	0.000
3.111	0.002	0.007	27.57	0.000
3.222	0.002	0.007	28.05	0.000
3.333	0.002	0.007	28.53	0.000
3.444	0.002	0.007	29.01	0.000
3.555	0.002	0.008	29.47	0.000
3.666	0.002	0.008	29.93	0.000
3.777	0.002	0.008	30.38	0.000
3.888	0.002	0.008	30.82	0.000
4.000	0.002	0.009	31.26	0.000
4.111	0.002	0.009	31.69	0.000
4.222	0.002	0.009	32.11	0.000
4.333	0.002	0.009	32.53	0.000
4.444	0.002	0.010	32.95	0.000
4.555	0.002	0.010	33.36	0.000
4.666	0.002	0.010	33.76	0.000
4.777	0.002	0.011	34.16	0.000
4.888	0.002	0.011	34.56	0.000
5.000	0.002	0.011	34.95	0.000
5.111	0.002	0.011	35.33	0.000

5.222	0.002	0.012	35.72	0.000
5.333	0.002	0.012	36.09	0.000
5.444	0.002	0.012	36.47	0.000
5.555	0.002	0.012	36.84	0.000
5.666	0.002	0.013	37.20	0.000
5.777	0.002	0.013	37.57	0.000
5.888	0.002	0.013	37.93	0.000
6.000	0.002	0.013	38.28	0.000
6.111	0.002	0.014	38.64	0.000
6.222	0.002	0.014	38.99	0.000
6.333	0.002	0.014	39.33	0.000
6.444	0.002	0.014	39.68	0.000
6.555	0.002	0.015	40.02	0.000
6.666	0.002	0.015	40.35	0.000
6.777	0.002	0.015	40.69	0.000
6.888	0.002	0.015	41.02	0.000
7.000	0.002	0.016	41.35	0.000
7.111	0.002	0.016	41.68	0.000
7.222	0.002	0.016	42.00	0.000
7.333	0.002	0.016	42.32	0.000
7.444	0.002	0.017	42.64	0.000
7.555	0.002	0.017	42.96	0.000
7.666	0.002	0.017	43.28	0.000
7.777	0.002	0.017	43.59	0.000
7.888	0.002	0.018	43.90	0.000
8.000	0.002	0.018	44.21	0.000
8.111	0.002	0.018	44.51	0.000
8.222	0.002	0.018	44.82	0.000
8.333	0.002	0.019	45.12	0.000
8.444	0.002	0.019	45.42	0.000
8.555	0.002	0.019	45.72	0.000
8.666	0.002	0.019	46.01	0.000
8.777	0.002	0.020	46.31	0.000
8.888	0.002	0.020	46.60	0.000
9.000	0.002	0.020	46.89	0.000
9.111	0.002	0.020	47.18	0.000
9.222	0.002	0.021	47.46	0.000
9.333	0.002	0.021	47.75	0.000
9.444	0.002	0.021	48.03	0.000
9.555	0.002	0.021	48.31	0.000
9.666	0.002	0.022	48.59	0.000
9.777	0.002	0.022	48.87	0.000
9.888	0.002	0.022	49.15	0.000
10.00	0.002	0.023	49.42	0.000
10.11	0.002	0.023	49.70	0.000

Discharge Structure

Riser Height: 0 ft.  
Riser Diameter: 0 in.  
Orifice 1 Diameter: 24 in. Elevation:0 ft.  
Element Flows To:  
Outlet 1 Outlet 2  
Trapezoidal Pond 1 Trapezoidal Pond 1

## Flow Splitter 2

Bottom Length: 10.00 ft.  
 Bottom Length: 10.00 ft.  
 Depth: 10 ft.  
 Side slope 1: 0 To 1  
 Side slope 2: 0 To 1  
 Side slope 3: 0 To 1  
 Side slope 4: 0 To 1  
 Control Structure Splitter Hydraulic Table

Stage(feet)	Area(ac.)	Volume(ac-ft.)	Primary(cfs)	Secondary(cfs)
0.000	0.002	0.000	0.000	0.000
0.111	0.002	0.000	5.210	0.000
0.222	0.002	0.000	7.368	0.000
0.333	0.002	0.000	9.024	0.000
0.444	0.002	0.001	10.42	0.000
0.555	0.002	0.001	11.65	0.000
0.666	0.002	0.001	12.76	0.000
0.777	0.002	0.001	13.78	0.000
0.888	0.002	0.002	14.73	0.000
1.000	0.002	0.002	15.63	0.000
1.111	0.002	0.002	16.47	0.000
1.222	0.002	0.002	17.28	0.000
1.333	0.002	0.003	18.04	0.000
1.444	0.002	0.003	18.78	0.000
1.555	0.002	0.003	19.49	0.000
1.666	0.002	0.003	20.17	0.000
1.777	0.002	0.004	20.84	0.000
1.888	0.002	0.004	21.48	0.000
2.000	0.002	0.004	22.10	0.000
2.111	0.002	0.004	22.71	0.784
2.222	0.002	0.005	23.30	2.205
2.333	0.002	0.005	23.87	3.979
2.444	0.002	0.005	24.43	5.917
2.555	0.002	0.005	24.98	7.826
2.666	0.002	0.006	25.52	9.523
2.777	0.002	0.006	26.05	10.86
2.888	0.002	0.006	26.56	11.81
3.000	0.002	0.006	27.07	12.59
3.111	0.002	0.007	27.57	13.28
3.222	0.002	0.007	28.05	13.92
3.333	0.002	0.007	28.53	14.54
3.444	0.002	0.007	29.01	15.14
3.555	0.002	0.008	29.47	15.71
3.666	0.002	0.008	29.93	16.26
3.777	0.002	0.008	30.38	16.79
3.888	0.002	0.008	30.82	17.31
4.000	0.002	0.009	31.26	17.81
4.111	0.002	0.009	31.69	18.30
4.222	0.002	0.009	32.11	18.78
4.333	0.002	0.009	32.53	19.24
4.444	0.002	0.010	32.95	19.69
4.555	0.002	0.010	33.36	20.14
4.666	0.002	0.010	33.76	20.57
4.777	0.002	0.011	34.16	20.99
4.888	0.002	0.011	34.56	21.41
5.000	0.002	0.011	34.95	21.82
5.111	0.002	0.011	35.33	22.22

5.222	0.002	0.012	35.72	22.61
5.333	0.002	0.012	36.09	23.00
5.444	0.002	0.012	36.47	23.38
5.555	0.002	0.012	36.84	23.75
5.666	0.002	0.013	37.20	24.12
5.777	0.002	0.013	37.57	24.48
5.888	0.002	0.013	37.93	24.84
6.000	0.002	0.013	38.28	25.19
6.111	0.002	0.014	38.64	25.54
6.222	0.002	0.014	38.99	25.88
6.333	0.002	0.014	39.33	26.22
6.444	0.002	0.014	39.68	26.56
6.555	0.002	0.015	40.02	26.89
6.666	0.002	0.015	40.35	27.21
6.777	0.002	0.015	40.69	27.53
6.888	0.002	0.015	41.02	27.85
7.000	0.002	0.016	41.35	28.17
7.111	0.002	0.016	41.68	28.48
7.222	0.002	0.016	42.00	28.79
7.333	0.002	0.016	42.32	29.09
7.444	0.002	0.017	42.64	29.39
7.555	0.002	0.017	42.96	29.69
7.666	0.002	0.017	43.28	29.99
7.777	0.002	0.017	43.59	30.28
7.888	0.002	0.018	43.90	30.57
8.000	0.002	0.018	44.21	30.86
8.111	0.002	0.018	44.51	31.14
8.222	0.002	0.018	44.82	31.42
8.333	0.002	0.019	45.12	31.70
8.444	0.002	0.019	45.42	31.98
8.555	0.002	0.019	45.72	32.25
8.666	0.002	0.019	46.01	32.52
8.777	0.002	0.020	46.31	32.79
8.888	0.002	0.020	46.60	33.06
9.000	0.002	0.020	46.89	33.33
9.111	0.002	0.020	47.18	33.59
9.222	0.002	0.021	47.46	33.85
9.333	0.002	0.021	47.75	34.11
9.444	0.002	0.021	48.03	34.37
9.555	0.002	0.021	48.31	34.63
9.666	0.002	0.022	48.59	34.88
9.777	0.002	0.022	48.87	35.13
9.888	0.002	0.022	49.15	35.38
10.00	0.002	0.023	49.42	35.63
10.11	0.002	0.023	49.70	35.88

Discharge Structure

Riser Height: 0 ft.  
Riser Diameter: 0 in.  
Orifice 1 Diameter: 24 in. Elevation:0 ft.  
Element Flows To:  
Outlet 1 Outlet 2  
Trapezoidal Pond 1 Trapezoidal Pond 1

## Trapezoidal Pond 2

Bottom Length: 55.00 ft.  
 Bottom Width: 30.00 ft.  
 Depth: 7 ft.  
 Volume at riser head: 0.1915 acre-feet.  
 Infiltration On  
 Infiltration rate: 0.5  
 Infiltration safety factor: 0.5  
 Total Volume Infiltrated (ac-ft.): 44.415  
 Total Volume Through Riser (ac-ft.): 117.146  
 Total Volume Through Facility (ac-ft.): 161.56  
 Percent Infiltrated: 27.49  
 Total Precip Applied to Facility: 8.667  
 Total Evap From Facility: 1.514  
 Side slope 1: 0 To 1  
 Side slope 2: 0 To 1  
 Side slope 3: 0 To 1  
 Side slope 4: 0 To 1  
 Discharge Structure  
 Riser Height: 5 ft.  
 Riser Diameter: 12 in.  
 Orifice 1 Diameter: 1.5 in. Elevation:0 ft.  
 Orifice 2 Diameter: 1 in. Elevation:4 ft.  
 Element Flows To:  
 Outlet 1 Outlet 2

Pond Hydraulic Table

Stage(feet)	Area(ac.)	Volume(ac-ft.)	Discharge(cfs)	Infilt(cfs)
0.0000	0.037	0.000	0.000	0.000
0.0778	0.037	0.002	0.017	0.009
0.1556	0.037	0.005	0.024	0.009
0.2333	0.037	0.008	0.029	0.009
0.3111	0.037	0.011	0.034	0.009
0.3889	0.037	0.014	0.038	0.009
0.4667	0.037	0.017	0.041	0.009
0.5444	0.037	0.020	0.045	0.009
0.6222	0.037	0.023	0.048	0.009
0.7000	0.037	0.026	0.051	0.009
0.7778	0.037	0.029	0.053	0.009
0.8556	0.037	0.032	0.056	0.009
0.9333	0.037	0.035	0.059	0.009
1.0111	0.037	0.038	0.061	0.009
1.0889	0.037	0.041	0.063	0.009
1.1667	0.037	0.044	0.065	0.009
1.2444	0.037	0.047	0.068	0.009
1.3222	0.037	0.050	0.070	0.009
1.4000	0.037	0.053	0.072	0.009
1.4778	0.037	0.056	0.074	0.009
1.5556	0.037	0.058	0.076	0.009
1.6333	0.037	0.061	0.078	0.009
1.7111	0.037	0.064	0.079	0.009
1.7889	0.037	0.067	0.081	0.009
1.8667	0.037	0.070	0.083	0.009
1.9444	0.037	0.073	0.085	0.009
2.0222	0.037	0.076	0.086	0.009



2.1000	0.037	0.079	0.088	0.009
2.1778	0.037	0.082	0.090	0.009
2.2556	0.037	0.085	0.091	0.009
2.3333	0.037	0.088	0.093	0.009
2.4111	0.037	0.091	0.094	0.009
2.4889	0.037	0.094	0.096	0.009
2.5667	0.037	0.097	0.097	0.009
2.6444	0.037	0.100	0.099	0.009
2.7222	0.037	0.103	0.100	0.009
2.8000	0.037	0.106	0.102	0.009
2.8778	0.037	0.109	0.103	0.009
2.9556	0.037	0.112	0.105	0.009
3.0333	0.037	0.114	0.106	0.009
3.1111	0.037	0.117	0.107	0.009
3.1889	0.037	0.120	0.109	0.009
3.2667	0.037	0.123	0.110	0.009
3.3444	0.037	0.126	0.111	0.009
3.4222	0.037	0.129	0.113	0.009
3.5000	0.037	0.132	0.114	0.009
3.5778	0.037	0.135	0.115	0.009
3.6556	0.037	0.138	0.116	0.009
3.7333	0.037	0.141	0.118	0.009
3.8111	0.037	0.144	0.119	0.009
3.8889	0.037	0.147	0.120	0.009
3.9667	0.037	0.150	0.121	0.009
4.0444	0.037	0.153	0.128	0.009
4.1222	0.037	0.156	0.133	0.009
4.2000	0.037	0.159	0.137	0.009
4.2778	0.037	0.162	0.140	0.009
4.3556	0.037	0.165	0.143	0.009
4.4333	0.037	0.167	0.146	0.009
4.5111	0.037	0.170	0.149	0.009
4.5889	0.037	0.173	0.151	0.009
4.6667	0.037	0.176	0.154	0.009
4.7444	0.037	0.179	0.156	0.009
4.8222	0.037	0.182	0.158	0.009
4.9000	0.037	0.185	0.160	0.009
4.9778	0.037	0.188	0.163	0.009
5.0556	0.037	0.191	0.303	0.009
5.1333	0.037	0.194	0.676	0.009
5.2111	0.037	0.197	1.146	0.009
5.2889	0.037	0.200	1.618	0.009
5.3667	0.037	0.203	2.007	0.009
5.4444	0.037	0.206	2.263	0.009
5.5222	0.037	0.209	2.453	0.009
5.6000	0.037	0.212	2.618	0.009
5.6778	0.037	0.215	2.773	0.009
5.7556	0.037	0.218	2.920	0.009
5.8333	0.037	0.221	3.059	0.009
5.9111	0.037	0.223	3.192	0.009
5.9889	0.037	0.226	3.319	0.009
6.0667	0.037	0.229	3.442	0.009
6.1444	0.037	0.232	3.560	0.009
6.2222	0.037	0.235	3.674	0.009
6.3000	0.037	0.238	3.785	0.009
6.3778	0.037	0.241	3.893	0.009
6.4556	0.037	0.244	3.997	0.009
6.5333	0.037	0.247	4.099	0.009

6.6111	0.037	0.250	4.198	0.009
6.6889	0.037	0.253	4.295	0.009
6.7667	0.037	0.256	4.390	0.009
6.8444	0.037	0.259	4.483	0.009
6.9222	0.037	0.262	4.573	0.009
7.0000	0.037	0.265	4.662	0.009
7.0778	0.037	0.268	4.750	0.009

### Flow Splitter 3

Bottom Length: 10.00 ft.  
 Bottom Length: 10.00 ft.  
 Depth: 10 ft.  
 Side slope 1: 0 To 1  
 Side slope 2: 0 To 1  
 Side slope 3: 0 To 1  
 Side slope 4: 0 To 1  
 Control Structure Splitter Hydraulic Table

Stage(feet)	Area(ac.)	Volume(ac-ft.)	Primary(cfs)	Secondary(cfs)
0.000	0.002	0.000	0.000	0.000
0.111	0.002	0.000	5.210	0.000
0.222	0.002	0.000	7.368	0.000
0.333	0.002	0.000	9.024	0.000
0.444	0.002	0.001	10.42	0.000
0.555	0.002	0.001	11.65	0.000
0.666	0.002	0.001	12.76	0.000
0.777	0.002	0.001	13.78	0.000
0.888	0.002	0.002	14.73	0.000
1.000	0.002	0.002	15.63	0.000
1.111	0.002	0.002	16.47	0.000
1.222	0.002	0.002	17.28	0.000
1.333	0.002	0.003	18.04	0.000
1.444	0.002	0.003	18.78	0.000
1.555	0.002	0.003	19.49	0.000
1.666	0.002	0.003	20.17	0.000
1.777	0.002	0.004	20.84	0.000
1.888	0.002	0.004	21.48	0.000
2.000	0.002	0.004	22.10	0.000
2.111	0.002	0.004	22.71	0.784
2.222	0.002	0.005	23.30	2.205
2.333	0.002	0.005	23.87	3.979
2.444	0.002	0.005	24.43	5.917
2.555	0.002	0.005	24.98	7.826
2.666	0.002	0.006	25.52	9.523
2.777	0.002	0.006	26.05	10.86
2.888	0.002	0.006	26.56	11.81
3.000	0.002	0.006	27.07	12.59
3.111	0.002	0.007	27.57	13.28
3.222	0.002	0.007	28.05	13.92
3.333	0.002	0.007	28.53	14.54
3.444	0.002	0.007	29.01	15.14
3.555	0.002	0.008	29.47	15.71
3.666	0.002	0.008	29.93	16.26
3.777	0.002	0.008	30.38	16.79
3.888	0.002	0.008	30.82	17.31
4.000	0.002	0.009	31.26	17.81
4.111	0.002	0.009	31.69	18.30
4.222	0.002	0.009	32.11	18.78
4.333	0.002	0.009	32.53	19.24
4.444	0.002	0.010	32.95	19.69
4.555	0.002	0.010	33.36	20.14
4.666	0.002	0.010	33.76	20.57
4.777	0.002	0.011	34.16	20.99
4.888	0.002	0.011	34.56	21.41
5.000	0.002	0.011	34.95	21.82
5.111	0.002	0.011	35.33	22.22



5.222	0.002	0.012	35.72	22.61
5.333	0.002	0.012	36.09	23.00
5.444	0.002	0.012	36.47	23.38
5.555	0.002	0.012	36.84	23.75
5.666	0.002	0.013	37.20	24.12
5.777	0.002	0.013	37.57	24.48
5.888	0.002	0.013	37.93	24.84
6.000	0.002	0.013	38.28	25.19
6.111	0.002	0.014	38.64	25.54
6.222	0.002	0.014	38.99	25.88
6.333	0.002	0.014	39.33	26.22
6.444	0.002	0.014	39.68	26.56
6.555	0.002	0.015	40.02	26.89
6.666	0.002	0.015	40.35	27.21
6.777	0.002	0.015	40.69	27.53
6.888	0.002	0.015	41.02	27.85
7.000	0.002	0.016	41.35	28.17
7.111	0.002	0.016	41.68	28.48
7.222	0.002	0.016	42.00	28.79
7.333	0.002	0.016	42.32	29.09
7.444	0.002	0.017	42.64	29.39
7.555	0.002	0.017	42.96	29.69
7.666	0.002	0.017	43.28	29.99
7.777	0.002	0.017	43.59	30.28
7.888	0.002	0.018	43.90	30.57
8.000	0.002	0.018	44.21	30.86
8.111	0.002	0.018	44.51	31.14
8.222	0.002	0.018	44.82	31.42
8.333	0.002	0.019	45.12	31.70
8.444	0.002	0.019	45.42	31.98
8.555	0.002	0.019	45.72	32.25
8.666	0.002	0.019	46.01	32.52
8.777	0.002	0.020	46.31	32.79
8.888	0.002	0.020	46.60	33.06
9.000	0.002	0.020	46.89	33.33
9.111	0.002	0.020	47.18	33.59
9.222	0.002	0.021	47.46	33.85
9.333	0.002	0.021	47.75	34.11
9.444	0.002	0.021	48.03	34.37
9.555	0.002	0.021	48.31	34.63
9.666	0.002	0.022	48.59	34.88
9.777	0.002	0.022	48.87	35.13
9.888	0.002	0.022	49.15	35.38
10.00	0.002	0.023	49.42	35.63
10.11	0.002	0.023	49.70	35.88

Discharge Structure

Riser Height: 0 ft.  
Riser Diameter: 0 in.  
Orifice 1 Diameter: 24 in. Elevation:0 ft.  
Element Flows To:  
Outlet 1 Outlet 2  
Trapezoidal Pond 2 Trapezoidal Pond 2

# Analysis Results

## POC 1



+ Predeveloped    x Mitigated

### Predeveloped Landuse Totals for POC #1

Total Pervious Area: 9.8  
 Total Impervious Area: 0.2

### Mitigated Landuse Totals for POC #1

Total Pervious Area: 4.87  
 Total Impervious Area: 5.13

Flow Frequency Method: Log Pearson Type III 17B

### Flow Frequency Return Periods for Predeveloped. POC #1

Return Period	Flow(cfs)
2 year	0.521641
5 year	1.010245
10 year	1.448232
25 year	2.150329
50 year	2.7932
100 year	3.548955

### Flow Frequency Return Periods for Mitigated. POC #1

Return Period	Flow(cfs)
2 year	0.320254
5 year	0.45499
10 year	0.563746
25 year	0.725969
50 year	0.866626
100 year	1.02587

## Annual Peaks

### Annual Peaks for Predeveloped and Mitigated. POC #1

Year	Predeveloped	Mitigated
1949	0.472	0.515
1950	0.420	0.286
1951	1.217	0.312
1952	0.386	0.320
1953	0.646	0.319
1954	1.432	0.380
1955	0.544	0.256
1956	1.355	0.493
1957	0.888	0.314
1958	0.625	0.368

1959	0.351	0.224
1960	0.289	0.248
1961	0.688	0.395
1962	0.336	0.276
1963	0.401	0.283
1964	0.495	0.301
1965	0.764	0.425
1966	0.598	0.293
1967	0.558	0.263
1968	0.610	0.349
1969	0.791	0.437
1970	5.377	0.656
1971	0.254	0.234
1972	0.580	0.271
1973	0.219	0.307
1974	1.015	0.534
1975	0.376	0.269
1976	1.030	0.317
1977	0.092	0.227
1978	1.560	0.412
1979	0.232	0.345
1980	0.401	0.298
1981	1.210	0.406
1982	0.785	0.353
1983	1.978	0.347
1984	0.326	0.278
1985	0.277	0.322
1986	0.243	0.292
1987	1.189	0.333
1988	0.229	0.292
1989	0.209	0.228
1990	0.210	0.226
1991	0.606	0.268
1992	0.612	0.268
1993	0.401	0.367
1994	0.429	0.332
1995	0.269	0.512
1996	1.916	2.394
1997	1.507	0.785
1998	0.607	0.384
1999	0.650	0.376
2000	0.663	0.174
2001	0.105	0.176
2002	1.456	0.375
2003	1.033	0.354
2004	0.154	0.256
2005	0.178	0.265
2006	0.736	0.296
2007	0.341	0.567
2008	0.399	0.326

### Ranked Annual Peaks

Ranked Annual Peaks for Predeveloped and Mitigated. POC #1

Rank	Predeveloped	Mitigated
1	5.3773	2.3937
2	1.9782	0.7849
3	1.9164	0.6556
4	1.5598	0.5668

5	1.5072	0.5343
6	1.4563	0.5148
7	1.4316	0.5124
8	1.3549	0.4934
9	1.2172	0.4368
10	1.2102	0.4249
11	1.1888	0.4122
12	1.0331	0.4064
13	1.0295	0.3947
14	1.0151	0.3836
15	0.8876	0.3805
16	0.7911	0.3758
17	0.7845	0.3753
18	0.7640	0.3684
19	0.7359	0.3671
20	0.6875	0.3538
21	0.6633	0.3535
22	0.6496	0.3489
23	0.6456	0.3468
24	0.6247	0.3454
25	0.6121	0.3328
26	0.6102	0.3316
27	0.6071	0.3264
28	0.6065	0.3221
29	0.5983	0.3198
30	0.5800	0.3192
31	0.5580	0.3171
32	0.5443	0.3142
33	0.4952	0.3125
34	0.4725	0.3068
35	0.4290	0.3011
36	0.4203	0.2975
37	0.4012	0.2962
38	0.4007	0.2927
39	0.4005	0.2921
40	0.3995	0.2920
41	0.3865	0.2864
42	0.3762	0.2829
43	0.3512	0.2783
44	0.3410	0.2762
45	0.3362	0.2708
46	0.3260	0.2692
47	0.2892	0.2682
48	0.2770	0.2680
49	0.2694	0.2654
50	0.2543	0.2631
51	0.2435	0.2565
52	0.2316	0.2559
53	0.2289	0.2476
54	0.2187	0.2341
55	0.2096	0.2281
56	0.2087	0.2269
57	0.1784	0.2259
58	0.1536	0.2239
59	0.1049	0.1761
60	0.0916	0.1738





## Duration Flows

The Facility PASSED

Flow(cfs)	Predev	Mit	Percentage	Pass/Fail
0.2608	4668	3511	75	Pass
0.2864	3530	2281	64	Pass
0.3120	2794	1722	61	Pass
0.3376	2203	1360	61	Pass
0.3631	1749	1149	65	Pass
0.3887	1412	990	70	Pass
0.4143	1150	813	70	Pass
0.4399	963	686	71	Pass
0.4655	782	558	71	Pass
0.4910	650	428	65	Pass
0.5166	543	323	59	Pass
0.5422	414	260	62	Pass
0.5678	330	220	66	Pass
0.5934	272	194	71	Pass
0.6189	212	147	69	Pass
0.6445	168	110	65	Pass
0.6701	132	81	61	Pass
0.6957	107	55	51	Pass
0.7213	88	39	44	Pass
0.7468	77	30	38	Pass
0.7724	67	21	31	Pass
0.7980	62	17	27	Pass
0.8236	61	15	24	Pass
0.8492	55	15	27	Pass
0.8747	54	15	27	Pass
0.9003	47	15	31	Pass
0.9259	39	14	35	Pass
0.9515	38	14	36	Pass
0.9770	35	14	40	Pass
1.0026	33	14	42	Pass
1.0282	30	13	43	Pass
1.0538	27	13	48	Pass
1.0794	26	12	46	Pass
1.1049	25	12	48	Pass
1.1305	22	11	50	Pass
1.1561	21	11	52	Pass
1.1817	18	11	61	Pass
1.2073	15	11	73	Pass
1.2328	13	11	84	Pass
1.2584	13	11	84	Pass
1.2840	13	10	76	Pass
1.3096	13	10	76	Pass
1.3352	12	10	83	Pass
1.3607	11	9	81	Pass
1.3863	11	9	81	Pass
1.4119	11	9	81	Pass
1.4375	10	9	90	Pass
1.4631	9	8	88	Pass
1.4886	9	7	77	Pass
1.5142	8	7	87	Pass
1.5398	8	7	87	Pass
1.5654	7	7	100	Pass
1.5910	7	7	100	Pass

1.6165	7	7	100	Pass
1.6421	7	7	100	Pass
1.6677	7	7	100	Pass
1.6933	7	6	85	Pass
1.7189	6	6	100	Pass
1.7444	6	5	83	Pass
1.7700	6	5	83	Pass
1.7956	6	5	83	Pass
1.8212	6	5	83	Pass
1.8468	6	5	83	Pass
1.8723	6	5	83	Pass
1.8979	6	4	66	Pass
1.9235	5	3	60	Pass
1.9491	5	3	60	Pass
1.9747	5	3	60	Pass
2.0002	4	3	75	Pass
2.0258	4	3	75	Pass
2.0514	4	3	75	Pass
2.0770	4	3	75	Pass
2.1026	4	3	75	Pass
2.1281	4	3	75	Pass
2.1537	4	2	50	Pass
2.1793	4	2	50	Pass
2.2049	4	2	50	Pass
2.2304	4	1	25	Pass
2.2560	4	1	25	Pass
2.2816	4	1	25	Pass
2.3072	4	1	25	Pass
2.3328	4	1	25	Pass
2.3583	4	1	25	Pass
2.3839	4	1	25	Pass
2.4095	4	0	0	Pass
2.4351	4	0	0	Pass
2.4607	4	0	0	Pass
2.4862	4	0	0	Pass
2.5118	4	0	0	Pass
2.5374	4	0	0	Pass
2.5630	4	0	0	Pass
2.5886	4	0	0	Pass
2.6141	4	0	0	Pass
2.6397	4	0	0	Pass
2.6653	4	0	0	Pass
2.6909	4	0	0	Pass
2.7165	4	0	0	Pass
2.7420	4	0	0	Pass
2.7676	4	0	0	Pass
2.7932	4	0	0	Pass

## Water Quality

Water Quality BMP Flow and Volume for POC #1

On-line facility volume: 0 acre-feet

On-line facility target flow: 0 cfs.

Adjusted for 15 min: 0 cfs.

Off-line facility target flow: 0 cfs.

Adjusted for 15 min: 0 cfs.

# LID Report

LID Technique	Used for Treatment ?	Total Volume Needs Treatment (ac-ft)	Volume Through Facility (ac-ft)	Infiltration Volume (ac-ft)	Cumulative Volume Infiltration Credit	Percent Volume Infiltrated	Water Quality	Percent Water Quality Treated	Comment
Trapezoidal Pond 1 POC	<input type="checkbox"/>	1090.94			<input type="checkbox"/>	61.70			
Flow Splitter 1	<input type="checkbox"/>	177.87			<input type="checkbox"/>	0.00			
Flow Splitter 2	<input type="checkbox"/>	49.66			<input type="checkbox"/>	0.00			
Trapezoidal Pond 2 POC	<input type="checkbox"/>	147.02			<input type="checkbox"/>	27.49			
Flow Splitter 3	<input type="checkbox"/>	51.40			<input type="checkbox"/>	0.00			
<b>Total Volume Infiltrated</b>		1516.89	0.00	0.00		47.04	0.00	0%	No Treat Credit
Compliance with LID Standard 8% of 2-yr to 50% of 2-yr									Duration Analysis Result = Failed

## *Model Default Modifications*

Total of 0 changes have been made.

### *PERLND Changes*

No PERLND changes have been made.

### *IMPLND Changes*


No IMPLND changes have been made.

*Appendix*  
*Predeveloped Schematic*



Basin 1  
10.00ac

# Mitigated Schematic



# Predeveloped UCI File

RUN

GLOBAL

```
WVHM4 model simulation
START      1948 10 01      END      2008 09 30
RUN INTERP OUTPUT LEVEL   3      0
RESUME     0 RUN         1
UNIT SYSTEM 1
```

END GLOBAL

FILES

```
<File> <Un#> <-----File Name----->***
<-ID->                                     ***
WDM      26      Valley View Estates.wdm
MESSU    25      PreValley View Estates.MES
          27      PreValley View Estates.L61
          28      PreValley View Estates.L62
          30      POCValley View Estates1.dat
```

END FILES

OPN SEQUENCE

```
INGRP          INDELT 00:15
  PERLND        21
  IMPLND         3
  COPY          501
  DISPLY         1
```

END INGRP

END OPN SEQUENCE

DISPLY

```
DISPLY-INFO1
# - #<-----Title----->***TRAN PIVL DIG1 FIL1  PYR DIG2 FIL2 YRND
1   Basin 1          MAX          1   2   30   9
```

END DISPLY-INFO1

END DISPLY

COPY

```
TIMESERIES
# - # NPT NMN ***
1   1   1
501 1   1
```

END TIMESERIES

END COPY

GENER

```
OPCODE
#   # OPCD ***
END OPCODE
PARM
#   #           K ***
```

END PARM

END GENER

PERLND

```
GEN-INFO
<PLS ><-----Name----->NBLKS  Unit-systems  Printer ***
# - #      User  t-series  Engl Metr ***
          in  out      ***
21      SG3, Forest, Steep  1  1  1  1  27  0
END GEN-INFO
*** Section PWATER***
```

ACTIVITY

```
<PLS > ***** Active Sections *****
# - # ATMP SNOW PWAT  SED  PST  PWG  PQAL MSTL  PEST  NITR  PHOS  TRAC  ***
21   0   0   1   0   0   0   0   0   0   0   0   0
```

END ACTIVITY

PRINT-INFO

```
<PLS > ***** Print-flags ***** PIVL  PYR
# - # ATMP SNOW PWAT  SED  PST  PWG  PQAL MSTL  PEST  NITR  PHOS  TRAC  *****
21   0   0   4   0   0   0   0   0   0   0   0   0   1   9
```

END PRINT-INFO



```

PWAT-PARM1
<PLS > PWATER variable monthly parameter value flags ***
# - # CSNO RTOP UZFG VCS VUZ VNN VIFW VIRC VLE INFC HWT ***
21 0 0 0 0 0 0 0 0 0 0 0
END PWAT-PARM1

```

```

PWAT-PARM2
<PLS > PWATER input info: Part 2 ***
# - # ***FOREST LZSN INFILT LRSUR SLSUR KVARV AGWRC
21 0 9 0.08 400 0.15 0 0.96
END PWAT-PARM2

```

```

PWAT-PARM3
<PLS > PWATER input info: Part 3 ***
# - # ***PETMAX PETMIN INFEXP INFILD DEEPFR BASETP AGWETP
21 0 0 2.5 2 0 0 0
END PWAT-PARM3

```

```

PWAT-PARM4
<PLS > PWATER input info: Part 4 ***
# - # CEPSC UZSN NSUR INTFW IRC LZETP ***
21 0.2 1 0.35 4 0.4 0.7
END PWAT-PARM4

```

```

PWAT-STATE1
<PLS > *** Initial conditions at start of simulation
ran from 1990 to end of 1992 (pat 1-11-95) RUN 21 ***
# - # *** CEPS SURS UZS IFWS LZS AGWS GWVS
21 0 0 0 0 3 1 0
END PWAT-STATE1

```

END PERLND

IMPLND

```

GEN-INFO
<PLS ><-----Name-----> Unit-systems Printer ***
# - # User t-series Engr Metr ***
in out ***
3 ROADS/STEEP 1 1 1 27 0
END GEN-INFO
*** Section IWATER***

```

```

ACTIVITY
<PLS > ***** Active Sections *****
# - # ATMP SNOW IWAT SLD IWG IQAL ***
3 0 0 1 0 0 0
END ACTIVITY

```

```

PRINT-INFO
<ILS > ***** Print-flags ***** PIVL PYR
# - # ATMP SNOW IWAT SLD IWG IQAL *****
3 0 0 4 0 0 0 1 9
END PRINT-INFO

```

```

IWAT-PARM1
<PLS > IWATER variable monthly parameter value flags ***
# - # CSNO RTOP VRS VNN RTLI ***
3 0 0 0 0 0
END IWAT-PARM1

```

```

IWAT-PARM2
<PLS > IWATER input info: Part 2 ***
# - # *** LRSUR SLSUR NSUR RETSC
3 400 0.1 0.1 0.05
END IWAT-PARM2

```

```

IWAT-PARM3
<PLS > IWATER input info: Part 3 ***
# - # ***PETMAX PETMIN
3 0 0

```

```

END IWAT-PARM3

IWAT-STATE1
  <PLS > *** Initial conditions at start of simulation
  # - # *** RETS      SURS
  3   0             0
END IWAT-STATE1

END IMPLND

SCHEMATIC
<-Source->
<Name> #
Basin 1***
PERLND 21
PERLND 21
IMPLND 3
          <--Area-->   <-Target->   MBLK   ***
          <-factor->   <Name> #     Tbl#   ***
          9.2         COPY 501    12
          9.2         COPY 501    13
          0.2         COPY 501    15

*****Routing*****
END SCHEMATIC

NETWORK
<-Volume-> <-Grp> <-Member-><--Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name> # <Name> # #<-factor->strg <Name> # # <Name> # # ***
COPY 501 OUTPUT MEAN 1 1 48.4 DISPLAY 1 INPUT TIMSER 1

<-Volume-> <-Grp> <-Member-><--Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name> # <Name> # #<-factor->strg <Name> # # <Name> # # ***
END NETWORK

RCHRES
  GEN-INFO
  RCHRES      Name          Nexits  Unit Systems  Printer      ***
  # - #<-----><----> User T-series Engl Metr LKFG      ***
  in out
  ***
END GEN-INFO
*** Section RCHRES***

ACTIVITY
  <PLS > ***** Active Sections *****
  # - # HYFG ADFG CNFG HTFG SDFG GQFG OXFG NUFG PKFG PHFG ***
END ACTIVITY

PRINT-INFO
  <PLS > ***** Print-flags ***** PIVL  PYR
  # - # HYDR ADCA CONS HEAT SED  GQL  OXRX NUTR PLNK PHCB PIVL  PYR *****
END PRINT-INFO

HYDR-PARM1
  RCHRES  Flags for each HYDR Section ***
  # - # VC A1 A2 A3  ODFVFG for each *** ODGTFG for each  FUNCT for each
  FG FG FG FG  possible exit *** possible exit  possible exit
  * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *
END HYDR-PARM1

HYDR-PARM2
  # - # FTABNO  LEN  DELTH  STCOR  KS  DB50  ***
<-----><-----><-----><-----><-----><-----> ***
END HYDR-PARM2

HYDR-INIT
  RCHRES  Initial conditions for each HYDR section ***
  # - # *** VOL  Initial value of COLIND  Initial value of OUTDGT
  *** ac-ft  for each possible exit  for each possible exit
<-----><-----> <-----><-----><-----><-----> *** <-----><-----><-----><-----><----->
END HYDR-INIT
END RCHRES

SPEC-ACTIONS

```

END SPEC-ACTIONS  
FTABLES  
END FTABLES

EXT SOURCES

<-Volume->	<Member>	SsysSgap<--Mult-->	Tran	<-Target	vols>	<-Grp>	<-Member->	***	
<Name>	#	<Name>	#	tem strg<-factor->	strg	<Name>	#	#	***
WDM	2	PREC	ENGL	1.3		PERLND	1 999	EXTNL	PREC
WDM	2	PREC	ENGL	1.3		IMPLND	1 999	EXTNL	PREC
WDM	1	EVAP	ENGL	0.8		PERLND	1 999	EXTNL	PETINP
WDM	1	EVAP	ENGL	0.8		IMPLND	1 999	EXTNL	PETINP

END EXT SOURCES

EXT TARGETS

<-Volume->	<-Grp>	<-Member->	<--Mult-->	Tran	<-Volume->	<Member>	Tsys	Tgap	Amd	***
<Name>	#	<Name>	#	#<-factor->	strg	<Name>	#	<Name>	tem strg	strg***
COPY	501	OUTPUT	MEAN	1 1	48.4	WDM	501	FLOW	ENGL	REPL

END EXT TARGETS

MASS-LINK

<Volume>	<-Grp>	<-Member->	<--Mult-->	<Target>	<-Grp>	<-Member->	***		
<Name>	#	<Name>	#	#<-factor->	<Name>	<Name>	#	#	***
MASS-LINK			12						
PERLND	PWATER	SURO		0.083333	COPY	INPUT	MEAN		
END MASS-LINK			12						
MASS-LINK			13						
PERLND	PWATER	IFWO		0.083333	COPY	INPUT	MEAN		
END MASS-LINK			13						
MASS-LINK			15						
IMPLND	IWATER	SURO		0.083333	COPY	INPUT	MEAN		
END MASS-LINK			15						

END MASS-LINK

END RUN

# Mitigated UCI File

RUN

GLOBAL

```
WVHM4 model simulation
START      1948 10 01      END      2008 09 30
RUN INTERP OUTPUT LEVEL   3      0
RESUME     0 RUN         1
UNIT SYSTEM 1
```

END GLOBAL

FILES

```
<File> <Un#> <-----File Name----->***
<-ID->                                     ***
WDM      26      Valley View Estates.wdm
MESSU    25      MitValley View Estates.MES
          27      MitValley View Estates.L61
          28      MitValley View Estates.L62
          30      POCValley View Estates1.dat
```

END FILES

OPN SEQUENCE

INGRP INDELT 00:15

```
PERLND 26
IMPLND 4
IMPLND 5
IMPLND 2
PERLND 27
IMPLND 3
PERLND 25
IMPLND 11
IMPLND 1
RCHRES 1
RCHRES 2
RCHRES 3
RCHRES 4
RCHRES 5
COPY 1
COPY 501
COPY 601
DISPLY 1
```

END INGRP

END OPN SEQUENCE

DISPLY

DISPLY-INFO1

```
# - #<-----Title----->***TRAN PIVL DIG1 FIL1 PYR DIG2 FIL2 YRND
1 Trapezoidal Pond 2 MAX 1 2 30 9
```

END DISPLY-INFO1

END DISPLY

COPY

TIMESERIES

```
# - # NPT NMN ***
1 1 1
501 1 1
601 1 1
```

END TIMESERIES

END COPY

GENER

OPCODE

```
# # OPCODE ***
```

END OPCODE

PARM

```
# # K ***
```

END PARM

END GENER

PERLND

GEN-INFO

```
<PLS ><-----Name----->NBLKS Unit-systems Printer ***
# - # User t-series Engl Metr ***
in out ***
```

```

26     SG3, Lawn, Mod           1   1   1   1   27   0
27     SG3, Lawn, Steep        1   1   1   1   27   0
25     SG3, Lawn, Flat         1   1   1   1   27   0

```

END GEN-INFO

\*\*\* Section PWATER\*\*\*

ACTIVITY

```

<PLS > ***** Active Sections *****
# - # ATMP SNOW PWAT  SED  PST  PWG  PQAL MSTL PEST  NITR  PHOS  TRAC  ***
26     0   0   1   0   0   0   0   0   0   0   0   0   0
27     0   0   1   0   0   0   0   0   0   0   0   0   0
25     0   0   1   0   0   0   0   0   0   0   0   0   0

```

END ACTIVITY

PRINT-INFO

```

<PLS > ***** Print-flags ***** PIVL  PYR
# - # ATMP SNOW PWAT  SED  PST  PWG  PQAL MSTL PEST  NITR  PHOS  TRAC  *****
26     0   0   4   0   0   0   0   0   0   0   0   0   1   9
27     0   0   4   0   0   0   0   0   0   0   0   0   1   9
25     0   0   4   0   0   0   0   0   0   0   0   0   1   9

```

END PRINT-INFO

PWAT-PARM1

```

<PLS > PWATER variable monthly parameter value flags ***
# - # CSNO RTOP UZFG  VCS  VUZ  VNN  VIFW  VIRC  VLE  INFC  HWT  ***
26     0   0   0   0   0   0   0   0   0   0   0   0
27     0   0   0   0   0   0   0   0   0   0   0   0
25     0   0   0   0   0   0   0   0   0   0   0   0

```

END PWAT-PARM1

PWAT-PARM2

```

<PLS > PWATER input info: Part 2          ***
# - # ***FOREST  LZSN  INFILF  LSUR  SLSUR  KVARY  AGWRC
26     0           9   0.05   400   0.1     0     0.96
27     0           9   0.05   400   0.15    0     0.96
25     0           9   0.05   400   0.05    0     0.96

```

END PWAT-PARM2

PWAT-PARM3

```

<PLS > PWATER input info: Part 3          ***
# - # ***PETMAX  PETMIN  INFEXP  INFILD  DEEPFR  BASETP  AGWETP
26     0           0     2.5     2       0       0       0
27     0           0     2.5     2       0       0       0
25     0           0     2.5     2       0       0       0

```

END PWAT-PARM3

PWAT-PARM4

```

<PLS > PWATER input info: Part 4          ***
# - # CEPSC  UZSN  NSUR  INTFW  IRC  LZETP  ***
26     0.1   0.8   0.25  4     0.4  0.25
27     0.1   0.8   0.25  4     0.4  0.25
25     0.1   0.8   0.25  4     0.4  0.25

```

END PWAT-PARM4

PWAT-STATE1

```

<PLS > *** Initial conditions at start of simulation
ran from 1990 to end of 1992 (pat 1-11-95) RUN 21 ***
# - # *** CEPS  SURS  UZS  IFWS  LZS  AGWS  GWVS
26     0       0     0     0     3     1     0
27     0       0     0     0     3     1     0
25     0       0     0     0     3     1     0

```

END PWAT-STATE1

END PERLND

IMPLND

GEN-INFO

```

<PLS ><-----Name-----> Unit-systems  Printer ***
# - # User t-series Engr Metr ***
in out ***
4     ROOF TOPS/FLAT      1   1   1   27   0

```

5	DRIVEWAYS/FLAT	1	1	1	27	0
2	ROADS/MOD	1	1	1	27	0
3	ROADS/STEEP	1	1	1	27	0
11	PARKING/FLAT	1	1	1	27	0
1	ROADS/FLAT	1	1	1	27	0

END GEN-INFO

\*\*\* Section IWATER\*\*\*

ACTIVITY

```
<PLS > ***** Active Sections *****
# - # ATMP SNOW IWAT SLD IWG IQAL ***
4      0      0      1      0      0      0
5      0      0      1      0      0      0
2      0      0      1      0      0      0
3      0      0      1      0      0      0
11     0      0      1      0      0      0
1      0      0      1      0      0      0
```

END ACTIVITY

PRINT-INFO

```
<ILS > ***** Print-flags ***** PIVL PYR
# - # ATMP SNOW IWAT SLD IWG IQAL *****
4      0      0      4      0      0      0      1      9
5      0      0      4      0      0      0      1      9
2      0      0      4      0      0      0      1      9
3      0      0      4      0      0      0      1      9
11     0      0      4      0      0      0      1      9
1      0      0      4      0      0      0      1      9
```

END PRINT-INFO

IWAT-PARM1

```
<PLS > IWATER variable monthly parameter value flags ***
# - # CSNO RTOP VRS VNN RTLI ***
4      0      0      0      0      0
5      0      0      0      0      0
2      0      0      0      0      0
3      0      0      0      0      0
11     0      0      0      0      0
1      0      0      0      0      0
```

END IWAT-PARM1

IWAT-PARM2

```
<PLS > IWATER input info: Part 2 ***
# - # *** LSUR SLSUR NSUR RETSC
4      400      0.01      0.1      0.1
5      400      0.01      0.1      0.1
2      400      0.05      0.1      0.08
3      400      0.1      0.1      0.05
11     400      0.01      0.1      0.1
1      400      0.01      0.1      0.1
```

END IWAT-PARM2

IWAT-PARM3

```
<PLS > IWATER input info: Part 3 ***
# - # ***PETMAX PETMIN
4      0      0
5      0      0
2      0      0
3      0      0
11     0      0
1      0      0
```

END IWAT-PARM3

IWAT-STATE1

```
<PLS > *** Initial conditions at start of simulation
# - # *** RETS SURS
4      0      0
5      0      0
2      0      0
3      0      0
```

```

11          0          0
1           0          0
END IWAT-STATE1

```

END IMPLND

SCHEMATIC

<-Source-> <Name> #	<--Area--> <-factor-->	<-Target--> <Name> #	MBLK Tbl#	*** ***
Basin 1***				
PERLND 26	2.2	RCHRES 5	2	
PERLND 26	2.2	RCHRES 5	3	
IMPLND 4	1	RCHRES 5	5	
IMPLND 5	0.5	RCHRES 5	5	
Basin 2***				
IMPLND 2	1	RCHRES 1	5	
Basin 3***				
PERLND 26	1.9	RCHRES 5	2	
PERLND 26	1.9	RCHRES 5	3	
IMPLND 4	0.9	RCHRES 5	5	
IMPLND 5	0.4	RCHRES 5	5	
Basin 4***				
IMPLND 2	0.2	RCHRES 5	5	
Basin 5***				
IMPLND 2	0.3	RCHRES 2	5	
Basin 6***				
PERLND 27	0.4	RCHRES 4	2	
PERLND 27	0.4	RCHRES 4	3	
IMPLND 4	0.2	RCHRES 4	5	
IMPLND 5	0.1	RCHRES 4	5	
Basin 7***				
IMPLND 3	0.3	RCHRES 3	5	
Basin 8***				
PERLND 25	0.07	RCHRES 4	2	
PERLND 25	0.07	RCHRES 4	3	
IMPLND 11	0.03	RCHRES 4	5	
Basin 9***				
PERLND 25	0.3	COPY 501	12	
PERLND 25	0.3	COPY 601	12	
PERLND 25	0.3	COPY 501	13	
PERLND 25	0.3	COPY 601	13	
IMPLND 1	0.2	COPY 501	15	
IMPLND 1	0.2	COPY 601	15	

\*\*\*\*\*Routing\*\*\*\*\*

PERLND 26	2.2	COPY 1	12	
IMPLND 4	1	COPY 1	15	
IMPLND 5	0.5	COPY 1	15	
PERLND 26	2.2	COPY 1	13	
RCHRES 1	1	RCHRES 5	7	
RCHRES 1		COPY 1	17	
RCHRES 1	1	RCHRES 5	8	
RCHRES 1		COPY 1	18	
PERLND 26	1.9	COPY 1	12	
IMPLND 4	0.9	COPY 1	15	
IMPLND 5	0.4	COPY 1	15	
PERLND 26	1.9	COPY 1	13	
IMPLND 2	0.2	COPY 1	15	
RCHRES 2	1	RCHRES 5	7	
RCHRES 2		COPY 1	17	
RCHRES 2	1	RCHRES 5	8	
RCHRES 2		COPY 1	18	
PERLND 27	0.4	COPY 1	12	
IMPLND 4	0.2	COPY 1	15	
IMPLND 5	0.1	COPY 1	15	
PERLND 27	0.4	COPY 1	13	
RCHRES 3	1	RCHRES 4	7	
RCHRES 3		COPY 1	17	
RCHRES 3	1	RCHRES 4	8	
RCHRES 3		COPY 1	18	

```

PERLND 25          0.07      COPY      1      12
IMPLND 11          0.03      COPY      1      15
PERLND 25          0.07      COPY      1      13
RCHRES  5           1         COPY     501     17
RCHRES  4           1         COPY     501     17
END SCHEMATIC

```

NETWORK

```

<-Volume-> <-Grp> <-Member-><--Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name> # <Name> # #<-factor->strg <Name> # # <Name> # # ***
COPY 501 OUTPUT MEAN 1 1 48.4 DISPLY 1 INPUT TIMSER 1

```

```

<-Volume-> <-Grp> <-Member-><--Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name> # <Name> # #<-factor->strg <Name> # # <Name> # # ***
END NETWORK

```

RCHRES

GEN-INFO

```

RCHRES          Name          Nexits  Unit Systems  Printer          ***
# - #<-----><----> User T-series  Engr Metr LKFG          ***
                                     in out          ***
1      Flow Splitter  1-010    2    1    1    1    28    0    1
2      Flow Splitter  2-013    2    1    1    1    28    0    1
3      Flow Splitter  3-018    2    1    1    1    28    0    1
4      Trapezoidal Pond-015  2    1    1    1    28    0    1
5      Trapezoidal Pond-006  2    1    1    1    28    0    1

```

END GEN-INFO

\*\*\* Section RCHRES\*\*\*

ACTIVITY

```

<PLS > ***** Active Sections *****
# - # HYFG ADFG CNFG HTFG SDFG GQFG OXFG NUFQ PKFG PHFG ***
1      1    0    0    0    0    0    0    0    0    0
2      1    0    0    0    0    0    0    0    0    0
3      1    0    0    0    0    0    0    0    0    0
4      1    0    0    0    0    0    0    0    0    0
5      1    0    0    0    0    0    0    0    0    0

```

END ACTIVITY

PRINT-INFO

```

<PLS > ***** Print-flags ***** PIVL  PYR
# - # HYDR ADCA CONS HEAT SED  GQL  OXRX NUTR PLNK PHCB PIVL  PYR  *****
1      4    0    0    0    0    0    0    0    0    0    1    9
2      4    0    0    0    0    0    0    0    0    0    1    9
3      4    0    0    0    0    0    0    0    0    0    1    9
4      4    0    0    0    0    0    0    0    0    0    1    9
5      4    0    0    0    0    0    0    0    0    0    1    9

```

END PRINT-INFO

HYDR-PARM1

```

RCHRES  Flags for each HYDR Section          ***
# - # VC A1 A2 A3 ODFVFG for each *** ODGTFG for each  FUNCT for each
      FG FG FG FG possible exit *** possible exit  possible exit
      * * * * * * * * * * * * * * * * * * * * * * *
1      0 1 0 0 4 5 0 0 0 0 0 0 0 0 0 2 2 2 2 2
2      0 1 0 0 4 5 0 0 0 0 0 0 0 0 0 2 2 2 2 2
3      0 1 0 0 4 5 0 0 0 0 0 0 0 0 0 2 2 2 2 2
4      0 1 0 0 4 5 0 0 0 0 0 0 0 0 0 2 2 2 2 2
5      0 1 0 0 4 5 0 0 0 0 0 0 0 0 0 2 2 2 2 2

```

END HYDR-PARM1

HYDR-PARM2

```

# - # FTABNO          LEN          DELTH          STCOR          KS          DB50          ***
<-----><-----><-----><-----><-----><----->
1      1          0.01          0.0          0.0          0.5          0.0          ***
2      2          0.01          0.0          0.0          0.5          0.0          ***
3      3          0.01          0.0          0.0          0.5          0.0          ***
4      4          0.01          0.0          0.0          0.5          0.0          ***

```



```

5          5          0.03          0.0          0.0          0.5          0.0
END HYDR-PARM2
HYDR-INIT
RCHRES Initial conditions for each HYDR section ***
# - # *** VOL Initial value of COLIND Initial value of OUTDGT
*** ac-ft for each possible exit for each possible exit
<-----><-----> <-----><-----><-----> *** <-----><-----><----->
1          0          4.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0
2          0          4.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0
3          0          4.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0
4          0          4.0 5.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0
5          0          4.0 5.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0
END HYDR-INIT
END RCHRES

```

```

SPEC-ACTIONS
END SPEC-ACTIONS
FTABLES

```

```

FTABLE      5
91      5
Depth      Area      Volume      Outflow1      Outflow2      Velocity      Travel Time***
(ft)      (acres)      (acre-ft)      (cfs)      (cfs)      (ft/sec)      (Minutes)***
0.000000  0.371901  0.000000  0.000000  0.000000
0.077778  0.371901  0.028926  0.027321  0.093750
0.155556  0.371901  0.057851  0.038637  0.093750
0.233333  0.371901  0.086777  0.047321  0.093750
0.311111  0.371901  0.115702  0.054642  0.093750
0.388889  0.371901  0.144628  0.061091  0.093750
0.466667  0.371901  0.173554  0.066922  0.093750
0.544444  0.371901  0.202479  0.072284  0.093750
0.622222  0.371901  0.231405  0.077275  0.093750
0.700000  0.371901  0.260331  0.081962  0.093750
0.777778  0.371901  0.289256  0.086396  0.093750
0.855556  0.371901  0.318182  0.090613  0.093750
0.933333  0.371901  0.347107  0.094642  0.093750
1.011111  0.371901  0.376033  0.098507  0.093750
1.088889  0.371901  0.404959  0.102225  0.093750
1.166667  0.371901  0.433884  0.105813  0.093750
1.244444  0.371901  0.462810  0.109283  0.093750
1.322222  0.371901  0.491736  0.112647  0.093750
1.400000  0.371901  0.520661  0.115912  0.093750
1.477778  0.371901  0.549587  0.119089  0.093750
1.555556  0.371901  0.578512  0.122182  0.093750
1.633333  0.371901  0.607438  0.125200  0.093750
1.711111  0.371901  0.636364  0.128146  0.093750
1.788889  0.371901  0.665289  0.131026  0.093750
1.866667  0.371901  0.694215  0.133844  0.093750
1.944444  0.371901  0.723140  0.136604  0.093750
2.022222  0.371901  0.752066  0.139309  0.093750
2.100000  0.371901  0.780992  0.141963  0.093750
2.177778  0.371901  0.809917  0.144568  0.093750
2.255556  0.371901  0.838843  0.147127  0.093750
2.333333  0.371901  0.867769  0.149642  0.093750
2.411111  0.371901  0.896694  0.152116  0.093750
2.488889  0.371901  0.925620  0.154550  0.093750
2.566667  0.371901  0.954545  0.156946  0.093750
2.644444  0.371901  0.983471  0.159306  0.093750
2.722222  0.371901  1.012397  0.161632  0.093750
2.800000  0.371901  1.041322  0.163925  0.093750
2.877778  0.371901  1.070248  0.166186  0.093750
2.955556  0.371901  1.099174  0.168417  0.093750
3.033333  0.371901  1.128099  0.170618  0.093750
3.111111  0.371901  1.157025  0.172792  0.093750
3.188889  0.371901  1.185950  0.174939  0.093750
3.266667  0.371901  1.214876  0.177059  0.093750
3.344444  0.371901  1.243802  0.179155  0.093750
3.422222  0.371901  1.272727  0.181226  0.093750
3.500000  0.371901  1.301653  0.183274  0.093750
3.577778  0.371901  1.330579  0.185299  0.093750
3.655556  0.371901  1.359504  0.187302  0.093750

```

3.733333	0.371901	1.388430	0.189284	0.093750
3.811111	0.371901	1.417355	0.191246	0.093750
3.888889	0.371901	1.446281	0.193187	0.093750
3.966667	0.371901	1.475207	0.195110	0.093750
4.044444	0.371901	1.504132	0.248502	0.093750
4.122222	0.371901	1.533058	0.284283	0.093750
4.200000	0.371901	1.561983	0.309990	0.093750
4.277778	0.371901	1.590909	0.331338	0.093750
4.355556	0.371901	1.619835	0.350082	0.093750
4.433333	0.371901	1.648760	0.367040	0.093750
4.511111	0.371901	1.677686	0.382675	0.093750
4.588889	0.371901	1.706612	0.397276	0.093750
4.666667	0.371901	1.735537	0.411040	0.093750
4.744444	0.371901	1.764463	0.424108	0.093750
4.822222	0.371901	1.793388	0.436585	0.093750
4.900000	0.371901	1.822314	0.448550	0.093750
4.977778	0.371901	1.851240	0.460069	0.093750
5.055556	0.371901	1.880165	0.471191	0.093750
5.133333	0.371901	1.909091	0.481959	0.093750
5.211111	0.371901	1.938017	0.492408	0.093750
5.288889	0.371901	1.966942	0.502567	0.093750
5.366667	0.371901	1.995868	0.512461	0.093750
5.444444	0.371901	2.024793	0.522112	0.093750
5.522222	0.371901	2.053719	0.584275	0.093750
5.600000	0.371901	2.082645	1.042934	0.093750
5.677778	0.371901	2.111570	1.731359	0.093750
5.755556	0.371901	2.140496	2.558530	0.093750
5.833333	0.371901	2.169421	3.449815	0.093750
5.911111	0.371901	2.198347	4.328725	0.093750
5.988889	0.371901	2.227273	5.121849	0.093750
6.066667	0.371901	2.256198	5.771055	0.093750
6.144444	0.371901	2.285124	6.249903	0.093750
6.222222	0.371901	2.314050	6.583203	0.093750
6.300000	0.371901	2.342975	6.954791	0.093750
6.377778	0.371901	2.371901	7.263491	0.093750
6.455556	0.371901	2.400826	7.559016	0.093750
6.533333	0.371901	2.429752	7.842939	0.093750
6.611111	0.371901	2.458678	8.116541	0.093750
6.688889	0.371901	2.487603	8.380881	0.093750
6.766667	0.371901	2.516529	8.636850	0.093750
6.844444	0.371901	2.545455	8.885204	0.093750
6.922222	0.371901	2.574380	9.126590	0.093750
7.000000	0.371901	2.603306	9.361569	0.093750

END FTABLE 5  
 FTABLE 1  
 90 5

Depth (ft)	Area (acres)	Volume (acre-ft)	Outflow1 (cfs)	Outflow2 (cfs)	Velocity (ft/sec)	Travel Time*** (Minutes)***
0.000000	0.002296	0.000000	0.000000	0.000000		
0.111111	0.002296	0.000255	5.210267	0.000000		
0.222222	0.002296	0.000510	7.368430	0.000000		
0.333333	0.002296	0.000765	9.024447	0.000000		
0.444444	0.002296	0.001020	10.42053	0.000000		
0.555556	0.002296	0.001275	11.65051	0.000000		
0.666667	0.002296	0.001530	12.76249	0.000000		
0.777778	0.002296	0.001786	13.78507	0.000000		
0.888889	0.002296	0.002041	14.73686	0.000000		
1.000000	0.002296	0.002296	15.63080	0.000000		
1.111111	0.002296	0.002551	16.47631	0.000000		
1.222222	0.002296	0.002806	17.28050	0.000000		
1.333333	0.002296	0.003061	18.04889	0.000000		
1.444444	0.002296	0.003316	18.78588	0.000000		
1.555556	0.002296	0.003571	19.49503	0.000000		
1.666667	0.002296	0.003826	20.17928	0.000000		
1.777778	0.002296	0.004081	20.84107	0.000000		
1.888889	0.002296	0.004336	21.48248	0.000000		
2.000000	0.002296	0.004591	22.10529	0.000000		
2.111111	0.002296	0.004846	22.71103	0.000000		
2.222222	0.002296	0.005102	23.30102	0.000000		
2.333333	0.002296	0.005357	23.87644	0.000000		

2.444444	0.002296	0.005612	24.43832	0.000000
2.555556	0.002296	0.005867	24.98756	0.000000
2.666667	0.002296	0.006122	25.52499	0.000000
2.777778	0.002296	0.006377	26.05133	0.000000
2.888889	0.002296	0.006632	26.56725	0.000000
3.000000	0.002296	0.006887	27.07334	0.000000
3.111111	0.002296	0.007142	27.57014	0.000000
3.222222	0.002296	0.007397	28.05814	0.000000
3.333333	0.002296	0.007652	28.53781	0.000000
3.444444	0.002296	0.007907	29.00954	0.000000
3.555556	0.002296	0.008162	29.47372	0.000000
3.666667	0.002296	0.008418	29.93070	0.000000
3.777778	0.002296	0.008673	30.38081	0.000000
3.888889	0.002296	0.008928	30.82435	0.000000
4.000000	0.002296	0.009183	31.26160	0.000000
4.111111	0.002296	0.009438	31.69281	0.000000
4.222222	0.002296	0.009693	32.11824	0.000000
4.333333	0.002296	0.009948	32.53810	0.000000
4.444444	0.002296	0.010203	32.95262	0.000000
4.555556	0.002296	0.010458	33.36198	0.000000
4.666667	0.002296	0.010713	33.76639	0.000000
4.777778	0.002296	0.010968	34.16600	0.000000
4.888889	0.002296	0.011223	34.56100	0.000000
5.000000	0.002296	0.011478	34.95153	0.000000
5.111111	0.002296	0.011733	35.33775	0.000000
5.222222	0.002296	0.011989	35.71979	0.000000
5.333333	0.002296	0.012244	36.09779	0.000000
5.444444	0.002296	0.012499	36.47187	0.000000
5.555556	0.002296	0.012754	36.84215	0.000000
5.666667	0.002296	0.013009	37.20875	0.000000
5.777778	0.002296	0.013264	37.57177	0.000000
5.888889	0.002296	0.013519	37.93131	0.000000
6.000000	0.002296	0.013774	38.28748	0.000000
6.111111	0.002296	0.014029	38.64037	0.000000
6.222222	0.002296	0.014284	38.99007	0.000000
6.333333	0.002296	0.014539	39.33665	0.000000
6.444444	0.002296	0.014794	39.68021	0.000000
6.555556	0.002296	0.015049	40.02082	0.000000
6.666667	0.002296	0.015305	40.35855	0.000000
6.777778	0.002296	0.015560	40.69348	0.000000
6.888889	0.002296	0.015815	41.02568	0.000000
7.000000	0.002296	0.016070	41.35521	0.000000
7.111111	0.002296	0.016325	41.68213	0.000000
7.222222	0.002296	0.016580	42.00651	0.000000
7.333333	0.002296	0.016835	42.32841	0.000000
7.444444	0.002296	0.017090	42.64787	0.000000
7.555556	0.002296	0.017345	42.96496	0.000000
7.666667	0.002296	0.017600	43.27973	0.000000
7.777778	0.002296	0.017855	43.59222	0.000000
7.888889	0.002296	0.018110	43.90249	0.000000
8.000000	0.002296	0.018365	44.21058	0.000000
8.111111	0.002296	0.018621	44.51654	0.000000
8.222222	0.002296	0.018876	44.82041	0.000000
8.333333	0.002296	0.019131	45.12223	0.000000
8.444444	0.002296	0.019386	45.42205	0.000000
8.555556	0.002296	0.019641	45.71990	0.000000
8.666667	0.002296	0.019896	46.01583	0.000000
8.777778	0.002296	0.020151	46.30986	0.000000
8.888889	0.002296	0.020406	46.60204	0.000000
9.000000	0.002296	0.020661	46.89240	0.000000
9.111111	0.002296	0.020916	47.18097	0.000000
9.222222	0.002296	0.021171	47.46779	0.000000
9.333333	0.002296	0.021426	47.75288	0.000000
9.444444	0.002296	0.021681	48.03629	0.000000
9.555556	0.002296	0.021937	48.31803	0.000000
9.666667	0.002296	0.022192	48.59813	0.000000
9.777778	0.002296	0.022447	48.87663	0.000000
9.888889	0.002296	0.022702	49.15356	0.000000

END F'TABLE 1  
F'TABLE 2

90 5

Depth (ft)	Area (acres)	Volume (acre-ft)	Outflow1 (cfs)	Outflow2 (cfs)	Velocity (ft/sec)	Travel Time*** (Minutes)***
0.000000	0.002296	0.000000	0.000000	0.000000		
0.111111	0.002296	0.000255	5.210267	0.000000		
0.222222	0.002296	0.000510	7.368430	0.000000		
0.333333	0.002296	0.000765	9.024447	0.000000		
0.444444	0.002296	0.001020	10.42053	0.000000		
0.555556	0.002296	0.001275	11.65051	0.000000		
0.666667	0.002296	0.001530	12.76249	0.000000		
0.777778	0.002296	0.001786	13.78507	0.000000		
0.888889	0.002296	0.002041	14.73686	0.000000		
1.000000	0.002296	0.002296	15.63080	0.000000		
1.111111	0.002296	0.002551	16.47631	0.000000		
1.222222	0.002296	0.002806	17.28050	0.000000		
1.333333	0.002296	0.003061	18.04889	0.000000		
1.444444	0.002296	0.003316	18.78588	0.000000		
1.555556	0.002296	0.003571	19.49503	0.000000		
1.666667	0.002296	0.003826	20.17928	0.000000		
1.777778	0.002296	0.004081	20.84107	0.000000		
1.888889	0.002296	0.004336	21.48248	0.000000		
2.000000	0.002296	0.004591	22.10529	0.000000		
2.111111	0.002296	0.004846	22.71103	0.784769		
2.222222	0.002296	0.005102	23.30102	2.205262		
2.333333	0.002296	0.005357	23.87644	3.979211		
2.444444	0.002296	0.005612	24.43832	5.917238		
2.555556	0.002296	0.005867	24.98756	7.826549		
2.666667	0.002296	0.006122	25.52499	9.523132		
2.777778	0.002296	0.006377	26.05133	10.86741		
2.888889	0.002296	0.006632	26.56725	11.81283		
3.000000	0.002296	0.006887	27.07334	12.59852		
3.111111	0.002296	0.007142	27.57014	13.28001		
3.222222	0.002296	0.007397	28.05814	13.92819		
3.333333	0.002296	0.007652	28.53781	14.54752		
3.444444	0.002296	0.007907	29.00954	15.14154		
3.555556	0.002296	0.008162	29.47372	15.71312		
3.666667	0.002296	0.008418	29.93070	16.26462		
3.777778	0.002296	0.008673	30.38081	16.79803		
3.888889	0.002296	0.008928	30.82435	17.31501		
4.000000	0.002296	0.009183	31.26160	17.81700		
4.111111	0.002296	0.009438	31.69281	18.30523		
4.222222	0.002296	0.009693	32.11824	18.78076		
4.333333	0.002296	0.009948	32.53810	19.24456		
4.444444	0.002296	0.010203	32.95262	19.69743		
4.555556	0.002296	0.010458	33.36198	20.14013		
4.666667	0.002296	0.010713	33.76639	20.57330		
4.777778	0.002296	0.010968	34.16600	20.99753		
4.888889	0.002296	0.011223	34.56100	21.41337		
5.000000	0.002296	0.011478	34.95153	21.82128		
5.111111	0.002296	0.011733	35.33775	22.22170		
5.222222	0.002296	0.011989	35.71979	22.61504		
5.333333	0.002296	0.012244	36.09779	23.00165		
5.444444	0.002296	0.012499	36.47187	23.38186		
5.555556	0.002296	0.012754	36.84215	23.75600		
5.666667	0.002296	0.013009	37.20875	24.12433		
5.777778	0.002296	0.013264	37.57177	24.48712		
5.888889	0.002296	0.013519	37.93131	24.84462		
6.000000	0.002296	0.013774	38.28748	25.19704		
6.111111	0.002296	0.014029	38.64037	25.54460		
6.222222	0.002296	0.014284	38.99007	25.88750		
6.333333	0.002296	0.014539	39.33665	26.22591		
6.444444	0.002296	0.014794	39.68021	26.56001		
6.555556	0.002296	0.015049	40.02082	26.88996		
6.666667	0.002296	0.015305	40.35855	27.21591		
6.777778	0.002296	0.015560	40.69348	27.53801		
6.888889	0.002296	0.015815	41.02568	27.85638		
7.000000	0.002296	0.016070	41.35521	28.17115		
7.111111	0.002296	0.016325	41.68213	28.48244		
7.222222	0.002296	0.016580	42.00651	28.79037		
7.333333	0.002296	0.016835	42.32841	29.09504		

7.444444	0.002296	0.017090	42.64787	29.39655
7.555556	0.002296	0.017345	42.96496	29.69500
7.666667	0.002296	0.017600	43.27973	29.99048
7.777778	0.002296	0.017855	43.59222	30.28307
7.888889	0.002296	0.018110	43.90249	30.57287
8.000000	0.002296	0.018365	44.21058	30.85995
8.111111	0.002296	0.018621	44.51654	31.14438
8.222222	0.002296	0.018876	44.82041	31.42623
8.333333	0.002296	0.019131	45.12223	31.70558
8.444444	0.002296	0.019386	45.42205	31.98249
8.555556	0.002296	0.019641	45.71990	32.25702
8.666667	0.002296	0.019896	46.01583	32.52924
8.777778	0.002296	0.020151	46.30986	32.79920
8.888889	0.002296	0.020406	46.60204	33.06695
9.000000	0.002296	0.020661	46.89240	33.33255
9.111111	0.002296	0.020916	47.18097	33.59605
9.222222	0.002296	0.021171	47.46779	33.85751
9.333333	0.002296	0.021426	47.75288	34.11695
9.444444	0.002296	0.021681	48.03629	34.37444
9.555556	0.002296	0.021937	48.31803	34.63002
9.666667	0.002296	0.022192	48.59813	34.88372
9.777778	0.002296	0.022447	48.87663	35.13559
9.888889	0.002296	0.022702	49.15356	35.38567

END FTABLE 2

FTABLE 4

91 5

Depth (ft)	Area (acres)	Volume (acre-ft)	Outflow1 (cfs)	Outflow2 (cfs)	Velocity (ft/sec)	Travel Time*** (Minutes)***
0.000000	0.037879	0.000000	0.000000	0.000000		
0.077778	0.037879	0.002946	0.017028	0.009549		
0.155556	0.037879	0.005892	0.024082	0.009549		
0.233333	0.037879	0.008838	0.029494	0.009549		
0.311111	0.037879	0.011785	0.034056	0.009549		
0.388889	0.037879	0.014731	0.038076	0.009549		
0.466667	0.037879	0.017677	0.041710	0.009549		
0.544444	0.037879	0.020623	0.045052	0.009549		
0.622222	0.037879	0.023569	0.048163	0.009549		
0.700000	0.037879	0.026515	0.051085	0.009549		
0.777778	0.037879	0.029461	0.053848	0.009549		
0.855556	0.037879	0.032407	0.056476	0.009549		
0.933333	0.037879	0.035354	0.058987	0.009549		
1.011111	0.037879	0.038300	0.061396	0.009549		
1.088889	0.037879	0.041246	0.063714	0.009549		
1.166667	0.037879	0.044192	0.065950	0.009549		
1.244444	0.037879	0.047138	0.068113	0.009549		
1.322222	0.037879	0.050084	0.070209	0.009549		
1.400000	0.037879	0.053030	0.072245	0.009549		
1.477778	0.037879	0.055976	0.074224	0.009549		
1.555556	0.037879	0.058923	0.076152	0.009549		
1.633333	0.037879	0.061869	0.078033	0.009549		
1.711111	0.037879	0.064815	0.079869	0.009549		
1.788889	0.037879	0.067761	0.081664	0.009549		
1.866667	0.037879	0.070707	0.083421	0.009549		
1.944444	0.037879	0.073653	0.085141	0.009549		
2.022222	0.037879	0.076599	0.086827	0.009549		
2.100000	0.037879	0.079545	0.088481	0.009549		
2.177778	0.037879	0.082492	0.090105	0.009549		
2.255556	0.037879	0.085438	0.091700	0.009549		
2.333333	0.037879	0.088384	0.093267	0.009549		
2.411111	0.037879	0.091330	0.094809	0.009549		
2.488889	0.037879	0.094276	0.096326	0.009549		
2.566667	0.037879	0.097222	0.097820	0.009549		
2.644444	0.037879	0.100168	0.099291	0.009549		
2.722222	0.037879	0.103114	0.100740	0.009549		
2.800000	0.037879	0.106061	0.102169	0.009549		
2.877778	0.037879	0.109007	0.103579	0.009549		
2.955556	0.037879	0.111953	0.104969	0.009549		
3.033333	0.037879	0.114899	0.106341	0.009549		
3.111111	0.037879	0.117845	0.107696	0.009549		
3.188889	0.037879	0.120791	0.109034	0.009549		

3.266667	0.037879	0.123737	0.110355	0.009549
3.344444	0.037879	0.126684	0.111661	0.009549
3.422222	0.037879	0.129630	0.112952	0.009549
3.500000	0.037879	0.132576	0.114229	0.009549
3.577778	0.037879	0.135522	0.115491	0.009549
3.655556	0.037879	0.138468	0.116740	0.009549
3.733333	0.037879	0.141414	0.117975	0.009549
3.811111	0.037879	0.144360	0.119197	0.009549
3.888889	0.037879	0.147306	0.120408	0.009549
3.966667	0.037879	0.150253	0.121606	0.009549
4.044444	0.037879	0.153199	0.122813	0.009549
4.122222	0.037879	0.156145	0.124011	0.009549
4.200000	0.037879	0.159091	0.125209	0.009549
4.277778	0.037879	0.162037	0.126407	0.009549
4.355556	0.037879	0.164983	0.127605	0.009549
4.433333	0.037879	0.167929	0.128803	0.009549
4.511111	0.037879	0.170875	0.130001	0.009549
4.588889	0.037879	0.173822	0.131199	0.009549
4.666667	0.037879	0.176768	0.132397	0.009549
4.744444	0.037879	0.179714	0.133595	0.009549
4.822222	0.037879	0.182660	0.134793	0.009549
4.900000	0.037879	0.185606	0.135991	0.009549
4.977778	0.037879	0.188552	0.137189	0.009549
5.055556	0.037879	0.191498	0.138387	0.009549
5.133333	0.037879	0.194444	0.139585	0.009549
5.211111	0.037879	0.197391	0.140783	0.009549
5.288889	0.037879	0.200337	0.141981	0.009549
5.366667	0.037879	0.203283	0.143179	0.009549
5.444444	0.037879	0.206229	0.144377	0.009549
5.522222	0.037879	0.209175	0.145575	0.009549
5.600000	0.037879	0.212121	0.146773	0.009549
5.677778	0.037879	0.215067	0.147971	0.009549
5.755556	0.037879	0.218013	0.149169	0.009549
5.833333	0.037879	0.220960	0.150367	0.009549
5.911111	0.037879	0.223906	0.151565	0.009549
5.988889	0.037879	0.226852	0.152763	0.009549
6.066667	0.037879	0.229798	0.153961	0.009549
6.144444	0.037879	0.232744	0.155159	0.009549
6.222222	0.037879	0.235690	0.156357	0.009549
6.300000	0.037879	0.238636	0.157555	0.009549
6.377778	0.037879	0.241582	0.158753	0.009549
6.455556	0.037879	0.244529	0.159951	0.009549
6.533333	0.037879	0.247475	0.161149	0.009549
6.611111	0.037879	0.250421	0.162347	0.009549
6.688889	0.037879	0.253367	0.163545	0.009549
6.766667	0.037879	0.256313	0.164743	0.009549
6.844444	0.037879	0.259259	0.165941	0.009549
6.922222	0.037879	0.262205	0.167139	0.009549
7.000000	0.037879	0.265152	0.168337	0.009549

END FTABLE 4

FTABLE 3

90 5

Depth (ft)	Area (acres)	Volume (acre-ft)	Outflow1 (cfs)	Outflow2 (cfs)	Velocity (ft/sec)	Travel Time*** (Minutes)***
0.000000	0.002296	0.000000	0.000000	0.000000		
0.111111	0.002296	0.000255	5.210267	0.000000		
0.222222	0.002296	0.000510	7.368430	0.000000		
0.333333	0.002296	0.000765	9.024447	0.000000		
0.444444	0.002296	0.001020	10.42053	0.000000		
0.555556	0.002296	0.001275	11.65051	0.000000		
0.666667	0.002296	0.001530	12.76249	0.000000		
0.777778	0.002296	0.001786	13.78507	0.000000		
0.888889	0.002296	0.002041	14.73686	0.000000		
1.000000	0.002296	0.002296	15.63080	0.000000		
1.111111	0.002296	0.002551	16.47631	0.000000		
1.222222	0.002296	0.002806	17.28050	0.000000		
1.333333	0.002296	0.003061	18.04889	0.000000		
1.444444	0.002296	0.003316	18.78588	0.000000		
1.555556	0.002296	0.003571	19.49503	0.000000		
1.666667	0.002296	0.003826	20.17928	0.000000		

1.777778	0.002296	0.004081	20.84107	0.000000
1.888889	0.002296	0.004336	21.48248	0.000000
2.000000	0.002296	0.004591	22.10529	0.000000
2.111111	0.002296	0.004846	22.71103	0.784769
2.222222	0.002296	0.005102	23.30102	2.205262
2.333333	0.002296	0.005357	23.87644	3.979211
2.444444	0.002296	0.005612	24.43832	5.917238
2.555556	0.002296	0.005867	24.98756	7.826549
2.666667	0.002296	0.006122	25.52499	9.523132
2.777778	0.002296	0.006377	26.05133	10.86741
2.888889	0.002296	0.006632	26.56725	11.81283
3.000000	0.002296	0.006887	27.07334	12.59852
3.111111	0.002296	0.007142	27.57014	13.28001
3.222222	0.002296	0.007397	28.05814	13.92819
3.333333	0.002296	0.007652	28.53781	14.54752
3.444444	0.002296	0.007907	29.00954	15.14154
3.555556	0.002296	0.008162	29.47372	15.71312
3.666667	0.002296	0.008418	29.93070	16.26462
3.777778	0.002296	0.008673	30.38081	16.79803
3.888889	0.002296	0.008928	30.82435	17.31501
4.000000	0.002296	0.009183	31.26160	17.81700
4.111111	0.002296	0.009438	31.69281	18.30523
4.222222	0.002296	0.009693	32.11824	18.78076
4.333333	0.002296	0.009948	32.53810	19.24456
4.444444	0.002296	0.010203	32.95262	19.69743
4.555556	0.002296	0.010458	33.36198	20.14013
4.666667	0.002296	0.010713	33.76639	20.57330
4.777778	0.002296	0.010968	34.16600	20.99753
4.888889	0.002296	0.011223	34.56100	21.41337
5.000000	0.002296	0.011478	34.95153	21.82128
5.111111	0.002296	0.011733	35.33775	22.22170
5.222222	0.002296	0.011989	35.71979	22.61504
5.333333	0.002296	0.012244	36.09779	23.00165
5.444444	0.002296	0.012499	36.47187	23.38186
5.555556	0.002296	0.012754	36.84215	23.75600
5.666667	0.002296	0.013009	37.20875	24.12433
5.777778	0.002296	0.013264	37.57177	24.48712
5.888889	0.002296	0.013519	37.93131	24.84462
6.000000	0.002296	0.013774	38.28748	25.19704
6.111111	0.002296	0.014029	38.64037	25.54460
6.222222	0.002296	0.014284	38.99007	25.88750
6.333333	0.002296	0.014539	39.33665	26.22591
6.444444	0.002296	0.014794	39.68021	26.56001
6.555556	0.002296	0.015049	40.02082	26.88996
6.666667	0.002296	0.015305	40.35855	27.21591
6.777778	0.002296	0.015560	40.69348	27.53801
6.888889	0.002296	0.015815	41.02568	27.85638
7.000000	0.002296	0.016070	41.35521	28.17115
7.111111	0.002296	0.016325	41.68213	28.48244
7.222222	0.002296	0.016580	42.00651	28.79037
7.333333	0.002296	0.016835	42.32841	29.09504
7.444444	0.002296	0.017090	42.64787	29.39655
7.555556	0.002296	0.017345	42.96496	29.69500
7.666667	0.002296	0.017600	43.27973	29.99048
7.777778	0.002296	0.017855	43.59222	30.28307
7.888889	0.002296	0.018110	43.90249	30.57287
8.000000	0.002296	0.018365	44.21058	30.85995
8.111111	0.002296	0.018621	44.51654	31.14438
8.222222	0.002296	0.018876	44.82041	31.42623
8.333333	0.002296	0.019131	45.12223	31.70558
8.444444	0.002296	0.019386	45.42205	31.98249
8.555556	0.002296	0.019641	45.71990	32.25702
8.666667	0.002296	0.019896	46.01583	32.52924
8.777778	0.002296	0.020151	46.30986	32.79920
8.888889	0.002296	0.020406	46.60204	33.06695
9.000000	0.002296	0.020661	46.89240	33.33255
9.111111	0.002296	0.020916	47.18097	33.59605
9.222222	0.002296	0.021171	47.46779	33.85751
9.333333	0.002296	0.021426	47.75288	34.11695
9.444444	0.002296	0.021681	48.03629	34.37444

9.555556 0.002296 0.021937 48.31803 34.63002  
 9.666667 0.002296 0.022192 48.59813 34.88372  
 9.777778 0.002296 0.022447 48.87663 35.13559  
 9.888889 0.002296 0.022702 49.15356 35.38567

END FTABLE 3  
 END FTABLES

EXT SOURCES

<-Volume-> <Name>	<Member> #	SsysSgap tem	<--Mult--> strg	Tran <-factor--> strg	<-Target <Name>	vols #	<-Grp> #	<-Member-> <Name>	#	*** #
WDM	2	PREC	ENGL	1.3	PERLND	1	999	EXTNL	PREC	
WDM	2	PREC	ENGL	1.3	IMPLND	1	999	EXTNL	PREC	
WDM	1	EVAP	ENGL	0.8	PERLND	1	999	EXTNL	PETINP	
WDM	1	EVAP	ENGL	0.8	IMPLND	1	999	EXTNL	PETINP	
WDM	2	PREC	ENGL	1.3	RCHRES	4		EXTNL	PREC	
WDM	2	PREC	ENGL	1.3	RCHRES	5		EXTNL	PREC	
WDM	1	EVAP	ENGL	0.8	RCHRES	4		EXTNL	POTEV	
WDM	1	EVAP	ENGL	0.8	RCHRES	5		EXTNL	POTEV	

END EXT SOURCES

EXT TARGETS

<-Volume-> <Name>	<-Grp> #	<-Member-> <Name>	#	<--Mult--> #	Tran <-factor--> strg	<-Volume-> <Name>	<-Member-> <Name>	Tsys tem	Tgap strg	Amd strg	*** ***
RCHRES	5	HYDR	RO	1	1	WDM	1000	FLOW	ENGL	REPL	
RCHRES	5	HYDR	O	1	1	WDM	1006	FLOW	ENGL	REPL	
RCHRES	5	HYDR	O	2	1	WDM	1007	FLOW	ENGL	REPL	
RCHRES	5	HYDR	STAGE	1	1	WDM	1001	STAG	ENGL	REPL	
COPY	1	OUTPUT	MEAN	1	1	48.4	WDM	701	FLOW	ENGL	REPL
COPY	501	OUTPUT	MEAN	1	1	48.4	WDM	801	FLOW	ENGL	REPL
COPY	601	OUTPUT	MEAN	1	1	48.4	WDM	901	FLOW	ENGL	REPL
RCHRES	1	HYDR	RO	1	1	WDM	1010	FLOW	ENGL	REPL	
RCHRES	1	HYDR	O	1	1	WDM	1011	FLOW	ENGL	REPL	
RCHRES	1	HYDR	O	2	1	WDM	1012	FLOW	ENGL	REPL	
RCHRES	1	HYDR	STAGE	1	1	WDM	1013	STAG	ENGL	REPL	
RCHRES	2	HYDR	RO	1	1	WDM	1014	FLOW	ENGL	REPL	
RCHRES	2	HYDR	O	1	1	WDM	1015	FLOW	ENGL	REPL	
RCHRES	2	HYDR	O	2	1	WDM	1016	FLOW	ENGL	REPL	
RCHRES	2	HYDR	STAGE	1	1	WDM	1017	STAG	ENGL	REPL	
RCHRES	4	HYDR	RO	1	1	WDM	1018	FLOW	ENGL	REPL	
RCHRES	4	HYDR	O	1	1	WDM	1019	FLOW	ENGL	REPL	
RCHRES	4	HYDR	O	2	1	WDM	1020	FLOW	ENGL	REPL	
RCHRES	4	HYDR	STAGE	1	1	WDM	1021	STAG	ENGL	REPL	
RCHRES	3	HYDR	RO	1	1	WDM	1022	FLOW	ENGL	REPL	
RCHRES	3	HYDR	O	1	1	WDM	1023	FLOW	ENGL	REPL	
RCHRES	3	HYDR	O	2	1	WDM	1024	FLOW	ENGL	REPL	
RCHRES	3	HYDR	STAGE	1	1	WDM	1025	STAG	ENGL	REPL	

END EXT TARGETS

MASS-LINK

<Volume> <Name>	<-Grp>	<-Member-> <Name>	#	<--Mult--> #	<-factor-->	<Target> <Name>	<-Grp>	<-Member-> <Name>	#	*** #
MASS-LINK			2							
PERLND	PWATER	SURO			0.083333	RCHRES		INFLOW	IVOL	
END MASS-LINK			2							
MASS-LINK			3							
PERLND	PWATER	IFWO			0.083333	RCHRES		INFLOW	IVOL	
END MASS-LINK			3							
MASS-LINK			5							
IMPLND	IWATER	SURO			0.083333	RCHRES		INFLOW	IVOL	
END MASS-LINK			5							
MASS-LINK			7							
RCHRES	OFLOW	OVOL	1			RCHRES		INFLOW	IVOL	
END MASS-LINK			7							
MASS-LINK			8							
RCHRES	OFLOW	OVOL	2			RCHRES		INFLOW	IVOL	



```

END MASS-LINK      8

MASS-LINK          12
PERLND      PWATER SURO      0.083333      COPY      INPUT      MEAN
END MASS-LINK      12

MASS-LINK          13
PERLND      PWATER IFWO      0.083333      COPY      INPUT      MEAN
END MASS-LINK      13

MASS-LINK          15
IMPLND      IWATER SURO      0.083333      COPY      INPUT      MEAN
END MASS-LINK      15

MASS-LINK          17
RCHRES      OFLOW  OVOL      1              COPY      INPUT      MEAN
END MASS-LINK      17

MASS-LINK          18
RCHRES      OFLOW  OVOL      2              COPY      INPUT      MEAN
END MASS-LINK      18

END MASS-LINK

END RUN

```

*Predeveloped HSPF Message File*

*Mitigated HSPF Message File*

## *Disclaimer*

### *Legal Notice*

This program and accompanying documentation are provided 'as-is' without warranty of any kind. The entire risk regarding the performance and results of this program is assumed by End User. Clear Creek Solutions Inc. and the governmental licensee or sublicensees disclaim all warranties, either expressed or implied, including but not limited to implied warranties of program and accompanying documentation. In no event shall Clear Creek Solutions Inc. be liable for any damages whatsoever (including without limitation to damages for loss of business profits, loss of business information, business interruption, and the like) arising out of the use of, or inability to use this program even if Clear Creek Solutions Inc. or their authorized representatives have been advised of the possibility of such damages. Software Copyright © by : Clear Creek Solutions, Inc. 2005-2018; All Rights Reserved.

Clear Creek Solutions, Inc.  
6200 Capitol Blvd. Ste F  
Olympia, WA. 98501  
Toll Free 1(866)943-0304  
Local (360)943-0304

[www.clearcreeksolutions.com](http://www.clearcreeksolutions.com)

**Appendix II: Perk Filter Information**

## Water Quality

Water Quality BMP Flow and Volume for POC #1


On-line facility volume: 0 acre-feet

On-line facility target flow: 0 cfs.


Adjusted for 15 min: 0 cfs.

Off-line facility target flow: 0 cfs.

Adjusted for 15 min: 0 cfs.



1-CARTRIDGE CATCHBASIN - PLAN VIEW 1  
1



1-CARTRIDGE CATCHBASIN - SECTION VIEW A  
1

THE STORMWATER MANAGEMENT  
StormFilter®  
U.S. PATENT No. 5,322,629,  
No. 5,707,527, No. 6,027,639  
No. 6,649,048, No. 5,624,576,  
AND OTHER U.S. AND FOREIGN  
PATENTS PENDING

© 2006 CONTECH Stormwater Solutions




STEEL CATCHBASIN STORMFILTER  
PLAN AND SECTION VIEWS  
STANDARD DETAIL - 1 CARTRIDGE UNIT


DRAWING
1
1/3

# Washington GULD\*

CARTRIDGE SIZE	TREATMENT FLOW RATE GPM / CFS	TOTAL FLOW CAPACITY CFS
12.00"	27.2 / 0.081	1.4
18.00"	40.8 / 0.091	1.4
STACKED 12.00" + 12.00"	54.4 / 0.121	1.4
STACKED 18.00" + 12.00"	68 / 0.152	1.4



4X TRAFFIC RATED SOLID PLATE COVER.





OUTLET, SEE BELOW & NOTE 3 FOR LOCATION OPTIONS & SPECS.

CARTRIDGE SIZE	MINIMUM DEPTHS (SEE NOTE 6)			
	Ø 6.0" OUTLET PIPE (IN INCHES)	Ø 8.0" OUTLET PIPE (IN INCHES)	Ø 10.0" OUTLET PIPE (IN INCHES)	Ø 12.0" OUTLET PIPE (IN INCHES)
12.00"	39	41	43	45
18.00"	46	48	50	52
STACKED 12.00" + 12.00"	56	58	60	62
STACKED 18.00" + 12.00"	63	65	67	69

**Notes:**

1. Precast concrete structure shall be manufactured in accordance with ASTM Designation C857 and C858.
2. Perk Filter™ Catch basin shall be supplied with traffic rated (H2O) bicycle-proof grates and solid plate cover.
3. Inlet pipe(s) may enter device on three sides of the inlet chamber. Outlet pipe(s) may exit on all four sides. All pipe is Ø 12" maximum.
4. Inlet chamber shall be supplied with a drain-down device designed to remove standing water between storm events.
5. Perk Filter™ catch basin shall be supplied with FloGard® pre-filter device. FloGard® pre-filter and Perk Filter™ cartridge shall be maintained in accordance with manufacturer recommendations.
6. For depths less than the specified minimum contact Oldcastle® Stormwater Solutions for engineering assistance.



**SECTION A-A**  
FOUR CARTRIDGE CONCRETE CATCH BASIN  
(END GRATE CONFIGURATION)

\* **Treatment Flow Rates shown conform to Washington State GULD Specifications.**



**Perk Filter™**  
Concrete Catch Basin  
Four Cartridge  
Washington State GULD  
(End Grate Configuration)




**Oldcastle®**  
Stormwater Solutions

7921 Southpark Plaza, Suite 200 | Littleton, CO | 80120 | Ph: 800.579.8819 | oldcastlestormwater.com  
THIS DOCUMENT IS THE PROPERTY OF OLDCASTLE PRECAST, INC. IT IS SUBMITTED FOR REFERENCE PURPOSES ONLY AND SHALL NOT BE USED IN ANY WAY INJURIOUS TO THE INTERESTS OF SAID COMPANY. COPYRIGHT © 2014 OLDCASTLE PRECAST, INC. ALL RIGHTS RESERVED.

DRAWING NO. PF-CCB-WA-0006	REV E	ECO ECO-0140	DATE JPR 4/18/16	DRAWN BY JPR 3/2/11	SHEET 1 OF 1
-------------------------------	----------	-----------------	---------------------	------------------------	--------------





Minimum Depth						
PIPE SIZE	$\varnothing 6.00''$	$\varnothing 8.00''$	$\varnothing 10.00''$	$\varnothing 12.00''$	$\varnothing 15.00''$	$\varnothing 18.00''$
CARTRIDGE TYPE	MINIMUM DEPTH RIM TO OUTLET	MINIMUM DEPTH RIM TO OUTLET	MINIMUM DEPTH RIM TO OUTLET	MINIMUM DEPTH RIM TO OUTLET	MINIMUM DEPTH RIM TO OUTLET	MINIMUM DEPTH RIM TO OUTLET
12"	3.67' [44.00"]	3.92' [47.00"]	4.17' [50.00"]	4.42' [53.00"]	4.67' [56.00"]	4.92' [59.00"]
18"	4.42' [53.00"]	4.67' [56.00"]	4.92' [59.00"]	5.17' [62.00"]	5.42' [65.00"]	5.67' [68.00"]
12" + 12"	5.17' [62.00"]	5.42' [65.00"]	5.67' [68.00"]	5.92' [71.00"]	6.17' [74.00"]	6.42' [77.00"]
12" + 18"	5.67' [68.00"]	5.92' [71.00"]	6.17' [74.00"]	6.42' [77.00"]	6.67' [80.00"]	6.92' [83.00"]

$\varnothing 48.00''$ PERK FILTER MANHOLE								
TREATMENT FLOW RATES, TOTAL FLOW CAPACITIES & MAXIMUM HEAD LOSS								
CARTRIDGE STACK QUANTITY	CARTRIDGE STACK CONFIGURATION							
	12"		18"		12" & 12"		12" & 18"	
	TREATMENT FLOW RATE (GPM / CFS)	TOTAL FLOW CAPACITY (CFS)	TREATMENT FLOW RATE (GPM / CFS)	TOTAL FLOW CAPACITY (CFS)	TREATMENT FLOW RATE (GPM / CFS)	TOTAL FLOW CAPACITY (CFS)	TREATMENT FLOW RATE (GPM / CFS)	TOTAL FLOW CAPACITY (CFS)
1	6.8 / 0.015	2.47	10.2 / 0.022	3.05	13.6 / 0.03	3.45	17 / 0.037	3.62
2	13.6 / 0.03	2.47	20.4 / 0.045	3.05	27.2 / 0.06	3.45	34 / 0.075	3.62
MAXIMUM HEAD LOSS	1.7 FEET		2.3 FEET		2.9 FEET		3.5 FEET	



**Perk Filter™**  
 $\varnothing 48.00''$  Manhole  
 Washington State GULD  
 One to Two Cartridges / Stacks



**Oldcastle®**  
 Stormwater Solutions

7921 Southpark Plaza, Suite 200 | Littleton, CO | 80120 | Ph: 800.579.8819 | oldcastlestormwater.com  
 THIS DOCUMENT IS THE PROPERTY OF OLDCASTLE PRECAST, INC. IT IS SUBMITTED FOR REFERENCE PURPOSES ONLY AND SHALL NOT BE USED IN ANY WAY INJURIOUS TO THE INTERESTS OF SAID COMPANY. COPYRIGHT © 2016 OLDCASTLE PRECAST, INC. ALL RIGHTS RESERVED.

DRAWING NO. PF-MH-48-WA	REV NR	ECO ECO-0132 ISM 4/27/15	DATE ISM 4/27/15	SHEET 2 OF 2
----------------------------	-----------	--------------------------------	---------------------	--------------

**Appendix III: Geotechnical Report**

# Geotechnical Report

## Valley View Sub-division

Camas, Washington

Prepared for:  
Stan Firestone  
Vancouver, Washington  
30 April 2014  
Updated 1 May 2018



**Rapid  
Soil Solutions** LLC  
3915 SW Plum St  
Portland, OR  
503-816-3689

## TABLE OF CONTENTS

<b>1.0 GENERAL INFORMATION .....</b>	<b>3</b>
<b>2.0 SITE CONDITIONS.....</b>	<b>3</b>
2.1 Surface Conditions .....	3
2.2 Regional Geology .....	3
2.3 Field Explorations and Surfaces Conditions .....	4
2.3.1 Field Explorations .....	4
2.3.2 Surface Conditions .....	4
2.3.3 Groundwater .....	4
<b>3.0 GEOTECHNICAL DESIGN RECOMMENDATIONS .....</b>	<b>4</b>
3.1 Foundation.....	4
3.2 Retaining Walls .....	5
3.3 Seismic Design.....	6
3.4 Hazards.....	6
<b>4.0 CONSTRUCTION RECOMMENDATIONS .....</b>	<b>7</b>
4.1 Site Preparation .....	7
4.1.1 Proof Rolling.....	7
4.1.2 Wet Soil Conditions.....	8
4.2 Excavation .....	8
4.3 Structural Fills .....	8
4.3.1 Native Soils.....	8
4.3.2 Imported Granular Fill .....	8
4.3.3 Floor Slab and Base Rock Aggregate .....	9
4.4 Drainage .....	9
<b>5.0 CONSTRUCTION OBSERVATIONS .....</b>	<b>9</b>
<b>6.0 LIMITATIONS .....</b>	<b>9</b>

### SUPPORTING DATA

#### Appendix A - Figures

Figure 1 Location Plan

Figure 2 Site Plan

#### Appendix B – Laboratory data and Soil Logs

## 1.0 PROJECT AND SITE DESCRIPTIONS

### Introduction

Rapid Soil Solutions has prepared this Geotechnical Report to provide bearing capacity, roadway design values, soil parameters for earth work operations and installation of utilities for the 30 lot sub-division.

## 2.0 SITE CONDITIONS


### 2.1 Surface Conditions

The property is located in the Clark County Washington, accessed off of SE 40<sup>th</sup> Street. The site was cleared in past. The site was covered with tall grasses and weeds. See below site photo.



### 2.2 Regional Geology

The Camas Quadrangle developed in 2008 by Evarts and O'Connor maps the site as boring volcanic rock. However, the rock is far below the site and the site is cover with fine grained flood deposits.



## 2.3 Field Exploration and Subsurface Conditions

### 2.3.1 Field Explorations

Four (4) hand augur holes were excavated. The location of the augur holes are shown on Figure 2 in Appendix A. A registered professional engineer performed the excavation and logged the subsurface materials. Hand augur logs detailing materials encountered is in Appendix B. The logs were created using the Unified Soil Classification and Visual Manual Procedure (ASTM-D 2488).

### 2.3.1 Subsurface Conditions

The soil conditions were fine grained stiff damp sandy SILT. The soil conditions in all augur holes were consistent with each other and local geology map. Moistures ranged from 23.1 % to 28%.

### 2.3.2 Groundwater

No ground water was found during the explorations.

## 3.0 GEOTECHNICAL DESIGN RECOMMENDATIONS

### 3.1 Foundation Design

The building foundations may be installed on either engineered fill or firm native sub-grade that is found at a depth of about 0.5 feet. This depth may be locally variable and should be confirmed by a geotechnical engineer or their representative at the time of construction.

Continuous wall and isolated spread footings should be at least 16 and 24 inches wide, respectively. The bottom of exterior footings should be at least 16 inches below the lowest adjacent exterior grade. The bottom of interior footings should be at least 12 inches below the base of the floor slab.

Footings placed on engineered fill or firm native sub-grade should be designed for an allowable bearing capacity of 2,000 *pounds per square foot (psf)* by IBC 2012/2015 code. The recommended allowable bearing pressure can be doubled for short-term loads such as those resulting from wind or seismic forces.

Based on our analysis the total post-construction settlement is calculated to be less than 1 inch, with differential settlement of less than 0.5 inch over a 50-foot span for maximum column, perimeter footing loads of less than 100 kips and 6.0 kips per linear foot.

Lateral loads on footings can be resisted by passive earth pressure on the sides of the structures and by friction at the base of the footings. An allowable lateral bearing pressure of 150 *pounds per cubic foot (psf/f)* below grade may be used. Adjacent floor slabs, pavements or the upper 12-inch depth of adjacent, unpaved areas should not be

considered when calculating passive resistance. An angle of internal friction of 30 degrees can be used.

If construction is undertaken during periods of rain, then I recommend a 2-inch (or greater) layer of compacted, crushed rock be placed over the native soil. The silty soil is moisture sensitive. Meaning when dry it is firm and non-yielding but exposed to season rains it will lose its strength and need to be excavated and replaced with rock. See section 4.1.2 for wet weather conditions.

### **3.2 Retaining Walls**

The retaining wall design recommendations are based on the following assumptions: (1) the walls consist of conventional, cantilevered retaining walls; (2) the walls are less than 8 feet in height; (3) the backfill is drained; and (4) the backfill has a slope flatter than 4H: 1V. Re-evaluation of our recommendations will be required if the retaining wall design criteria for the project varies from these assumptions.

Unrestrained site walls that retain native soils should be designed to resist an active equivalent fluid unit weight of 35 pcf where supporting slopes are flatter than 4H: 1V. If retaining walls are restrained from rotation prior to being backfilled, the active equivalent fluid unit weight shall be increased to 50 pcf. For embedded building walls, a superimposed seismic lateral force should be calculated based on a dynamic force of  $5H^2$  pounds per lineal foot of wall, where H is the height of the wall in feet, and applied at 0.6H from the base of the wall. If other surcharges (e.g., slopes steeper than 4H:1V, foundations, vehicles, etc.) are located within a horizontal distance from the back of a wall equal to twice the height of the wall, then additional pressures will need to be accounted for in the wall design. Our office should be contacted for appropriate wall surcharges based upon the actual magnitude and configuration of the applied loads.

The wall footings should be designed in accordance with the guidelines provided in the “Foundation Design” section of this report.

These design parameters have been provided assuming that back-of-wall drains will be installed to prevent buildup of hydrostatic pressures behind all walls.

The backfill material placed behind the walls and extending a horizontal distance equal to at least half of the height of the retaining wall should consist of granular retaining wall backfill as specified in the “Structural Fill” section of this report.

The wall backfill should be compacted to a minimum of 92 percent of the maximum dry density, as determined by ASTM D1557. However, backfill located within a horizontal distance of 3 feet from the retaining walls should only be compacted to approximately 90 percent of the maximum dry density, as determined by ASTM D1557. Backfill placed within 3 feet of the wall should be compacted in lifts less than 6 inches thick using hand-operated tamping equipment (e.g., jumping jack or vibratory plate compactors). If flat work (e.g., sidewalks or pavements) will be placed atop the wall backfill, we recommend that the upper

2 feet of material be compacted to 92 percent of the maximum dry density, as determined by ASTM D1557.

A minimum 12-inch-wide zone of drain rock, extending from the base of the wall to within 6 inches of finished grade, should be placed against the back of all retaining walls. Perforated collector pipes should be embedded at the base of the drain rock. The drain rock should meet the requirements provided in the “Structural Fill” section of this report. The perforated collector pipes should discharge at an appropriate location away from the base of the wall. The discharge pipe(s) should not be tied directly into storm water drain systems, unless measures are taken to prevent backflow into the wall’s drainage system.

Settlements of up to 1 percent of the wall height commonly occur immediately adjacent to the wall as the wall rotates and develops active lateral earth pressures. Consequently, we recommend that construction of flat work adjacent to retaining walls be postponed at least 4 weeks after backfilling of the wall, unless survey data indicates that settlement is complete prior to that time.


### 3.3 Seismic Design Criteria

The seismic design criteria for this project USGS Earthquake Hazards Program. A summary of IBC 2012/2015 seismic design criterion below: using a Lat of 45.5909 and Long of -122.4650, site class D.

	<b>Short Period</b>	<b>1 Second</b>
Maximum Credible Earthquake Spectral Acceleration	Ss = 0.94	S1 = 0.38
Adjusted Spectral Acceleration	Sms = 1.05	Sm1 = 0.38
Design Spectral Response Acceleration Perimeters	Sds = 0.70	Sd1= 0.42

### 3.4 Hazards

Slopes: The field reconnaissance on 27 March 2014 showed the steepest slopes are located in the southern end of the property. Here the slopes vary from less than 5% to 25% in the SE corner of the lot. See below figure from Clark County GIS mapping of the site.



Liquefaction: From the Liquefaction Susceptibility Map of Clark County, Washington



2004. The site has very little susceptibility.



### **Landslide Hazards**

RSS site reconnaissance on 27 March 2014 found no signs of land slide hazards. Site is covered with black berries, grasses. See site photo's of the slopes. Figure 3 shows the mapped landslides in Clark County as well as slope stability map of the Vancouver area. As well as IMS -43, this uses LIDAR to map landslides. LIDAR is a bare earth photo that shows landside and slow moving slopes as the lines on the map become fuzzy when the ground is moving. *There are no mapped slides on the project site. Figure 3 also lists the site has having little to no issues with liquefaction.*

From field reconnaissance RSS reviewed all the steep slopes surrounding the project site. There are no signs of slope instability, any sages, slumps or fan of debris from slides on the slopes in the SW corner of the property. There also no surface water features on the property. No seeps springs or other surface expressions of ground water were found when RSS was on site on 3/27/14.

## **4.0 CONSTRUCTION RECOMMENDATIONS**

### **4.1 Site Preparation**

Demolition should include removal of existing improvements throughout the project site. Underground utility lines, vaults, basement walls or tanks should be removed or grouted full if left in place. I recommend that soil disturbed during grubbing operations be removed to firm, undisturbed sub-grade. The excavations should then be backfilled with compacted structural fill. On this site only disturb the area in which can be covered with rock during the day. The moisture sensitive SILT soil when exposed to wet weather becomes soft and yielding. See wet weather conditions below.

#### **4.1.1 Proof Rolling**

Following stripping and prior to placing aggregate base course, pavement the exposed sub-grade should be evaluated by proof rolling. The sub-grade should be proof rolled to identify soft, loose, or unsuitable areas. Please give 24 hour notice to observe the proof rolling. Soft or loose zones identified during the field evaluation should be compacted to an unyielding condition or be excavated and

replaced with structural fill, as discussed in the *Structural Fill* section of this report.

#### **4.1.2 Wet Weather Conditions**

The near-surface soils will be difficult during or after extended wet periods or when the moisture content of the surface soil is more than a few percentage points above optimum. Soils that have been disturbed during site preparation activities, or soft or loose zones identified during probing or proof rolling, should be removed and replaced with compacted structural fill. Track-mounted excavating equipment will be required during wet weather. The imported granular material should be placed in one lift over the prepared, undisturbed sub-grade and compacted using a smooth drum, non-vibratory roller. Additionally, a geo-textile fabric should be placed as a barrier between the sub-grade and imported granular material in areas of repeated traffic.

#### **4.2 Excavation**

Subsurface conditions of accessible cleared areas of the project site show predominately sands, silty soil to the depth explored (4.0 feet). Excavations in the upper soils may be readily accomplished with conventional earthwork equipment with smooth and teeth faced bucket.

#### **4.3 Structural Fills**

Fills should be placed over sub-grade prepared in compliance with Section 4.1 of this report. Material used, as structural fill should be free of organic matter or other unsuitable materials and should meet specifications provided in WSDOT, depending upon the application. A discussion of these materials is in the following sections.

##### **4.3.1 Native Soils**

Native soil can be used for filling operations to raise the site grades for flat backyards. Compaction testing of native soils shall use a standard ASTM D698 proctor and achieve 95%. See lab results in appendix b. Compaction testing is required as per WSDOT every 18in of fill material. Native soils can only be used if they are within optimum moisture content.

##### **4.3.2 Imported Granular Fill**

Material meeting WSDOT 9.03.12(1) B or WSDOT 9.03.11 Imported granular material should be placed in lifts 8 to 12 inches and be compacted to at least 95% of the maximum dry density, as determined by ASTM D 698. Where imported granular material is placed over wet or soft soil sub-grades, we recommend that a geo-textile serve as a barrier between the sub-grade and imported granular material. Compaction testing is required as per WSDOT every 18in of fill material.

### **4.3.3 Floor Slab Base and Footing Base Aggregate**

Base aggregate for floor slabs should be clean, crushed rock or crushed gravel meeting WSDOT 9.03.12(1) B Class B Gravel Backfill for Foundations, if acceptable WSDOT 9.03.11 Recycled Portland Cement Concrete Rubble can be used. The imported granular material should be placed in lifts and compacted to at least 95% of the maximum dry density, as determined by ASTM D 698. Compaction testing is required as per WSDOT every 18in of fill material.

### **4.4 Surface and Subsurface Drainage Requirements**

The Contractor shall be made responsible for temporary drainage of surface water and groundwater as necessary to prevent standing water and/or erosion at the working surface. We recommend removing only the foliage necessary for construction to help minimize erosion. Slope the ground surface around the structures to create a minimum gradient of 2% away from the building foundations for a distance of at least 5 feet. Surface water should be directed away from all buildings into drainage swales or into a storm drainage system.

## **5.0 CONSTRUCTION OBSERVATIONS**

Satisfactory pavement and earthwork performance depends on the quality of construction. Sufficient monitoring of the activities of the contractor is a key part of determining that the work is completed in accordance with the construction drawings and specifications. I recommend that a geotechnical engineer observe general excavation, stripping, fill placement, and sub-grades in addition to base. Subsurface conditions observed during construction should be compared with those encountered during the subsurface explorations. Recognition of changed conditions requires experience. Therefore, qualified personnel should visit the site with sufficient frequency to detect whether subsurface conditions changes significantly from those anticipated.

## **6.0 LIMITATIONS**

This report has been prepared for the exclusive use of the addressee, and their architects and engineers for aiding in the design and construction of the proposed development. It is the addressee's responsibility to provide this report to the appropriate design professionals, building officials, and contractors to ensure correct implementation of the recommendations. The opinions, comments and conclusions presented in this report were based upon information derived from our literature review, field investigation, and laboratory testing. Conditions between, or beyond, our exploratory borings may vary from those encountered. Unanticipated soil conditions and seasonal soil moisture variations are commonly encountered and cannot be fully determined by merely taking soil samples or soil borings. Such variations may result in changes to our recommendations and may require that additional expenditures be made to attain a properly constructed project. Therefore, some contingency fund is recommended to accommodate such potential extra costs.

If there is more than 2years time between the submission of this report and the start of work at the site; if conditions have changed due to natural causes or construction operations at, or

adjacent to, the site; or, if the basic project scheme is significantly modified from that assumed, it is recommended this report be reviewed to determine the applicability of the conclusions and recommendations.

The work has been conducted in general conformance with the standard of care in the field of geotechnical engineering currently in practice in the Pacific Northwest for projects of this nature and magnitude. No warranty, express or implied, exists on the information presented in this report. By utilizing the design recommendations within this report, the addressee acknowledges and accepts the risks and limitations of development at the site, as outlined within the report.

## **APPENDIX A**

---




Figure 1 – Site locations



**Legend**






- Landslide Hazard Areas**
-  Areas of Historic or Active Landslide
  -  Areas of Potential Instability
  -  Areas of Older Landslide Debris
  -  Slopes > 15%
  -  Slopes > 25%

Figure 3 – Landslide hazards

Project site is clear of landslide hazards



**SLOPE STABILITY**  
**CLARK COUNTY WASHINGTON**  
**ALLEN FIKSDAL**  
**1975**



IMS-43

## **APPENDIX B**

---





7409 SW Tech Center Dr, #145  
 Tigard, OR 97223  
 phn: 503-443-3799  
 fax: 503-620-2748

**RAPID SOIL SOLUTIONS**  
**3915 SW PLUM STREET**  
**PORTLAND, OR 97219-6018**

PROJECT: RSS 2014 LAB SERVICES  
 LOCATION: VALLEY VIEW ESTATES  
 SAMPLE SOURCE: SEE BELOW

JOB NO: 14-4790  
 WORK ORDER NO: N/A  
 DATE SAMPLED: 4/18/14

**MECHANICAL SIEVE ANALYSIS**  
**GROUP SYMBOL, USCS (ASTM D-2487)**

Location & Depth	USCS	LL	PI	Silt or Clay #200	SAND						GRAVEL					COBBLES 6"	Lab #
					Fine			Coarse			Fine		Coarse				
					#100	#50	#40	#30	#16	#10	#8	#4	1/4"	3/8"	1/2"		

**PERCENT PASSING BY WEIGHT**

Location & Depth	USCS	LL	PI	#200	#100	#50	#40	#30	#16	#10	#8	#4	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	3"	6"	Lab #			
HA1@2'		27	3																					7267		
HA2@ 4'		28	9																						7267	

BORING	DEPTH	MC%
HA1@2'		25.9
HA2 @ 4'		28.0
HA3@ 4'		23.1
HA4@ 4'		24.9

REVIEWED BY *[Signature]* DE/fs

SuperLog CivilTech Software, USA www.civitech.com File: D:\Users\Mia\Desktop\MIA WORK\2014\Reports\Report to end April\Happy Valley Dental Clinic\HA 1.log Date: 4/30/2014

# #1

Surface Elevation: 414  
Boring Date: 4/23/14  
Boring Location: Camas, WA  
Drilling Method: Hand Augur

Depth	Remarks	Moisture (%)	Dry Density	Blow Counts	Sample Type	Water Table
0						
					ML	Top Soil
						Damp, medium light brown, fine grained medium plastic SILT
2	PI=3, LL=27 25.9				ML	End hand augur hole
3						
4						
5						
6						
7						

### LOG OF BORING

**Rapid Soil Solutions**

Valley View Sub-division  
Stan Firestone

Plate 1

# #2

Surface Elevation: 464  
Boring Date: 4/23/14  
Boring Location: Camas, WA  
Drilling Method: Hand Augur

SuperLog CivilTech Software, USA www.civiltech.com File: D:\Users\Mia\Desktop\WIA WORK\2014\Reports\Report to end April\Valley View\HA 2.log Date: 4/30/2014

Depth	Remarks	Moisture (%)	Dry Density	Blow Counts	Sample Type	Water Table
0						
					ML	Top Soil
					ML	Damp, dark brown, fine grained medium plastic SILT
1						
					ML	Damp, dark to medium brown clayey SILT trace gray
2						
3						
4	28				ML	End hand augur hole
5						
6						
7						

## LOG OF BORING

# #3

Surface Elevation: 418  
Boring Date: 4/23/14  
Boring Location: Camas, WA  
Drilling Method: Hand Augur

SuperLog CivilTech Software, USA www.civiltech.com  
File: D:\Users\Mia\Desktop\WIA WORK\2014\Reports\Report to end April\Valley View\HA 3.log Date: 4/30/2014

Depth	Remarks	Moisture (%)	Dry Density	Blow Counts	Sample Type	Water Table
0						
0					ML	Top Soil
0						Damp, dark brown, fine grained medium plastic clayey SILT
1						
2						
3						
4	$\rho_s = 9, u = 28$	23.1			ML	End hand augur hole
5						
6						
7						

## LOG OF BORING

# #4

Surface Elevation: 448  
Boring Date: 4/23/14  
Boring Location: Camas, WA  
Drilling Method: Hand Augur

SuperLog CivilTech Software, USA www.cvtlltech.com File: D:\Users\Mia\Desktop\WIA WORK\2014\Reports\Report to end April\Valley View\VA 3.log Date: 4/30/2014

Depth	Remarks	Moisture (%)	Dry Density	Blow Counts	Sample Type	Water Table
0						
0					ML	Top Soil
0						Damp, dark brown, fine grained medium plastic clayey SILT
1						
2						
3						
4	23.1				ML	End hand augur hole
5						
6						
7						

## LOG OF BORING

**Appendix IV: Maintenance Manual (Clark County Version)**

## 4.6 Maintenance Standards for Drainage Facilities

The facility-specific maintenance standards contained in this section are intended to be conditions for determining if maintenance actions are required as identified through inspection. They are not intended to be measures of the facility's required condition at all times between inspections. In other words, exceedence of these conditions at any time between inspections and/or maintenance does not automatically constitute a violation of these standards. However, based upon inspection observations, the inspection and maintenance schedules shall be adjusted to minimize the length of time that a facility is in a condition that requires a maintenance action.

**Table 4.5.2 Maintenance Standards**

### No. 1 – Detention Ponds

Maintenance Component	Defect	Conditions When Maintenance Is Needed	Results Expected When Maintenance Is Performed
General	Trash & Debris	Any trash and debris which exceed 1 cubic feet per 1,000 square feet. In general, there should be no visual evidence of dumping.  If less than threshold all trash and debris will be removed as part of next scheduled maintenance.	Trash and debris cleared from site.
	Poisonous Vegetation and noxious weeds	Any poisonous or nuisance vegetation which may constitute a hazard to maintenance personnel or the public.  Any evidence of noxious weeds as defined by State or local regulations. (Apply requirements of adopted IPM policies for the use of herbicides).	No danger of poisonous vegetation where maintenance personnel or the public might normally be. (Coordinate with local health department)  Complete eradication of noxious weeds may not be possible. Compliance with State or local eradication policies required
	Contaminants and Pollution	Any evidence of oil, gasoline, contaminants or other pollutants  (Coordinate removal/cleanup with local water quality response agency).	<del>No contaminants or pollutants present.</del>
	Rodent Holes	Any evidence of rodent holes if facility is acting as a dam or berm, or any evidence of water piping through dam or berm via rodent holes.	Rodents destroyed and dam or berm repaired. (Coordinate with local health department; coordinate with Ecology Dam Safety Office if pond exceeds 10 acre-feet.)

## No. 1 – Detention Ponds

Maintenance Component	Defect	Conditions When Maintenance Is Needed	Results Expected When Maintenance Is Performed
	Beaver Dams	Dam results in change or function of the facility.	Facility is returned to design function. (Coordinate trapping of beavers and removal of dams with appropriate permitting agencies)
	Insects	When insects such as wasps and hornets interfere with maintenance activities.	Insects destroyed or removed from site. Apply insecticides in compliance with adopted IPM policies
	Tree Growth and Hazard Trees	Tree growth does not allow maintenance access or interferes with maintenance activity (i.e., slope mowing, silt removal, vactoring, or equipment movements). If trees are not interfering with access or maintenance, do not remove  If dead, diseased, or dying trees are identified  (Use a certified Arborist to determine health of tree or removal requirements)	Trees do not hinder maintenance activities. Harvested trees should be recycled into mulch or other beneficial uses (e.g., alders for firewood).  Remove hazard Trees
Side Slopes of Pond	Erosion	Eroded damage over 2 inches deep where cause of damage is still present or where there is potential for continued erosion.  Any erosion observed on a compacted berm embankment.	Slopes should be stabilized using appropriate erosion control measure(s); e.g., rock reinforcement, planting of grass, compaction.  If erosion is occurring on compacted berms a licensed civil engineer should be consulted to resolve source of erosion.
Storage Area	Sediment	Accumulated sediment that exceeds 10% of the designed pond depth unless otherwise specified or affects inletting or outletting condition of the facility.	Sediment cleaned out to designed pond shape and depth; pond reseeded if necessary to control erosion.
	Liner (If Applicable)	Liner is visible and has more than three 1/4-inch holes in it.	Liner repaired or replaced. Liner is fully covered.
Pond Berms (Dikes)	Settlements	Any part of berm which has settled 4 inches lower than the design elevation.  If settlement is apparent, measure berm to determine amount of settlement.  Settling can be an indication of more severe problems with the berm or outlet works. A licensed civil engineer should be consulted to determine the source of the settlement.	Dike is built back to the design elevation.
	Piping	Discernable water flow through pond berm. Ongoing erosion with potential for erosion to continue.  (Recommend a Geotechnical engineer be called in to inspect and evaluate condition and recommend repair of condition.	Piping eliminated. Erosion potential resolved.



## No. 1 – Detention Ponds

Maintenance Component	Defect	Conditions When Maintenance Is Needed	Results Expected When Maintenance Is Performed
Emergency Overflow/ Spillway and Berms over 4 feet in height.	Tree Growth	<p>Tree growth on emergency spillways creates blockage problems and may cause failure of the berm due to uncontrolled overtopping.</p> <p>Tree growth on berms over 4 feet in height may lead to piping through the berm which could lead to failure of the berm.</p>	Trees should be removed. If root system is small (base less than 4 inches) the root system may be left in place. Otherwise the roots should be removed and the berm restored. A licensed civil engineer should be consulted for proper berm/spillway restoration.
	Piping	<p>Discernable water flow through pond berm. Ongoing erosion with potential for erosion to continue.</p> <p>(Recommend a Geotechnical engineer be called in to inspect and evaluate condition and recommend repair of condition.</p>	Piping eliminated. Erosion potential resolved.
Emergency Overflow/ Spillway	Emergency Overflow/ Spillway	<p>Only one layer of rock exists above native soil in area five square feet or larger, or any exposure of native soil at the top of out flow path of spillway.</p> <p>(Rip-rap on inside slopes need not be replaced.)</p>	Rocks and pad depth are restored to design standards.
	Erosion	See "Side Slopes of Pond"	

## No. 2 – Infiltration

Maintenance Component	Defect	Conditions When Maintenance Is Needed	Results Expected When Maintenance Is Performed
General	Trash & Debris	See "Detention Ponds" (No. 1).	See "Detention Ponds" (No. 1).
	Poisonous/Noxious Vegetation	See "Detention Ponds" (No. 1).	See "Detention Ponds" (No. 1).
	Contaminants and Pollution	See "Detention Ponds" (No. 1).	See "Detention Ponds" (No. 1).
	Rodent Holes	See "Detention Ponds" (No. 1).	See "Detention Ponds" (No. 1).
Storage Area	Sediment	Water ponding in infiltration pond after rainfall ceases and appropriate time allowed for infiltration. Treatment basins should infiltrate Water Quality Design Storm Volume within 48 hours, and empty within 24 hours after cessation of most rain events.  (A percolation test pit or test of facility indicates facility is only working at 90% of its designed capabilities. Test every 2 to 5 years. If two inches or more sediment is present, remove).	Sediment is removed and/or facility is cleaned so that infiltration system works according to design.
Filter Bags (if applicable)	Filled with Sediment and Debris	Sediment and debris fill bag more than 1/2 full.	Filter bag is replaced or system is redesigned.
Rock Filters	Sediment and Debris	By visual inspection, little or no water flows through filter during heavy rain storms.	Gravel in rock filter is replaced.
Side Slopes of Pond	Erosion	See "Detention Ponds" (No. 1).	See "Detention Ponds" (No. 1).
Emergency Overflow Spillway and Berms over 4 feet in height.	Tree Growth	See "Detention Ponds" (No. 1).	See "Detention Ponds" (No. 1).
	Piping	See "Detention Ponds" (No. 1).	See "Detention Ponds" (No. 1).
Emergency Overflow Spillway	Rock Missing	See "Detention Ponds" (No. 1).	See "Detention Ponds" (No. 1).
	Erosion	See "Detention Ponds" (No. 1).	See "Detention Ponds" (No. 1).
Pre-settling Ponds and Vaults	Facility or sump filled with Sediment and/or debris	6" or designed sediment trap depth of sediment.	Sediment is removed.

### No. 3 – Closed Detention Systems (Tanks/Vaults)

Maintenance Component	Defect	Conditions When Maintenance is Needed	Results Expected When Maintenance is Performed
Storage Area	Plugged Air Vents	One-half of the cross section of a vent is blocked at any point or the vent is damaged.	Vents open and functioning.
	Debris and Sediment	Accumulated sediment depth exceeds 10% of the diameter of the storage area for 1/2 length of storage vault or any point depth exceeds 15% of diameter.  (Example: 72-inch storage tank would require cleaning when sediment reaches depth of 7 inches for more than 1/2 length of tank.)	All sediment and debris removed from storage area.
	Joints Between Tank/Pipe Section	Any openings or voids allowing material to be transported into facility.  (Will require engineering analysis to determine structural stability).	All joint between tank/pipe sections are sealed.
	Tank Pipe Bent Out of Shape	Any part of tank/pipe is bent out of shape more than 10% of its design shape. (Review required by engineer to determine structural stability).	Tank/pipe repaired or replaced to design.
	Vault Structure Includes Cracks in Wall, Bottom, Damage to Frame and/or Top Slab	Cracks wider than 1/2-inch and any evidence of soil particles entering the structure through the cracks, or maintenance/inspection personnel determines that the vault is not structurally sound.  Cracks wider than 1/2-inch at the joint of any inlet/outlet pipe or any evidence of soil particles entering the vault through the walls.	Vault replaced or repaired to design specifications and is structurally sound.  No cracks more than 1/4-inch wide at the joint of the inlet/outlet pipe.
Manhole	Cover Not in Place	Cover is missing or only partially in place. Any open manhole requires maintenance.	Manhole is closed.
	Locking Mechanism Not Working	Mechanism cannot be opened by one maintenance person with proper tools. Bolts into frame have less than 1/2 inch of thread (may not apply to self-locking lids).	Mechanism opens with proper tools.
	Cover Difficult to Remove	One maintenance person cannot remove lid after applying normal lifting pressure. Intent is to keep cover from sealing off access to maintenance.	Cover can be removed and reinstalled by one maintenance person.
	Ladder Rungs Unsafe	Ladder is unsafe due to missing rungs, misalignment, not securely attached to structure wall, rust, or cracks.	Ladder meets design standards. Allows maintenance person safe access.
Catch Basins	See "Catch Basins" (No. 5)	See "Catch Basins" (No. 5).	See "Catch Basins" (No. 5).

#### No. 4 – Control Structure/Flow Restrictor

Maintenance Component	Defect	Condition When Maintenance is Needed	Results Expected When Maintenance is Performed
General	Trash and Debris (Includes Sediment)	Material exceeds 25% of sump depth or 1 foot below orifice plate.	Control structure orifice is not blocked. All trash and debris removed.
	Structural Damage	Structure is not securely attached to manhole wall.	Structure securely attached to wall and outlet pipe.
		Structure is not in upright position (allow up to 10% from plumb).	Structure in correct position.
		Connections to outlet pipe are not watertight and show signs of rust.	Connections to outlet pipe are water tight; structure repaired or replaced and works as designed.
		Any holes--other than designed holes--in the structure.	Structure has no holes other than designed holes.
Cleanout Gate	Damaged or Missing	Cleanout gate is not watertight or is missing.	Gate is watertight and works as designed.
		Gate cannot be moved up and down by one maintenance person.	Gate moves up and down easily and is watertight.
		Chain/rod leading to gate is missing or damaged.	Chain is in place and works as designed.
		Gate is rusted over 50% of its surface area.	Gate is repaired or replaced to meet design standards.
Orifice Plate	Damaged or Missing	Control device is not working properly due to missing, out of place, or bent orifice plate.	Plate is in place and works as designed.
	Obstructions	Any trash, debris, sediment, or vegetation blocking the plate.	Plate is free of all obstructions and works as designed.
Overflow Pipe	Obstructions	Any trash or debris blocking (or having the potential of blocking) the overflow pipe.	Pipe is free of all obstructions and works as designed.
Manhole	See "Closed Detention Systems" (No. 3).	See "Closed Detention Systems" (No. 3).	See "Closed Detention Systems" (No. 3).
Catch Basin	See "Catch Basins" (No. 5).	See "Catch Basins" (No. 5).	See "Catch Basins" (No. 5).

## No. 5 – Catch Basins

Maintenance Component	Defect	Conditions When Maintenance is Needed	Results Expected When Maintenance is performed
General	Trash & Debris	Trash or debris which is located immediately in front of the catch basin opening or is blocking inletting capacity of the basin by more than 10%.	No Trash or debris located immediately in front of catch basin or on grate opening.
		Trash or debris (in the basin) that exceeds 60 percent of the sump depth as measured from the bottom of basin to invert of the lowest pipe into or out of the basin, but in no case less than a minimum of six inches clearance from the debris surface to the invert of the lowest pipe.	No trash or debris in the catch basin.
		Trash or debris in any inlet or outlet pipe blocking more than 1/3 of its height.	Inlet and outlet pipes free of trash or debris.
		Dead animals or vegetation that could generate odors that could cause complaints or dangerous gases (e.g., methane).	No dead animals or vegetation present within the catch basin.
	Sediment	Sediment (in the basin) that exceeds 60 percent of the sump depth as measured from the bottom of basin to invert of the lowest pipe into or out of the basin, but in no case less than a minimum of 6 inches clearance from the sediment surface to the invert of the lowest pipe.	No sediment in the catch basin
	Structure Damage to Frame and/or Top Slab	Top slab has holes larger than 2 square inches or cracks wider than 1/4 inch (Intent is to make sure no material is running into basin).	Top slab is free of holes and cracks.
		Frame not sitting flush on top slab, i.e., separation of more than 3/4 inch of the frame from the top slab. Frame not securely attached	Frame is sitting flush on the riser rings or top slab and firmly attached.
	Fractures or Cracks in Basin Walls/ Bottom	Maintenance person judges that structure is unsound.	Basin replaced or repaired to design standards.
		Grout fillet has separated or cracked wider than 1/2 inch and longer than 1 foot at the joint of any inlet/outlet pipe or any evidence of soil particles entering catch basin through cracks.	Pipe is regouted and secure at basin wall.
	Settlement/ Misalignment	If failure of basin has created a safety, function, or design problem.	Basin replaced or repaired to design standards.
	Vegetation	Vegetation growing across and blocking more than 10% of the basin opening.	No vegetation blocking opening to basin.
		Vegetation growing in inlet/outlet pipe joints that is more than six inches tall and less than six inches apart.	No vegetation or root growth present.
	Contamination and Pollution	See "Detention Ponds" (No. 1).	No pollution present.

## No. 5 – Catch Basins

Maintenance Component	Defect	Conditions When Maintenance is Needed	Results Expected When Maintenance is performed
Catch Basin Cover	Cover Not in Place	Cover is missing or only partially in place. Any open catch basin requires maintenance.	Catch basin cover is closed
	Locking Mechanism Not Working	Mechanism cannot be opened by one maintenance person with proper tools. Bolts into frame have less than 1/2 inch of thread.	Mechanism opens with proper tools.
	Cover Difficult to Remove	One maintenance person cannot remove lid after applying normal lifting pressure. (Intent is keep cover from sealing off access to maintenance.)	Cover can be removed by one maintenance person.
Ladder	Ladder Rungs Unsafe	Ladder is unsafe due to missing rungs, not securely attached to basin wall, misalignment, rust, cracks, or sharp edges.	Ladder meets design standards and allows maintenance person safe access.
Metal Grates (If Applicable)	Grate opening Unsafe	Grate with opening wider than 7/8 inch.	Grate opening meets design standards.
	Trash and Debris	Trash and debris that is blocking more than 20% of grate surface inletting capacity.	Grate free of trash and debris.
	Damaged or Missing.	Grate missing or broken member(s) of the grate.	Grate is in place and meets design standards.

## No. 6 – Debris Barriers (e.g., Trash Racks)

Maintenance Components	Defect	Condition When Maintenance is Needed	Results Expected When Maintenance is Performed
General	Trash and Debris	Trash or debris that is plugging more than 20% of the openings in the barrier.	Barrier cleared to design flow capacity.
Metal	Damaged/ Missing Bars.	Bars are bent out of shape more than 3 inches.	Bars in place with no bends more than 3/4 inch.
		Bars are missing or entire barrier missing.	Bars in place according to design.
		Bars are loose and rust is causing 50% deterioration to any part of barrier.	Barrier replaced or repaired to design standards.
	Inlet/Outlet Pipe	Debris barrier missing or not attached to pipe	Barrier firmly attached to pipe

## No. 7 – Energy Dissipaters

Maintenance Components	Defect	Conditions When Maintenance is Needed	Results Expected When Maintenance is Performed
External:			
Rock Pad	Missing or Moved Rock	Only one layer of rock exists above native soil in area five square feet or larger, or any exposure of native soil.	Rock pad replaced to design standards.
	Erosion	Soil erosion in or adjacent to rock pad.	Rock pad replaced to design standards.
Dispersion Trench	Pipe Plugged with Sediment	Accumulated sediment that exceeds 20% of the design depth.	Pipe cleaned/flushed so that it matches design.
	Not Discharging Water Properly	Visual evidence of water discharging at concentrated points along trench (normal condition is a "sheet flow" of water along trench). Intent is to prevent erosion damage.	Trench redesigned or rebuilt to standards.
	Perforations Plugged.	Over 1/2 of perforations in pipe are plugged with debris and sediment.	Perforated pipe cleaned or replaced.
	Water Flows Out Top of "Distributor" Catch Basin.	Maintenance person observes or receives credible report of water flowing out during any storm less than the design storm or its causing or appears likely to cause damage.	Facility rebuilt or redesigned to standards.
	Receiving Area Over-Saturated	Water in receiving area is causing or has potential of causing landslide problems.	No danger of landslides.
Internal:			
Manhole/Chamber	Worn or Damaged Post, Baffles, Side of Chamber	Structure dissipating flow deteriorates to 1/2 of original size or any concentrated worn spot exceeding one square foot which would make structure unsound.	Structure replaced to design standards.
	Other Defects	See "Catch Basins" (No. 5).	See "Catch Basins" (No. 5).

## No. 8 – Typical Biofiltration Swale

Maintenance Component	Defect or Problem	Condition When Maintenance is Needed	Recommended Maintenance to Correct Problem
General	Sediment Accumulation on Grass	Sediment depth exceeds 2 inches.	Remove sediment deposits on grass treatment area of the bio-swale. When finished, swale should be level from side to side and drain freely toward outlet. There should be no areas of standing water once inflow has ceased.
	Standing Water	When water stands in the swale between storms and does not drain freely.	Any of the following may apply: remove sediment or trash blockages, improve grade from head to foot of swale, remove clogged check dams, add underdrains or convert to a wet biofiltration swale.
	Flow spreader	Flow spreader uneven or clogged so that flows are not uniformly distributed through entire swale width.	Level the spreader and clean so that flows are spread evenly over entire swale width.
	Constant Baseflow	When small quantities of water continually flow through the swale, even when it has been dry for weeks, and an eroded, muddy channel has formed in the swale bottom.	Add a low-flow pea-gravel drain the length of the swale or by-pass the baseflow around the swale.
	Poor Vegetation Coverage	When grass is sparse or bare or eroded patches occur in more than 10% of the swale bottom.	Determine why grass growth is poor and correct that condition. Re-plant with plugs of grass from the upper slope: plant in the swale bottom at 8-inch intervals. Or re-seed into loosened, fertile soil.
	Vegetation	When the grass becomes excessively tall (greater than 10-inches); when nuisance weeds and other vegetation starts to take over.	Mow vegetation or remove nuisance vegetation so that flow not impeded. Grass should be mowed to a height of 3 to 4 inches. Remove grass clippings.
	Excessive Shading	Grass growth is poor because sunlight does not reach swale.	If possible, trim back over-hanging limbs and remove brushy vegetation on adjacent slopes.
	Inlet/Outlet	Inlet/outlet areas clogged with sediment and/or debris.	Remove material so that there is no clogging or blockage in the inlet and outlet area.
	Trash and Debris Accumulation	Trash and debris accumulated in the bio-swale.	Remove trash and debris from bioswale.
Erosion/Scouring	Eroded or scoured swale bottom due to flow channelization, or higher flows.	For ruts or bare areas less than 12 inches wide, repair the damaged area by filling with crushed gravel. If bare areas are large, generally greater than 12 inches wide, the swale should be re-graded and re-seeded. For smaller bare areas, overseed when bare spots are evident, or take plugs of grass from the upper slope and plant in the swale bottom at 8-inch intervals.	



## No. 9 – Wet Biofiltration Swale

Maintenance Component	Defect or Problem	Condition When Maintenance is Needed	Recommended Maintenance to Correct Problem
General	Sediment Accumulation	Sediment depth exceeds 2-inches in 10% of the swale treatment area.	Remove sediment deposits in treatment area.
	Water Depth	Water not retained to a depth of about 4 inches during the wet season.	Build up or repair outlet berm so that water is retained in the wet swale.
	Wetland Vegetation	Vegetation becomes sparse and does not provide adequate filtration, OR vegetation is crowded out by very dense clumps of cattail, which do not allow water to flow through the clumps.	Determine cause of lack of vigor of vegetation and correct. Replant as needed. For excessive cattail growth, cut cattail shoots back and compost off-site. Note: normally wetland vegetation does not need to be harvested unless die-back is causing oxygen depletion in downstream waters.
	Inlet/Outlet	Inlet/outlet area clogged with sediment and/or debris.	Remove clogging or blockage in the inlet and outlet areas.
	Trash and Debris Accumulation	See "Detention Ponds" (No. 1).	Remove trash and debris from wet swale.
	Erosion/Scouring	Swale has eroded or scoured due to flow channelization, or higher flows.	Check design flows to assure swale is large enough to handle flows. By-pass excess flows or enlarge swale. Replant eroded areas with fibrous-rooted plants such as <i>Juncus effusus</i> (soft rush) in wet areas or snowberry ( <i>Symphoricarpos albus</i> ) in dryer areas.

## No. 10 – Filter Strips

Maintenance Component	Defect or Problem	Condition When Maintenance is Needed	Recommended Maintenance to Correct Problem
General	Sediment Accumulation on Grass	Sediment depth exceeds 2 inches.	Remove sediment deposits, re-level so slope is even and flows pass evenly through strip.
	Vegetation	When the grass becomes excessively tall (greater than 10-inches); when nuisance weeds and other vegetation starts to take over.	Mow grass, control nuisance vegetation, such that flow not impeded. Grass should be mowed to a height between 3-4 inches.
	Trash and Debris Accumulation	Trash and debris accumulated on the filter strip.	Remove trash and Debris from filter.
	Erosion/Scouring	Eroded or scoured areas due to flow channelization, or higher flows.	For ruts or bare areas less than 12 inches wide, repair the damaged area by filling with crushed gravel. The grass will creep in over the rock in time. If bare areas are large, generally greater than 12 inches wide, the filter strip should be re-graded and re-seeded. For smaller bare areas, overseed when bare spots are evident.
	Flow spreader	Flow spreader uneven or clogged so that flows are not uniformly distributed through entire filter width.	Level the spreader and clean so that flows are spread evenly over entire filter width.

## No. 11 – Wetponds

Maintenance Component	Defect	Condition When Maintenance is Needed	Results Expected When Maintenance is Performed
General	Water level	First cell is empty, doesn't hold water.	Line the first cell to maintain at least 4 feet of water. Although the second cell may drain, the first cell must remain full to control turbulence of the incoming flow and reduce sediment resuspension.
	Trash and Debris	Accumulation that exceeds 1 CF per 1000-SF of pond area.	Trash and debris removed from pond.
	Inlet/Outlet Pipe	Inlet/Outlet pipe clogged with sediment and/or debris material.	No clogging or blockage in the inlet and outlet piping.
	Sediment Accumulation in Pond Bottom	Sediment accumulations in pond bottom that exceeds the depth of sediment zone plus 6-inches, usually in the first cell.	Sediment removed from pond bottom.
	Oil Sheen on Water	Prevalent and visible oil sheen.	Oil removed from water using oil-absorbent pads or vactor truck. Source of oil located and corrected. If chronic low levels of oil persist, plant wetland plants such as <i>Juncus effusus</i> (soft rush) which can uptake small concentrations of oil.
	Erosion	Erosion of the pond's side slopes and/or scouring of the pond bottom, that exceeds 6-inches, or where continued erosion is prevalent.	Slopes stabilized using proper erosion control measures and repair methods.
	Settlement of Pond Dike/Berm	Any part of these components that has settled 4-inches or lower than the design elevation, or inspector determines dike/berm is unsound.	Dike/berm is repaired to specifications.
	Internal Berm	Berm dividing cells should be level.	Berm surface is leveled so that water flows evenly over entire length of berm.
Overflow Spillway	Rock is missing and soil is exposed at top of spillway or outside slope.	Rocks replaced to specifications.	

## No. 12 – Wetvaults

Maintenance Component	Defect	Condition When Maintenance is Needed	Results Expected When Maintenance is Performed
General	Trash/Debris Accumulation	Trash and debris accumulated in vault, pipe or inlet/outlet (includes floatables and non-floatables).	Remove trash and debris from vault.
	Sediment Accumulation in Vault	Sediment accumulation in vault bottom exceeds the depth of the sediment zone plus 6-inches.	Remove sediment from vault.
	Damaged Pipes	Inlet/outlet piping damaged or broken and in need of repair.	Pipe repaired and/or replaced.
	Access Cover Damaged/Not Working	Cover cannot be opened or removed, especially by one person.	Pipe repaired or replaced to proper working specifications.
	Ventilation	Ventilation area blocked or plugged.	Blocking material removed or cleared from ventilation area. A specified % of the vault surface area must provide ventilation to the vault interior (see design specifications).
	Vault Structure Damage - Includes Cracks in Walls Bottom, Damage to Frame and/or Top Slab	Maintenance/inspection personnel determine that the vault is not structurally sound.	Vault replaced or repairs made so that vault meets design specifications and is structurally sound.
		Cracks wider than 1/2-inch at the joint of any inlet/outlet pipe or evidence of soil particles entering through the cracks.	Vault repaired so that no cracks exist wider than 1/4-inch at the joint of the inlet/outlet pipe.
	Baffles	Baffles corroding, cracking, warping and/or showing signs of failure as determined by maintenance/inspection staff.	Baffles repaired or replaced to specifications.
Access Ladder Damage	Ladder is corroded or deteriorated, not functioning properly, not attached to structure wall, missing rungs, has cracks and/or misaligned. Confined space warning sign missing.	Ladder replaced or repaired to specifications, and is safe to use as determined by inspection personnel. Replace sign warning of confined space entry requirements. Ladder and entry notification complies with OSHA standards.	

### No. 13 – Sand Filters (above ground/open)

Maintenance Component	Defect	Condition When Maintenance is Needed	Results Expected When Maintenance is Performed
Above Ground (open sand filter)	Sediment Accumulation on top layer	Sediment depth exceeds 1/2-inch.	No sediment deposit on grass layer of sand filter that would impede permeability of the filter section.
	Trash and Debris Accumulations	Trash and debris accumulated on sand filter bed.	Trash and debris removed from sand filter bed.
	Sediment/ Debris in Clean-Outs	When the clean-outs become full or partially plugged with sediment and/or debris.	Sediment removed from clean-outs.
	Sand Filter Media	Drawdown of water through the sand filter media takes longer than 24-hours, and/or flow through the overflow pipes occurs frequently.	Top several inches of sand are scraped. May require replacement of entire sand filter depth depending on extent of plugging (a sieve analysis is helpful to determine if the lower sand has too high a proportion of fine material).
	Prolonged Flows	Sand is saturated for prolonged periods of time (several weeks) and does not dry out between storms due to continuous base flow or prolonged flows from detention facilities.	Low, continuous flows are limited to a small portion of the facility by using a low wooden divider or slightly depressed sand surface.
	Short Circuiting	When flows become concentrated over one section of the sand filter rather than dispersed.	Flow and percolation of water through sand filter is uniform and dispersed across the entire filter area.
	Erosion Damage to Slopes	Erosion over 2-inches deep where cause of damage is prevalent or potential for continued erosion is evident.	Slopes stabilized using proper erosion control measures.
	Rock Pad Missing or Out of Place	Soil beneath the rock is visible.	Rock pad replaced or rebuilt to design specifications.
	Flow Spreader	Flow spreader uneven or clogged so that flows are not uniformly distributed across sand filter.	Spreader leveled and cleaned so that flows are spread evenly over sand filter.
Damaged Pipes	Any part of the piping that is crushed or deformed more than 20% or any other failure to the piping.	Pipe repaired or replaced.	

## No. 14 –Sand Filters (below ground/enclosed)

Maintenance Component	Defect	Condition When Maintenance is Needed	Results Expected When Maintenance is Performed
Below Ground Vault.	Sediment Accumulation on Sand Media Section	Sediment depth exceeds 1/2-inch.	No sediment deposits on sand filter section that which would impede permeability of the filter section.
	Sediment Accumulation in Pre-Settling Portion of Vault	Sediment accumulation in vault bottom exceeds the depth of the sediment zone plus 6-inches.	No sediment deposits in first chamber of vault.
	Trash/Debris Accumulation	Trash and debris accumulated in vault, or pipe inlet/outlet, floatables and non-floatables.	Trash and debris removed from vault and inlet/outlet piping.
	Sediment in Drain Pipes/Cleanouts	When drain pipes, cleanouts become full with sediment and/or debris.	Sediment and debris removed.
	Short Circuiting	When seepage/flow occurs along the vault walls and corners. Sand eroding near inflow area.	Sand filter media section re-laid and compacted along perimeter of vault to form a semi-seal. Erosion protection added to dissipate force of incoming flow and curtail erosion.
	Damaged Pipes	Inlet or outlet piping damaged or broken and in need of repair.	Pipe repaired and/or replaced.
	Access Cover Damaged/Not Working	Cover cannot be opened, corrosion/deformation of cover. Maintenance person cannot remove cover using normal lifting pressure.	Cover repaired to proper working specifications or replaced.
	Ventilation	Ventilation area blocked or plugged	Blocking material removed or cleared from ventilation area. A specified % of the vault surface area must provide ventilation to the vault interior (see design specifications).
	Vault Structure Damaged; Includes Cracks in Walls, Bottom, Damage to Frame and/or Top Slab.	Cracks wider than 1/2-inch or evidence of soil particles entering the structure through the cracks, or maintenance/inspection personnel determine that the vault is not structurally sound.	Vault replaced or repairs made so that vault meets design specifications and is structurally sound.
		Cracks wider than 1/2-inch at the joint of any inlet/outlet pipe or evidence of soil particles entering through the cracks.	Vault repaired so that no cracks exist wider than 1/4-inch at the joint of the inlet/outlet pipe.
Baffles/Internal walls	Baffles or walls corroding, cracking, warping and/or showing signs of failure as determined by maintenance/inspection person.	Baffles repaired or replaced to specifications.	
Access Ladder Damaged	Ladder is corroded or deteriorated, not functioning properly, not securely attached to structure wall, missing rungs, cracks, and misaligned.	Ladder replaced or repaired to specifications, and is safe to use as determined by inspection personnel.	

**No. 15 – Manufactured Media Filters)**

<b>Maintenance Component</b>	<b>Defect</b>	<b>Condition When Maintenance is Needed</b>	<b>Results Expected When Maintenance is Performed</b>
Below Ground Vault	Sediment Accumulation on Media.	Sediment depth exceeds 0.25-inches.	No sediment deposits which would impede permeability of the compost media.
	Sediment Accumulation in Vault	Sediment depth exceeds 6-inches in first chamber.	No sediment deposits in vault bottom of first chamber.
	Trash/Debris Accumulation	Trash and debris accumulated on compost filter bed.	Trash and debris removed from the compost filter bed.
	Sediment in Drain Pipes/Clean-Outs	When drain pipes, clean-outs, become full with sediment and/or debris.	Sediment and debris removed.
	Damaged Pipes	Any part of the pipes that are crushed or damaged due to corrosion and/or settlement.	Pipe repaired and/or replaced.
	Access Cover Damaged/Not Working	Cover cannot be opened; one person cannot open the cover using normal lifting pressure, corrosion/deformation of cover.	Cover repaired to proper working specifications or replaced.
	Vault Structure Includes Cracks in Wall, Bottom, Damage to Frame and/or Top Slab	Cracks wider than 1/2-inch or evidence of soil particles entering the structure through the cracks, or maintenance/inspection personnel determine that the vault is not structurally sound.	Vault replaced or repairs made so that vault meets design specifications and is structurally sound.
		Cracks wider than 1/2-inch at the joint of any inlet/outlet pipe or evidence of soil particles entering through the cracks.	Vault repaired so that no cracks exist wider than 1/4-inch at the joint of the inlet/outlet pipe.
	Baffles	Baffles corroding, cracking warping, and/or showing signs of failure as determined by maintenance/inspection person.	Baffles repaired or replaced to specifications.
Access Ladder Damaged	Ladder is corroded or deteriorated, not functioning properly, not securely attached to structure wall, missing rungs, cracks, and misaligned.	Ladder replaced or repaired and meets specifications, and is safe to use as determined by inspection personnel.	
Below Ground Cartridge Type	Media	Drawdown of water through the media takes longer than 1 hour, and/or overflow occurs frequently.	Media cartridges replaced.
	Short Circuiting	Flows do not properly enter filter cartridges.	Filter cartridges replaced.

## No. 16 – Baffle Oil/Water Separators (API Type)

Maintenance Component	Defect	Condition When Maintenance is Needed	Results Expected When Maintenance is Performed
General	Monitoring	Inspection of discharge water for obvious signs of poor water quality.	Effluent discharge from vault should be clear with out thick visible sheen.
	Sediment Accumulation	Sediment depth in bottom of vault exceeds 6-inches in depth.	No sediment deposits on vault bottom that would impede flow through the vault and reduce separation efficiency.
	Trash and Debris Accumulation	Trash and debris accumulation in vault, or pipe inlet/outlet, floatables and non-floatables.	Trash and debris removed from vault, and inlet/outlet piping.
	Oil Accumulation	Oil accumulations that exceed 1-inch, at the surface of the water.	Extract oil from vault by vactoring. Disposal in accordance with state and local rules and regulations.
	Damaged Pipes	Inlet or outlet piping damaged or broken and in need of repair.	Pipe repaired or replaced.
	Access Cover Damaged/Not Working	Cover cannot be opened, corrosion/deformation of cover.	Cover repaired to proper working specifications or replaced.
	Vault Structure Damage - Includes Cracks in Walls Bottom, Damage to Frame and/or Top Slab	See "Catch Basins" (No. 5)	Vault replaced or repairs made so that vault meets design specifications and is structurally sound.
		Cracks wider than 1/2-inch at the joint of any inlet/outlet pipe or evidence of soil particles entering through the cracks.	Vault repaired so that no cracks exist wider than 1/4-inch at the joint of the inlet/outlet pipe.
	Baffles	Baffles corroding, cracking, warping and/or showing signs of failure as determined by maintenance/inspection person.	Baffles repaired or replaced to specifications.
Access Ladder Damaged	Ladder is corroded or deteriorated, not functioning properly, not securely attached to structure wall, missing rungs, cracks, and misaligned.	Ladder replaced or repaired and meets specifications, and is safe to use as determined by inspection personnel.	



## No. 17 – Coalescing Plate Oil/Water Separators

Maintenance Component	Defect	Condition When Maintenance is Needed	Results Expected When Maintenance is Performed
General	Monitoring	Inspection of discharge water for obvious signs of poor water quality.	Effluent discharge from vault should be clear with no thick visible sheen.
	Sediment Accumulation	Sediment depth in bottom of vault exceeds 6-inches in depth and/or visible signs of sediment on plates.	No sediment deposits on vault bottom and plate media, which would impede flow through the vault and reduce separation efficiency.
	Trash and Debris Accumulation	Trash and debris accumulated in vault, or pipe inlet/outlet, floatables and non-floatables.	Trash and debris removed from vault, and inlet/outlet piping.
	Oil Accumulation	Oil accumulation that exceeds 1-inch at the water surface.	Oil is extracted from vault using vacuoring methods. Coalescing plates are cleaned by thoroughly rinsing and flushing. Should be no visible oil depth on water.
	Damaged Coalescing Plates	Plate media broken, deformed, cracked and/or showing signs of failure.	A portion of the media pack or the entire plate pack is replaced depending on severity of failure.
	Damaged Pipes	Inlet or outlet piping damaged or broken and in need of repair.	Pipe repaired and or replaced.
	Baffles	Baffles corroding, cracking, warping and/or showing signs of failure as determined by maintenance/inspection person.	Baffles repaired or replaced to specifications.
	Vault Structure Damage - Includes Cracks in Walls, Bottom, Damage to Frame and/or Top Slab	Cracks wider than 1/2-inch or evidence of soil particles entering the structure through the cracks, or maintenance/inspection personnel determine that the vault is not structurally sound.	Vault replaced or repairs made so that vault meets design specifications and is structurally sound.
		Cracks wider than 1/2-inch at the joint of any inlet/outlet pipe or evidence of soil particles entering through the cracks.	Vault repaired so that no cracks exist wider than 1/4-inch at the joint of the inlet/outlet pipe.
Access Ladder Damaged	Ladder is corroded or deteriorated, not functioning properly, not securely attached to structure wall, missing rungs, cracks, and misaligned.	Ladder replaced or repaired and meets specifications, and is safe to use as determined by inspection personnel.	

## No. 18 – Catchbasin Inserts

Maintenance Component	Defect	Conditions When Maintenance is Needed	Results Expected When Maintenance is Performed
General	Sediment Accumulation	When sediment forms a cap over the insert media of the insert and/or unit.	No sediment cap on the insert media and its unit.
	Trash and Debris Accumulation	Trash and debris accumulates on insert unit creating a blockage/restriction.	Trash and debris removed from insert unit. Runoff freely flows into catch basin.
	Media Insert Not Removing Oil	Effluent water from media insert has a visible sheen.	Effluent water from media insert is free of oils and has no visible sheen.
	Media Insert Water Saturated	Catch basin insert is saturated with water and no longer has the capacity to absorb.	Remove and replace media insert
	Media Insert-Oil Saturated	Media oil saturated due to petroleum spill that drains into catch basin.	Remove and replace media insert.
	Media Insert Use Beyond Normal Product Life	Media has been used beyond the typical average life of media insert product.	Remove and replace media at regular intervals, depending on insert product.

## No. 19 – MEDIA FILTER DRAIN (MFD)

Maintenance Component	Defect	Conditions When Maintenance is Needed	Results Expected When Maintenance is Performed
General	Sediment accumulation on grass filter strip	Sediment depth exceeds 2 inches or creates uneven grading that interferes with sheet flow.	Remove sediment deposits on grass treatment area of the embankment. When finished, embankment should be level from side to side and drain freely toward the toe of the embankment slope. There should be no areas of standing water once inflow has ceased.
	No-vegetation zone/flow spreader	Flow spreader is uneven or clogged so that flows are not uniformly distributed over entire embankment width.	Level the spreader and clean to spread flows evenly over entire embankment width.
	Poor vegetation coverage	Grass is sparse or bare, or eroded patches are observed in more than 10% of the grass strip surface area.	Determine why grass growth is poor and correct the offending condition. Reseed into loosened, fertile soil or compost; or, replant with plugs of grass from the upper slope.
	Vegetation	Grass becomes excessively tall (greater than 10 inches); nuisance weeds and other vegetation start to take over.	Mow vegetation or remove nuisance vegetation to not impede flow. Mow grass to a height of 6 inches.
	Media filter drain mix replacement	Water is seen on the surface of the media filter drain mix long after the storms have ceased. Typically, the 6-month, 24-hour precipitation event should drain within 48 hours. More common storms should drain within 24 hours. Maintenance also needed on a 10-year cycle and during a preservation project.	Excavate and replace all of the media filter drain mix contained within the media filter drain.
	Excessive shading	Grass growth is poor because sunlight does not reach embankment.	If possible, trim back overhanging limbs and remove brushy vegetation on adjacent slopes.
	Trash and debris	Trash and debris have accumulated on embankment.	Remove trash and debris from embankment.
	Flooding of Media filter drain	When media filter drain is inundated by flood water	Evaluate media filter drain material for acceptable infiltration rate and replace if media filter drain does not meet long-term infiltration rate standards.

## No. 20 – COMPOST AMENDED VEGETATED FILTER STRIP (CAVFS)

Maintenance Component	Defect	Conditions When Maintenance is Needed	Results Expected When Maintenance is Performed
General	Sediment accumulation on grass	Sediment depth exceeds 2 inches.	Remove sediment deposits. Relevel so slope is even and flows pass evenly through strip.
	Vegetation	Grass becomes excessively tall (greater than 10 inches); nuisance weeds and other vegetation start to take over.	Mow grass and control nuisance vegetation so that flow is not impeded. Grass should be mowed to a height of 6 inches.
	Trash and debris	Trash and debris have accumulated on the vegetated filter strip.	Remove trash and debris from filter.
	Erosion/scouring	Areas have eroded or scoured due to flow channelization or high flows.	For ruts or bare areas less than 12 inches wide, repair the damaged area by filling with a 50/50 mixture of crushed gravel and compost. The grass will creep in over the rock in time. If bare areas are large, generally greater than 12 inches wide, the vegetated filter strip should be regraded and reseeded. For smaller bare areas, overseed when bare spots are evident.
	Flow spreader	Flow spreader is uneven or clogged so that flows are not uniformly distributed over entire filter width.	Level the spreader and clean so that flows are spread evenly over entire filter width

**No. 21 - Maintenance Standards and Procedures for Bioretention Facilities.**

Note that the inspection and routine maintenance frequencies listed below are recommended by Ecology. They do not supersede or replace the municipal stormwater permit requirements for inspection frequency required of municipal stormwater permittees for “stormwater treatment and flow control BMPs/facilities.”

Maintenance Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Facility Footprint</b>				
Earthen side slopes and berms	B, S		Erosion (gullies/ rills) greater than 2 inches deep around inlets, outlet, and alongside slopes	<ul style="list-style-type: none"> <li>Eliminate cause of erosion and stabilize damaged area (regrade, rock, vegetation, erosion control matting)</li> <li>For deep channels or cuts (over 3 inches in ponding depth), temporary erosion control measures should be put in place until permanent repairs can be made.</li> <li>Properly designed, constructed and established facilities with appropriate flow velocities should not have erosion problems except perhaps in extreme events. If erosion problems persist, the following should be reassessed: (1) flow volumes from contributing areas and bioretention facility sizing; (2) flow velocities and gradients within the facility; and (3) flow dissipation and erosion protection strategies at the facility inlet.</li> </ul>
	A		Erosion of sides causes slope to become a hazard	Take actions to eliminate the hazard and stabilize slopes
	A, S		Settlement greater than 3 inches (relative to undisturbed sections of berm)	Restore to design height
	A, S		Downstream face of berm wet, seeps or leaks evident	Plug any holes and compact berm (may require consultation with engineer, particularly for larger berms)
	A		Any evidence of rodent holes or water piping in berm	<ul style="list-style-type: none"> <li>Eradicate rodents (see "Pest control")</li> <li>Fill holes and compact (may require consultation with engineer, particularly for larger berms)</li> </ul>
Concrete sidewalls	A		Cracks or failure of concrete sidewalls	<ul style="list-style-type: none"> <li>Repair/ seal cracks</li> <li>Replace if repair is insufficient</li> </ul>
Rockery sidewalls	A		Rockery side walls are insecure	Stabilize rockery sidewalls (may require consultation with engineer, particularly for walls 4 feet or greater in height)
Facility area		All maintenance visits (at least biannually)	Trash and debris present	Clean out trash and debris
Facility bottom area	A, S		Accumulated sediment to extent that infiltration rate is reduced (see "Ponded water") or surface storage capacity significantly impacted	<ul style="list-style-type: none"> <li>Remove excess sediment</li> <li>Replace any vegetation damaged or destroyed by sediment accumulation and removal</li> <li>Mulch newly planted vegetation</li> <li>Identify and control the sediment source (if feasible)</li> <li>If accumulated sediment is recurrent, consider adding presettlement or installing berms to create a forebay at the inlet</li> </ul>
		During/after fall leaf drop	Accumulated leaves in facility	Remove leaves if there is a risk to clogging outlet structure or water flow is impeded
Low permeability check dams and weirs	A, S		Sediment, vegetation, or debris accumulated at or blocking (or having the potential to block) check dam, flow control weir or orifice	Clear the blockage
	A, S		Erosion and/or undercutting present	Repair and take preventative measures to prevent future erosion and/or undercutting
	A		Grade board or top of weir damaged or not level	Restore to level position

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least one visit should occur during the wet season (for debris/clog related maintenance, this inspection/maintenance visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

IPM - Integrated Pest Management

ISA - International Society of Arboriculture

No. 21 (continued) - Maintenance Standards and Procedures for Bioretention Facilities.

Maintenance Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Facility Footprint (cont'd)</b>				
Ponded water	B, S		Excessive ponding water: Water overflows during storms smaller than the design event or ponded water remains in the basin 48 hours or longer after the end of a storm.	Determine cause and resolve in the following order: 1) Confirm leaf or debris buildup in the bottom of the facility is not impeding infiltration. If necessary, remove leaf litter/debris. 2) Ensure that underdrain (if present) is not clogged. If necessary, clear underdrain. 3) Check for other water inputs (e.g., groundwater, illicit connections). 4) Verify that the facility is sized appropriately for the contributing area. Confirm that the contributing area has not increased. If steps #1-4 do not solve the problem, the bioretention soil is likely clogged by sediment accumulation at the surface or has become overly compacted. Dig a small hole to observe soil profile and identify compaction depth or clogging front to help determine the soil depth to be removed or otherwise rehabilitated (e.g., tilled). Consultation with an engineer is recommended.
Bioretention soil media	As needed		Bioretention soil media protection is needed when performing maintenance requiring entrance into the facility footprint	<ul style="list-style-type: none"> <li>Minimize all loading in the facility footprint (foot traffic and other loads) to the degree feasible in order to prevent compaction of bioretention soils.</li> <li>Never drive equipment or apply heavy loads in facility footprint.</li> <li>Because the risk of compaction is higher during saturated soil conditions, any type of loading in the cell (including foot traffic) should be minimized during wet conditions.</li> <li>Consider measures to distribute loading if heavy foot traffic is required or equipment must be placed in facility. As an example, boards may be placed across soil to distribute loads and minimize compaction.</li> <li>If compaction occurs, soil must be loosened or otherwise rehabilitated to original design state.</li> </ul>
<b>Inlets/Outlets/Pipes</b>				
Splash block inlet	A		Water is not being directed properly to the facility and away from the inlet structure	Reconfigure/ repair blocks to direct water to facility and away from structure
Curb cut inlet/outlet	M during the wet season and before severe storm is forecasted	Weekly during fall leaf drop	Accumulated leaves at curb cuts	Clear leaves (particularly important for key inlets and low points along long, linear facilities)
Pipe inlet/outlet	A		Pipe is damaged	Repair/ replace
	W		Pipe is clogged	Remove roots or debris
	A, S		Sediment, debris, trash, or mulch reducing capacity of inlet/outlet	<ul style="list-style-type: none"> <li>Clear the blockage</li> <li>Identify the source of the blockage and take actions to prevent future blockages</li> </ul>
		Weekly during fall leaf drop	Accumulated leaves at inlets/outlets	Clear leaves (particularly important for key inlets and low points along long, linear facilities)
		A	Maintain access for inspections	<ul style="list-style-type: none"> <li>Clear vegetation (transplant vegetation when possible) within 1 foot of inlets and outlets, maintain access pathways</li> <li>Consultation with a landscape architect is recommended for removal, transplant, or substitution of plants</li> </ul>
Erosion control at inlet	A		Concentrated flows are causing erosion	Maintain a cover of rock or cobbles or other erosion protection measure (e.g., matting) to protect the ground where concentrated water enters the facility (e.g., a pipe, curb cut or swale)

No. 21 (continued) - Maintenance Standards and Procedures for Bioretention Facilities.

Maintenance Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Inlets/Outlets/Pipes (cont'd)</b>				
Trash rack	S		Trash or other debris present on trash rack	Remove/dispose
	A		Bar screen damaged or missing	Repair/replace
Overflow	A, S		Capacity reduced by sediment or debris	Remove sediment or debris/dispose
Underdrain pipe	Clean pipe as needed	Clean orifice at least biannually (may need more frequent cleaning during wet season)	<ul style="list-style-type: none"> <li>Plant roots, sediment or debris reducing capacity of underdrain</li> <li>Prolonged surface ponding (see "Ponded water")</li> </ul>	<ul style="list-style-type: none"> <li>Jet clean or rotary cut debris/roots from underdrain(s)</li> <li>If underdrains are equipped with a flow restrictor (e.g., orifice) to attenuate flows, the orifice must be cleaned regularly.</li> </ul>
<b>Vegetation</b>				
Facility bottom area and upland slope vegetation	Fall and Spring		Vegetation survival rate falls below 75% within first two years of establishment (unless project O&M manual or record drawing stipulates more or less than 75% survival rate).	<ul style="list-style-type: none"> <li>Determine cause of poor vegetation growth and correct condition</li> <li>Replant as necessary to obtain 75% survival rate or greater. Refer to original planting plan, or approved jurisdictional species list for appropriate plant replacements (See Appendix 3 - Bioretention Plant List, in the LID Technical Guidance Manual for Puget Sound).</li> <li>Confirm that plant selection is appropriate for site growing conditions</li> <li>Consultation with a landscape architect is recommended for removal, transplant, or substitution of plants</li> </ul>
Vegetation (general)	As needed		Presence of diseased plants and plant material	<ul style="list-style-type: none"> <li>Remove any diseased plants or plant parts and dispose of in an approved location (e.g., commercial landfill) to avoid risk of spreading the disease to other plants</li> <li>Disinfect gardening tools after pruning to prevent the spread of disease</li> <li>See Pacific Northwest Plant Disease Management Handbook for information on disease recognition and for additional resources</li> <li>Replant as necessary according to recommendations provided for "facility bottom area and upland slope vegetation".</li> </ul>
Trees and shrubs		All pruning seasons (timing varies by species)	Pruning as needed	<ul style="list-style-type: none"> <li>Prune trees and shrubs in a manner appropriate for each species. Pruning should be performed by landscape professionals familiar with proper pruning techniques</li> <li>All pruning of mature trees should be performed by or under the direct guidance of an ISA certified arborist</li> </ul>
	A		Large trees and shrubs interfere with operation of the facility or access for maintenance	<ul style="list-style-type: none"> <li>Prune trees and shrubs using most current ANSI A300 standards and ISA BMPs.</li> <li>Remove trees and shrubs, if necessary.</li> </ul>
	Fall and Spring		Standing dead vegetation is present	<ul style="list-style-type: none"> <li>Remove standing dead vegetation</li> <li>Replace dead vegetation within 30 days of reported dead and dying plants (as practical depending on weather/planting season)</li> <li>If vegetation replacement is not feasible within 30 days, and absence of vegetation may result in erosion problems, temporary erosion control measures should be put in place immediately.</li> <li>Determine cause of dead vegetation and address issue, if possible</li> <li>If specific plants have a high mortality rate, assess the cause and replace with appropriate species. Consultation with a landscape architect is recommended.</li> </ul>
	Fall and Spring		Planting beneath mature trees	<ul style="list-style-type: none"> <li>When working around and below mature trees, follow the most current ANSI A300 standards and ISA BMPs to the extent practicable (e.g., take care to minimize any damage to tree roots and avoid compaction of soil).</li> <li>Planting of small shrubs or groundcovers beneath mature trees may be desirable in some cases; such plantings should use mainly plants that come as bulbs, bare root or in 4-inch pots; plants should be in no larger than 1-gallon containers.</li> </ul>

No. 21 (continued) - Maintenance Standards and Procedures for Bioretention Facilities.

Maintenance Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Vegetation (cont'd)</b>				
Trees and shrubs (cont'd)	Fall and Spring		Planting beneath mature trees	<ul style="list-style-type: none"> <li>When working around and below mature trees, follow the most current ANSI A300 standards and ISA BMPs to the extent practicable (e.g., take care to minimize any damage to tree roots and avoid compaction of soil).</li> <li>Planting of small shrubs or groundcovers beneath mature trees may be desirable in some cases; such plantings should use mainly plants that come as bulbs, bare root or in 4-inch pots; plants should be in no larger than 1-gallon containers.</li> </ul>
	Fall and Spring		Presence of or need for stakes and guys (tree growth, maturation, and support needs)	<ul style="list-style-type: none"> <li>Verify location of facility liners and underdrain (if any) prior to stake installation in order to prevent liner puncture or pipe damage</li> <li>Monitor tree support systems: Repair and adjust as needed to provide support and prevent damage to tree.</li> <li>Remove tree supports (stakes, guys, etc.) after one growing season or maximum of 1 year.</li> <li>Backfill stake holes after removal.</li> </ul>
Trees and shrubs adjacent to vehicle travel areas (or areas where visibility needs to be maintained)	A		Vegetation causes some visibility (line of sight) or driver safety issues	<ul style="list-style-type: none"> <li>Maintain appropriate height for sight clearance</li> <li>When continued, regular pruning (more than one time/ growing season) is required to maintain visual sight lines for safety or clearance along a walk or drive, consider relocating the plant to a more appropriate location.</li> <li>Remove or transplant if continual safety hazard</li> <li>Consultation with a landscape architect is recommended for removal, transplant, or substitution of plants</li> </ul>
Flowering plants		A	Dead or spent flowers present	Remove spent flowers (deadhead)
Perennials		Fall	Spent plants	Cut back dying or dead and fallen foliage and stems
Emergent vegetation		Spring	Vegetation compromises conveyance	<ul style="list-style-type: none"> <li>Hand rake sedges and rushes with a small rake or fingers to remove dead foliage before new growth emerges in spring or earlier only if the foliage is blocking water flow (sedges and rushes do not respond well to pruning)</li> </ul>
Ornamental grasses (perennial)		Winter and Spring	Dead material from previous year's growing cycle or dead collapsed foliage	<ul style="list-style-type: none"> <li>Leave dry foliage for winter interest</li> <li>Hand rake with a small rake or fingers to remove dead foliage back to within several inches from the soil before new growth emerges in spring or earlier if the foliage collapses and is blocking water flow</li> </ul>
Ornamental grasses (evergreen)		Fall and Spring	Dead growth present in spring	<ul style="list-style-type: none"> <li>Hand rake with a small rake or fingers to remove dead growth before new growth emerges in spring</li> <li>Clean, rake, and comb grasses when they become too tall</li> <li>Cut back to ground or thin every 2-3 years as needed</li> </ul>
Noxious weeds		M (March – October, preceding seed dispersal)	Listed noxious vegetation is present (refer to current county noxious weed list)	<ul style="list-style-type: none"> <li>By law, class A &amp; B noxious weeds must be removed, bagged and disposed as garbage immediately</li> <li>Reasonable attempts must be made to remove and dispose of class C noxious weeds</li> <li>It is strongly encouraged that herbicides and pesticides not be used in order to protect water quality; use of herbicides and pesticides may be prohibited in some jurisdictions</li> <li>Apply mulch after weed removal (see "Mulch")</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least one visit should occur during the wet season (for debris/clog related maintenance, this inspection/maintenance visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

IPM – Integrated Pest Management

ISA - International Society of Arboriculture



No. 21 (continued) - Maintenance Standards and Procedures for Bioretention Facilities.

Maintenance Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Vegetation (cont'd)</b>				
Weeds		M (March – October, preceding seed dispersal)	Weeds are present	<ul style="list-style-type: none"> <li>Remove weeds with their roots manually with pincer-type weeding tools, flame weeders, or hot water weeders as appropriate</li> <li>Follow IPM protocols for weed management (see "Additional Maintenance Resources" section for more information on IPM protocols)</li> </ul>
Excessive vegetation		Once in early to mid-May and once in early- to mid-September	Low-lying vegetation growing beyond facility edge onto sidewalks, paths, or street edge poses pedestrian safety hazard or may clog adjacent permeable pavement surfaces due to associated leaf litter, mulch, and soil	<ul style="list-style-type: none"> <li>Edge or trim groundcovers and shrubs at facility edge</li> <li>Avoid mechanical blade-type edger and do not use edger or trimmer within 2 feet of tree trunks</li> <li>While some clippings can be left in the facility to replenish organic material in the soil, excessive leaf litter can cause surface soil clogging</li> </ul>
	As needed		Excessive vegetation density inhibits stormwater flow beyond design ponding or becomes a hazard for pedestrian and vehicular circulation and safety	<ul style="list-style-type: none"> <li>Determine whether pruning or other routine maintenance is adequate to maintain proper plant density and aesthetics</li> <li>Determine if planting type should be replaced to avoid ongoing maintenance issues (an aggressive grower under perfect growing conditions should be transplanted to a location where it will not impact flow)</li> <li>Remove plants that are weak, broken or not true to form; replace in-kind</li> <li>Thin grass or plants impacting facility function without leaving visual holes or bare soil areas</li> <li>Consultation with a landscape architect is recommended for removal, transplant, or substitution of plants</li> </ul>
	As needed		Vegetation blocking curb cuts, causing excessive sediment buildup and flow bypass	<ul style="list-style-type: none"> <li>Remove vegetation and sediment buildup</li> </ul>
<b>Mulch</b>				
Mulch		Following weeding	Bare spots (without mulch cover) are present or mulch depth less than 2 inches	<ul style="list-style-type: none"> <li>Supplement mulch with hand tools to a depth of 2 to 3 inches</li> <li>Replenish mulch per O&amp;M manual. Often coarse compost is used in the bottom of the facility and arborist wood chips are used on side slopes and rim (above typical water levels)</li> <li>Keep all mulch away from woody stems</li> </ul>
<b>Watering</b>				
Irrigation system (if any)		Based on manufacturer's instructions	Irrigation system present	<ul style="list-style-type: none"> <li>Follow manufacturer's instructions for O&amp;M</li> </ul>
	A		Sprinklers or drip irrigation not directed/located to properly water plants	<ul style="list-style-type: none"> <li>Redirect sprinklers or move drip irrigation to desired areas</li> </ul>
Summer watering (first year)		Once every 1-2 weeks or as needed during prolonged dry periods	Trees, shrubs and groundcovers in first year of establishment period	<ul style="list-style-type: none"> <li>10 to 15 gallons per tree</li> <li>3 to 5 gallons per shrub</li> <li>2 gallons water per square foot for groundcover areas</li> <li>Water deeply, but infrequently, so that the top 6 to 12 inches of the root zone is moist</li> <li>Use soaker hoses or spot water with a shower type wand when irrigation system is not present                             <ul style="list-style-type: none"> <li>Pulse water to enhance soil absorption, when feasible</li> <li>Pre-moisten soil to break surface tension of dry or hydrophobic soils/mulch, followed by several more passes. With this method, each pass increases soil absorption and allows more water to infiltrate prior to runoff</li> </ul> </li> <li>Add a tree bag or slow-release watering device (e.g., bucket with a perforated bottom) for watering newly installed trees when irrigation system is not present</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least one visit should occur during the wet season (for debris/clog related maintenance, this inspection/maintenance visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

IPM – Integrated Pest Management

ISA - International Society of Arboriculture

No. 21 (continued) - Maintenance Standards and Procedures for Bioretention Facilities.

Maintenance Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Watering (cont'd)</b>				
Summer watering (second and third years)		Once every 2-4 weeks or as needed during prolonged dry periods	Trees, shrubs and groundcovers in second or third year of establishment period	<ul style="list-style-type: none"> <li>• 10 to 15 gallons per tree</li> <li>• 3 to 5 gallons per shrub</li> <li>• 2 gallons water per square foot for groundcover areas</li> <li>• Water deeply, but infrequently, so that the top 6 to 12 inches of the root zone is moist</li> <li>• Use soaker hoses or spot water with a shower type wand when irrigation system is not present                             <ul style="list-style-type: none"> <li>○ Pulse water to enhance soil absorption, when feasible</li> <li>○ Pre-moisten soil to break surface tension of dry or hydrophobic soils/mulch, followed by several more passes. With this method, each pass increases soil absorption and allows more water to infiltrate prior to runoff</li> </ul> </li> </ul>
Summer watering (after establishment)		As needed	Established vegetation (after 3 years)	<ul style="list-style-type: none"> <li>• Plants are typically selected to be drought tolerant and not require regular watering after establishment; however, trees may take up to 5 years of watering to become fully established</li> <li>• Identify trigger mechanisms for drought-stress (e.g., leaf wilt, leaf senescence, etc.) of different species and water immediately after initial signs of stress appear</li> <li>• Water during drought conditions or more often if necessary to maintain plant cover</li> </ul>
<b>Pest Control</b>				
Mosquitoes	B, S		Standing water remains for more than 3 days after the end of a storm	<ul style="list-style-type: none"> <li>• Identify the cause of the standing water and take appropriate actions to address the problem (see "Ponded water")</li> <li>• To facilitate maintenance, manually remove standing water and direct to the storm drainage system (if runoff is from non pollution-generating surfaces) or sanitary sewer system (if runoff is from pollution-generating surfaces) after getting approval from sanitary sewer authority.</li> <li>• Use of pesticides or <i>Bacillus thuringiensis israelensis</i> (Bti) may be considered only as a temporary measure while addressing the standing water cause. If overflow to a surface water will occur within 2 weeks after pesticide use, apply for coverage under the Aquatic Mosquito Control NPDES General Permit.</li> </ul>
Nuisance animals	As needed		Nuisance animals causing erosion, damaging plants, or depositing large volumes of feces	<ul style="list-style-type: none"> <li>• Reduce site conditions that attract nuisance species where possible (e.g., plant shrubs and tall grasses to reduce open areas for geese, etc.)</li> <li>• Place predator decoys</li> <li>• Follow IPM protocols for specific nuisance animal issues (see "Additional Maintenance Resources" section for more information on IPM protocols)</li> <li>• Remove pet waste regularly</li> <li>• For public and right-of-way sites consider adding garbage cans with dog bags for picking up pet waste.</li> </ul>
Insect pests	Every site visit associated with vegetation management		Signs of pests, such as wilting leaves, chewed leaves and bark, spotting or other indicators	<ul style="list-style-type: none"> <li>• Reduce hiding places for pests by removing diseased and dead plants</li> <li>• For infestations, follow IPM protocols (see "Additional Maintenance Resources" section for more information on IPM protocols)</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least one visit should occur during the wet season (for debris/clog related maintenance, this inspection/maintenance visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

IPM – Integrated Pest Management

ISA - International Society of Arboriculture

**No. 22 - Maintenance Standards and Procedures for Permeable Pavement.**

Note that the inspection and routine maintenance frequencies listed below are recommended by Ecology. They do not supersede or replace the municipal stormwater permit requirements for inspection frequency required of municipal stormwater permittees for “stormwater treatment and flow control BMPs/facilities.”

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Surface/Wearing Course</b>				
Permeable Pavements, all	A, S		Runoff from adjacent pervious areas deposits soil, mulch or sediment on paving	<ul style="list-style-type: none"> <li>• Clean deposited soil or other materials from permeable pavement or other adjacent surfacing</li> <li>• Check if surface elevation of planted area is too high, or slopes towards pavement, and can be regraded (prior to regrading, protect permeable pavement by covering with temporary plastic and secure covering in place)</li> <li>• Mulch and/or plant all exposed soils that may erode to pavement surface</li> </ul>
Porous asphalt or pervious concrete		A or B	None (routine maintenance)	Clean surface debris from pavement surface using one or a combination of the following methods: <ul style="list-style-type: none"> <li>• Remove sediment, debris, trash, vegetation, and other debris deposited onto pavement (rakes and leaf blowers can be used for removing leaves)</li> <li>• Vacuum/sweep permeable paving installation using:               <ul style="list-style-type: none"> <li>○ Walk-behind vacuum (sidewalks)</li> <li>○ High efficiency regenerative air or vacuum sweeper (roadways, parking lots)</li> <li>○ ShopVac or brush brooms (small areas)</li> </ul> </li> <li>• Hand held pressure washer or power washer with rotating brushes</li> </ul> Follow equipment manufacturer guidelines for when equipment is most effective for cleaning permeable pavement. Dry weather is more effective for some equipment.
	Ab		Surface is clogged: Ponding on surface or water flows off the permeable pavement surface during a rain event (does not infiltrate)	<ul style="list-style-type: none"> <li>• Review the overall performance of the facility (note that small clogged areas may not reduce overall performance of facility)</li> <li>• Test the surface infiltration rate using ASTM C1701 as a corrective maintenance indicator. Perform one test per installation, up to 2,500 square feet. Perform an additional test for each additional 2,500 square feet up to 15,000 square feet total. Above 15,000 square feet, add one test for every 10,000 square feet.</li> <li>• If the results indicate an infiltration rate of 10 inches per hour or less, then perform corrective maintenance to restore permeability. To clean clogged pavement surfaces, use one or combination of the following methods:</li> <li>• Combined pressure wash and vacuum system calibrated to not dislodge wearing course aggregate.</li> <li>• Hand held pressure washer or power washer with rotating brushes</li> <li>• Pure vacuum sweepers</li> </ul> Note: If the annual/biannual routine maintenance standard to clean the pavement surface is conducted using equipment from the list above, corrective maintenance may not be needed.
	A		Sediment present at the surface of the pavement	<ul style="list-style-type: none"> <li>• Assess the overall performance of the pavement system during a rain event. If water runs off the pavement and/or there is ponding then see above.</li> <li>• Determine source of sediment loading and evaluate whether or not the source can be reduced/eliminated. If the source cannot be addressed, consider increasing frequency of routine cleaning (e.g., twice per year instead of once per year).</li> </ul>
	Summer		Moss growth inhibits infiltration or poses slip safety hazard	<ul style="list-style-type: none"> <li>• Sidewalks: Use a stiff broom to remove moss in the summer when it is dry</li> <li>• Parking lots and roadways: Pressure wash, vacuum sweep, or use a combination of the two for cleaning moss from pavement surface. May require stiff broom or power brush in areas of heavy moss.</li> </ul>
	A		Major cracks or trip hazards and concrete spalling and raveling	<ul style="list-style-type: none"> <li>• Fill potholes or small cracks with patching mixes</li> <li>• Large cracks and settlement may require cutting and replacing the pavement section. Replace in-kind where feasible. Replacing porous asphalt with conventional asphalt is acceptable if it is a small percentage of the total facility area and does not impact the overall facility function.</li> <li>• Take appropriate precautions during pavement repair and replacement efforts to prevent clogging of adjacent porous materials</li> </ul>

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.

No. 22 (continued) - Maintenance Standards and Procedures for Permeable Pavement.

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Surface/Wearing Course (cont'd)</b>				
Interlocking concrete paver blocks and aggregate pavers		A or B	None (routine maintenance)	Clean pavement surface using one or a combination of the following methods: <ul style="list-style-type: none"> <li>Remove sediment, debris, trash, vegetation, and other debris deposited onto pavement (rakes and leaf blowers can be used for removing leaves)</li> <li>Vacuum/sweep permeable paving installation using: <ul style="list-style-type: none"> <li>Walk-behind vacuum (sidewalks)</li> <li>High efficiency regenerative air or vacuum sweeper (roadways, parking lots)</li> <li>ShopVac or brush brooms (small areas)</li> </ul> </li> <li>Note: Vacuum settings may have to be adjusted to prevent excess uptake of aggregate from paver openings or joints. Vacuum surface openings in dry weather to remove dry, encrusted sediment.</li> </ul>
	A <sup>b</sup>		Surface is clogged: Ponding on surface or water flows off the permeable pavement surface during a rain event (does not infiltrate)]	<ul style="list-style-type: none"> <li>Review the overall performance of the facility (note that small clogged areas may not reduce overall performance of facility)</li> <li>Test the surface infiltration rate using ASTM C1701 as a corrective maintenance indicator. Perform one test per installation, up to 2,500 square feet. Perform an additional test for each additional 2,500 square feet up to 15,000 square feet total. Above 15,000 square feet, add one test for every 10,000 square feet.</li> <li>If the results indicate an infiltration rate of 10 inches per hour or less, then perform corrective maintenance to restore permeability.</li> <li>Clogging is usually an issue in the upper 2 to 3 centimeters of aggregate. Remove the upper layer of encrusted sediment, and fines, and/or vegetation from openings and joints between the pavers by mechanical means and/or suction equipment (e.g., pure vacuum sweeper).</li> <li>Replace aggregate in paver cells, joints, or openings per manufacturer's recommendations</li> </ul>
	A		Sediment present at the surface of the pavement	<ul style="list-style-type: none"> <li>Assess the overall performance of the pavement system during a rain event. If water runs off the pavement and/or there is ponding, then see above.</li> <li>Determine source of sediment loading and evaluate whether or not the source can be reduced/eliminated. If the source cannot be addressed, consider increasing frequency of routine cleaning (e.g., twice per year instead of once per year).</li> </ul>
	Summer		Moss growth inhibits infiltration or poses slip safety hazard	<ul style="list-style-type: none"> <li>Sidewalks: Use a stiff broom to remove moss in the summer when it is dry</li> <li>Parking lots and roadways: Vacuum sweep or stiff broom/power brush for cleaning moss from pavement surface</li> </ul>
	A		Paver block missing or damaged	Remove individual damaged paver blocks by hand and replace or repair per manufacturer's recommendations
	A		Loss of aggregate material between paver blocks	Refill per manufacturer's recommendations for interlocking paver sections
	A		Settlement of surface	May require resetting
Open-celled paving grid with gravel		A or B	None (routine maintenance)	<ul style="list-style-type: none"> <li>Remove sediment, debris, trash, vegetation, and other debris deposited onto pavement (rakes and leaf blowers can be used for removing leaves)</li> <li>Follow equipment manufacturer guidelines for cleaning surface.</li> </ul>
	A <sup>b</sup>		Aggregate is clogged: Ponding on surface or water flows off the permeable pavement surface during a rain event (does not infiltrate)]	<ul style="list-style-type: none"> <li>Use vacuum truck to remove and replace top course aggregate</li> <li>Replace aggregate in paving grid per manufacturer's recommendations</li> </ul>
	A		Paving grid missing or damaged	<ul style="list-style-type: none"> <li>Remove pins, pry up grid segments, and replace gravel</li> <li>Replace grid segments where three or more adjacent rings are broken or damaged</li> <li>Follow manufacturer guidelines for repairing surface.</li> </ul>
	A		Settlement of surface	May require resetting
	A		Loss of aggregate material in paving grid	Replenish aggregate material by spreading gravel with a rake (gravel level should be maintained at the same level as the plastic rings or no more than 1/4 inch above the top of rings). See manufacturer's recommendations.
		A	Weeds present	<ul style="list-style-type: none"> <li>Manually remove weeds</li> <li>Presence of weeds may indicate that too many fines are present (refer to Actions Needed under "Aggregate is clogged" to address this issue)</li> </ul>

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.

No. 22 (continued) - Maintenance Standards and Procedures for Permeable Pavement.

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Surface/Wearing Course (cont'd)</b>				
Open-celled paving grid with grass		A or B	None (routine maintenance)	<ul style="list-style-type: none"> <li>Remove sediment, debris, trash, vegetation, and other debris deposited onto pavement (rakes and leaf blowers can be used for removing leaves)</li> <li>Follow equipment manufacturer guidelines for cleaning surface.</li> </ul>
	A <sup>b</sup>		Aggregate is clogged: Ponding on surface or water flows off the permeable pavement surface during a rain event (does not infiltrate)]	<ul style="list-style-type: none"> <li>Rehabilitate per manufacturer's recommendations.</li> </ul>
	A		Paving grid missing or damaged	<ul style="list-style-type: none"> <li>Remove pins, pry up grid segments, and replace grass</li> <li>Replace grid segments where three or more adjacent rings are broken or damaged</li> <li>Follow manufacturer guidelines for repairing surface.</li> </ul>
	A		Settlement of surface	<ul style="list-style-type: none"> <li>May require resetting</li> </ul>
	A		Poor grass coverage in paving grid	<ul style="list-style-type: none"> <li>Restore growing medium, reseed or plant, aerate, and/or amend vegetated area as needed</li> <li>Traffic loading may be inhibiting grass growth; reconsider traffic loading if feasible</li> </ul>
		As needed	None (routine maintenance)	<ul style="list-style-type: none"> <li>Use a mulch mower to mow grass</li> </ul>
		A	None (routine maintenance)	<ul style="list-style-type: none"> <li>Sprinkle a thin layer of compost on top of grass surface (1/2" top dressing) and sweep it in</li> <li>Do not use fertilizer</li> </ul>
		A	Weeds present	<ul style="list-style-type: none"> <li>Manually remove weeds</li> <li>Mow, torch, or inoculate and replace with preferred vegetation</li> </ul>
<b>Inlets/Outlets/Pipes</b>				
Inlet/outlet pipe	A		Pipe is damaged	Repair/replace
	A		Pipe is clogged	Remove roots or debris
Underdrain pipe	Clean pipe as needed	Clean orifice at least biannually (may need more frequent cleaning during wet season)	Plant roots, sediment or debris reducing capacity of underdrain (may cause prolonged drawdown period)	<ul style="list-style-type: none"> <li>Jet clean or rotary cut debris/roots from underdrain(s)</li> <li>If underdrains are equipped with a flow restrictor (e.g., orifice) to attenuate flows, the orifice must be cleaned regularly</li> </ul>
Raised subsurface overflow pipe	Clean pipe as needed	Clean orifice at least biannually (may need more frequent cleaning during wet season)	Plant roots, sediment or debris reducing capacity of underdrain	<ul style="list-style-type: none"> <li>Jet clean or rotary cut debris/roots from underdrain(s)</li> <li>If underdrains are equipped with a flow restrictor (e.g., orifice) to attenuate flows, the orifice must be cleaned regularly</li> </ul>
Outlet structure	A, S		Sediment, vegetation, or debris reducing capacity of outlet structure	<ul style="list-style-type: none"> <li>Clear the blockage</li> <li>Identify the source of the blockage and take actions to prevent future blockages</li> </ul>

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.

No. 22 (continued) - Maintenance Standards and Procedures for Permeable Pavement.

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Inlets/Outlets/Pipes (cont'd)</b>				
Overflow	B		Native soil is exposed or other signs of erosion damage are present at discharge point	Repair erosion and stabilize surface
<b>Aggregate Storage Reservoir</b>				
Observation port	A, S		Water remains in the storage aggregate longer than anticipated by design after the end of a storm	If immediate cause of extended ponding is not identified, schedule investigation of subsurface materials or other potential causes of system failure.
<b>Vegetation</b>				
Adjacent large shrubs or trees		As needed	Vegetation related fallout clogs or will potentially clog voids	<ul style="list-style-type: none"> <li>• Sweep leaf litter and sediment to prevent surface clogging and ponding</li> <li>• Prevent large root systems from damaging subsurface structural components</li> </ul>
		Once in May and Once in September	Vegetation growing beyond facility edge onto sidewalks, paths, and street edge	Edging and trimming of planted areas to control groundcovers and shrubs from overreaching the sidewalks, paths and street edge improves appearance and reduces clogging of permeable pavements by leaf litter, mulch and soil.
Leaves, needles, and organic debris		In fall (October to December) after leaf drop (1-3 times, depending on canopy cover)	Accumulation of organic debris and leaf litter	Use leaf blower or vacuum to blow or remove leaves, evergreen needles, and debris (i.e., flowers, blossoms) off of and away from permeable pavement

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.

# GUIDANCE DOCUMENT

## WESTERN WASHINGTON LOW IMPACT DEVELOPMENT (LID) OPERATION AND MAINTENANCE (O&M)

Prepared for  
Washington State Department of Ecology  
Water Quality Program

Prepared by  
Herrera Environmental Consultants, Inc.  
and  
Washington Stormwater Center



**Note:**

Some pages in this document have been purposely skipped or blank pages inserted so that this document will copy correctly when duplexed.



# GUIDANCE DOCUMENT

## WESTERN WASHINGTON LOW IMPACT DEVELOPMENT (LID) OPERATION AND MAINTENANCE (O&M)

Prepared for  
Washington State Department of Ecology  
Water Quality Program  
P.O. Box 47600  
Olympia, Washington 98504-7600

Prepared by  
Herrera Environmental Consultants, Inc.  
2200 Sixth Avenue, Suite 1100  
Seattle, Washington 98121  
Telephone: 206/441-9080

and  
Washington Stormwater Center  
2606 West Pioneer  
Puyallup, Washington 98371  
Telephone: 253/445-4505

July 8, 2013

This project has been funded wholly or in part by the United States Environmental Protection Agency under Puget Sound Ecosystem Restoration and Protection Cooperative Agreement Grant PC-00J20101 with Washington State Department of Ecology. The contents of this document do not necessarily reflect the views and policies of the Environmental Protection Agency, nor does mention of trade names or commercial products constitute endorsement or recommendation for use.

# CONTENTS

Acknowledgments .....	v
LID Maintenance Advisory Committee.....	v
LID Maintenance Administrative Issues Advisory Committee .....	v
Introduction .....	1
Purpose .....	1
Ecology Requirements for LID BMP Maintenance .....	1
Phase I Permit Special Conditions .....	2
Phase II Permit Special Conditions .....	3
Summary .....	4
How to Use this Guidance Document.....	5
Maintaining LID BMPs Section.....	5
Programmatic and Administrative Guidance Section .....	5
Definitions/Acronyms.....	6
Maintaining LID BMPs.....	9
All LID BMPs .....	11
Maintenance Standards and Procedures .....	11
Equipment and Materials.....	13
Skills .....	13
Bioretention Facilities.....	15
Key Maintenance Considerations.....	15
Key Operations to Preserve Facility Function.....	16
Maintenance Standards and Procedures .....	16
Additional Maintenance Resources .....	29
Equipment and Materials.....	30
Skills and Staffing .....	31
Rain Gardens.....	33
Key Maintenance Considerations.....	33
Key Operations to Preserve Facility Function.....	33
Maintenance Standards and Procedures .....	33
Additional Maintenance Resources .....	39
Equipment and Materials.....	39
Permeable Pavement .....	41
Key Maintenance Considerations.....	41
Key Operations to Preserve Facility Function.....	42
Maintenance Standards and Procedures .....	43
Equipment and Materials.....	53
Skills and Staffing .....	54
Vegetated Roofs.....	57
Key Maintenance Considerations.....	57

Key Operations to Preserve Facility Function.....	58
Maintenance Standards and Procedures .....	58
Additional Maintenance Resources .....	64
Equipment and Materials.....	65
Skills and Staffing .....	66
Downspout Full Infiltration Systems .....	67
Key Maintenance Considerations.....	67
Key Operations to Preserve Facility Function.....	67
Maintenance Standards and Procedures .....	68
Equipment and Materials.....	71
Skills .....	71
Downspout, Sheet Flow, and Concentrated Dispersion Systems .....	73
Key Maintenance Considerations.....	73
Key Operations to Preserve Facility Function.....	74
Maintenance Standards and Procedures .....	74
Equipment and Materials.....	79
Skills .....	79
Compost-amended Soils .....	81
Key Maintenance Considerations.....	81
Key Operations to Preserve Facility Function.....	81
Maintenance Standards and Procedures .....	81
Equipment and Materials.....	85
Skills .....	85
Programmatic and Administrative Guidance .....	87
Ecology Requirements for LID BMP Maintenance Programs .....	87
Tools for Implementing an LID Maintenance Program .....	93
Stormwater Code / Manual .....	99
Legal Agreements and Recordable Documents .....	100
Project-Specific BMP Maintenance Requirements .....	101
Financial Surety Measures .....	102
Record Keeping & Tracking Process .....	102
Inspection Programs .....	103
Mapping.....	104
Private Property Owner Education .....	105
References .....	107

- Appendix A Examples of Covenants
- Appendix B Examples of Private Property Owner Education

*(Note: The examples provided in the appendices were included as examples based on format only; the content of these examples has not been reviewed for consistency with the 2013-2018 Permit requirements or the material included in this guidance document.)*

# TABLES

Table 1.	Maintenance Standards and Procedures for All LID BMPs.....	12
Table 2.	Equipment and Materials List for All LID BMPs.....	13
Table 3.	Maintenance Standards and Procedures for Bioretention Facilities. ....	17
Table 4.	Bioretention Equipment and Materials List.....	30
Table 5.	Maintenance Frequency and Staffing for Bioretention Facilities.....	31
Table 6.	Maintenance Standards and Procedures for Rain Gardens. ....	34
Table 7.	Rain Garden Equipment and Materials List. ....	39
Table 8.	Maintenance Standards and Procedures for Permeable Pavement.....	45
Table 9.	Permeable Pavement Equipment and Materials List. ....	53
Table 10.	Maintenance Frequency and Staffing for Permeable Pavement.....	55
Table 11.	Maintenance Standards and Procedures for Vegetated Roofs. ....	59
Table 12.	Vegetated Roof Equipment and Materials List. ....	65
Table 13.	Maintenance Frequency and Staffing for Vegetated Roofs.....	66
Table 14.	Maintenance Standards and Procedures for Downspout Full Infiltration Systems. ....	69
Table 15.	Downspout Full Infiltration System Equipment and Materials List. ....	71
Table 16.	Maintenance Standards and Procedures for Downspout, Sheet Flow, and Concentrated Dispersion Systems.....	75
Table 17.	Downspout, Sheet Flow, and Concentrated Dispersion Systems Equipment and Materials List. ....	79
Table 18.	Maintenance Standards and Procedures for Compost-amended Soils.....	82
Table 19.	Compost Amended Soils Equipment and Materials List. ....	85
Table 20.	Phase I Permit Requirements and 2012 SWMMWW Guidance Related to LID BMP Maintenance Programs. ....	88
Table 21.	Phase II WWA Permit Requirements and 2012 SWMMWW Guidance Related to LID BMP Maintenance Programs. ....	90
Table 22.	Administrative Tools to Implement O&M Programs. ....	95

# ACKNOWLEDGMENTS

Staff from Herrera Environmental Consultants and the Washington Stormwater Center developed this guidance document with assistance from two advisory committees and staff from the Washington State Department of Ecology. The authors would like to thank the following people for their contributions:

## LID Maintenance Advisory Committee

<u>Name</u>	<u>Organization</u>
Don McQuilliams	City of Bellevue
Bill Reilly	City of Bellingham
Steve Wise	City of Olympia
Drena Donofrio	City of Seattle
David McDonald	City of Seattle
Merita Trohimovich	City of Tacoma
Mark Wilgus	King County
Chris May	Kitsap County
Dawn Anderson	Pierce County
Pat Allen	Thurston County
Denis O'Brien	Portland BES
Andy Marks	Puget Sound Concrete Specification Council
Kathy Gwilym	SvR

## LID Maintenance Administrative Issues Advisory Committee

<u>Name</u>	<u>Organization</u>
Mark Dewey	City of Bellevue
Greg Vigoren	City of Lakewood
Joe Roush	City of Olympia
Michelle Macias	City of Seattle
Theresa Wagner	City of Seattle
Merita Trohimovich	City of Tacoma
Doug Frick	Kitsap County

The authors would also like to thank Josh Johnson from the City of Longview, Marcus Goodman from the City of Olympia, and Craig Chatburn from the City of Seattle for peer review support.

# INTRODUCTION

## Purpose

As local governments in western Washington implement the Washington State Department of Ecology (Ecology) National Pollutant Discharge Elimination System (NPDES) Municipal Stormwater permits (Permits), our region will increasingly rely on low impact development (LID) practices to protect water quality and aquatic natural resources. LID is a stormwater and land use management strategy that strives to mimic the pre-disturbance hydrologic processes of infiltration, filtration, storage, evaporation and transpiration by emphasizing conservation, use of on-site natural features, site planning, and distributed stormwater management practices that are integrated into a project design. LID best management practices (BMPs), such as bioretention and permeable pavements, are also commonly known as green stormwater infrastructure, integrated management practices, and on-site stormwater management BMPs.

This guidance provides recommendations on LID operations and maintenance (O&M) to help ensure that LID BMPs continue to function as designed in the long-term and is intended to support municipal stormwater Permittees in implementing their LID maintenance programs. While intended for a municipal audience, some guidance in this document may also be useful for private entities. Ecology encourages local governments to draw on this document to educate developers, homeowners' associations, and private property owners who are responsible for the O&M of LID BMPs.

## Ecology Requirements for LID BMP Maintenance

The Phase I and Western Washington Phase II Municipal Stormwater Permits (Phase I Permit and Phase II Permit, or "Permits"), effective from August 2013 to July 2018, include provisions for municipalities to adopt and implement O&M programs and to facilitate proper O&M of LID BMPs. The Permit maintenance-related requirements for "On-site Stormwater Management BMPs" differ depending on if they are classified as "Stormwater Treatment and Flow Control BMPs/Facilities<sup>1</sup>". The side bars below highlight the distinctions made for Stormwater Treatment and Flow Control BMPs/Facilities. In general, the O&M Permit requirements for Stormwater Treatment and Flow Control BMPs/Facilities are more extensive and include, for example, long-term inspection and maintenance obligations that do not apply to other LID BMPs. The Phase I and Phase II Permits provisions that apply to LID BMPs are summarized in the following sections.

---

<sup>1</sup> This document does not include guidance for traditional end of pipe treatment and detention facilities; though these facilities are included in the definition of "Stormwater Treatment and Flow Control BMPs/Facilities".

## Phase I Permit Special Conditions

The Phase I Permit<sup>2</sup> (Ecology 2012a) special conditions that pertain to LID BMP maintenance are listed below:

- **S5.C.5.a.v.(4)** - Requires municipalities to inspect all permitted development sites, that meet certain thresholds, upon completion of construction and prior to final approval or occupancy to ensure proper installation of permanent storm water facilities. It also requires identification of a party responsible for maintenance, and verification of a maintenance plan for all Stormwater Treatment and Flow Control BMPs/Facilities.
- **S5.C.9.a.** - Requires adoption of maintenance standards that are at least as protective of facility function as those in Chapter 4 of Volume V of the 2012 Stormwater Management Manual for Western Washington (2012 SWMMWW).
- **S5.C.9.b.i.** - Requires adoption of an ordinance or other enforceable mechanism requiring maintenance of all permanent Stormwater Treatment and Flow Control BMPs/Facilities regulated by the Permittee.
- **S5.C.9.b.ii.** - Requires annual inspections of all Stormwater Treatment and Flow Control BMPs/Facilities regulated by the Permittee. Permittees must enforce compliance with the adopted maintenance standards as needed based on inspection.

### *“On-site Stormwater Management BMPs”*

“On-site Stormwater Management BMPs” (also known as LID BMPs) used to meet Permit Minimum Requirement #5 (On-site Stormwater Management) include:

- Rain Gardens (BMP T5.14A)
- Bioretention (BMP T5.14B)
- Permeable Pavement (BMP T5.15)
- Vegetated Roofs (BMP T5.17)
- Downspout Full Infiltration (BMP T5.10B)
- Downspout Dispersion (BMP T5.10A)
- Concentrated Flow Dispersion (BMP T5.11)
- Sheet Flow Dispersion (BMP T5.12)
- Compost-amended soils (BMP T5.13)

Permit requirements for On-site Stormwater Management BMPs that are not also Stormwater Treatment and Flow Control BMPs/Facilities are less extensive and include, for example, construction inspections to ensure proper installation.

### *“Stormwater treatment and flow control BMPs/facilities”*

The LID BMPs listed below are considered to be “Stormwater Treatment and Flow Control BMPs/Facilities” if they are used to help meet Minimum Requirements #6 (Treatment) and/or #7 (Flow Control):

- Bioretention (BMP T5.14B)
- Permeable Pavement (BMP T5.15)
- Vegetated Roofs (BMP T5.17)

Permit requirements for Stormwater Treatment and Flow Control BMPs/Facilities are more extensive and include, for example, long-term inspection and maintenance obligations.

---

<sup>2</sup> The special conditions listed in this document are for city and county permittees. Secondary permittees should refer Section S6 of the permit for their special conditions that pertain to LID BMP maintenance.



- **S5.C.9.b.iii.** - Requires inspection of all permanent Stormwater Treatment and Flow Control BMPs/Facilities and catch basins regulated by the Permittee every 6 months during construction of residential developments until 90 percent of the lots are constructed (or when construction is stopped and the site is fully stabilized). Permittees must identify maintenance needs and enforce compliance with maintenance standards as needed.
- **S5.C.9.c.i.** - Requires annual inspection of all permanent Stormwater Treatment and Flow Control BMPs/Facilities owned or operated by the Permittee. Permittees are to implement appropriate maintenance action(s) in accordance with adopted maintenance standards.
- **S5.C.9.c.ii.** - Requires spot checks of potentially damaged permanent Stormwater Treatment and Flow Control BMPs/Facilities after major storm events. If spot checks indicate widespread damage/maintenance needs, inspect all Stormwater Treatment and Flow Control BMPs/Facilities that may be affected. Conduct repairs or perform maintenance in accordance with the standards established under S5.C.9.a.

### *Phase II Permit Special Conditions*

The Phase II Permit<sup>3</sup> (Ecology 2012b) special conditions that pertain to LID BMP maintenance are listed below:

- **S5.C.4.b.iv.** - Requires municipalities to inspect all permitted development sites upon completion of construction and prior to final approval or occupancy to ensure proper installation of permanent stormwater facilities. Municipalities must require identification of a party responsible for maintenance, and a maintenance plan for all Stormwater Treatment and Flow Control BMPs/Facilities.
- **S5.C.4.c.** - Requires a program to verify adequate operation and maintenance of Stormwater Treatment and Flow Control BMPs/Facilities that have been and will be approved and built under local code requirements adopted to comply with the 2007, 2012, and 2013 NPDES municipal stormwater Permits. The program must include:
  - i) Implementation of an ordinance or other enforceable mechanism that requires identification of a party responsible for maintenance, and requires inspections of facilities in accordance with ii) through iv) below.
  - ii) Requires establishment of maintenance standards that are at least as protective of facility function as those in Chapter 4 of Volume V of the 2012 SWMMWW.
  - iii) Requires annual inspection of all Stormwater Treatment and Flow Control BMPs/Facilities that discharge to the MS4 and were permitted according to S5.C.4.b. including those permitted pursuant to the 2007 - 2012 Permit.

---

<sup>3</sup> The special conditions listed in this document are for city and county permittees. Secondary permittees should refer Section S6 of the permit for their special conditions that pertain to LID BMP maintenance.

- iv) Requires inspections of permanent Stormwater Treatment and Flow Control BMPs/Facilities and catch basins every 6 months during construction of residential developments until 90 percent of the lots are constructed (or when construction is stopped and the site is fully stabilized).
- **S5.C.5.a.** - Requires implementation of maintenance standards that are at least as protective of facility function as those in Chapter 4 of Volume V of the 2012 SWMMWW.
- **S5.C.5.b.** - Requires annual inspections of all municipally owned or operated permanent Stormwater Treatment and Flow Control BMPs/Facilities, and taking appropriate maintenance actions in accordance with the adopted maintenance standards.
- **S5.C.5.c.** - Requires spot checks of potentially damaged permanent Stormwater Treatment and Flow Control BMPs/Facilities after major storm events. If spot checks indicate widespread damage/maintenance needs, inspect all “storm water treatment and flow control BMPs” that may be affected. Conduct repairs or perform maintenance in accordance with the standards established under S5.C.5.a.

## *Summary*

Both Phase I and Phase II municipal Permittees bear long-term inspection and enforcement responsibilities to require proper maintenance of Stormwater Treatment and Flow Control BMPs/Facilities. Although the On-site Stormwater Management BMPs that are not Stormwater Treatment and Flow Control BMPs/Facilities do not require long-term inspections, municipalities are obligated to inspect these BMPs upon completion of construction to ensure proper installation.

The Permits also require Permittees to adopt site planning requirements (Western Washington Phase II Permit - S5.C.4.a.ii; Western Washington Phase I Permit - S5.C.5.a.ii). They can choose to use the site planning requirements in the 2012 SWMMWW, or they can adopt requirements that protect water quality, reduce the discharge of pollutants to the maximum extent practicable (MEP), and satisfy the “all known, available and reasonable” provisions of State statute (Chapter 90.48 RCW). The 2012 SWMMWW site planning guidance includes information on the production, submission and recording of legal documents that provide both design information and maintenance instructions for each On-site Stormwater Management BMP, and help allow local government access to these BMPs.

Ecology encourages local governments to use the guidance in this document to meet their Permit obligation to adopt maintenance standards for LID BMPs. Additionally, they can use the guidance to gain an understanding of the procedures, equipment, materials, legal documents and staffing they will need to meet their inspection and maintenance responsibilities.

## How to Use this Guidance Document

This guidance document is organized into two sections. The first section, “Maintaining LID BMPs,” provides detailed maintenance guidance for LID BMPs, recommendations for equipment and materials, and information on what types of skills and staffing may be needed. The second section, “Programmatic and Administrative Guidance,” includes guidance to support jurisdictions in administering their LID maintenance programs.

### *Maintaining LID BMPs Section*

The “Maintaining LID BMPs” section is intended to be used by municipal maintenance staff and private parties who are responsible for LID BMP O&M. The tables and guidance in this document may be used:

- To create O&M manuals for Stormwater Treatment and Flow Control BMPs/Facilities
- As maintenance instructions that can be submitted as part of the stormwater site plan for LID BMPs that are not Stormwater Treatment and Flow Control BMPs/Facilities
- As a reference to help homeowners maintain on-site LID BMPs

The guidance provides support by:

- Explaining how LID BMPs function (e.g., how water moves through the facility and the importance of key facility components) to provide a framework for the maintenance standards and procedures, and support smart maintenance decisions in the field
- Providing clear guidance on LID BMP maintenance frequencies, standards and procedures in an easy-to-use table. These tables can easily be reformatted as maintenance checklists.
- Providing a comprehensive equipment and materials list for each BMP
- Providing information on staff skills needed for O&M
- Providing information on the level of effort required to maintain bioretention, permeable pavement, and vegetated roofs

The maintenance standards and procedures presented in this guidance should be used by municipalities for the long-term inspection and maintenance of Stormwater Treatment and Flow Control BMPs/Facilities. While not required, long-term observation of all on-site systems by municipal inspectors is recommended, particularly when the property is subject to inspection for Stormwater Treatment and Flow Control BMPs/Facilities.

### *Programmatic and Administrative Guidance Section*

The Programmatic and Administrative Guidance section is intended to be used by municipal staff responsible for developing and implementing LID BMP maintenance programs. The guidance provides support by:

- Presenting Ecology’s requirements that relate to LID BMP maintenance programs, such as systems for permitting, plan review, inspections, enforcement and record keeping
- Providing guidance regarding administrative tools for implementing these requirements, such as municipal stormwater codes, stormwater manuals, legal agreements, financial surety measures, inspection programs, and mapping systems
- Providing examples of administrative tools, including covenants and easements, and private property owner education

## Definitions/Acronyms

- **Applicant:** Individuals, associations, organizations, partnerships, firms, corporations, developers, or other entities applying for a development proposal, permit, or approval.
- **Bond:** A surety bond, cash deposit or escrow account, assignment of savings, irrevocable letter of credit or other means acceptable to or required by the manager to guarantee that work is completed in compliance with the project’s drainage plan and in compliance with all local government requirements. Bonds can also be used to protect and guarantee the performance of a stormwater BMP after construction.
- **Codes:** Collections of laws and regulations which have been codified based on the activities they regulate. These laws are ordinances that are enforced locally in addition to state and federal law. City or county stormwater codes may include laws regulating the requirements for maintenance of private stormwater facilities, the right of the jurisdiction to intervene in maintenance or repair of the facility, or any documents or contracts required for the construction of a stormwater facility.
- **Covenants:** Binding legal documents in which a person (commonly a property owner) promises the local government to either engage in or refrain from a certain action. A jurisdiction’s code, at the jurisdiction’s option, may require a covenant or easement agreement for the construction of a stormwater facility. The agreement may require the facility owner to perform certain maintenance activities and grants the jurisdiction limited authority to access the site (through an easement or agreement) for facility inspection, maintenance, or repair work.
- **Developer:** A person who purchases and develops property, primarily by preparing a site for residential or commercial use.
- **Director:** Typically the Public Works Director, Planning and Development Services Director, or Natural Resources and Parks Director (depending on the organization of the City or County and what department the stormwater program is included in) or an appointed representative or designee with an appropriate background.
- **Green stormwater infrastructure:** A synonym for Low Impact Development BMPs (see definition below).

- **Integrated management practices:** Used in the LID Technical Guidance Manual for Puget Sound as a synonym for Low Impact Development BMPs (see definition below).
- **Low impact development (LID):** A stormwater and land use management strategy that strives to mimic pre-disturbance hydrologic processes of infiltration, filtration, storage, evaporation and transpiration by emphasizing conservation, use of on-site natural features, site planning, and distributed stormwater management practices that are integrated into a project design.
- **LID best management practices (BMPs):** Distributed stormwater management practices, integrated into a project design, that emphasize pre-disturbance hydrologic processes of infiltration, filtration, storage, evaporation and transpiration. LID BMPs include, but are not limited to, bioretention/rain gardens, permeable pavements, roof downspout controls, dispersion, soil quality and depth, vegetated roofs, minimum excavation foundations, and water re-use.
- **On-site Stormwater Management BMPs:** A synonym for Low Impact Development BMPs.
- **Pollution-generating surfaces:** Any hard or impervious surface considered to be a significant source of pollutants in stormwater runoff, or any pervious surface that is subject to rainfall and vehicular use, industrial activities, storage of erodible or leachable materials, wastes, or chemicals, or use of pesticides or fertilizers, or loss of soil.
- **Property owner:** The person who is the legal record owner of the parcel.
- **Responsible party:** The parties (e.g., property owners, homeowners' associations, corporations, public agencies) responsible for maintaining stormwater features at a site and/or in a public right-of-way.
- **Stormwater Treatment and Flow Control BMPs:** Detention facilities, treatment BMPs/facilities, bioretention, vegetated roofs, and permeable pavements that help meet Appendix 1 Minimum Requirements #6 (treatment), #7 (flow control), or both.
- **Surety:** A surety is a bond or other security signed by the contractor and a surety company that assures the project owner or municipality the contract will be completed. A surety can include bonds or assignment of accounts (also called assignment of savings).



# MAINTAINING LID BMPs

This section is organized by BMP type and includes guidance for the following LID BMPs:

- Bioretention facilities
- Rain gardens
- Permeable pavement
- Vegetated roofs
- Downspout full infiltration systems
- Downspout, sheet flow, and concentrated dispersion systems
- Compost-amended soils

Each BMP section includes the following information:

- **BMP Description:** brief description of the BMP and how the facility functions (i.e., how water moves through the facility).
- **Key Maintenance Considerations:** summary of key facility maintenance considerations for each main BMP components, such as inlets, aggregate, soil, vegetation.
- **Key Operations to Preserve Facility Function:** operational considerations that may reduce routine maintenance needs and prevent the need for corrective maintenance.
- **Maintenance Standards and Procedures:** a table providing detailed guidance for regular maintenance (e.g., bioretention vegetation care) and some guidance for corrective maintenance (e.g., bioretention soil replacement). The table lists the recommended inspection frequency, conditions when maintenance is needed (maintenance “standards”) and the associated maintenance actions triggered by those conditions (maintenance “procedures”).
- **Equipment and Material List:** a sample list of equipment and materials that field crews can take into the field.
- **Skills and Staffing:** a list of the skills needed for routine and corrective maintenance, and summary of the staffing resources recommended for BMP maintenance based on input from local jurisdictions and other nationally-recognized LID programs (for the Stormwater Treatment and Flow Control BMPs/Facilities only).

This section’s detailed maintenance guidance can be pared down to meet project-specific needs. For example, tables can be tailored to show only site-specific BMPs and their subcomponents (e.g., underdrains). Additionally, the routine maintenance frequencies should

be tailored to minimize a site’s need for corrective maintenance (e.g., specify more frequent sweeping of permeable pavement located under deciduous tree canopies).

Jurisdictions may also want to consider tailoring the tables to address “level of service” (i.e., the BMP conditions that trigger maintenance procedures). As an example, the City of Seattle maintains public facilities to levels of service “A” through “D”, with level A being the highest degree of maintenance. Lower levels of service require only maintenance activities that preserve facility function (not aesthetics). While this guidance document includes recommended quantitative thresholds for some BMP maintenance actions (e.g., supplemental planting is triggered when bioretention vegetative coverage falls below 75 percent), jurisdictions may wish to develop their own maintenance triggers and/or establish ranges of triggers based on higher levels of service. Such decisions will affect the maintenance resources required to maintain public projects.

The maintenance standards provided in this section are not intended to be a measure of the facility’s required condition at all times between inspections. However, the inspection and maintenance schedules should be adjusted to minimize the length of time that a facility is in a condition that requires a maintenance action.



## All LID BMPs

The maintenance recommendations included in this section are applicable to all LID BMPs.

### *Maintenance Standards and Procedures*

Table 1 provides the recommended maintenance frequencies, standards, and procedures for spill prevention, spill response, and pest management actions common to all LID BMP facilities included in this guidance document.

**Table 1. Maintenance Standards and Procedures for All LID BMPs.**

Category	Recommended Frequency		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>General</b>				
Facility presence	All visits		None (ongoing inspections)	Inspect to ensure the facility is present on site as shown on the as-built (or record drawings) and previous photos.
<b>Spill Prevention and Response</b>				
Spill prevention	Ongoing		None (ongoing inspections)	All sites must implement BMPs to prevent hazardous or solid wastes or excessive oil and sediment from contaminating stormwater.
Spill cleanup	As needed		Release of pollutants	<ul style="list-style-type: none"> <li>• Call your local or regional hotline number to report any spills or other illicit discharges</li> <li>• Clean up spills as soon as possible to prevent contamination of stormwater</li> <li>• Restore BMP facility design and function per the record drawings</li> </ul>
<b>Pests</b>				
Pest management	As needed		Pest of concern is present and impacting BMP facility function	<ul style="list-style-type: none"> <li>• Pesticide use should be generally discouraged, even conditionally prohibited in some cases</li> <li>• Pesticides include the following: herbicides, fungicides, insecticides, rodenticides, and pediculicides</li> <li>• If pesticide use is planned in or near LID BMPs, make sure to check the following current regulations:               <ol style="list-style-type: none"> <li>1) Federal- Environmental Protection Agency (EPA) Federal Insecticide and Rodenticide Act</li> <li>2) State- Ecology, Washington State Department of Agriculture, Washington Department of Fish and Wildlife, Natural Resources Conservation Services</li> <li>3) Local city or county ordinances/codes, and/or applicable Integrated Pest Management (IPM) plan</li> </ol> </li> <li>• For the protection of health and safety, check the following:               <ol style="list-style-type: none"> <li>1) Washington State Department of Labor &amp; Industries</li> <li>2) Washington State Department of Health (local branch if applicable)</li> </ol> </li> </ul>

## Equipment and Materials

Table 2 includes recommendations for equipment and materials common to all LID BMPs included in this guidance document.

Table 2. Equipment and Materials List for All LID BMPs.
<input type="checkbox"/> Camera
<input type="checkbox"/> Safety gear/equipment (including boots, long sleeves and pants, gloves, eye and ear protection, and/or high visibility safety vest)
<input type="checkbox"/> Shovel (to check depth and condition of soils)
<input type="checkbox"/> Measuring tape
<input type="checkbox"/> Photos, reports, and/or checklists from past maintenance visits (to help identify changes such as thinning plants and changing pavement conditions)
<input type="checkbox"/> Copy of the site's O&M manual or maintenance plan
<input type="checkbox"/> O&M checklist
<input type="checkbox"/> As-built (i.e., record) drawings of the facility, including site drawings with facility location(s)
<input type="checkbox"/> Manufacturer information (if applicable)

## Skills

The required skills common to maintenance of all LID BMPs are listed in the text box to the right.

### *Skills Needed for Maintenance of all LID BMPs*

- Understanding of as-built (or record) drawings of the facility
- Understanding of facility design and intent (to identify issues that would inhibit function)
- General labor (manual tool skills)



## Bioretention Facilities

Bioretention facilities are engineered facilities that store and treat stormwater by filtering it through a specified soil profile. Water that enters the facility ponds in an earthen depression or other basin (e.g., concrete planter) before it infiltrates into the underlying bioretention soil. Stormwater that exceeds the surface storage capacity overflows to an adjacent drainage system. Treated water is either infiltrated into the underlying native soil or collected by an underdrain and discharged. Bioretention facilities are considered Stormwater Treatment and Flow Control BMPs/Facilities when used to help meet Minimum Requirements #6 (treatment), #7 (flow control), or both.

### *Key Maintenance Considerations*

The main components of bioretention facilities are listed below with descriptions of their function and key maintenance considerations.

- **Inlet:** Stormwater can flow into a bioretention facility in a number of ways including: dispersed flow across vegetated areas, sheet flow across impervious areas, or concentrated flow through curb cuts and/or piped flow inlets. Inlets must be maintained to be unobstructed to ensure that stormwater enters the facility as designed. Erosion control measures must also be maintained in areas of concentrated flows (e.g., pipes inlets or narrow curb cuts).
- **Facility footprint:** The facility footprint is typically an earthen depression or another type of basin (e.g., concrete planter box) that provides surface storage for stormwater before it infiltrates into the underlying bioretention soil. If the facility is located on a slope, low permeability check dams may be included (oriented perpendicular to the slope) to encourage ponding. Key maintenance considerations for the facility footprint include the following:
  - The integrity of earthen berms and basin walls must be maintained, soil areas must be protected from erosion, and accumulated sediment must be removed.
  - Bioretention facilities are designed to infiltrate all ponded water within a 24- to 48-hour “drawdown” time after the end of a storm. This allows the soil to dry out periodically in order to restore the hydraulic capacity of the system and prevent conditions supportive of mosquito breeding. Slower drawdown times may indicate that the underdrain (if present) is plugged or the bioretention soil is overly compacted, clogged, or does not meet design specifications. Corrective maintenance may include clearing underdrain obstructions or partial or complete replacement of bioretention soil to restore bioretention facility function.
- **Bioretention soil:** Infiltration of stormwater through the engineered bioretention soil mix provides water quality treatment. All maintenance activities must be performed in a manner to prevent compaction of the bioretention soil.
- **Mulch:** The bioretention soil is covered by a layer of mulch, comprised of arborist wood chips, compost, and/or rocks. Mulch reduces weed establishment. Organic

mulches regulate soil temperatures and moisture, and add organic matter to soil. The mulch layer must be supplemented regularly.

- **Vegetation:** Bioretention systems rely on vegetation (i.e., grasses, shrubs, and sometimes trees) to intercept, uptake, and evapotranspire stormwater. In addition, plant roots improve soil structure and increase infiltration capacity. Regular maintenance activities associated with vegetation include weeding and pruning. Plants also require irrigation during the first 2 to 3 years of establishment and during extended dry periods.
- **Overflow:** Flows exceeding the capacity of the facility are discharged via an overflow structure (e.g., pipe, curb cut, earthen channel). It is important to maintain clear outlet pipes and overflow structures to ensure that stormwater can be safely conveyed to a designated discharge point (e.g., storm drain system).
- **Underdrains (optional):** Underdrains are optional components of a bioretention facility that may be included in bioretention systems where, for example, infiltration to underlying soil is not prudent or feasible. Underdrains are installed under the bioretention soil layer to collect and convey treated water. An underdrain system can be comprised of perforated or slotted pipe, wrapped in an aggregate blanket. It is important to maintain clear drains so that water moves through system as designed. Maintenance may include occasional cleaning to remove plant roots or debris. If underdrains are equipped with a flow restrictor (e.g., orifice) to attenuate flows, the orifice must be inspected and cleaned regularly.

Nutrient sensitivity of the receiving water is also an important maintenance consideration, particularly in watersheds draining to phosphorous limited water bodies. The addition of excess fertilizers to the system and/or systems operating in bypass, can increase the potential for export of phosphorous found in bioretention soil or compost and increase nutrient loads to downstream receiving waters.

### *Key Operations to Preserve Facility Function*

For a bioretention system to function properly, stormwater must infiltrate freely through the bioretention soil. The soil infiltration rate can be reduced if the soil is subject to compaction (e.g., foot and vehicle traffic loads). To limit the likelihood of corrective maintenance (e.g., bioretention soil replacement), the facility footprint area should be protected from external loads. Because the risk of compaction is higher when soils are saturated, any type of loading in the bioretention facility (including foot traffic) should be avoided during wet conditions.

Signage can also be used to identify the vegetated area as a stormwater BMP and inform maintenance crews and the general public about protecting the facility's function.

### *Maintenance Standards and Procedures*

Table 3 provides the recommended maintenance frequencies, standards, and procedures for bioretention facility components. The level of routine maintenance required and the frequency of corrective maintenance actions may increase for facilities subject to high sediment loads from the contributing drainage area.

**Table 3. Maintenance Standards and Procedures for Bioretention Facilities.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Facility Footprint</b>				
Earthen side slopes and berms	B, S		Erosion (gullies/ rills) greater than 2 inches deep around inlets, outlet, and alongside slopes	<ul style="list-style-type: none"> <li>Eliminate cause of erosion and stabilize damaged area (regrade, rock, vegetation, erosion control matting)</li> <li>For deep channels or cuts (over 3 inches in ponding depth), temporary erosion control measures should be put in place until permanent repairs can be made.</li> <li>Properly designed, constructed and established facilities with appropriate flow velocities should not have erosion problems except perhaps in extreme events. If erosion problems persist, the following should be reassessed: (1) flow volumes from contributing areas and bioretention facility sizing; (2) flow velocities and gradients within the facility; and (3) flow dissipation and erosion protection strategies at the facility inlet.</li> </ul>
	A		Erosion of sides causes slope to become a hazard	Take actions to eliminate the hazard and stabilize slopes
	A, S		Settlement greater than 3 inches (relative to undisturbed sections of berm)	Restore to design height
	A, S		Downstream face of berm wet, seeps or leaks evident	Plug any holes and compact berm (may require consultation with engineer, particularly for larger berms)
	A		Any evidence of rodent holes or water piping in berm	<ul style="list-style-type: none"> <li>Eradicate rodents (see "Pest control")</li> <li>Fill holes and compact (may require consultation with engineer, particularly for larger berms)</li> </ul>
Concrete sidewalls	A		Cracks or failure of concrete sidewalls	<ul style="list-style-type: none"> <li>Repair/ seal cracks</li> <li>Replace if repair is insufficient</li> </ul>
Rockery sidewalls	A		Rockery side walls are insecure	Stabilize rockery sidewalls (may require consultation with engineer, particularly for walls 4 feet or greater in height)
Facility area		All maintenance visits (at least biannually)	Trash and debris present	Clean out trash and debris
Facility bottom area	A, S		Accumulated sediment to extent that infiltration rate is reduced (see "Ponded water") or surface storage capacity significantly impacted	<ul style="list-style-type: none"> <li>Remove excess sediment</li> <li>Replace any vegetation damaged or destroyed by sediment accumulation and removal</li> <li>Mulch newly planted vegetation</li> <li>Identify and control the sediment source (if feasible)</li> <li>If accumulated sediment is recurrent, consider adding presettlement or installing berms to create a forebay at the inlet</li> </ul>
		During/after fall leaf drop	Accumulated leaves in facility	Remove leaves if there is a risk to clogging outlet structure or water flow is impeded
Low permeability check dams and weirs	A, S		Sediment, vegetation, or debris accumulated at or blocking (or having the potential to block) check dam, flow control weir or orifice	Clear the blockage
	A, S		Erosion and/or undercutting present	Repair and take preventative measures to prevent future erosion and/or undercutting
	A		Grade board or top of weir damaged or not level	Restore to level position

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least one visit should occur during the wet season (for debris/clog related maintenance, this inspection/maintenance visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

IPM - Integrated Pest Management

ISA - International Society of Arboriculture





**Table 3 (continued). Maintenance Standards and Procedures for Bioretention Facilities.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Facility Footprint (cont'd)</b>				
Ponded water	B, S		Excessive ponding water: Water overflows during storms smaller than the design event or ponded water remains in the basin 48 hours or longer after the end of a storm.	<p>Determine cause and resolve in the following order:</p> <ol style="list-style-type: none"> <li>1) Confirm leaf or debris buildup in the bottom of the facility is not impeding infiltration. If necessary, remove leaf litter/debris.</li> <li>2) Ensure that underdrain (if present) is not clogged. If necessary, clear underdrain.</li> <li>3) Check for other water inputs (e.g., groundwater, illicit connections).</li> <li>4) Verify that the facility is sized appropriately for the contributing area. Confirm that the contributing area has not increased.</li> </ol> <p>If steps #1-4 do not solve the problem, the bioretention soil is likely clogged by sediment accumulation at the surface or has become overly compacted. Dig a small hole to observe soil profile and identify compaction depth or clogging front to help determine the soil depth to be removed or otherwise rehabilitated (e.g., tilled). Consultation with an engineer is recommended.</p>
Bioretention soil media	As needed		Bioretention soil media protection is needed when performing maintenance requiring entrance into the facility footprint	<ul style="list-style-type: none"> <li>• Minimize all loading in the facility footprint (foot traffic and other loads) to the degree feasible in order to prevent compaction of bioretention soils.</li> <li>• Never drive equipment or apply heavy loads in facility footprint.</li> <li>• Because the risk of compaction is higher during saturated soil conditions, any type of loading in the cell (including foot traffic) should be minimized during wet conditions.</li> <li>• Consider measures to distribute loading if heavy foot traffic is required or equipment must be placed in facility. As an example, boards may be placed across soil to distribute loads and minimize compaction.</li> <li>• If compaction occurs, soil must be loosened or otherwise rehabilitated to original design state.</li> </ul>
<b>Inlets/Outlets/Pipes</b>				
Splash block inlet	A		Water is not being directed properly to the facility and away from the inlet structure	Reconfigure/ repair blocks to direct water to facility and away from structure
Curb cut inlet/outlet	M during the wet season and before severe storm is forecasted	Weekly during fall leaf drop	Accumulated leaves at curb cuts	Clear leaves (particularly important for key inlets and low points along long, linear facilities)
Pipe inlet/outlet	A		Pipe is damaged	Repair/ replace
	W		Pipe is clogged	Remove roots or debris
	A, S		Sediment, debris, trash, or mulch reducing capacity of inlet/outlet	<ul style="list-style-type: none"> <li>• Clear the blockage</li> <li>• Identify the source of the blockage and take actions to prevent future blockages</li> </ul>
		Weekly during fall leaf drop	Accumulated leaves at inlets/outlets	Clear leaves (particularly important for key inlets and low points along long, linear facilities)
		A	Maintain access for inspections	<ul style="list-style-type: none"> <li>• Clear vegetation (transplant vegetation when possible) within 1 foot of inlets and outlets, maintain access pathways</li> <li>• Consultation with a landscape architect is recommended for removal, transplant, or substitution of plants</li> </ul>
Erosion control at inlet	A		Concentrated flows are causing erosion	Maintain a cover of rock or cobbles or other erosion protection measure (e.g., matting) to protect the ground where concentrated water enters the facility (e.g., a pipe, curb cut or swale)

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least one visit should occur during the wet season (for debris/clog related maintenance, this inspection/maintenance visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

IPM - Integrated Pest Management  
ISA - International Society of Arboriculture



**Table 3 (continued). Maintenance Standards and Procedures for Bioretention Facilities.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Inlets/Outlets/Pipes (cont'd)</b>				
Trash rack	S		Trash or other debris present on trash rack	Remove/dispose
	A		Bar screen damaged or missing	Repair/replace
Overflow	A, S		Capacity reduced by sediment or debris	Remove sediment or debris/dispose
Underdrain pipe	Clean pipe as needed	Clean orifice at least biannually (may need more frequent cleaning during wet season)	<ul style="list-style-type: none"> <li>Plant roots, sediment or debris reducing capacity of underdrain</li> <li>Prolonged surface ponding (see "Ponded water")</li> </ul>	<ul style="list-style-type: none"> <li>Jet clean or rotary cut debris/roots from underdrain(s)</li> <li>If underdrains are equipped with a flow restrictor (e.g., orifice) to attenuate flows, the orifice must be cleaned regularly.</li> </ul>
<b>Vegetation</b>				
Facility bottom area and upland slope vegetation	Fall and Spring		Vegetation survival rate falls below 75% within first two years of establishment (unless project O&M manual or record drawing stipulates more or less than 75% survival rate).	<ul style="list-style-type: none"> <li>Determine cause of poor vegetation growth and correct condition</li> <li>Replant as necessary to obtain 75% survival rate or greater. Refer to original planting plan, or approved jurisdictional species list for appropriate plant replacements (See Appendix 3 - Bioretention Plant List, in the LID Technical Guidance Manual for Puget Sound).</li> <li>Confirm that plant selection is appropriate for site growing conditions</li> <li>Consultation with a landscape architect is recommended for removal, transplant, or substitution of plants</li> </ul>
Vegetation (general)	As needed		Presence of diseased plants and plant material	<ul style="list-style-type: none"> <li>Remove any diseased plants or plant parts and dispose of in an approved location (e.g., commercial landfill) to avoid risk of spreading the disease to other plants</li> <li>Disinfect gardening tools after pruning to prevent the spread of disease</li> <li>See Pacific Northwest Plant Disease Management Handbook for information on disease recognition and for additional resources</li> <li>Replant as necessary according to recommendations provided for "facility bottom area and upland slope vegetation".</li> </ul>
Trees and shrubs		All pruning seasons (timing varies by species)	Pruning as needed	<ul style="list-style-type: none"> <li>Prune trees and shrubs in a manner appropriate for each species. Pruning should be performed by landscape professionals familiar with proper pruning techniques</li> <li>All pruning of mature trees should be performed by or under the direct guidance of an ISA certified arborist</li> </ul>
	A		Large trees and shrubs interfere with operation of the facility or access for maintenance	<ul style="list-style-type: none"> <li>Prune trees and shrubs using most current ANSI A300 standards and ISA BMPs.</li> <li>Remove trees and shrubs, if necessary.</li> </ul>
	Fall and Spring		Standing dead vegetation is present	<ul style="list-style-type: none"> <li>Remove standing dead vegetation</li> <li>Replace dead vegetation within 30 days of reported dead and dying plants (as practical depending on weather/planting season)</li> <li>If vegetation replacement is not feasible within 30 days, and absence of vegetation may result in erosion problems, temporary erosion control measures should be put in place immediately.</li> <li>Determine cause of dead vegetation and address issue, if possible</li> <li>If specific plants have a high mortality rate, assess the cause and replace with appropriate species. Consultation with a landscape architect is recommended.</li> </ul>
	Fall and Spring		Planting beneath mature trees	<ul style="list-style-type: none"> <li>When working around and below mature trees, follow the most current ANSI A300 standards and ISA BMPs to the extent practicable (e.g., take care to minimize any damage to tree roots and avoid compaction of soil).</li> <li>Planting of small shrubs or groundcovers beneath mature trees may be desirable in some cases; such plantings should use mainly plants that come as bulbs, bare root or in 4-inch pots; plants should be in no larger than 1-gallon containers.</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least one visit should occur during the wet season (for debris/clog related maintenance, this inspection/maintenance visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

IPM - Integrated Pest Management  
 ISA - International Society of Arboriculture

July 2013



**Table 3 (continued). Maintenance Standards and Procedures for Bioretention Facilities.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Vegetation (cont'd)</b>				
Trees and shrubs (cont'd)	Fall and Spring		Planting beneath mature trees	<ul style="list-style-type: none"> <li>When working around and below mature trees, follow the most current ANSI A300 standards and ISA BMPs to the extent practicable (e.g., take care to minimize any damage to tree roots and avoid compaction of soil).</li> <li>Planting of small shrubs or groundcovers beneath mature trees may be desirable in some cases; such plantings should use mainly plants that come as bulbs, bare root or in 4-inch pots; plants should be in no larger than 1-gallon containers.</li> </ul>
	Fall and Spring		Presence of or need for stakes and guys (tree growth, maturation, and support needs)	<ul style="list-style-type: none"> <li>Verify location of facility liners and underdrain (if any) prior to stake installation in order to prevent liner puncture or pipe damage</li> <li>Monitor tree support systems: Repair and adjust as needed to provide support and prevent damage to tree.</li> <li>Remove tree supports (stakes, guys, etc.) after one growing season or maximum of 1 year.</li> <li>Backfill stake holes after removal.</li> </ul>
Trees and shrubs adjacent to vehicle travel areas (or areas where visibility needs to be maintained)	A		Vegetation causes some visibility (line of sight) or driver safety issues	<ul style="list-style-type: none"> <li>Maintain appropriate height for sight clearance</li> <li>When continued, regular pruning (more than one time/ growing season) is required to maintain visual sight lines for safety or clearance along a walk or drive, consider relocating the plant to a more appropriate location.</li> <li>Remove or transplant if continual safety hazard</li> <li>Consultation with a landscape architect is recommended for removal, transplant, or substitution of plants</li> </ul>
Flowering plants		A	Dead or spent flowers present	Remove spent flowers (deadhead)
Perennials		Fall	Spent plants	Cut back dying or dead and fallen foliage and stems
Emergent vegetation		Spring	Vegetation compromises conveyance	<ul style="list-style-type: none"> <li>Hand rake sedges and rushes with a small rake or fingers to remove dead foliage before new growth emerges in spring or earlier only if the foliage is blocking water flow (sedges and rushes do not respond well to pruning)</li> </ul>
Ornamental grasses (perennial)		Winter and Spring	Dead material from previous year's growing cycle or dead collapsed foliage	<ul style="list-style-type: none"> <li>Leave dry foliage for winter interest</li> <li>Hand rake with a small rake or fingers to remove dead foliage back to within several inches from the soil before new growth emerges in spring or earlier if the foliage collapses and is blocking water flow</li> </ul>
Ornamental grasses (evergreen)		Fall and Spring	Dead growth present in spring	<ul style="list-style-type: none"> <li>Hand rake with a small rake or fingers to remove dead growth before new growth emerges in spring</li> <li>Clean, rake, and comb grasses when they become too tall</li> <li>Cut back to ground or thin every 2-3 years as needed</li> </ul>
Noxious weeds		M (March – October, preceding seed dispersal)	Listed noxious vegetation is present (refer to current county noxious weed list)	<ul style="list-style-type: none"> <li>By law, class A &amp; B noxious weeds must be removed, bagged and disposed as garbage immediately</li> <li>Reasonable attempts must be made to remove and dispose of class C noxious weeds</li> <li>It is strongly encouraged that herbicides and pesticides not be used in order to protect water quality; use of herbicides and pesticides may be prohibited in some jurisdictions</li> <li>Apply mulch after weed removal (see "Mulch")</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least one visit should occur during the wet season (for debris/clog related maintenance, this inspection/maintenance visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

IPM - Integrated Pest Management  
ISA - International Society of Arboriculture



Table 3 (continued). Maintenance Standards and Procedures for Bioretention Facilities.

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Vegetation (cont'd)</b>				
Weeds		M (March – October, preceding seed dispersal)	Weeds are present	<ul style="list-style-type: none"> <li>Remove weeds with their roots manually with pincer-type weeding tools, flame weeders, or hot water weeders as appropriate</li> <li>Follow IPM protocols for weed management (see “Additional Maintenance Resources” section for more information on IPM protocols)</li> </ul>
Excessive vegetation		Once in early to mid- May and once in early- to mid- September	Low-lying vegetation growing beyond facility edge onto sidewalks, paths, or street edge poses pedestrian safety hazard or may clog adjacent permeable pavement surfaces due to associated leaf litter, mulch, and soil	<ul style="list-style-type: none"> <li>Edge or trim groundcovers and shrubs at facility edge</li> <li>Avoid mechanical blade-type edger and do not use edger or trimmer within 2 feet of tree trunks</li> <li>While some clippings can be left in the facility to replenish organic material in the soil, excessive leaf litter can cause surface soil clogging</li> </ul>
	As needed		Excessive vegetation density inhibits stormwater flow beyond design ponding or becomes a hazard for pedestrian and vehicular circulation and safety	<ul style="list-style-type: none"> <li>Determine whether pruning or other routine maintenance is adequate to maintain proper plant density and aesthetics</li> <li>Determine if planting type should be replaced to avoid ongoing maintenance issues (an aggressive grower under perfect growing conditions should be transplanted to a location where it will not impact flow)</li> <li>Remove plants that are weak, broken or not true to form; replace in-kind</li> <li>Thin grass or plants impacting facility function without leaving visual holes or bare soil areas</li> <li>Consultation with a landscape architect is recommended for removal, transplant, or substitution of plants</li> </ul>
	As needed		Vegetation blocking curb cuts, causing excessive sediment buildup and flow bypass	<ul style="list-style-type: none"> <li>Remove vegetation and sediment buildup</li> </ul>
<b>Mulch</b>				
Mulch		Following weeding	Bare spots (without mulch cover) are present or mulch depth less than 2 inches	<ul style="list-style-type: none"> <li>Supplement mulch with hand tools to a depth of 2 to 3 inches</li> <li>Replenish mulch per O&amp;M manual. Often coarse compost is used in the bottom of the facility and arborist wood chips are used on side slopes and rim (above typical water levels)</li> <li>Keep all mulch away from woody stems</li> </ul>
<b>Watering</b>				
Irrigation system (if any)		Based on manufacturer's instructions	Irrigation system present	<ul style="list-style-type: none"> <li>Follow manufacturer's instructions for O&amp;M</li> </ul>
	A		Sprinklers or drip irrigation not directed/located to properly water plants	<ul style="list-style-type: none"> <li>Redirect sprinklers or move drip irrigation to desired areas</li> </ul>
Summer watering (first year)		Once every 1-2 weeks or as needed during prolonged dry periods	Trees, shrubs and groundcovers in first year of establishment period	<ul style="list-style-type: none"> <li>10 to 15 gallons per tree</li> <li>3 to 5 gallons per shrub</li> <li>2 gallons water per square foot for groundcover areas</li> <li>Water deeply, but infrequently, so that the top 6 to 12 inches of the root zone is moist</li> <li>Use soaker hoses or spot water with a shower type wand when irrigation system is not present                             <ul style="list-style-type: none"> <li>Pulse water to enhance soil absorption, when feasible</li> <li>Pre-moisten soil to break surface tension of dry or hydrophobic soils/mulch, followed by several more passes. With this method , each pass increases soil absorption and allows more water to infiltrate prior to runoff</li> </ul> </li> <li>Add a tree bag or slow-release watering device (e.g., bucket with a perforated bottom) for watering newly installed trees when irrigation system is not present</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least one visit should occur during the wet season (for debris/clog related maintenance, this inspection/maintenance visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

IPM - Integrated Pest Management

ISA - International Society of Arboriculture





Table 3 (continued). Maintenance Standards and Procedures for Bioretention Facilities.

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Watering (cont'd)</b>				
Summer watering (second and third years)		Once every 2-4 weeks or as needed during prolonged dry periods	Trees, shrubs and groundcovers in second or third year of establishment period	<ul style="list-style-type: none"> <li>• 10 to 15 gallons per tree</li> <li>• 3 to 5 gallons per shrub</li> <li>• 2 gallons water per square foot for groundcover areas</li> <li>• Water deeply, but infrequently, so that the top 6 to 12 inches of the root zone is moist</li> <li>• Use soaker hoses or spot water with a shower type wand when irrigation system is not present                             <ul style="list-style-type: none"> <li>○ Pulse water to enhance soil absorption, when feasible</li> <li>○ Pre-moisten soil to break surface tension of dry or hydrophobic soils/mulch, followed by several more passes. With this method, each pass increases soil absorption and allows more water to infiltrate prior to runoff</li> </ul> </li> </ul>
Summer watering (after establishment)		As needed	Established vegetation (after 3 years)	<ul style="list-style-type: none"> <li>• Plants are typically selected to be drought tolerant and not require regular watering after establishment; however, trees may take up to 5 years of watering to become fully established</li> <li>• Identify trigger mechanisms for drought-stress (e.g., leaf wilt, leaf senescence, etc.) of different species and water immediately after initial signs of stress appear</li> <li>• Water during drought conditions or more often if necessary to maintain plant cover</li> </ul>
<b>Pest Control</b>				
Mosquitoes	B, S		Standing water remains for more than 3 days after the end of a storm	<ul style="list-style-type: none"> <li>• Identify the cause of the standing water and take appropriate actions to address the problem (see "Ponded water")</li> <li>• To facilitate maintenance, manually remove standing water and direct to the storm drainage system (if runoff is from non pollution-generating surfaces) or sanitary sewer system (if runoff is from pollution-generating surfaces) after getting approval from sanitary sewer authority.</li> <li>• Do not use pesticides or <i>Bacillus thuringiensis israelensis</i> (Bti)</li> </ul>
Nuisance animals	As needed		Nuisance animals causing erosion, damaging plants, or depositing large volumes of feces	<ul style="list-style-type: none"> <li>• Reduce site conditions that attract nuisance species where possible (e.g., plant shrubs and tall grasses to reduce open areas for geese, etc.)</li> <li>• Place predator decoys</li> <li>• Follow IPM protocols for specific nuisance animal issues (see "Additional Maintenance Resources" section for more information on IPM protocols)</li> <li>• Remove pet waste regularly</li> <li>• For public and right-of-way sites consider adding garbage cans with dog bags for picking up pet waste.</li> </ul>
Insect pests	Every site visit associated with vegetation management		Signs of pests, such as wilting leaves, chewed leaves and bark, spotting or other indicators	<ul style="list-style-type: none"> <li>• Reduce hiding places for pests by removing diseased and dead plants</li> <li>• For infestations, follow IPM protocols (see "Additional Maintenance Resources" section for more information on IPM protocols)</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least one visit should occur during the wet season (for debris/clog related maintenance, this inspection/maintenance visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

IPM - Integrated Pest Management

ISA - International Society of Arboriculture



## *Additional Maintenance Resources*

Useful related guidance documents include the following:

- LID Technical Guidance Manual for Puget Sound:  
<http://www.wastormwatercenter.org/files/library/lid-manual-2012-final-secure.pdf>.
- Natural Lawn and Garden Care resources (King County and SPU 2008; Saving Water Partnership 2006, 2007, and 2012) include guidance on building healthy soil with compost and mulch, selecting appropriate plants, watering, using alternatives to pesticides, and implementing natural lawn care techniques.
- Integrated Pest Management (IPM) protocols (the term “pest” covers a broad range of species including harmful insects, plant pathogens, rodents, and weedy vegetation) provide an approach to pest control that uses regular monitoring to determine if and when treatments are needed, and employs physical, mechanical, cultural, and biological tactics to keep pest numbers low enough to prevent intolerable damage or annoyance (Ecology 2012c) while avoiding or minimizing the use of pesticides and fertilizers herbicides as a management strategy.
- See EPA’s website for general information on IPM:  
[www.epa.gov/pesticides/factsheets/ipm.htm](http://www.epa.gov/pesticides/factsheets/ipm.htm)
- See the City of Seattle’s website for IPM Fact Sheets and Washington specific resources:  
[www.seattle.gov/util/forbusinesses/landscapes/integrated\\_pest\\_management](http://www.seattle.gov/util/forbusinesses/landscapes/integrated_pest_management)
- The International Society of Arboriculture (ISA) is a group that promotes the professional practice of arboriculture and fosters a greater worldwide awareness of the benefits of trees through research, technology, and education. ISA standards used for managing trees, shrubs, and other woody plants are the American National Standards Institute (ANSI) A300 standards. The ANSI A300 standards are voluntary industry consensus standards developed by the Tree Care Industry Association (TCIA) and written by the Accredited Standards Committee (ASC). The ANSI standards can be found on the ISA website: [www.isa-arbor.com/education/publications/index.aspx](http://www.isa-arbor.com/education/publications/index.aspx).
- Volume IV (Source Control) of Ecology’s 2012 SWMMWW provides guidance on herbicide and pesticide application and alternative management strategies for controlling weeds and pests.
- WSU Weeding Guidelines: <http://gardening.wsu.edu>
- Pacific Northwest Plant Disease Management Handbook for information on disease recognition and for additional resources:  
<http://pnwhandbooks.org/plantdisease/diagnosis-and-testing/disease-diagnosis-and-control>

These resources are supplemental and do not supersede guidance provided in the *Standards and Procedures* tables.

## Equipment and Materials

Table 4 includes recommendations for equipment and materials commonly used to maintain bioretention facilities. Some of the equipment and materials will be used for routine maintenance activities, while other equipment and materials will be necessary for specialized maintenance.

Table 4. Bioretention Equipment and Materials List.	
<b>Landscaping equipment</b>	<b>Landscaping materials*</b>
<input type="checkbox"/> Gloves <input type="checkbox"/> Weeding tool <input type="checkbox"/> Soil knife <input type="checkbox"/> Pruners <input type="checkbox"/> Loppers <input type="checkbox"/> Stakes and guys <input type="checkbox"/> Manual edger <input type="checkbox"/> Line trimmer (also known as a string trimmer, weed eater, or weed whacker) <input type="checkbox"/> Rototiller <input type="checkbox"/> Hoe <input type="checkbox"/> Rake <input type="checkbox"/> Wheelbarrow <input type="checkbox"/> Shovel <input type="checkbox"/> Push broom <input type="checkbox"/> Hand tamper <input type="checkbox"/> Blade sharpeners <input type="checkbox"/> Tarp/ Buckets (to remove leaf litter/debris) <input type="checkbox"/> Garbage bags (for disposal of trash/noxious weeds) <input type="checkbox"/> Bark and mulch blower <input type="checkbox"/> Boards to stand on during maintenance to prevent soil compaction (if maintenance is necessary during periods when Bioretention media is wet)	<input type="checkbox"/> Plants <input type="checkbox"/> Stakes and ties <b>Erosion control material*</b> <input type="checkbox"/> Rock or cobbles for rock pad <input type="checkbox"/> Erosion control matting <b>Mulch</b> <input type="checkbox"/> Arborist wood chip mulch <input type="checkbox"/> Coarse compost mulch <input type="checkbox"/> Rock mulch <b>Pipe/structure inspection and maintenance equipment</b> <input type="checkbox"/> Hand tools <input type="checkbox"/> Wrench or manhole lifter (for opening manhole lids, grates, etc.) <input type="checkbox"/> Flashlight <input type="checkbox"/> Mirror (for viewing pipes without entering structure) <input type="checkbox"/> Garden hose <input type="checkbox"/> Plumbing snake <input type="checkbox"/> Measuring tape or ruler <b>Specialized equipment*</b> <input type="checkbox"/> Mini excavator <input type="checkbox"/> Vector truck <input type="checkbox"/> Manual seed broadcaster <input type="checkbox"/> Soil monitoring equipment (T handle core sampler, soil auger, soil nutrient test kit) <input type="checkbox"/> Flame weeder or hot water weeder <input type="checkbox"/> Water jet or root saw (Vector truck tools) for clearing roots from underdrains <input type="checkbox"/> Equipment for infiltration testing <b>Bioretention soil*</b> <input type="checkbox"/> Bioretention soil per design specifications
<b>Watering equipment</b>	
<input type="checkbox"/> Soaker hose <input type="checkbox"/> Hose/shower-type wand <input type="checkbox"/> Sprinklers <input type="checkbox"/> Tree watering bags <input type="checkbox"/> Buckets <input type="checkbox"/> Keys for irrigation boxes <input type="checkbox"/> Water source (e.g., watering truck), if necessary	

\* Items not required for routine maintenance

## Skills and Staffing

The skills required for maintenance of bioretention facilities are listed in the text box to the right. Additional specialized skills may also be required for corrective maintenance such as: horticulturalists, arborists, erosion control specialists, engineers, landscape architects, and soil scientists.

The staff effort required for maintenance varies. Table 5 provides some examples of staffing estimates from Washington jurisdictions, the City of Portland, a study conducted among Minnesota jurisdictions (Wilson et al. 2008), and the BMP and LID Whole Life Cost Models (WERF 2009). Annual staff hours are listed for an individual facility (i.e., a “typical” facility of undefined area), 1,000 square feet of facility, or 1,000 linear feet of facility.

### Skills Needed for Maintenance of Bioretention Facilities

- Landscaping skills (e.g., general plant care)
- Plant identification skills (weeds vs. planted species, invasive vs. common weeds, how to dispose of invasive weeds, timing of weed seed dispersal)
- Erosion control knowledge
- General drainage system maintenance skills (e.g., inlet/pipe/underdrain cleaning experience, inlet/ pipe maintenance or repair experience)
- Operation of specialized equipment
- Engineer and/or landscape architect for major maintenance
- Certified arborist (or equivalently trained staff) for pruning of mature trees

<b>Routine Maintenance Activity</b>	<b>Frequency<sup>a</sup></b>	<b>Annual Staff Hours</b>	<b>Source</b>
General (no activity specified)	A or B	1 to 16 hours (per facility)	Maintenance of Stormwater BMPs: Frequency, Effort, and Cost (Wilson et al. 2008)
Vegetation management	A	0 to 2 hours (per facility)	BMP and LID Whole Life Cost Models (WERF 2009)
General (no activity specified)	M	24 hours (per 1,000 sf)	City of Bellevue
General (no activity specified)	M	16 hours (per facility)	Kitsap County
Weeding	M (May-Sept)	7 hours (per 1,000 lf)	Thurston County
Replanting and mulching	A		
Typical facility maintenance	Q	10 to 30 hours <sup>b</sup> (per 1,000 sf)	City of Portland
More complex site maintenance <sup>c</sup>	> Q	14 to 38 hours <sup>b</sup> (per 1,000 sf)	
General (no activity specified)	Unspecified	10 hours (per 1,000 sf)	City of Olympia

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; Q = Quarterly (four times per year)

<sup>b</sup> Low end of range pertains to City staff and high end of range pertains to Contractor staff

<sup>c</sup> Deciduous canopy, poor soils, adjacent weed vectors, unmaintained commercial right-of-way

lf = linear feet

sf = square feet

Staffing estimates averaged approximately 16 to 22 hours per bioretention facility on an annual basis. The City of Portland estimated that bioretention facilities with more complex maintenance requirements could require up to 38 hours of staff time when using less seasoned maintenance crews.

## Rain Gardens

Rain gardens are non-engineered, shallow, landscaped depressions with compost-amended soils and adapted plants. The depression temporarily stores stormwater runoff from adjacent areas. Some or all of the influent stormwater passes through the amended soil profile and into the underlying native soil. Stormwater that exceeds the storage capacity is designed to overflow to an adjacent drainage system.

### *Key Maintenance Considerations*

The main components of rain gardens (and the associated maintenance considerations) are very similar to those listed for bioretention facilities. However, rain gardens do not require an engineered soil mix (native soils may be amended) and usually do not have underdrains or other control structures.

Fertilizer use should be avoided in rain gardens, particularly those located in watersheds draining to phosphorous limited water bodies.

### *Key Operations to Preserve Facility Function*

As explained for bioretention facilities, rain gardens must be protected from foot traffic, vehicles and other loads, particularly during wet conditions, to prevent compaction of the amended soil and preserve infiltration capacity.

Signage can also be used to identify the vegetated area as a stormwater BMP and inform maintenance crews and the general public about protecting the rain garden's function (e.g., no walking in the garden).

### *Maintenance Standards and Procedures*

Table 6 provides the recommended maintenance frequencies, standards, and procedures for rain garden components. For guidance on underdrains, check dams and other control structures, see "Bioretention Facilities".

**Table 6. Maintenance Standards and Procedures for Rain Gardens.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Rain Garden Footprint</b>				
Earthen side slopes	B (during the wet season)		Persistent soil erosion on slopes	If erosion persists, water may be flowing into the garden too rapidly. In this case, the slope of the pipe or swale directing water to the garden, or the amount of water may need to be reduced (see “Erosion control at inlet”)
Rockery sidewalls	A		Rockery side walls are insecure	Stabilize rockery sidewalls (may require consultation with engineer, particularly for walls 4 feet or greater in height)
Rain garden footprint		B	Trash and debris present	Clean out trash and debris
Rain garden bottom area	A		Visible sediment deposition in the rain garden that reduces drawdown time of water in the rain garden	<ul style="list-style-type: none"> <li>Remove sediment accumulation</li> <li>If sediment is deposited from water entering the rain garden, determine the source and stabilize the area</li> </ul>
		During/after fall leaf drop	Accumulated leaves in rain garden (may reduce infiltration capacity of rain garden or clog overflow)	Remove leaves
Ponded water	B, S		Excessive ponding water: Ponded water remains in the basin more than 3 days after the end of a storm	<p>Confirm leaf, debris or sediment buildup in the bottom of the rain garden is not impeding infiltration. If necessary, remove leaf litter/debris/sediment.</p> <p>If this does not solve the problem, consultation with a professional with rain garden expertise is recommended to evaluate the following:</p> <ul style="list-style-type: none"> <li>Check for other water inputs (e.g., groundwater, illicit connections)</li> <li>Verify that the facility is sized appropriately for the contributing area. Confirm that the contributing area has not increased</li> <li>Determine if the soil is clogged by sediment accumulation at the surface or if the soil has become overly compacted</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).



**Table 6 (continued). Maintenance Standards and Procedures for Rain Gardens.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b><i>Inlets/Outlets/Pipes</i></b>				
Splash block inlet	A		Water is not being directed properly to the rain garden and away from the building	Reconfigure/ repair blocks to direct water to the rain garden and away from building
Pipe inlet/ outlet	A		Pipe capacity is reduced by sediment or debris (can cause backups and flooding)	Clear pipes of sediment and debris
	A		Damaged/cracked drain pipes	<ul style="list-style-type: none"> <li>• Repair/seal cracks</li> <li>• Replace when repair is insufficient</li> </ul>
Erosion control at inlet	A		Rock or cobble is removed or missing and concentrated flows are contacting soil	Maintain a cover of rock or cobbles to protect the ground where concentrated water flows into the rain garden from a pipe or swale
<b><i>Vegetation</i></b>				
Vegetation		As needed	Dying, dead, or unhealthy plants	<ul style="list-style-type: none"> <li>• Maintain a healthy cover of plants</li> <li>• Remove any diseased plants or plant parts and dispose of in commercial landfill to avoid risk of spreading the disease to other plants</li> <li>• Disinfect gardening tools after pruning to prevent the spread of disease</li> <li>• Re-stake trees if they need more support, but plan to remove stakes and ties after the first year</li> <li>• Cars can damage roots – protect root areas of trees and plants from vehicle traffic</li> </ul>
		As needed	Vegetation inhibits sight distances and sidewalks	Keep sidewalks and sight distances on roadways clear
		As needed	Broken, dead, or sucker vegetation is present	Remove broken or dead branches and suckers
		As needed	Vegetation is crowding inlets and outlets	Keep water inlets and outlets in the rain garden clear of vegetation

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

**Table 6 (continued). Maintenance Standards and Procedures for Rain Gardens.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Vegetation (cont'd)</b>				
Vegetation (cont'd)		As needed	Broken, dead, or sucker vegetation is present	Remove broken or dead branches and suckers
		As needed	Vegetation is crowding inlets and outlets	Keep water inlets and outlets in the rain garden clear of vegetation
	One time March through June		<ul style="list-style-type: none"> <li>• Yellowing: possible Nitrogen (N) deficiency</li> <li>• Poor growth: possible Phosphorous (P) deficiency</li> <li>• Poor flowering, spotting or curled leaves, or weak roots or stems: possible Potassium (K) deficiency</li> </ul>	<ul style="list-style-type: none"> <li>• Test soil to identify specific nutrient deficiencies</li> <li>• Consult with a professional knowledgeable in the area of natural amendments or refer to Natural Lawn and Garden Care resources and avoid synthetic fertilizers</li> <li>• Consider selecting different plants for soil conditions</li> </ul>
Weeds		As needed, preceding seed dispersal	Problem weeds are present	<ul style="list-style-type: none"> <li>• Remove weeds by hand, especially in spring when the soil is moist and the weeds are small</li> <li>• Dig or pull weeds out by the roots before they go to seed</li> <li>• Apply mulch after weeding (see "Mulch")</li> </ul>
<b>Mulch</b>				
Mulch		Following weeding	Bare spots (without mulch cover) are present or mulch depth less than 2 inches	<ul style="list-style-type: none"> <li>• Supplement mulch with hand tools to a depth of 2 to 3 inches</li> <li>• Use coarse compost in the bottom of the rain garden and arborist wood chips on side slopes and rim (above typical water levels)</li> <li>• Keep all mulch from being in contact with woody stems.</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

**Table 6 (continued). Maintenance Standards and Procedures for Rain Gardens.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Watering</b>				
Summer watering (first year)		Once every 1-2 weeks or as needed during prolonged dry periods	Tree, shrubs and groundcovers in first year of establishment period	<ul style="list-style-type: none"> <li>• 10 to 15 gallons per tree</li> <li>• 3 to 5 gallons per shrub</li> <li>• 2 gallons water per square foot for groundcover areas</li> <li>• Water deeply, but infrequently, so that the top 6 to 12 inches of the root zone is moist</li> <li>• Use soaker hoses or spot water with a shower type wand when irrigation system is not present</li> <li>• Add a tree bag or slow-release watering device (e.g., bucket with a perforated bottom) for watering newly installed trees when irrigation system is not present</li> </ul>
Summer watering (second and third years)		Once every 2-4 weeks or as needed during prolonged dry periods	Tree, shrubs and groundcovers in second or third year of establishment period	<ul style="list-style-type: none"> <li>• 10 to 15 gallons per tree</li> <li>• 3 to 5 gallons per shrub</li> <li>• 2 gallons water per square foot for groundcover areas</li> <li>• Water deeply, but infrequently, so that the top 6 to 12 inches of the root zone is moist</li> <li>• Use soaker hoses or spot water with a shower type wand when irrigation system is not present</li> </ul>
Summer watering (after establishment)		As needed	Established vegetation (after 3 years)	<ul style="list-style-type: none"> <li>• Water during drought conditions or more often if necessary to maintain plant cover</li> <li>• Identify trigger mechanisms for drought-stress (e.g., leaf wilt, leaf senescence, etc.) of different rain garden species and water immediately after initial signs of stress appear</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

**Table 6 (continued). Maintenance Standards and Procedures for Rain Gardens.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b><i>Pest Control</i></b>				
Mosquitoes	B, S		Standing water remains for more than 3 days after the end of a storm	<ul style="list-style-type: none"> <li>• Identify the cause of the standing water and take appropriate actions to address the problem (see “Ponded water”)</li> <li>• Do not use pesticides or <i>Bacillus thuringiensis israelensis</i> (Bti)</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

## Additional Maintenance Resources

In addition to the resources listed for bioretention, useful guidance for rain gardens can be found in the Rain Garden Handbook for Western Washington Homeowners (<http://www.wastormwatercenter.org/low-impact/>). These resources are supplemental and do not supersede guidance provided in the Standards and Procedures tables.

## Equipment and Materials

Table 7 includes recommendations for equipment and materials commonly used to maintain rain gardens. Some of the equipment and materials will be used for routine maintenance activities, while other equipment and materials will be necessary for specialized maintenance.

Table 7. Rain Garden Equipment and Materials List.	
Landscaping equipment	Watering equipment
<input type="checkbox"/> Gloves <input type="checkbox"/> Weeding tool <input type="checkbox"/> Soil knife <input type="checkbox"/> Pruners <input type="checkbox"/> Loppers <input type="checkbox"/> Stakes and guys <input type="checkbox"/> Manual edger <input type="checkbox"/> Line trimmer (also known as a string trimmer, weed eater, or weed whacker) <input type="checkbox"/> Rototiller <input type="checkbox"/> Hoe <input type="checkbox"/> Rake <input type="checkbox"/> Wheelbarrow <input type="checkbox"/> Shovel <input type="checkbox"/> Push broom <input type="checkbox"/> Hand tamper <input type="checkbox"/> Blade sharpeners <input type="checkbox"/> Tarp/Buckets (to remove leaf litter/debris) <input type="checkbox"/> Garbage bags (for disposal of trash/noxious weeds)	<input type="checkbox"/> Soaker hose <input type="checkbox"/> Hose/shower-type wand <input type="checkbox"/> Sprinklers <input type="checkbox"/> Tree watering bags <input type="checkbox"/> Buckets <hr/> <b>Mulch</b> <input type="checkbox"/> Arborist wood chip mulch <input type="checkbox"/> Coarse compost mulch <input type="checkbox"/> Rock mulch <hr/> <b>Landscaping materials*</b> <input type="checkbox"/> Plants <hr/> <b>Erosion control materials*</b> <input type="checkbox"/> Rock or cobbles for rock pad <input type="checkbox"/> Erosion control matting <hr/> <b>Soil*</b> <input type="checkbox"/> Compost (for soil amendment) <input type="checkbox"/> Bioretention soil mix

\* Items not required for routine maintenance



## Permeable Pavement

Permeable pavement is a paving system which allows rainfall to percolate through the surface into the underlying soil or an aggregate bed, where stormwater is stored and infiltrated to underlying subgrade, or removed by an overflow drainage system. Permeable pavement facilities are considered Stormwater Treatment and Flow Control BMPs and can be used to meet Minimum Requirements #6 (treatment), #7 (flow control), or both. To satisfy Minimum Requirement #6, stormwater must be infiltrated into underlying soils that meet Ecology's soil treatment requirements or filtered through an engineered treatment layer included in the pavement section.

### *Key Maintenance Considerations*

The main components of permeable pavement facilities are listed below with descriptions of their function and key maintenance considerations.

- **Wearing course:** The surface layer of any permeable pavement system is the wearing course. Categories of wearing courses include:
  - **Porous asphalt:** A flexible pavement similar to standard asphalt that uses a bituminous binder to adhere aggregate. However, the fine material (sand and finer) is reduced or eliminated, resulting in the formation of voids between the aggregate in the pavement surface that allows water to infiltrate to the underlying aggregate base.
  - **Pervious concrete:** A rigid pavement similar to conventional concrete that uses a cementitious material to bind aggregate together. However, the fine aggregate (sand) component is reduced or eliminated in the gradation, resulting in the formation of voids between the aggregate in the pavement surface that allows water to infiltrate to the underlying aggregate base.
  - **Interlocking concrete paver blocks:** Solid, precast, manufactured modular units. Pavements constructed with these units create joints that are filled with permeable aggregate and installed on an open-graded aggregate base.
  - **Aggregate Pavers (or Pervious Pavers):** Modular precast paving units made with uniformly sized aggregates and bound with Portland cement concrete using a high strength adhesive. Unlike concrete paver blocks, these pavers are permeable. Pavements constructed with these units create joints that are filled with permeable aggregate and installed on an open-graded aggregate base.
  - **Open-celled paving grid with gravel:** Concrete or plastic grids that are filled with permeable aggregate. The system can be installed on an open-graded aggregate base.
  - **Open-celled paving grid with grass:** Concrete or plastic grids that are filled with a mix of sand, gravel, and topsoil for planting vegetation. The cells can be planted with a variety of non-turf forming grasses or low-growing groundcovers. The system can be installed on an open-graded aggregate base.

A critical component of a successful maintenance program is regular removal of sediment and debris, excessive moss from the facility surface to prevent clogging of the permeable wearing course.

- **Inlet (optional):** While permeable pavement facilities often manage only the rain falling directly on the pavement surface, they may also be designed to accept stormwater runoff from additional areas (e.g., adjacent impervious areas, nearby rooftops). Runoff can be directed to the facility by two main methods:
  - Sheet flow to the surface: Surface areas of the facility receiving runoff contributions will likely be prone to clogging due to sediment inputs, particularly in areas of concentrated inflow. These areas should be carefully inspected and corrective maintenance should be performed as necessary to maintain the function of the pavement at these sites. In addition, the source of the sediment loads should be evaluated to determine if modifications to features in the drainage area landscape (e.g., stabilization of adjacent planted areas) would help to prevent clogging.
  - Piped flow into the aggregate base: Pipes dispersing water into the aggregate bed should be designed with cleanout access to allow pipe maintenance. Runoff that is piped into the aggregate base should be pretreated for sediment removal (e.g., screens, sumps) to protect the subbase from sedimentation and clogging. The pretreatment system must be maintained to remove accumulated sediment.
- **Aggregate Base / Storage Reservoir:** Stormwater passes through the wearing course to an underlying aggregate storage reservoir where it is stored prior to infiltration into the underlying soil. This aggregate bed also provides the structural function of supporting design loads (e.g., vehicle loading) for flexible pavement systems. To allow inspection of the aggregate course, some facilities have an observation port (typically installed during construction) that allows monitoring of the water levels in the aggregate bed to determine if the facility is draining properly.
- **Overflow:** Unless designed to provide full infiltration of stormwater, permeable pavement facilities have an overflow. Facility overflow can be provided by subsurface slotted drain pipe(s) (elevated in the aggregate bed) routed to an inlet or catch basin structure or by lateral flow through the storage reservoir to a daylighted drainage system.
- **Underdrain with flow restrictor (optional):** A slotted drain pipe with flow restrictor assembly may be installed at the bottom of or elevated within the aggregate storage reservoir. Permeable pavement facilities with underdrains and flow restrictors operate as underground detention systems with some infiltration.

### *Key Operations to Preserve Facility Function*

There are several permeable pavement operational actions that can limit the likelihood of corrective maintenance actions or replacement including the following:



- Prohibiting use of sealant on porous asphalt
- Protecting from construction site runoff with proper temporary erosion and sediment controls and flow diversion measures
- Modifying utility cut procedures for permeable pavements. Protocols should *recommend* restoring permeable pavement section in-kind, where feasible, and *require* restoring permeable pavement section in-kind where replacement with conventional pavement would impact overall facility function. Replacing permeable pavement with conventional pavement is acceptable if it is a small percentage of the total facility area and does not impact the overall facility function.
- Modifying snow removal procedures such as:
  - Using a snow plow with skids or rollers to slightly raise the blade above permeable pavers or open-celled paving grid systems to prevent loss of top course aggregate and damage to paver blocks or grids
  - Avoiding stockpiling plowed snow (i.e., dirty snow) directly on top of permeable pavement
  - Avoiding application of sand to pervious pavement and adjacent streets where vehicles may track it onto the pervious pavement. If sand is applied, on an emergency basis during snowy conditions, vacuum sweep surface as soon as possible after the sand is no longer needed.
  - Use alternative deicers in moderation (e.g., salt, molasses-based and chemical deicers).
- Protecting the surface from stockpiles of landscaping materials (e.g., mulch, soil, compost) being used for adjacent pervious areas
- Stabilizing adjacent landscaped areas to avoid eroding soil and clogging surfaces or sloping adjacent landscaped areas away from permeable pavement , if possible

Signage or pavement marking can also be used to identify permeable pavement as a stormwater BMP and inform maintenance crews and the general public about protecting the facility's function (e.g., no stockpiling of soils or mulch on pavement surface).

### *Maintenance Standards and Procedures*

Table 8 provides the recommended maintenance frequencies, standards, and procedures for permeable pavement components. The level of routine maintenance required and the frequency of corrective maintenance actions may increase for facilities receiving high sediment loads (e.g., sanding) or facilities subject to extended wet, shady conditions where moss may accumulate.



**Table 8. Maintenance Standards and Procedures for Permeable Pavement.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Surface/Wearing Course</b>				
Permeable Pavements, all	A, S		Runoff from adjacent pervious areas deposits soil, mulch or sediment on paving	<ul style="list-style-type: none"> <li>Clean deposited soil or other materials from permeable pavement or other adjacent surfacing</li> <li>Check if surface elevation of planted area is too high, or slopes towards pavement, and can be regraded (prior to regrading, protect permeable pavement by covering with temporary plastic and secure covering in place)</li> <li>Mulch and/or plant all exposed soils that may erode to pavement surface</li> </ul>
Porous asphalt or pervious concrete		A or B	None (routine maintenance)	<p>Clean surface debris from pavement surface using one or a combination of the following methods:</p> <ul style="list-style-type: none"> <li>Remove sediment, debris, trash, vegetation, and other debris deposited onto pavement (rakes and leaf blowers can be used for removing leaves)</li> <li>Vacuum/sweep permeable paving installation using:                             <ul style="list-style-type: none"> <li>Walk-behind vacuum (sidewalks)</li> <li>High efficiency regenerative air or vacuum sweeper (roadways, parking lots)</li> <li>ShopVac or brush brooms (small areas)</li> </ul> </li> <li>Hand held pressure washer or power washer with rotating brushes</li> </ul> <p>Follow equipment manufacturer guidelines for when equipment is most effective for cleaning permeable pavement. Dry weather is more effective for some equipment.</p>
	A <sup>b</sup>		Surface is clogged: Ponding on surface or water flows off the permeable pavement surface during a rain event (does not infiltrate)	<ul style="list-style-type: none"> <li>Review the overall performance of the facility (note that small clogged areas may not reduce overall performance of facility)</li> <li>Test the surface infiltration rate using ASTM C1701 as a corrective maintenance indicator. Perform one test per installation, up to 2,500 square feet. Perform an additional test for each additional 2,500 square feet up to 15,000 square feet total. Above 15,000 square feet, add one test for every 10,000 square feet.</li> <li>If the results indicate an infiltration rate of 10 inches per hour or less, then perform corrective maintenance to restore permeability.</li> </ul> <p>To clean clogged pavement surfaces, use one or combination of the following methods:</p> <ul style="list-style-type: none"> <li>Combined pressure wash and vacuum system calibrated to not dislodge wearing course aggregate.</li> <li>Hand held pressure washer or power washer with rotating brushes</li> <li>Pure vacuum sweepers</li> </ul> <p>Note: If the annual/biannual routine maintenance standard to clean the pavement surface is conducted using equipment from the list above, corrective maintenance may not be needed.</p>
	A		Sediment present at the surface of the pavement	<ul style="list-style-type: none"> <li>Assess the overall performance of the pavement system during a rain event. If water runs off the pavement and/or there is ponding then see above.</li> <li>Determine source of sediment loading and evaluate whether or not the source can be reduced/eliminated. If the source cannot be addressed, consider increasing frequency of routine cleaning (e.g., twice per year instead of once per year).</li> </ul>
	Summer		Moss growth inhibits infiltration or poses slip safety hazard	<ul style="list-style-type: none"> <li>Sidewalks: Use a stiff broom to remove moss in the summer when it is dry</li> <li>Parking lots and roadways: Pressure wash, vacuum sweep, or use a combination of the two for cleaning moss from pavement surface. May require stiff broom or power brush in areas of heavy moss.</li> </ul>
	A		Major cracks or trip hazards and concrete spalling and raveling	<ul style="list-style-type: none"> <li>Fill potholes or small cracks with patching mixes</li> <li>Large cracks and settlement may require cutting and replacing the pavement section. Replace in-kind where feasible. Replacing porous asphalt with conventional asphalt is acceptable if it is a small percentage of the total facility area and does not impact the overall facility function.</li> <li>Take appropriate precautions during pavement repair and replacement efforts to prevent clogging of adjacent porous materials</li> </ul>

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.



Table 8 (continued). Maintenance Standards and Procedures for Permeable Pavement.

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Surface/Wearing Course (cont'd)</b>				
Interlocking concrete paver blocks and aggregate pavers		A or B	None (routine maintenance)	<ul style="list-style-type: none"> <li>Clean pavement surface using one or a combination of the following methods:                             <ul style="list-style-type: none"> <li>Remove sediment, debris, trash, vegetation, and other debris deposited onto pavement (rakes and leaf blowers can be used for removing leaves)</li> <li>Vacuum/sweep permeable paving installation using:                                     <ul style="list-style-type: none"> <li>Walk-behind vacuum (sidewalks)</li> <li>High efficiency regenerative air or vacuum sweeper (roadways, parking lots)</li> <li>ShopVac or brush brooms (small areas)</li> </ul> </li> <li>Note: Vacuum settings may have to be adjusted to prevent excess uptake of aggregate from paver openings or joints. Vacuum surface openings in dry weather to remove dry, encrusted sediment.</li> </ul> </li> </ul>
	A <sup>b</sup>		Surface is clogged: Ponding on surface or water flows off the permeable pavement surface during a rain event (does not infiltrate)]	<ul style="list-style-type: none"> <li>Review the overall performance of the facility (note that small clogged areas may not reduce overall performance of facility)</li> <li>Test the surface infiltration rate using ASTM C1701 as a corrective maintenance indicator. Perform one test per installation, up to 2,500 square feet. Perform an additional test for each additional 2,500 square feet up to 15,000 square feet total. Above 15,000 square feet, add one test for every 10,000 square feet.</li> <li>If the results indicate an infiltration rate of 10 inches per hour or less, then perform corrective maintenance to restore permeability.</li> <li>Clogging is usually an issue in the upper 2 to 3 centimeters of aggregate. Remove the upper layer of encrusted sediment, and fines, and/or vegetation from openings and joints between the pavers by mechanical means and/or suction equipment (e.g., pure vacuum sweeper).</li> <li>Replace aggregate in paver cells, joints, or openings per manufacturer's recommendations</li> </ul>
	A		Sediment present at the surface of the pavement	<ul style="list-style-type: none"> <li>Assess the overall performance of the pavement system during a rain event. If water runs off the pavement and/or there is ponding, then see above.</li> <li>Determine source of sediment loading and evaluate whether or not the source can be reduced/eliminated. If the source cannot be addressed, consider increasing frequency of routine cleaning (e.g., twice per year instead of once per year).</li> </ul>
	Summer		Moss growth inhibits infiltration or poses slip safety hazard	<ul style="list-style-type: none"> <li>Sidewalks: Use a stiff broom to remove moss in the summer when it is dry</li> <li>Parking lots and roadways: Vacuum sweep or stiff broom/power brush for cleaning moss from pavement surface</li> </ul>
	A		Paver block missing or damaged	Remove individual damaged paver blocks by hand and replace or repair per manufacturer's recommendations
	A		Loss of aggregate material between paver blocks	Refill per manufacturer's recommendations for interlocking paver sections
	A		Settlement of surface	May require resetting
Open-celled paving grid with gravel		A or B	None (routine maintenance)	<ul style="list-style-type: none"> <li>Remove sediment, debris, trash, vegetation, and other debris deposited onto pavement (rakes and leaf blowers can be used for removing leaves)</li> <li>Follow equipment manufacturer guidelines for cleaning surface.</li> </ul>
	A <sup>b</sup>		Aggregate is clogged: Ponding on surface or water flows off the permeable pavement surface during a rain event (does not infiltrate)]	<ul style="list-style-type: none"> <li>Use vacuum truck to remove and replace top course aggregate</li> <li>Replace aggregate in paving grid per manufacturer's recommendations</li> </ul>
	A		Paving grid missing or damaged	<ul style="list-style-type: none"> <li>Remove pins, pry up grid segments, and replace gravel</li> <li>Replace grid segments where three or more adjacent rings are broken or damaged</li> <li>Follow manufacturer guidelines for repairing surface.</li> </ul>
	A		Settlement of surface	May require resetting
	A		Loss of aggregate material in paving grid	Replenish aggregate material by spreading gravel with a rake (gravel level should be maintained at the same level as the plastic rings or no more than 1/4 inch above the top of rings). See manufacturer's recommendations.
		A	Weeds present	<ul style="list-style-type: none"> <li>Manually remove weeds</li> <li>Presence of weeds may indicate that too many fines are present (refer to Actions Needed under "Aggregate is clogged" to address this issue)</li> </ul>

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.



Table 8 (continued). Maintenance Standards and Procedures for Permeable Pavement.

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Surface/Wearing Course (cont'd)</b>				
Open-celled paving grid with grass		A or B	None (routine maintenance)	<ul style="list-style-type: none"> <li>Remove sediment, debris, trash, vegetation, and other debris deposited onto pavement (rakes and leaf blowers can be used for removing leaves)</li> <li>Follow equipment manufacturer guidelines for cleaning surface.</li> </ul>
	A <sup>b</sup>		Aggregate is clogged: Ponding on surface or water flows off the permeable pavement surface during a rain event (does not infiltrate)]	<ul style="list-style-type: none"> <li>Rehabilitate per manufacturer's recommendations.</li> </ul>
	A		Paving grid missing or damaged	<ul style="list-style-type: none"> <li>Remove pins, pry up grid segments, and replace grass</li> <li>Replace grid segments where three or more adjacent rings are broken or damaged</li> <li>Follow manufacturer guidelines for repairing surface.</li> </ul>
	A		Settlement of surface	<ul style="list-style-type: none"> <li>May require resetting</li> </ul>
	A		Poor grass coverage in paving grid	<ul style="list-style-type: none"> <li>Restore growing medium, reseed or plant, aerate, and/or amend vegetated area as needed</li> <li>Traffic loading may be inhibiting grass growth; reconsider traffic loading if feasible</li> </ul>
		As needed	None (routine maintenance)	<ul style="list-style-type: none"> <li>Use a mulch mower to mow grass</li> </ul>
		A	None (routine maintenance)	<ul style="list-style-type: none"> <li>Sprinkle a thin layer of compost on top of grass surface (1/2" top dressing) and sweep it in</li> <li>Do not use fertilizer</li> </ul>
		A	Weeds present	<ul style="list-style-type: none"> <li>Manually remove weeds</li> <li>Mow, torch, or inoculate and replace with preferred vegetation</li> </ul>
<b>Inlets/Outlets/Pipes</b>				
Inlet/outlet pipe	A		Pipe is damaged	Repair/replace
	A		Pipe is clogged	Remove roots or debris
Underdrain pipe	Clean pipe as needed	Clean orifice at least biannually (may need more frequent cleaning during wet season)	Plant roots, sediment or debris reducing capacity of underdrain (may cause prolonged drawdown period)	<ul style="list-style-type: none"> <li>Jet clean or rotary cut debris/roots from underdrain(s)</li> <li>If underdrains are equipped with a flow restrictor (e.g., orifice) to attenuate flows, the orifice must be cleaned regularly</li> </ul>
Raised subsurface overflow pipe	Clean pipe as needed	Clean orifice at least biannually (may need more frequent cleaning during wet season)	Plant roots, sediment or debris reducing capacity of underdrain	<ul style="list-style-type: none"> <li>Jet clean or rotary cut debris/roots from under-drain(s)</li> <li>If underdrains are equipped with a flow restrictor (e.g., orifice) to attenuate flows, the orifice must be cleaned regularly</li> </ul>
Outlet structure	A, S		Sediment, vegetation, or debris reducing capacity of outlet structure	<ul style="list-style-type: none"> <li>Clear the blockage</li> <li>Identify the source of the blockage and take actions to prevent future blockages</li> </ul>

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.





Table 8 (continued). Maintenance Standards and Procedures for Permeable Pavement.

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Inlets/Outlets/Pipes (cont'd)</b>				
Overflow	B		Native soil is exposed or other signs of erosion damage are present at discharge point	Repair erosion and stabilize surface
<b>Aggregate Storage Reservoir</b>				
Observation port	A, S		Water remains in the storage aggregate longer than anticipated by design after the end of a storm	If immediate cause of extended ponding is not identified, schedule investigation of subsurface materials or other potential causes of system failure.
<b>Vegetation</b>				
Adjacent large shrubs or trees		As needed	Vegetation related fallout clogs or will potentially clog voids	<ul style="list-style-type: none"> <li>Sweep leaf litter and sediment to prevent surface clogging and ponding</li> <li>Prevent large root systems from damaging subsurface structural components</li> </ul>
		Once in May and Once in September	Vegetation growing beyond facility edge onto sidewalks, paths, and street edge	Edging and trimming of planted areas to control groundcovers and shrubs from overreaching the sidewalks, paths and street edge improves appearance and reduces clogging of permeable pavements by leaf litter, mulch and soil.
Leaves, needles, and organic debris		In fall (October to December) after leaf drop (1-3 times, depending on canopy cover)	Accumulation of organic debris and leaf litter	Use leaf blower or vacuum to blow or remove leaves, evergreen needles, and debris (i.e., flowers, blossoms) off of and away from permeable pavement

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.



## Equipment and Materials

Table 9 includes recommendations for equipment and materials commonly used to maintain permeable pavement. Some of the equipment and materials will be used for routine maintenance activities, while other equipment and materials will be necessary for specialized maintenance.

Table 9. Permeable Pavement Equipment and Materials List.	
<b>Equipment to address clogging of wearing course, such as:</b>	<b>Weed / vegetation removal equipment, such as:</b>
<input type="checkbox"/> Hand held pressure washer or power washer with rotating brushes (not recommended for open-celled aggregate-filled systems) <input type="checkbox"/> Walk-behind vacuum (sidewalks) <input type="checkbox"/> Pure vacuum sweeper <input type="checkbox"/> ShopVac (small areas) <input type="checkbox"/> Combined higher pressure wash and vacuum system	<input type="checkbox"/> Weeding tools <input type="checkbox"/> Weed burner <input type="checkbox"/> Edging and trimming equipment to control groundcover and other vegetation from extending onto pavement surface
<b>Equipment to remove sediment, debris, and leaf litter, such as:</b>	<b>Additional equipment for grass-filled open-celled grid systems</b>
<input type="checkbox"/> High efficiency regenerative air or vacuum sweeper (roadways, parking lots) <input type="checkbox"/> Push broom (can also be used to spread and clean aggregate in gravel-filled open-celled grid and permeable paver systems) <input type="checkbox"/> Brush broom (course bristled broom) to remove moss <input type="checkbox"/> Leaf blower	<input type="checkbox"/> Mower or mulch mower <input type="checkbox"/> Topdress grass seed <input type="checkbox"/> Compost <input type="checkbox"/> Replacement grid segments
<b>Erosion control equipment (to stabilize adjacent landscaped areas and protect pavement from sediment inputs)*</b>	<b>Additional equipment for gravel-filled open-celled grid systems</b>
<input type="checkbox"/> Erosion control matting <input type="checkbox"/> Rocks <input type="checkbox"/> Mulch <input type="checkbox"/> Plants <input type="checkbox"/> Landscaping tools <input type="checkbox"/> Tarps (to protect pavement in area of landscaping from clogging, e.g., mulch stockpiles)	<input type="checkbox"/> Rakes and shovels <input type="checkbox"/> Aggregate to replace material after vacuuming or to replenish material in high use areas <input type="checkbox"/> Replacement grid segments <input type="checkbox"/> Wheelbarrow (for transporting replacement aggregate)
<b>Pipe/structure inspection and maintenance equipment</b>	<b>Additional equipment for permeable paver systems</b>
<input type="checkbox"/> Hand tools <input type="checkbox"/> Wrench or manhole opener (for opening manhole lids, grates, etc.) <input type="checkbox"/> Flashlight <input type="checkbox"/> Mirror (for viewing pipes without entering structure) <input type="checkbox"/> Garden hose <input type="checkbox"/> Plumbing snake <input type="checkbox"/> Measuring tape or ruler	<input type="checkbox"/> Rakes and shovels <input type="checkbox"/> Extra pavers and bedding material <input type="checkbox"/> Aggregate to replace materials between pavers after vacuuming <input type="checkbox"/> Wheelbarrow (for transporting replacement aggregate)
	<b>Snow removal equipment, such as:</b>
	<input type="checkbox"/> Plow with skids to prevent damage to permeable pavement <input type="checkbox"/> Snow blower

\* Items not required for routine maintenance

## Skills and Staffing

The skills required for the maintenance of permeable pavement facilities are listed in the text box to the right.

The staff effort required for maintenance varies based on the type of facility, sediment loading, and site conditions.

Table 10 provides some examples of staffing estimates from Washington jurisdictions, Washington contractors/vendors, a study conducted among Minnesota jurisdictions

(Wilson et al. 2008), and the BMP and LID Whole Life Cost Models (WERF 2009). Staff estimates are listed as the number of hours to maintain an individual facility (i.e., a “typical” facility of undefined area) per year or as the area of facility maintained per hour of staff time. Staffing estimates ranged from 1 to 24 hours per facility on an annual basis, with an average of approximately 4 to 6 hours per permeable pavement facility on an annual basis. Cleaning estimates in sf/hr ranged from 1,000 to 87,000 sf/hr depending on the type of maintenance activity.

### Skills Needed for Maintenance of Permeable Pavement

- Sweeper and equipment operation
- Commercial driver’s license (CDL)
- Landscaping skills (e.g., general plant care) for grass-filled open-celled grid systems
- Engineer and/or landscape architect for major maintenance

<b>Type of Pavement</b>	<b>Routine Maintenance Activity</b>	<b>Frequency <sup>a</sup></b>	<b>Annual Staff Hours</b>	<b>Source</b>
Permeable Pavement (all)	NG	A or B	1 to 4 hours (per facility)	Maintenance of Stormwater BMPs: Frequency, Effort, and Cost (Wilson et al. 2008)
Permeable Pavement (all)	Permeable Pavement Sweeping; Litter and Minor Debris Removal; and Recordkeeping	A	4 to 6 hours (per facility)	BMP and LID Whole Life Cost Models (WERF 2009)
Permeable Pavement (all)	Cleaning	A	4,000 sf/hour	City of Olympia
Permeable Pavement (all)	NG	B	4 hours (per facility)	Kitsap County
Permeable Pavement (all)	NG	3 times/year	24 hours (per facility)	Pierce County
Pervious Concrete	Parking lot (dry)	Q	6,000-9,000 sf/hr	Backstrom Curb & Sidewalk
	Sidewalk (dry)	B	1,000 sf/hr	
GrassPave2	Mowing	Weekly to M	22,000-33,000 sf/hr	Northwest Linings & Geotextile
	Fertilizing and liming		65,000-87,000 sf/hr	
GravelPave2	Gravel raking / re-distribution		11,000-22,000 sf/hr	
	Weed control		65,000-87,000 sf/hr	

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; Q = Quarterly (four times per year); NG = no guidance provided  
sf/hr = square feet per hour



## Vegetated Roofs

Vegetated roofs (also known as ecoroofs and green roofs) are thin layers of engineered soil and vegetation constructed on top of a conventional roof. Vegetated roofs consist of four basic components: a waterproof membrane, drainage layer, lightweight growth medium, and vegetation. Deeper installations, referred to as “intensive” roofs, are comprised of at least 6 inches of growth media and are planted with groundcovers, grasses, shrubs and sometimes trees. These intensive systems require regular landscape maintenance. Shallower installations, referred to as “extensive” roofs, are comprised of less than 6 inches of growth media and use a planting palette of drought-tolerant, low maintenance groundcovers. The procedures outlined below focus on extensive roof systems, and different procedures for intensive roofs are noted.

### *Key Maintenance Considerations*

The main components of vegetated roof facilities are listed below with descriptions of their function and key maintenance considerations. Components are listed in the order of installation from the roof deck upwards.

- **Waterproof membrane:** Waterproof membranes are installed on the roof deck below the vegetated roof system. Systems also include a protection layer and root barrier to preserve the integrity of the waterproof membrane. These components are not visible, so inspection is typically not possible unless a leak detection system is installed. During maintenance, sharp tools, lawn staples, and stakes should be avoided to prevent damage to membrane.
- **Drainage layer:** All vegetated roofs have a drainage component that routes excess water to the roof drain system. Usually this takes the form of a manufactured drain mat or granular drainage media. A separation layer (e.g., filter fabric) is typically installed above the drainage mat or granular drainage media to prevent fine components of the growth media from being washed into the roof drain system. This component is also not visible, so inspection is difficult. During maintenance, sharp tools, lawn staples, and stakes should be avoided to prevent damage to the drainage layer.
- **Growth media:** Vegetated roofs use a light-weight growth medium with adequate fertility and drainage capacity to support plant growth and allow infiltration and storage of water. In general the media is composed of porous and lightweight mineral aggregates such as pumice, lava rock, expanded shale and expanded slate. The growth media may be covered by a mat (or other erosion control measure) to prevent surface erosion due to rain and wind scour before plants are established.
- **Vegetation:** The plants on vegetated roofs are typically succulents, grass, herbs, and/or wildflowers adapted to the harsh conditions (minimal soils, seasonal drought, high winds, and strong sun exposure) prevalent on rooftops. A wider variety of vegetation types may be used on intensive roofs, but these typically require additional maintenance. Regular maintenance activities associated with vegetation include

weeding and pruning. Plants also require watering during establishment and extended dry periods.

- **Structural drainage elements:** The roof drainage system routes water from the vegetated roof drainage layer to a nearby drainage system. It is important to maintain unobstructed outlet pipes and structures to ensure that stormwater is safely conveyed from the roof to a discharge point. There are also other structural components of a roof that may interface with the vegetated roof (e.g., flashing, roof ventilation points, utilities).
- **Border zone:** This zone forms an area, composed of gravel and devoid of vegetation, around the perimeter of the vegetated roof, typically used as a fire prevention method and to prevent water damage.
- **Gravel stops:** These are sheet metal edges, typically installed outside of the border zone, along the perimeter of the roof to prevent growth medium from blowing or washing off of the roof.

### *Key Operations to Preserve Facility Function*

For vegetated roofs to function properly, stormwater must filter through several layers. Similar to bioretention facilities, filtration can be reduced if the growth media is subject to compaction (e.g., foot traffic). To limit the likelihood of corrective maintenance (e.g., growth media), the planted area of the vegetated roof should be protected from external loads. The risk of compaction is higher when soils are saturated, therefore any type of loading in the planted areas of the vegetated roof (including foot traffic) should be avoided or minimized during wet conditions.

Signage is recommended to identify the planted areas of the vegetated roof as a stormwater BMP and educate maintenance crews and the general public about protecting the facility's function (e.g., no walking on the facility). Clear walkways or pathways should be present to discourage foot traffic on the planted portions of the vegetated roof.

### *Maintenance Standards and Procedures*

Table 11 provides the recommended maintenance frequencies, standards, and procedures for vegetated roof components.

Each vegetated roof installation will have specific O&M guidelines provided by the manufacturer and installer. The following guidelines provide a general set of standards for prolonged vegetated roof performance. Note that some maintenance recommendations are different for extensive versus intensive vegetated roof systems. The procedures outlined below focus on extensive roof systems, and different procedures for intensive roofs are noted.



**Table 11. Maintenance Standards and Procedures for Vegetated Roofs.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Growth medium area</b>				
Growth medium	A <sup>b</sup>		Water does not permeate growth media (runs off soil surface) or crusting is observed	Aerate (e.g., rake) or replace medium taking care not to damage the waterproof membrane
	A		Growth medium thickness is less than design thickness (due to erosion and plant uptake)	Supplement growth medium to design thickness
	B, W		Fallen leaves or debris are present	Remove/dispose
	A, W, S		Growth media erosion/scour is visible (e.g., gullies)	<ul style="list-style-type: none"> <li>Take steps to repair or prevent erosion</li> <li>Fill, hand tamp, or lightly compact, and stabilize with additional soil substrate/growth medium (similar in nature to the original material) and additional plants</li> </ul>
Erosion control measures	B <sup>c</sup>		Mat or other erosion control is damaged or depleted during plant establishment period	<ul style="list-style-type: none"> <li>Repair/replace erosion control measures until 90% vegetation coverage attained</li> <li>Avoid application of mulch on extensive vegetated roofs</li> </ul>
<b>System Drainage and Structural Components</b>				
Roof drain	B, S		Sediment, vegetation, or debris reducing capacity of inlet structure	<ul style="list-style-type: none"> <li>Clear blockage</li> <li>Identify and correct any problems that led to blockage</li> </ul>
	A		Pipe is clogged	Remove roots or debris
	A		Inlet pipe is in poor condition	Repair/replace

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least once during the wet season (for debris/clog related maintenance, this visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.

<sup>c</sup> Inspection should occur during plant establishment period (typically first 2 years).

IPM - Integrated Pest Management

ISA - International Society of Arboriculture

**Table 11 (continued). Maintenance Standards and Procedures for Vegetated Roofs.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>System Drainage and Structural Components (cont'd)</b>				
Border zone	A		Vegetation is encroaching into border zone aggregate	Remove and dispose of weeds and transplant desirable vegetation to growth medium area
Flashing, gravel stops, utilities, or other structures on roof	A		Flashing, utilities or other structures on roof are deteriorating (can serve as source of metal pollution in vegetated roof runoff)	Repair (e.g., recoat) or replace to eliminate potential pollutant source. Note that any work done around flashings and drains should be done with care to protect the waterproof membrane.
Access and safety	B		Insufficient egress/ingress routes and fall protection	<ul style="list-style-type: none"> <li>• Maintain egress and ingress routes to design standards and fire codes</li> <li>• Ensure appropriate fall protection</li> </ul>
<b>Vegetation</b>				
Plant coverage	B		Vegetative coverage falls below 90% (unless design specifications stipulate less than 90% coverage)	<ul style="list-style-type: none"> <li>• Plant bare areas with vegetation</li> <li>• If necessary, install erosion control measures until percent coverage goal is attained</li> </ul>
Sedums		A (first 2 years in Spring); As needed (after first 2 years)	Extensive roof with low density sedum population	<ul style="list-style-type: none"> <li>• Mulch mow sedums- creating cuttings from existing plants to encourage colonization</li> </ul>
Dead plants	Fall and Spring		Dead vegetation is present	Normally dead plant material can be recycled on the roof; however, specific plants or aesthetic considerations may warrant removing and replacing dead material (see manufacturer's recommendations).
Trees and shrubs–intensive vegetated roof		All pruning seasons (timing varies by species)	Pruning as needed	All pruning of mature trees should be performed by or under the direct guidance of an ISA certified arborist

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least once during the wet season (for debris/clog related maintenance, this visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.

<sup>c</sup> Inspection should occur during plant establishment period (typically first 2 years).

IPM – Integrated Pest Management

ISA - International Society of Arboriculture



**Table 11 (continued). Maintenance Standards and Procedures for Vegetated Roofs.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Vegetation (cont'd)</b>				
Fertilization– extensive vegetated roof	A		Poor plant establishment and possible nutrient deficiency in growth medium	<ul style="list-style-type: none"> <li>• Allow organic debris to replenish and maintain long-term nutrient balance and growth medium structure</li> <li>• Conduct annual soil test 2-3 weeks prior to the spring growth flush to assess need for fertilizer. Utilize test results to adjust fertilizer type and quantity appropriately.</li> <li>• Apply minimum amount slow-release fertilizer necessary to achieve successful plant establishment.</li> <li>• Apply fertilizer only after acquiring required approval from facility owner and operator. Note that extensive vegetated roofs are designed to require zero to minimal fertilization after establishment (excess fertilization can contribute to nutrient export)</li> </ul>
Fertilization– intensive vegetated roof	A		Fertilization may be necessary during establishment period or for plant health and survivability after establishment	<ul style="list-style-type: none"> <li>• Conduct annual soil test 2-3 weeks prior to the spring growth flush to assess need for fertilizer. Utilize test results to adjust fertilizer type and quantity appropriately.</li> <li>• Apply minimum amount slow-release fertilizer necessary to achieve successful plant establishment.</li> <li>• Apply fertilizer only after acquiring required approval from facility owner and operator.</li> <li>• Intensive vegetated roofs may require more fertilization than extensive vegetated roofs</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least once during the wet season (for debris/clog related maintenance, this visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.

<sup>c</sup> Inspection should occur during plant establishment period (typically first 2 years).

IPM – Integrated Pest Management

ISA - International Society of Arboriculture

**Table 11 (continued). Maintenance Standards and Procedures for Vegetated Roofs.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Vegetation (cont'd)</b>				
Weeds		M (March – October, preceding seed dispersal)	Weeds are present	<ul style="list-style-type: none"> <li>Remove weeds with their roots manually with pincer-type weeding tools, flame weeders, or hot water weeders as appropriate</li> <li>Follow IPM protocols for weed management (see “Additional Maintenance Resources” for more information on IPM protocols)</li> </ul>
Noxious weeds		M (March – October, preceding seed dispersal)	Listed noxious vegetation is present (refer to current county noxious weed list)	<ul style="list-style-type: none"> <li>By law, class A &amp; B noxious weeds must be removed, bagged and disposed as garbage immediately</li> <li>Reasonable attempts must be made to remove and dispose of class C noxious weeds</li> <li>It is strongly encouraged that herbicides and pesticides not be used in order to protect water quality; use of herbicides and pesticides may be prohibited in some jurisdictions</li> </ul>
<b>Irrigation System (or Watering)</b>				
Irrigation system (if any)		Based on manufacturer's instructions	Irrigation system present	Follow manufacturer's instructions for operation and maintenance
Summer watering – extensive vegetated roof		Once every 1-2 weeks as needed during prolonged dry periods	Vegetation in establishment period (1-2 years)	Water weekly during periods of no rain to ensure plant establishment (30 to 50 gallons per 100 square feet)
		As needed	Established vegetation (after 2 years)	Water during drought conditions or more often if necessary to maintain plant cover (30 to 50 gallons per 100 square feet)

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least once during the wet season (for debris/clog related maintenance, this visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.

<sup>c</sup> Inspection should occur during plant establishment period (typically first 2 years).

IPM – Integrated Pest Management

ISA - International Society of Arboriculture



**Table 11 (continued). Maintenance Standards and Procedures for Vegetated Roofs.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Irrigation System (or Watering) (cont'd)</b>				
Summer watering – intensive vegetated roof		Once every 1-2 weeks as needed during prolonged dry periods	Vegetation in establishment period (1-2 years)	<ul style="list-style-type: none"> <li>Water deeply, but infrequently, so that the top 6 to 12 inches of the root zone is moist</li> <li>Use soaker hoses or spot water with a shower type wand when irrigation system not present</li> </ul>
		As needed	Established vegetation (after 2 years)	Water during drought conditions or more often if necessary to maintain plant cover
<b>Pest Control</b>				
Mosquitoes	B, S		Standing water remains for more than 3 days after the end of a storm	<ul style="list-style-type: none"> <li>Identify the cause of the standing water and take appropriate actions to address the problem (e.g., aerate or replace medium, unplug drainage)</li> <li>Manually remove standing water and direct to storm drainage system</li> <li>Do not use pesticides or <i>Bacillus thuringiensis israelensis</i> (Bti)</li> </ul>
Nuisance animals	As needed		Nuisance animals causing erosion, damaging plants, or depositing large volumes of feces	<ul style="list-style-type: none"> <li>Reduce site conditions that attract nuisance species</li> <li>Place predator decoys</li> <li>Follow IPM protocols for specific nuisance animal issues (see “Additional Maintenance Resources” in Bioretention Facilities section for more information on IPM protocols)</li> </ul>

<sup>a</sup> Frequency: A = Annually; B = Biannually (twice per year); M = Monthly; W = At least once during the wet season (for debris/clog related maintenance, this visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during storm event.

<sup>c</sup> Inspection should occur during plant establishment period (typically first 2 years).

IPM – Integrated Pest Management

ISA - International Society of Arboriculture

## *Additional Maintenance Resources*

Useful related guidance documents include the following:

- Vegetation resources listed for bioretention
- LID Technical Guidance Manual for Puget Sound:  
<http://www.wastormwatercenter.org/files/library/lid-manual-2012-final-secure.pdf>
- Green Roof ANSI standards developed in conjunction with Green Roofs for Healthy Cities (GRHC). GRHC is a group working to increase awareness of the economic, social, and environmental benefits of vegetated roofs through education and outreach. GRHC standards used for fire and wind uplift design of vegetated roofs are the ANSI RP-14 and VF-1 standards. These standards cover several key design components of vegetated roofs that, once installed, require upkeep to maintain the functionality of these features.
- Integrated Pest Management (IPM) protocols (the term “pest” covers a broad range of species including harmful insects, plant pathogens, rodents, and weedy vegetation) provide an approach to pest control that uses regular monitoring to determine if and when treatments are needed, and employs physical, mechanical, cultural, and biological tactics to keep pest numbers low enough to prevent intolerable damage or annoyance (Ecology 2012c) while avoiding or minimizing the use of pesticides and fertilizers herbicides as a management strategy.
- See EPA’s website for general information on IPM:  
[www.epa.gov/pesticides/factsheets/ipm.htm](http://www.epa.gov/pesticides/factsheets/ipm.htm).
- See the City of Seattle’s website for IPM Fact Sheets and Washington specific resources:  
[www.seattle.gov/util/forbusinesses/landscapes/integrated\\_pest\\_management](http://www.seattle.gov/util/forbusinesses/landscapes/integrated_pest_management)
- The International Society of Arboriculture (ISA) is a group that promotes the professional practice of arboriculture and fosters a greater worldwide awareness of the benefits of trees through research, technology, and education. ISA standards used for managing trees, shrubs, and other woody plants are the American National Standards Institute (ANSI) A300 standards. The ANSI A300 standards are voluntary industry consensus standards developed by the Tree Care Industry Association (TCIA) and written by the Accredited Standards Committee (ASC). The ANSI standards can be found on the ISA website: [www.isa-arbor.com/education/publications/index.aspx](http://www.isa-arbor.com/education/publications/index.aspx).

These resources are supplemental and do not supersede guidance provided in the *Standards and Procedures* tables.

## Equipment and Materials

Table 12 includes recommendations for equipment and materials commonly used to maintain vegetated roofs. Some of the equipment and materials will be used for routine maintenance activities, while other equipment and materials will be necessary for specialized maintenance.

Table 12. Vegetated Roof Equipment and Materials List.	
General gardening and landscaping equipment	Gardening and landscaping materials
<input type="checkbox"/> Gloves <input type="checkbox"/> Weeding tool <input type="checkbox"/> Soil knife <input type="checkbox"/> Hand tamper <input type="checkbox"/> Hoe <input type="checkbox"/> Rake <input type="checkbox"/> Push broom <input type="checkbox"/> Buckets <input type="checkbox"/> Garbage bags (for disposal of noxious weeds)	<input type="checkbox"/> Plants/seeds <input type="checkbox"/> Growing media <input type="checkbox"/> Fertilizer (encapsulated, slow release)
	<b>Erosion control material*</b>
	<input type="checkbox"/> Mulch (intensive roofs) <input type="checkbox"/> Erosion control matting
	<b>Equipment and materials for subsurface or drip irrigation system repairs</b>
<b>Additional equipment for intensive roofs:</b> <input type="checkbox"/> Pruners <input type="checkbox"/> Loppers <input type="checkbox"/> Manual edger <input type="checkbox"/> Line trimmer (also known as a string trimmer, weed eater, or weed whacker) <input type="checkbox"/> Wheelbarrow <input type="checkbox"/> Shovel <input type="checkbox"/> Stakes and guys	<input type="checkbox"/> Soaker hose <input type="checkbox"/> Hose/shower-type wand <input type="checkbox"/> Sprinklers <input type="checkbox"/> Tree watering bags <input type="checkbox"/> Buckets <input type="checkbox"/> Water source, if necessary
	<b>Safety equipment</b>
	<input type="checkbox"/> Fall protection as applicable

\* Items not required for routine maintenance

## Skills and Staffing

The skills required for the maintenance of vegetated roofs are listed in the text box to the right. Additional specialized skills may also be required for corrective maintenance of intensive vegetated roofs such as: horticulturalists and arborists.

The maintenance associated with vegetated roofs may sometimes pose safety hazards and require controls (e.g., fall protection) currently covered under the Washington State Department of Labor & Industries.

Table 13 provides some examples of staffing estimates from the City of Olympia and the BMP and LID Whole Life Cost Models (WERF 2009). The WERF (2009) study provides annual staffing estimates for a “typical”

facility of undefined area, while the City of Olympia provided a staffing estimate as the area of vegetated roof that can be maintained per hour of staff time. Staffing estimates presented below range from 53 to 90 hours per facility from the WERF (2009) study (summing all of the routine maintenance activities) or 2,000 sf/hr for the City of Olympia.

### Skills Needed for Maintenance of Vegetated Roofs

- Landscaping skills (e.g., general plant care)
- Plant identification skills (weeds vs. planted species, invasive vs. common weeds, how to dispose of invasive weeds, timing of weed seed dispersal)
- General drainage system maintenance skills (e.g., subsurface or drip irrigation system repair)
- Roof work safety training
- Engineer and/or landscape architect for major maintenance
- Certified arborist (or equivalently trained staff) for pruning of mature trees (intensive vegetated roofs)

<b>Routine Maintenance Activity</b>	<b>Frequency <sup>a</sup></b>	<b>Annual Staff Hours</b>	<b>Source</b>
Vegetation management	Every 2 months	30 to 60 hours (per facility)	BMP and LID Whole Life Cost Models (WERF 2009)
Irrigation repair	A	5 to 10 hours (per facility)	
Corrective maintenance <sup>b</sup>	A	8 hours (per facility)	
Soil replacement	A	8 hours (per facility)	
Recordkeeping	A	2 to 4 hours (per facility)	
General (no activity specified)	M	2,000 sf/hr	City of Olympia

<sup>a</sup> Frequency: A = Annually; M = Monthly

<sup>b</sup> Membrane patching, re-vegetation, component failure  
sf/hr = square feet per hour



## Downspout Full Infiltration Systems

Downspout full infiltration systems include infiltration trenches or drywells intended only for use in infiltrating runoff from roof downspout drains. Infiltration trenches and drywells are backfilled with washed drain rock, allowing for temporary storage of stormwater runoff in the voids of the drain rock material. Stored runoff gradually infiltrates into the surrounding soil. These systems are considered On-site Stormwater Management BMPs and can be used to help meet Minimum Requirements #5 (On-site Stormwater Management BMPs), #7 (flow control), or both.

### *Key Maintenance Considerations*

The main components of downspout full infiltration systems are listed below with descriptions of their function and key maintenance considerations.

- **Rock trench/well:** Trenches and drywells are excavated depressions filled with uniformly graded washed drain rock. Non-woven geotextile fabric may be used along the walls, bottom, and top of the drain rock. The surface of the trench can be covered with grating, pavement, and/or consist of stone, gabion, sand, or a grassed covered area with a surface inlet. To allow inspection of the drain rock trench/well, some facilities have an observation port (typically installed during construction) that allows monitoring of the water levels in the drain rock bed to determine if the facility is dewatering properly.
- **Inlet:** Stormwater runoff is typically routed to a trench/well with a solid-wall pipe and then distributed into the drain rock bed using a perforated or slotted subsurface pipe. Some trenches are designed to receive sheet flow that enters the facility by infiltrating through a top course of drain rock or sand. Maintenance must be performed to ensure inlets (e.g., pipes) are unobstructed and that surface sheet flow first passes through a grass buffer strip to remove larger sediment particles.
- **Storage sump:** Trenches and drywells designed to receive concentrated flows (e.g., piped flow) typically include a storage sump to settle particulates from inflow. Concentrated flows must be distributed into the aggregate using a perforated or slotted subsurface pipe. The sump must be maintained to remove accumulated sediment.

### *Key Operations to Preserve Facility Function*

When the rock trench/well is designed to receive inflow from the surface via a grate or by infiltrating through an exposed top course of drain rock or sand, the following operational actions can limit the need for corrective maintenance actions or replacement:

- Protecting the surface inlet from stockpiles of landscaping materials (e.g., mulch, soil, compost)
- Prevent discharge of debris to the infiltration trench from roof cleaning practices (e.g., moss removal)

- Stabilize adjacent landscaped areas to avoid runoff mobilizing soil into the surface inlet

### *Maintenance Standards and Procedures*

Table 14 provides the recommended maintenance frequencies, standards, and procedures for downspout full infiltration system components. The level of routine maintenance required and the frequency of corrective maintenance actions may increase for facilities subject to high sediment loads from the contributing drainage area.

**Table 14. Maintenance Standards and Procedures for Downspout Full Infiltration Systems.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Rock Trench/Well</b>				
Surface of trench/well (i.e., water enters through exposed aggregate)	Fall and Spring		Accumulated trash, debris, or sediment on drain rock surface impedes sheet flow into facility	Remove/dispose in accordance with local solid waste requirements
	A, W		Vegetation/moss present on drain rock surface impedes sheet flow into facility	Maintain open, freely draining drain rock surface
Drain rock	Fall and Spring		<ul style="list-style-type: none"> <li>• If water enters the facility from the surface, inspect to see if water is ponding at the surface during storm events</li> <li>• If buried drain rock, observe drawdown through observation port or cleanout</li> </ul>	<ul style="list-style-type: none"> <li>• Clear piping through facility when ponding occurs</li> <li>• Replace rock/sand reservoirs as necessary</li> <li>• Tilling of subgrade below reservoir may be necessary (for trenches) prior to backfill</li> </ul>
<b>Inlet/ Outlet Pipe Conveyance</b>				
Pipe(s)	A, W		Accumulation of trash, debris, or sediment in roof drains, gutters, driveway drains, area drains, etc.	Remove/ dispose
	A, W		Pipe from sump to trench or drywell has accumulated sediment or is plugged	Clear sediment from inlet/outlet pipe screen and inlet/outlet pipe
	A, W		Cracked, collapsed, broken, or misaligned drain pipes	<ul style="list-style-type: none"> <li>• Repair/seal cracks</li> <li>• Replace when repair is insufficient</li> </ul>
Roof downspout	B, W		Splash pad missing or damaged	Repair/ replace
	A, W		Leaves or other debris plugging downspout	Remove/ dispose

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); W= At least one visit should occur during the wet season (for debris/clog related maintenance, this inspection/maintenance visit should occur in the early fall, after deciduous trees have lost their leaves).

**Table 14 (continued). Maintenance Standards and Procedures for Downspout Full Infiltration Systems.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Storage Sump</b>				
Sump	A		Sediment in the sump	Remove/ dispose in accordance with local solid waste requirements
Access lid	A		Cannot be easily opened	Repair/ replace
	A		Buried	Refer to record drawings for design intent. If the access lid was designed to be exposed, expose and restore to surface grade
	A		Cover missing	Replace

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); W= At least one visit should occur during the wet season (for debris/clog related maintenance, this inspection/maintenance visit should occur in the early fall, after deciduous trees have lost their leaves).

## Equipment and Materials

Table 15 includes recommendations for equipment and materials commonly used to maintain downspout full infiltration systems.

Table 15. Downspout Full Infiltration System Equipment and Materials List.	
<b><i>Pipe/ structure system inspection and maintenance equipment</i></b>	<b><i>Weed / vegetation removal equipment, such as:</i></b>
<input type="checkbox"/> Hand tools <input type="checkbox"/> Flashlight <input type="checkbox"/> Mirror (for viewing pipes without entering structure) <input type="checkbox"/> Garden hose <input type="checkbox"/> Plumbing snake	<input type="checkbox"/> Weeding tools <input type="checkbox"/> Weed burner <input type="checkbox"/> Buckets
	<b><i>Equipment to clear accumulated sediment from sump</i></b>
	<input type="checkbox"/> Shop-Vac <input type="checkbox"/> Shovel

## Skills

The skills required for the maintenance of downspout full infiltration systems are listed in the text box to the right.

### *Skills Needed for Maintenance of Downspout Full Infiltration Systems*

- General drainage system maintenance skills (e.g., inlet/pipe cleaning experience, inlet/pipe maintenance or repair experience)
- Landscape or drainage contractor for major maintenance



## Downspout, Sheet Flow, and Concentrated Dispersion Systems

Dispersion attenuates peak flows by slowing the runoff entering into the conveyance system, allowing some infiltration, and providing some water quality benefits. The following three types of dispersion systems are covered in this section:

- **Downspout dispersion systems:** Splash blocks or gravel-filled trenches, which serve to spread roof runoff over vegetated pervious areas.
- **Sheet flow dispersion systems:** Sheet flow dispersion is the simplest method of runoff control. This BMP can be used for any impervious or pervious surface that is graded to avoid concentrating flows. Because flows are already dispersed as they leave the surface, they need only traverse a narrow band of adjacent vegetation for effective attenuation and treatment.
- **Concentrated dispersion systems:** Dispersion of concentrated flows from driveways or other pavement through a vegetated pervious area.

### *Key Maintenance Considerations*

The main components of dispersion systems are listed below with descriptions of their function and key maintenance considerations.

- **Splash block (downspout dispersion):** Splash blocks are used to spread stormwater runoff from a downspout drain over vegetated pervious area. A downspout extension may be included if the ground is fairly level, if the structure includes a basement, or if foundation drains are proposed.
- **Dispersion trench (downspout dispersion):** Gravel-filled trenches are also used to spread stormwater runoff from a downspout drain over a vegetated pervious area. Downspout drains are routed to a trench via a perforated or slotted pipe. The trench typically includes a notched grade board or other device to distribute flow equally along the length of the trench. This board must be maintained at a level grade to prevent concentrated flow. Downspout drains are directed to the trench via a storage sump that must be maintained to remove accumulated sediment.
- **Transition zone (sheet flow dispersion):** A 2-foot-wide transition zone is typically included to discourage channeling between the edge of the impervious surface (or building eaves) and the downslope vegetation. This transition zone may consist of an extension of subgrade material (crushed rock), modular pavement, drain rock, or other material.
- **Rock pad at discharge point (concentrated flow dispersion):** A rock pad must be maintained at any point that a concentrated flow enters a dispersion area.
- **Dispersal area:** Stormwater is dispersed to an area vegetated with well-established lawn or pasture, landscaping with well-established groundcover, or native vegetation with natural groundcover. The required vegetated flow path is 50 feet for splash

blocks and concentrated dispersion, 25 feet when using a dispersion trench and varies for sheet flow dispersion. The groundcover for the extent of the flow must be maintained to be dense enough to help disperse and infiltrate flows and to prevent erosion.

### *Key Operations to Preserve Facility Function*

For dispersion practices to be effective, the dispersion area must remain covered with dense, well-established vegetation. Site uses should protect vegetation and avoid compaction.

### *Maintenance Standards and Procedures*

Table 16 provides the recommended maintenance frequencies, standards, and procedures for dispersion system components.



**Table 16. Maintenance Standards and Procedures for Downspout, Sheet Flow, and Concentrated Dispersion Systems.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Splash Block (Downspout Dispersion)</b>				
Splash block	B		Water is being directed towards building structure	Reconfigure/ repair blocks to direct water away from building structure
	B		Water disrupts soil media	Reconfigure/ repair blocks
<b>Transition Zone (Sheet Flow Dispersion)</b>				
Transition zone	A		Adjacent soil erosion; uneven surface creating concentrated flow discharge; or less than 2 foot of width	Repair/replace transition zone to meet design criteria and eliminate concentrated flows
<b>Dispersion Trench (Downspout Dispersion)</b>				
Dispersion trench	A		Visual evidence of water discharging at concentrated points along trench (normal condition is a "sheet flow" from edge of trench; intent is to prevent erosion damage)	<ul style="list-style-type: none"> <li>Remove debris from trench surface, if necessary</li> <li>Realign notched grade board or other distributor type, if possible</li> <li>Rebuild trench to standards, if necessary</li> </ul>
Surface of trench	Fall and Spring		Accumulated trash, debris, or sediment on drain rock surface impedes sheet flow from facility	Remove/dispose in accordance with local solid waste requirements
	A, W		Vegetation/moss present on drain rock surface impedes sheet flow from facility	Maintain open, freely draining drain rock surface
Pipe(s) to trench	A, W		Accumulation of trash, debris, or sediment in roof drains, gutters, driveway drains, area drains, etc.	Remove/ dispose
	A, W		Pipe from sump to trench or drywell has accumulated sediment or is plugged	Clear sediment from inlet/outlet pipe screen and inlet/outlet pipe
	A, W		Cracked, collapsed, broken, or misaligned drain pipes	<ul style="list-style-type: none"> <li>Repair/seal cracks</li> <li>Replace when repair is insufficient</li> </ul>
Sump	A		Sediment in the sump	<ul style="list-style-type: none"> <li>Remove/ dispose in accordance with local solid waste requirements</li> <li>Clear sediment from inlet/outlet pipe screen and/or inlet/outlet pipe</li> </ul>
Access lid	A		Cannot be easily opened	Repair/ replace
	A		Buried	Refer to record drawings for design intent. If the access lid was designed to be exposed, expose and restore to surface grade
	A		Cover missing	Replace
<b>Rock Pad (Concentrated Flow Dispersion)</b>				
Rock pad	A		Only one layer of rock exists above native soil in area 6 square feet or larger, or any exposure of native soil	<ul style="list-style-type: none"> <li>Replace/ repair rock pad to meet design standards</li> <li>Enlarge pad size or add additional courses of rock, if necessary</li> </ul>
	A		Soil erosion in or adjacent to rock pad	Repair/replace rock pad to meet design standards
<b>Dispersal Area</b>				
Dispersal area (general)	B, S		Erosion (gullies/ rills) greater than 2 inches deep in dispersal area	Eliminate cause of erosion and stabilize damaged area (regrade, rock, revegetate)
	B, S		Accumulated sediment or debris to extent that blocks or channelizes flow path	<ul style="list-style-type: none"> <li>Remove excess sediment or debris</li> <li>Identify and control the sediment source (if feasible)</li> </ul>
Ponded water	B, S		Standing surface water in dispersion area remains for more than 3 days after the end of a storm event	Identify the cause of the standing water (e.g., grade depressions, compacted soil) and take appropriate actions to address the problem (e.g., regrade to eliminate depressions or aerate/ amend soils)

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); W = At least once during the wet season (for debris/clog related maintenance, this visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during plant establishment period (1-2 years, or additional 3rd year during extreme dry weather). IPM – Integrated Pest Management



Table 16 (continued). Maintenance Standards and Procedures for Downspout, Sheet Flow, and Concentrated Dispersion Systems.

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>Dispersal Area (cont'd)</b>				
Plant establishment	B	Once every 1-2 weeks or as needed during prolonged dry periods <sup>b</sup>	Dispersal area vegetation in establishment period (1-2 years, or additional 3rd year during extreme dry weather)	Water weekly during periods of no rain to ensure plant establishment
Vegetation	As needed		Poor vegetation cover such that erosion is occurring	<ul style="list-style-type: none"> <li>• Ensure proper care (e.g., watering)</li> <li>• Assess for nutrient deficiencies</li> <li>• Replant as needed with appropriate plant species for the soil and moisture conditions</li> <li>• Consider amending soils to promote plant health</li> </ul>
	B, S		Vegetation inhibits dispersed flow along flow path	Trim, weed or replant to restore dispersed flow path
<b>Storage Sump</b>				
Sump	A		Accumulated sediment in the sump	<ul style="list-style-type: none"> <li>• Remove/ dispose in accordance with local solid waste requirements</li> <li>• Clear sediment from inlet/outlet pipe screen and/or inlet/outlet pipe</li> </ul>
Access lid	A		Cannot be easily opened	Repair/ replace
	A		Buried	Expose and restore to surface grade
	A		Cover missing	Replace
<b>Pest Control</b>				
General Pests	As needed		Signs of pest infestations (IPM protocol threshold(s) are exceeded)	<ul style="list-style-type: none"> <li>• Follow IPM protocols for weed and pest management (see "Additional Maintenance Resources" in Bioretention Facilities section for more information on IPM protocols)</li> </ul>
Mosquitoes	B, S		Standing surface water in dispersion area remains for more than 3 days after the end of a storm	<ul style="list-style-type: none"> <li>• Identify the cause of the standing water and take appropriate actions to address the problem (see "Ponded water")</li> <li>• Do not use pesticides or <i>Bacillus thuringiensis israelensis</i> (Bti)</li> </ul>
Rodents	As needed		Rodent holes or mounds disturb dispersion flow paths	Fill and compact soil around the holes and vegetate to restore flow path

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); W = At least once during the wet season (for debris/clog related maintenance, this visit should occur in the early fall, after deciduous trees have lost their leaves); S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).

<sup>b</sup> Inspection should occur during plant establishment period (1-2 years, or additional 3rd year during extreme dry weather).



## Equipment and Materials

Table 17 includes recommendations for equipment and materials commonly used to maintain downspout, sheet flow, and concentrated dispersion systems.

Table 17. Downspout, Sheet Flow, and Concentrated Dispersion Systems Equipment and Materials List.	
<i>Pipe/ structure system inspection and maintenance equipment</i>	<i>General landscaping equipment and materials to maintain dispersal area</i>
<input type="checkbox"/> Hand tools <input type="checkbox"/> Flashlight <input type="checkbox"/> Mirror (for viewing pipes without entering structure) <input type="checkbox"/> Garden hose <input type="checkbox"/> Plumbing snake <input type="checkbox"/> Level	<input type="checkbox"/> Mower <input type="checkbox"/> Gloves <input type="checkbox"/> Weeding tool <input type="checkbox"/> Soil knife <input type="checkbox"/> Manual edger <input type="checkbox"/> Line trimmer (also known as a string trimmer, weed eater, or weed whacker) <input type="checkbox"/> Hoe <input type="checkbox"/> Rake <input type="checkbox"/> Shovel <input type="checkbox"/> Push broom <input type="checkbox"/> Compost <input type="checkbox"/> Seeds <input type="checkbox"/> Plants <input type="checkbox"/> Watering equipment
<i>Equipment to clear accumulated sediment from sump</i>	
<input type="checkbox"/> Shop-Vac <input type="checkbox"/> Shovel	
<i>Material to replenish rock pad for concentrated dispersion</i>	
<input type="checkbox"/> Aggregate	

\* Items not required for routine maintenance

## Skills

The skills required for the maintenance of downspout, sheet flow, and concentrated dispersion systems are listed in the text box to the right. Additional specialized skills may also be required for corrective maintenance such as: horticulturalists, arborists, erosion control specialists, and soil scientists.

### Skills Needed for Maintenance of Dispersion Systems

- General drainage system maintenance skills (e.g., inlet/pipe cleaning experience, inlet/pipe maintenance or repair experience)
- Landscaping skills (e.g., general plant care)
- Landscape or drainage contractor for major maintenance



## Compost-amended Soils

Naturally occurring (undisturbed) soil and vegetation provide important stormwater functions including: water infiltration; nutrient, sediment, and pollutant adsorption; sediment and pollutant biofiltration; water interflow storage and transmission; and pollutant decomposition. Compaction from construction can reduce the soils natural ability to provide these functions. Establishing a minimum soil quality and depth in the post-development landscape can regain some of these stormwater functions including increased treatment of pollutants and sediments that result from development and habitation, and minimizes the need for some landscaping chemicals. Sufficient organic content is a key to soil quality. Soil organic matter can be attained through numerous amendments such as compost, composted woody material, biosolids, and forest product residuals.

### *Key Maintenance Considerations*

Key maintenance considerations for compost-amended soils include the replenishment of soil media as needed (as a result of erosion) and addressing compacted, poorly draining soils. Site uses should protect vegetation and avoid compaction.

### *Key Operations to Preserve Facility Function*

The full benefits of compost-amended soils are realized when desired soil media depths are maintained and soil compaction is minimized. Care should be taken to prevent compaction of soils via vehicular loads and/or excessive foot traffic, especially during wet conditions.

### *Maintenance Standards and Procedures*

Table 18 provides the recommended maintenance frequencies, standards, and procedures for compost-amended soils. The level of routine maintenance required and the frequency of corrective maintenance actions may increase for facilities prone to erosion due to site conditions such as steep slopes or topography tending to concentrate flows.


**Table 18. Maintenance Standards and Procedures for Compost-amended Soils.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>General</b>				
Soil media (maintain high organic soil content)	A		Vegetation not fully covering ground surface or vegetation health is poor	<ul style="list-style-type: none"> <li>• Maintain 2 to 3 inches of mulch over bare areas in landscape beds</li> <li>• Add plants if sufficient space</li> <li>• Re-seed bare turf areas until the vegetation fully covers ground surface</li> </ul>
		Ongoing	None (routine maintenance)	Return leaf fall and shredded woody materials from the landscape to the site when possible in order to replenish soil nutrients and structure
		Ongoing	None (routine maintenance)	On turf areas, “grasscycle” (mulch-mow or leave the clippings) to build turf health
		Ongoing	None (routine maintenance)	Avoiding use of pesticides (bug and weed killers), like “weed & feed”, which damage the soil
		A	None (routine maintenance)	<ul style="list-style-type: none"> <li>• Where fertilization is needed (mainly turf and annual flower beds), a moderate fertilization program should be used which relies on compost, natural fertilizers or slow-release synthetic balanced fertilizers</li> <li>• Follow IPM protocols for fertilization procedures (see “Additional Maintenance Resources” in Bioretention Facilities section for more information on IPM protocols)</li> </ul>
Soil media (maintain infiltration)	A <sup>b</sup>		Soils become waterlogged, do not appear to be infiltrating	<ul style="list-style-type: none"> <li>• To remediate compaction, aerate soil, till to at least 8-inch depth, or further amend soil with compost and re-till</li> <li>• If areas are turf, aerate compacted areas and topdress them with 1/4 to 1/2 inch of compost to renovate them</li> <li>• If drainage is still slow, consider investigating alternative causes (e.g., high wet season groundwater levels, low permeability soils)</li> <li>• Also consider site use and protection from compacting activities</li> </ul>

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); M = monthly; S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval); W = At least one inspection/maintenance visit should occur during the wet season (for debris/clog related maintenance, this maintenance visit should occur in the early fall, after deciduous trees have lost their leaves).

<sup>b</sup> Inspection should occur during storm event.

IPM – Integrated Pest Management





**Table 18 (continued). Maintenance Standards and Procedures for Compost-amended Soils.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>General (cont'd)</b>				
Erosion/ Scouring	A, W, S		Areas of potential erosion are visible	<ul style="list-style-type: none"> <li>Identify and address cause of erosion (e.g., concentrate flow entering area, channelization of runoff) and stabilize damaged area (regrade, rock, vegetation, erosion control matting)</li> <li>For deep channels or cuts (over 3 inches in ponding depth), temporary erosion control measures should be put in place until permanent repairs can be made.</li> </ul>
Grass/ Vegetation		A	Less than 75% of planted vegetation is healthy with a generally good appearance.	<ul style="list-style-type: none"> <li>Take appropriate maintenance actions (e.g., remove/ replace plants)</li> <li>If problem persists, evaluate if vegetation is appropriate for the location (e.g., exposure, soil, soil moisture)</li> </ul>
Noxious weeds		M (March – October, preceding seed dispersal)	Listed noxious vegetation is present (refer to current county noxious weed list)	<ul style="list-style-type: none"> <li>By law, class A &amp; B noxious weeds must be removed, bagged and disposed as garbage immediately</li> <li>Reasonable attempts must be made to remove and dispose of class C noxious weeds</li> <li>Watch for and respond to new occurrences of especially aggressive weeds such as Himalayan blackberry, Japanese knotweed, morning glory, English ivy, and reed canary grass to avoid invasions</li> <li>It is strongly encouraged that herbicides and pesticides not be used in order to protect water quality; use of herbicides and pesticides may be prohibited in some jurisdictions</li> </ul>

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); M = monthly; S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).; W = At least one inspection/maintenance visit should occur during the wet season (for debris/clog related maintenance, this maintenance visit should occur in the early fall, after deciduous trees have lost their leaves).

<sup>b</sup> Inspection should occur during storm event.

IPM – Integrated Pest Management

**Table 18 (continued). Maintenance Standards and Procedures for Compost-amended Soils.**

Component	Recommended Frequency <sup>a</sup>		Condition when Maintenance is Needed (Standards)	Action Needed (Procedures)
	Inspection	Routine Maintenance		
<b>General (cont'd)</b>				
Weeds		M (March – October, preceding seed dispersal)	Weeds are present	<ul style="list-style-type: none"> <li>Remove weeds with their roots manually with pincer-type weeding tools, flame weeders, or hot water weeders as appropriate</li> <li>Follow IPM protocols for weed management(see “Additional Maintenance Resources” in Bioretention Facilities section for more information on IPM protocols)</li> </ul>

<sup>a</sup> Frequency: A= Annually; B= Biannually (twice per year); M = monthly; S = Perform inspections after major storm events (24-hour storm event with a 10-year or greater recurrence interval).; W = At least one inspection/maintenance visit should occur during the wet season (for debris/clog related maintenance, this maintenance visit should occur in the early fall, after deciduous trees have lost their leaves).

<sup>b</sup> Inspection should occur during storm event.

IPM – Integrated Pest Management

## Equipment and Materials

Table 19 includes recommendations for equipment and materials commonly used to maintain compost-amended soils. Some of the equipment and materials will be used for routine maintenance activities, while other equipment and materials will be necessary for specialized maintenance.

Table 19. Compost Amended Soils Equipment and Materials List.	
<b>General landscaping equipment</b>	
<input type="checkbox"/>	Gloves
<input type="checkbox"/>	Pincer-type weeding tool
<input type="checkbox"/>	Soil knife
<input type="checkbox"/>	Pruners
<input type="checkbox"/>	Loppers
<input type="checkbox"/>	Hoe
<input type="checkbox"/>	Rake
<input type="checkbox"/>	Wheelbarrow
<input type="checkbox"/>	Shovel
<input type="checkbox"/>	Push broom
<input type="checkbox"/>	Garbage bags (for disposal of noxious weeds)
<b>General landscaping materials</b>	
<input type="checkbox"/>	Arborist wood chip mulch (around trees and woody plants)
<input type="checkbox"/>	Compost or leaf mulch (around annuals)
<input type="checkbox"/>	Fertilizer (natural fertilizers or slow-release synthetic balanced fertilizers)
<b>Specialized equipment*</b>	
<input type="checkbox"/>	Deep tine aerator and compost (or compost/sand mixture) to fill aeration holes (if necessary to correct overly compacted soil)
<input type="checkbox"/>	Flame weeder or hot water weeder
<input type="checkbox"/>	Rototiller
<input type="checkbox"/>	Soil probe

\* Items not required for routine maintenance

## Skills

The skills required for the maintenance of compost-amended soils are listed in the text box to the right. Additional specialized skills may also be required for corrective maintenance of compost-amended soils such as: horticulturalists, arborists, erosion control specialists, and soil scientists.

### Skills Needed for Maintenance of Compost-amended Soils

- Landscaping skills (e.g., general plant care)
- Landscaper for major maintenance



# PROGRAMMATIC AND ADMINISTRATIVE GUIDANCE

To implement the new Phase I Permit and Phase II Permit requirements for LID BMP maintenance, local governments may face a variety of programmatic and administrative challenges. This section summarizes Ecology's requirements that relate to LID BMP maintenance and provides guidance regarding administrative tools for implementing these requirements.

This section is not intended to identify specific administrative actions for meeting LID BMP maintenance requirements (e.g., specify how jurisdictions administer bonds) but rather to support jurisdictions by providing optional and flexible guidance for administrative procedures and tools related to LID BMP maintenance programs.

## Ecology Requirements for LID BMP Maintenance Programs

Phase I and Phase II municipal stormwater Permittees are required to:

- Adopt an ordinance or other enforceable mechanism requiring maintenance of all permanent Stormwater Treatment and Flow Control BMPs/Facilities
- Adopt maintenance standards that are at least as protective of facility function as those in Chapter 4 of Volume V of the 2012 Stormwater Management Manual for Western Washington (2012 SWMMWW)
- Establish legal authority to inspect private stormwater facilities and enforce maintenance standards
- Implement permitting, plan review, inspections, and enforcement programs to meet the Permit standards for both private and public projects

To implement these requirements, Permittees may need to revise their programs and procedures to support plan review, inspection, enforcement, record keeping, and mapping for LID BMPs. Tables 20 and 21 summarize and reference municipal Permit requirements and 2012 SWMMWW guidance in regard to O&M of LID BMPs. Please refer to the Permits and 2012 SWMMWW for more complete and accurate descriptions.

**Table 20. Phase I Permit<sup>4</sup> Requirements and 2012 SWMMWW Guidance Related to LID BMP Maintenance Programs.**

Requirement	LID BMP Type	
	On-site Stormwater Management BMPs	Stormwater Treatment and Flow Control BMPs/Facilities (MR #6 and/or MR #7)
<b>Standards</b>		
Implement maintenance standards	S5.C.9.a	S5.C.9.a
Update ordinance or other enforceable documents	N/A	S5.C.9.b.i
Implement practices, policies, & procedures to reduce stormwater impacts associated with runoff	N/A	S5.C.9.e
<b>Plan Review</b>		
Verify that a maintenance plan is completed and responsibility for maintenance is assigned for each Stormwater Treatment and Flow Control BMP	N/A	S5.C.5.a.v.4
Verify submission of maintenance instructions for each On-site Stormwater Management BMP	Vol. I, Section 3.1.5	Vol. 1, Section 3.1.5
Verify that an O&M manual is complete for each Stormwater Treatment and Flow Control BMP	N/A	Appendix 1 (Section 4.9) and Vol. 1, Section 3.1.7
Review and approve declaration of covenant (including design details, figures, and maintenance instructions for each On-site Stormwater Management BMP) and grant of easement	Vol. 1, Section 3.1.7	Vol. 1, Section 3.1.7
<b>Inspections</b>		
Legal authority to inspect private stormwater facilities and enforce maintenance standards for all new and redevelopment	S5.C.5.a.iv	S5.C.5.a.iv
Conduct post-construction inspections to ensure proper installation	S5.C.5.a.v.4	S5.C.5.a.v.4
Conduct inspections during construction for all permanent Stormwater Treatment and Flow Control BMPs/Facilities and catch basins in new residential developments (every 6 months until 90% of the lots are constructed or when construction is stopped and the site is fully stabilized)	N/A	S5.C.9.b.iii
Conduct ongoing annual inspections	N/A	S5.C.9.b.ii and c.i
Perform spot checks of potentially damaged BMPs owned or operated by the Permittee after major storm events	N/A	S5.C.9.c.ii

BMPs = best management practices

N/A = not applicable

Note: Phase I Permit references are from Ecology (2012a) and 2012 SWMMWW references are from Ecology (2012c).

<sup>4</sup> The special conditions listed in this document are for city and county permittees. Secondary permittees should refer Section S6 of the permit for their special conditions that pertain to LID BMP maintenance.

**Table 20 (continued). Phase I Permit Requirements and 2012 SWMMWW Guidance Related to LID BMP Maintenance Programs.**

Requirement	LID BMP Type	
	On-site Stormwater Management BMPs	Stormwater Treatment and Flow Control BMPs/Facilities (MR #6 and/or MR #7)
<b>Enforcement</b>		
Enforce compliance with maintenance standards as needed based on inspections	N/A	S5.C.9.b.ii
<b>Training</b>		
Train staff involved in plan review, permitting, construction site inspections, and enforcement.	S5.C.5.a.vii	S5.C.5.a.vii
Implement an ongoing training program for employees who have primary O&M job functions that may impact stormwater quality	S5.C.9.f	S5.C.9.f
<b>Record Keeping</b>		
Keep records of inspections and enforcement actions (e.g., inspection reports, notices of violations)	S5.C.5.a.v.6 and S5.C.9.h	S5.C.5.a.v.6 and S5.C.9.h
<b>Mapping</b>		
Scale drawing of the lot(s), and any public-right-of-way that displays the location of On-site Stormwater Management BMPs	Vol. I, Section 3.1.5	Vol. I, Section 3.1.5
Map Stormwater Treatment and Flow Control BMPs/Facilities owned or operated by the Permittee	N/A	S5.C.2.a.iii
Map connections between Stormwater Treatment and Flow Control BMPs/Facilities and tributary conveyances mapped in accordance with S5.C.2	N/A	S5.C.2.b.iv

BMPs = best management practices

N/A = not applicable

Note: Phase I Permit references are from Ecology (2012a) and 2012 SWMMWW references are from Ecology (2012c).

**Table 21. Phase II<sup>5</sup> WWA Permit Requirements and 2012 SWMMWW Guidance Related to LID BMP Maintenance Programs.**

Requirement	LID BMP Type	
	On-site Stormwater Management BMPs	Stormwater Treatment and Flow Control BMPs/Facilities (MR #6 and/or MR #7)
<b>Standards</b>		
Implement maintenance standards	S5.C.5.a	S5.C.4.c.ii and S5.C.5.a
Adopt and make effective ordinance or other enforceable mechanisms	N/A	S5.C.4.a
Implement practices, policies, & procedures to reduce stormwater impacts associated with runoff	N/A	S5.C.5.f
<b>Plan Review</b>		
Verify that maintenance plan is completed and responsibility for maintenance is assigned for each Stormwater Treatment and Flow Control BMP.	N/A	S5.C.4.b.iv
Verify submission of maintenance instructions for each On-site Stormwater Management BMP	Vol. I, Section 3.1.5	Vol. 1, Section 3.1.5
Verify that an O&M manual is complete for each Stormwater Treatment and Flow Control BMP	N/A	Appendix 1 (Section 4.9) and Vol. 1, Section 3.1.7
Review and approve declaration of covenant (including design details, figures and maintenance instructions for each BMP) and grant of easement	Vol. 1, Section 3.1.7	Vol. 1, Section 3.1.7
<b>Inspections</b>		
Legal authority to inspect private stormwater facilities and enforce maintenance standards for all new and redevelopment	S5.C.4.a.iii	S5.C.4.a.iii
Conduct post-construction inspections to ensure proper installation	S5.C.4.a.iv	S5.C.4.a.iv
Conduct inspections during construction for all permanent Stormwater Treatment and Flow Control BMPs/Facilities in new residential developments (every 6 months until 90% of the lots are constructed or when construction is stopped and the site is fully stabilized)	N/A	S5.C.4.c.iv
Conduct ongoing annual inspections	N/A	S5.C.4.c.iii and S5.C.5.b
Perform spot checks of potentially damaged BMPs owned or operated by the Permittee after major storm events	N/A	S5.C.5.c

BMPs = best management practices

N/A = not applicable

Note: Phase II Permit references are from Ecology (2012b) and 2012 SWMMWW references are from Ecology (2012c).

<sup>5</sup> The special conditions listed in this document are for city and county permittees. Secondary permittees should refer Section S6 of the permit for their special conditions that pertain to LID BMP maintenance.



**Table 21 (continued). Phase II WWA Permit Requirements and 2012 SWMMWW Guidance Related to LID BMP Maintenance Programs.**

Requirement	LID BMP Type	
	On-site Stormwater Management BMPs	Stormwater Treatment and Flow Control BMPs/Facilities (MR #6 and/or MR #7)
<b>Enforcement</b>		
Enforce compliance with maintenance standards as needed based on inspections	N/A	S5.C.4.b.iii and iv
<b>Training</b>		
Train staff involved in plan review, permitting, construction site inspections, and enforcement.	S5.C.4.e	S5.C.4.e
Implement an ongoing training program for employees who have primary O&M job functions that may impact stormwater quality	S5.C.5.g	S5.C.5.g
<b>Record Keeping</b>		
Keep records of inspections and enforcement actions (e.g., inspection reports, notices of violations)	S5.C.4.c.vii and S5.C.5.i	S5.C.4.c.vii and S5.C.5.i
<b>Mapping</b>		
Scale drawing of the lot(s), and any public-right-of-way that displays the location of On-site Stormwater Management BMPs	Vol. I, Section 3.1.5	Vol. I, Section 3.1.5
Map Stormwater Treatment and Flow Control BMPs/Facilities owned or operated by the Permittee	N/A	S5.C.3.a.iii

BMPs = best management practices

N/A = not applicable

Note: Phase II Permit references are from Ecology (2012b) and 2012 SWMMWW references are from Ecology (2012c).



## Tools for Implementing an LID Maintenance Program

This section discusses a range of administrative tools available to assist jurisdictions in implementing the LID BMP maintenance requirements outlined above. The following key tools are discussed in detail below.

- Stormwater code/manual
- Legal agreements (such as declarations of covenant and access easements between a property owner and the City/County)
- Project-specific BMP maintenance requirements
- Financial surety measures
- Record keeping and tracking process
- Inspection programs
- Mapping
- Private property owner education

Table 22 summarizes the utility of these tools for typical elements of a maintenance program (e.g., plan review, inspection program). A local government can select and tailor the tools described in this section to meet Permit requirements in a manner that fits within their existing program.



**Table 22. Administrative Tools to Implement O&M Programs.**

Maintenance Program Element	Administrative Tool
<b>Maintenance Requirements</b>	
Require maintenance of all permanent Stormwater Treatment and Flow Control BMPs/Facilities	<ul style="list-style-type: none"> <li>Stormwater code/manual</li> </ul>
Set forth minimum inspection and O&M requirements	<ul style="list-style-type: none"> <li>Stormwater code/manual</li> </ul>
<b>Plan Review</b>	
Define permitting and plan review process to meet NPDES Permit requirements for both private and public projects	<ul style="list-style-type: none"> <li>Stormwater code/manual</li> <li>Permitting and plan review processes are typically streamlined or modified for public projects</li> </ul>
List required development project submittal elements	<ul style="list-style-type: none"> <li>Stormwater code/manual</li> </ul>
Identify and characterizes stormwater features on site	<ul style="list-style-type: none"> <li>Stormwater Site Plan including scale drawing of the lot(s), and any public-right-of-way that displays the location of On-site Stormwater Management BMPs</li> <li>Legal agreements/documents should include scale drawings, design details, figures, and maintenance instructions as attachments or refer to building permit, plan, or document in public files</li> </ul>
Provide project-specific (or BMP-specific) inspection, operation, and maintenance requirements	<ul style="list-style-type: none"> <li>Legal agreements (direct responsible party to code and/or project-specific maintenance requirements)</li> <li>Stormwater code/manual provides general requirements</li> <li>Project-specific maintenance requirements include maintenance instructions for each On-site Stormwater Management BMP and project O&amp;M manual for each Stormwater Treatment and Flow Control BMP/Facility</li> <li>Private property owner education</li> </ul>
Identify the party responsible for the retention, protection and maintenance of the BMPs	<ul style="list-style-type: none"> <li>Stormwater code/manual sets forth requirements for legal agreements</li> <li>Legal agreements describe maintenance responsibility</li> </ul>
Describe how the responsibility for maintenance is transferred when property ownership changes	<ul style="list-style-type: none"> <li>Stormwater code/manual sets forth requirements for legal agreements</li> <li>Legal agreements describe maintenance responsibility</li> </ul>
<b>Inspection</b>	
Set forth inspection process to meet NPDES Permit requirements for both private and public projects	<ul style="list-style-type: none"> <li>Stormwater code/manual or internal procedures</li> </ul>
Establish legal authority of local government to inspect private stormwater facilities	<ul style="list-style-type: none"> <li>Stormwater code/manual sets forth requirements for legal agreements</li> <li>Legal agreements help allow access for inspection</li> </ul>
Ensure proper construction of BMPs	<ul style="list-style-type: none"> <li>Inspections during construction and immediately after construction</li> <li>Inspection checklists</li> </ul>
Ensure long-term maintenance of BMPs	<ul style="list-style-type: none"> <li>Ongoing annual inspections and inspections after large storm events (review record drawings during inspection)</li> <li>Inspection checklists</li> </ul>
<b>Enforcement</b>	
Set forth enforcement process to meet NPDES Permit requirements for both private and public projects	<ul style="list-style-type: none"> <li>Stormwater code/manual or internal procedures</li> <li>Enforcement processes may not be necessary for public projects, but are helpful to include in contractor specifications/contract language</li> </ul>
Establish legal authority of local government to enforce BMP maintenance standards	<ul style="list-style-type: none"> <li>Stormwater code/manual</li> </ul>
Establish enforcement mechanisms, such as fee triggers and schedule for unmaintained facilities	<ul style="list-style-type: none"> <li>Stormwater code/manual lists escalating enforcement actions</li> <li>Stormwater code/manual sets forth requirement for financial surety measures (e.g., bonds) for development plats to guarantee maintenance of BMPs after construction</li> </ul>



Table 22 (continued). Administrative Tools to Implement O&M Programs.	
Maintenance Program Element	Administrative Tool
<b>Record Keeping and Tracking Process</b>	
Keep records of inspections and enforcement actions (e.g., inspection reports, notices of violations)	<ul style="list-style-type: none"> <li>Develop interdepartmental record keeping and tracking process</li> </ul>
<b>Mapping</b>	
Implement ongoing program for mapping BMPs	<ul style="list-style-type: none"> <li>Update mapping program as needed, including procedures for mapping distributed LID BMPs within a larger development.</li> </ul>
<b>Education/Training</b>	
Train inspectors and staff on LID maintenance	<ul style="list-style-type: none"> <li>Develop / update internal training program</li> <li>Develop /update a public outreach and education program for LID maintenance</li> </ul>
Train developers and contractors on LID maintenance	<ul style="list-style-type: none"> <li>Develop and provide training on LID maintenance requirements in stormwater code/manual or internal procedures</li> </ul>





## Stormwater Code / Manual

A stormwater code can be used to require maintenance of private LID BMPs, and legally authorize local governments to inspect BMPs and enforce BMP maintenance requirements. While codes can be written to explicitly address all maintenance requirements, they often refer to a stormwater manual for details (i.e., 2012 SWMMWW or equivalent). Stormwater code and manuals can be used to accomplish the following:

- Require maintenance of all permanent stormwater BMPs and facilities
- Set forth minimum inspection, operation, and maintenance requirements
- Define permitting and plan review processes
- List required development project submittal elements (e.g., Stormwater Site Plans, legal agreements, project O&M manual)
- Require legal agreements with private property owners that identify the party responsible for retention, protection, and maintenance of BMPs
- Require legal agreements with private property owners that describe how the responsibility for maintenance of BMPs is transferred when property ownership changes
- Define the inspection process
- Establish legal authority of local government to inspect private stormwater facilities
- Define the enforcement process
- Establish legal authority of local government to enforce BMP maintenance standards
- Establish enforcement mechanisms, such as fee triggers and schedule, for unmaintained facilities
- Set forth requirement for financial surety measures (e.g., bonds) for development plats to guarantee maintenance of BMPs after construction

### *Incorporating private facilities into a City/County stormwater maintenance program*

Cities and counties generally have a maintenance program in place and have made decisions regarding whether they assume maintenance responsibility for private facilities. The jurisdiction's decision regarding LID BMP maintenance responsibility would be evaluated in the context of its existing program approach. Options include the following:

- 1) City/County could inspect facilities and require that the property owner hire a qualified contractor to conduct necessary maintenance
- 2) City/County could require facility owners to contract with a third party inspector and provide an inspection certification letter to the City/County, as well as proof that any required maintenance has been completed
- 3) City/County could perform maintenance and charge the property owner
- 4) City/County could assume maintenance responsibilities through a deed or easement.

- Establish limited legal authority to conduct maintenance when not conducted in a timely manner and bill the property owner for the costs.

Often the owner of the property on which the BMP is located is responsible for LID BMP maintenance. However, the local government can choose to incorporate private BMPs into a City/County stormwater maintenance program (see the sidebar for tips).

### *Legal Agreements and Recordable Documents*

Legal agreements between a private party, responsible for BMP maintenance, and the local government can be recorded against a property title to help require and ensure long-term facility maintenance. Examples of these agreements include declarations of covenant and grants of access easement. Some type of legal agreements and recordable documents are necessary to accomplish the following:

- Identify and characterize the stormwater features on site (i.e., attach as-built drawing of the lot with the location of the On-site Stormwater Management BMPs and the area served by them, design details, figures, and maintenance instructions)
- Require inspection and O&M activities and direct responsible party to local municipal code, manual, and/or project-specific O&M manual
- Identify the party responsible for retention, protection, and maintenance of BMPs
- Describe how the responsibility for maintenance of BMPs is transferred when property ownership changes
- Help give the local government legal access for inspection of BMPs

#### *What happens when a property is sold?*

When a property is sold, it is important that the new owner is informed of their maintenance responsibilities and that the local government tracks the sale to ensure legal agreements are in place. Options include the following:

- Include language in the covenant that the property owner must inform all future purchasers of the existence and maintenance requirements of the stormwater BMPs on their property and transfer possession of the project O&M manual (or in the case of lots without Stormwater Treatment and Flow Control BMPs/Facilities, maintenance instructions) to the new property owner
- Require informational handouts at point-of-sale inspections
- Require escrow companies to fax or e-mail the City/County when they perform the “tap and connection” check at time of sale to help the local government track the responsible party
- If a financial surety is in place, require the new owner to obtain one before releasing the existing bond

Several example covenants and access easements from Washington jurisdictions are included in Appendix A. Note that a covenant to be recorded against the property can be used to identify the LID BMPs on the property and the land owner’s obligations to protect, operate, and maintain the BMPs. If the covenant does not cover access for maintenance then a separate legal agreement is necessary.

Permittees should review the local process for recording legal agreements through the recorder’s office/county assessor in order to address barriers or time-consuming delays. For example, if an easement requires city/county council approval, solutions could include:

- Using a covenant instead
- Exempting access easements for maintenance from city/county council approval
- Streamlining or simplifying the process in other ways.

An administrative challenge related to legal agreements is establishing procedures to inform new property owners of their maintenance responsibilities for BMPs on their site. See side bar “What Happens When a Property is Sold” for tips.

Some local governments make the legal agreements with homeowners’ associations (HOAs). An advantage of this is that it may be easier to work with the HOA than with individual property owners. The HOA can conduct maintenance or arrange for a qualified third party professional to conduct the maintenance. Another advantage of HOAs is as a point of contact for outreach and education. An incentive to encourage ongoing HOA responsibility for stormwater facility maintenance could include a reduced stormwater utility fee. A disadvantage of assigning responsibility to the HOA through a legal agreement is that some HOAs dissolve over time. The legal agreement can be written to transfer the maintenance responsibility for a shared facility to the individual property owners if an HOA goes defunct. For subdivisions, it is important to list the individual homeowners or lots on permit documents to simplify future enforcement actions, if necessary.

***Tips for tracking LID BMP information***

To establish an efficient inspection and maintenance program, it is critical to track and link pertinent information. Consider the following

- Establish an interdepartmental coordination process between information technology (IT), GIS, and different permitting administrators
- Develop a geodatabase or web-based database with tags to link electronic “as built” or “record drawings”, inspection forms, O&M manuals, and other BMP information to the BMP location. Consider indexing the BMP(s) by an identifier that will not change over time (e.g., parcel numbers can change).
- Tagging a property will alert plan review staff of the existence of a BMP and help to ensure the BMP is protected or replaced during redevelopment activities
- Conduct an end of the year audit to ensure that everything has been tracked and require that information is transferred between departments (e.g., from permitting administrators to department(s) responsible for inspections and enforcement)

### ***Project-Specific BMP Maintenance Requirements***

For development projects subject only to Minimum Requirements #1 through #5, Stormwater Site Plans should include maintenance instructions for On-Site Stormwater Management BMPs.

For projects subject to Minimum Requirements #1 through #9, maintenance instructions should also be developed for all On-site Stormwater Management BMPs that are not defined as Stormwater Treatment and Flow Control BMPs/Facilities.

Where projects must meet MR #6 and/or MR #7, O&M manuals must be developed for each Stormwater Treatment and Flow Control BMP. That means a manual for every bioretention, permeable pavement, and vegetated roof built as part of the project. These manuals identify the party responsible for maintenance, specify maintenance activities, and contain maintenance logs and a maintenance schedule.

At private facilities, a copy of each O&M manual must be retained onsite, or within reasonable access to the site, and must be transferred with the property to the new owner. If the LID BMPs are distributed on individual lots, then each property owner should have an O&M manual. For public facilities, a copy of the project O&M manual must be retained in the appropriate department. A log of maintenance activity, indicating actions taken, must be kept and made available for review upon request by the local government.

The project-specific maintenance requirements must be at least as stringent as those in the local maintenance standards. Because maintenance requirements and recommended procedures may evolve over time, consider allowing project proponents to include a reference to a document that can be updated periodically. The agreement can refer to “the current version of” the document. Some jurisdictions have online maintenance manuals that can be referenced in legal agreements, so that the most up-to-date maintenance information is available for property owners.

### *Financial Surety Measures*

One mechanism for ensuring that LID BMPs are protected and maintained after construction is to require a financial surety, such as a bond or an assignment of accounts (also called an assignment of savings). If authorized by the jurisdiction’s code, local governments can require that sureties are obtained by developers (surety measures are typically not used for single infill lots). The financial surety allows the government to enforce maintenance requirements (e.g., by pulling the bond) until the plat is fully constructed, or longer. This is particularly important if a jurisdiction assumes responsibility for private facility maintenance once construction has been completed. It is critical to ensure that adequate funds are available in the event of a non-compliant facility. One drawback to sureties is that they are generally only valid for two years before they are released (RCW 58.17.130), and if LID BMPs are on individual lots, they may not all be in place within 2 years.

### *Record Keeping & Tracking Process*

An effective maintenance program requires the collection and tracking of LID BMP and maintenance information, beginning with the plan review process and continuing for the life of the facility. The following information should be included in a City/County record keeping system for BMP maintenance:

- Parcel information
- City/County permit (right-of-way permit for roads and utilities for a subdivision, and/or building permits for individual lots)

- Relevant sections of the Stormwater Site Plan (e.g., Permanent Stormwater Control Plan) and attached documents
- “As-builts” or “record drawings” for individual lots and for public rights-of-way
- Legal agreements (e.g., covenants or easements)
- Location information (e.g., GPS data, digital maps)
- Project O&M manual (where applicable, see Tables 20 and 21)
- Maintenance logs (typically included in a project O&M manual)
- Inspection forms (e.g., during construction, post-construction, ongoing annual)
- Enforcement documents

It is critical for local governments to develop effective interdepartmental recording and record management procedures to support ongoing annual inspections. The information including, but not limited to, the items listed above should be “linked” for individual property and to a related subdivision (if applicable). See the sidebar for some tips on how to approach tracking.

### *Inspection Programs*

Inspections are required for all LID BMPs immediately post-construction. These inspections are critical to check that the BMPs are installed per plan and functioning properly. Inspections are also required for all permanent Stormwater Treatment and Flow Control BMPs/Facilities in new residential developments every 6 months until 90 percent of the lots are constructed (or when construction is stopped and the site is fully stabilized) to identify maintenance needs and enforce compliance with maintenance standards, as needed. These inspections can require interdepartmental coordination because the site/building inspection process may include multiple departments administering different permits.

### *Challenges & tips for larger development sites*

Large subdivision development sites pose challenges for LID BMP maintenance programs because:

- Subdivisions may include numerous distributed LID BMPs with a large number of responsible parties
- The developer may not have all BMPs sited and designed at time of plan review
- There is a risk that the plat will be cleared and the project abandoned
- Lots could be sold to multiple builders and construction could occur over a long period of time

Local governments could consider the following:

- Require bonding until full build out and stormwater BMP construction
- Ensure financial surety amount is sufficient
- Require recording of multi-party covenants for BMPs in the right-of-way (e.g., roadside bioretention) for each lot adjacent to the right-of-way
- Prohibiting or limiting wholesale clearing (mass grading) of sites
- Require recording of covenant and access easement agreements prior to final plat or final short plat
- Revise/supplement plan review checklist and procedures to record, track and establish agreements for single lots in addition to full plats

Ongoing annual inspections are required for all Stormwater Treatment and Flow Control BMPs/Facilities (designed to meet or help meet MR #6 and/or MR #7). While legal agreements authorize some access to the BMP, the local jurisdiction procedures may include requirements to provide written notice and secure consent from the property owner prior to the inspection. Securing consent may help to avoid potential conflict and allows a “contact” and opportunity for education of the private property owner. In addition, educational door hangers or handouts can be distributed prior to and during inspections to inform property owners of the BMPs located on their site, how the BMP functions, and where to find BMP maintenance requirements.

Local governments could consider allowing third party inspection for BMPs in settings that are difficult for a City/County inspector to access (e.g., backyard of a private residence) or if property owners do not want City/County inspectors on their properties. The property owner would be required to provide the City/County with inspection documentation from an approved third party inspector, or inspections and maintenance could be arranged through the HOA. This would reduce the potential liability concerns and reduce staffing needs while still allowing the jurisdiction to meet their annual inspection requirements. Local governments could consider mitigating the cost to the private property owner by crediting the inspection fee on their utility bill.

Inspectors should be trained on the function of LID BMPs and proper procedures for BMP inspection during and after construction. Inspection checklists for LID BMPs are a good tool to support consistent inspection practices and can be used for record keeping. The project specific O&M document and record drawings should be reviewed before and during the inspection.

## *Mapping*

Jurisdictions increasingly rely on Global Positioning System (GPS) data, digital maps, and field-accessible databases to locate and track inspection and maintenance of stormwater facilities. Unlike traditional centralized stormwater facilities, LID BMPs are small, distributed features. Because there are typically many LID BMPs scattered across development sites, mapping can be a challenge. Local governments can consider the following options for mapping LID BMPs:

- Placing single points on stormwater system maps that reference permanent stormwater control plans (also referred to as “as-builts,” or “record drawings”). These plans typically contain the information to support inspections, provided they are maintained, to reflect any modifications made to the facilities, and are readily accessible to inspectors in the field. With this approach, single points would be placed on the map near the center of the dispersed LID BMPs.
- Mapping the location of each LID BMP. This may be more time consuming and clutter some stormwater system maps; however, it will provide the location of each known LID BMP and may be easier to track inspections and maintenance.

## *Private Property Owner Education*

Education is a key component to ensuring that private property owners understand LID BMPs and their maintenance requirements. Some suggestions for public education include:

- Door hangers or handouts distributed at maintenance inspections
- Booklet on how to maintain LID features (e.g., rain gardens), provided to the homeowner, along with other property documentation, by the developer
- Homeowner education program(s) that require realtors to inform potential home buyers of the presence of LID features, their maintenance requirements, and recommends inspection prior to purchase (similar to side sewer education model)
- Placard in the house or signage outside of the house that identifies the LID BMP and refers to maintenance information
- Program for homeowner education provided at the permit counter (e.g., scheduled meeting in which the review staff “walk” the homeowner through the property “as built” and explain how the BMPs function
- Program for HOA education provided in the classroom and as a site visit. Staff meet with the HOA to go through the property “as built” and explain how the BMPs function. Staff also describe maintenance techniques specific to the HOA’s LID BMPs and review Operations & Maintenance manuals or maintenance instructions for the LID BMPs that HOA maintains. Then staff and the HOA visit their LID BMPs so that staff can teach the HOA about inspecting their LID BMPs and additional maintenance techniques.
- Classes for homeowners/private property owners/HOAs through universities or groups such as extension programs, Conservation Districts, or Master Gardeners Associations
- Educational handouts/fact sheets distributed via local partnerships and programs
- Utility bill inserts
- Broader community outreach through media, web resources, or activities at community events.

An excerpt from Pierce County’s stormwater maintenance manual for private facilities is included in Appendix B. Note that this document is provided as an example based on format only; the content has not been reviewed for consistency with the 2013-2018 Permit requirements or the material included in this guidance document.





## REFERENCES

Ecology. 2012a. Phase I Municipal Stormwater Permit. Washington State Department of Ecology Water Quality Program. August 1, 2012.

Ecology. 2012b. Western Washington Phase II Municipal Stormwater Permit. Washington State Department of Ecology Water Quality Program. August 1, 2012.

Ecology. 2012c. Stormwater Management Manual for Western Washington. Publication No. 12-10-030. Prepared by the Washington State Department of Ecology, Olympia, Washington. August 2012.

Herrera. 2012. Preliminary LID Maintenance Equipment, Skills and Staffing Recommendations Memorandum. Prepared for Washington State Department of Ecology by Herrera Environmental Consultants, Seattle, Washington. September 25, 2012.

King County and SPU. 2008. Natural Yard Care. Five steps to make your piece of the planet a healthier place to live. King County Solid Waste Division and City of Seattle Public Utilities. December 9, 2008

Saving Water Partnership. 2006. The Natural Lawn & Garden Series: Smart Watering. May 2006.

Saving Water Partnership. 2007. Natural Lawn Care for Western Washington.

Saving Water Partnership. 2012. The Natural Lawn & Garden Series: Growing Healthy Soil; Choosing the Right Plants; and Natural Pest, Weed and Disease Control. January and August 2012.

WERF. 2009. BMP and LID Whole Life Cost Models. Developed by the Water Environment Research Foundation.

Wilson, B.C., J.S. Gulliver, J-H. Kang, and P.T. Weiss. 2008. Maintenance of Stormwater BMPs: Frequency, Effort, and Cost. Stormwater Magazine. November-December 2008.



# APPENDIX A

---

## Examples of Covenants and Easements



When Recorded, Return to

**Department of Planning and Development**

700 5<sup>th</sup> Ave, Suite 1800

P.O. Box 34019

Seattle, WA 98124-4019

11/08/11

**MEMORANDUM OF DRAINAGE CONTROL  
(SMC 22.807.020)**

GRANTOR: 1) \_\_\_\_\_

2) \_\_\_\_\_

3) \_\_\_\_\_

Additional Owners/Grantors on page \_\_\_\_\_

GRANTEE: The City of Seattle

LEGAL DESCRIPTION (ABBREVIATED):

Additional legal description on page 2.

**ASSESSOR'S TAX PARCEL ID NO(S).** \_\_\_\_\_

Permit Street Address \_\_\_\_\_

Application No. (by DPD staff): \_\_\_\_\_

Date (by DPD staff): \_\_\_\_/\_\_\_\_/\_\_\_\_

Grantor's Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip \_\_\_\_\_

Memorandum of Drainage Control--1

**MEMORANDUM OF DRAINAGE CONTROL  
(SMC 22.807.020)**

THIS Agreement is executed in favor of the City of Seattle (“City”) by the undersigned owner(s (“Grantor”) of the following described real property situated in City of Seattle, King County, State of Washington (the “Property”) (insert complete legal description):

In consideration of the City’s granting a permit for the drainage control facilities proposed by Grantor, and for the City’s allowing the connection thereof to the City’s drainage system if applicable, Grantor hereby agrees and covenants, pursuant to SMC 22.807.020, as follows:

On \_\_\_\_\_, 20\_\_\_\_\_, Side Sewer Permit # \_\_\_\_\_ and Building Permit # \_\_\_\_\_ were issued for the above described Property.

WHEREAS; the drainage control facilities permitted by said side sewer permit are the following and are key terms of the Property’s drainage control plan, which is documented in the drainage control plan drawing(s) as amended by the side sewer construction as-built record drawing(s) on file with the City of Seattle:

1. The following flow control best management practices (BMPs):

- Existing Trees
- Dispersion (downspout or sheet flow)
- Bioretention Cells/Planters
- Rainwater Harvesting
- Permeable Pavement Surfaces
- Permeable Pavement Facilities
- Green Roof
- Detention Cistern for a Single-Family Project
- Infiltration Basins
- Infiltration Trenches
- Dry wells
- Detention Pond
- Detention Pipe
- Detention Vault
- Surface Ponding
- Other (describe) \_\_\_\_\_

Memorandum of Drainage Control--2

**MEMORANDUM OF DRAINAGE CONTROL  
(SMC 22.807.020)**

2. The following stormwater treatment BMPs:

- Pretreatment Facilities \_\_\_\_\_
- Biofiltration Swales
- Filter Strips
- Infiltration Basins, Trenches or Dry Wells
- Bioretention System
- Permeable Pavement Facilities
- Sand Filtration
- Wet Pond/Wet Vault
- Stormwater Treatment Wetland
- Oil Control Facilities: API / Coalescing Plate
- StormFilter Units
- Filterra Units
- Other (describe) \_\_\_\_\_

3. The following source control structures:

- Roof, Awning, Cover
- Ground Surface Treatment
- Sumps, Tanks
- Berms, Dikes
- Pavement
- Containment
- Washpad
- Other (describe) \_\_\_\_\_

to contain the following activities:

- Cleaning and Washing
- Material Transfer
- Product and Application
- Storage and Stockpiling
- Dust Control and Soil and Sediment Control
- Other: (describe) \_\_\_\_\_

4. and the following items, terms and/or limitations:

- catch basin(s), quantity \_\_\_\_
- submersible pump(s), quantity \_\_\_\_\_
- Roof leader connections
- Pipes with less than 2% grade
- Invert connection less than 12 inches above main sewer or drain
- Other (describe) \_\_\_\_\_

Memorandum of Drainage Control--3

NOW THEREFORE; the Grantor, on behalf of Grantor and Grantor's heirs, successors and assigns, agrees to the following and hereby creates a covenant running with the land that shall be binding upon all parties and their heirs, successors and assigns forever:

The Grantor, on behalf of Grantor and Grantor's heirs, successors and assigns, agrees to and shall (1) inspect and maintain the above described drainage control facilities in accordance with the provisions of Seattle Municipal Code (SMC) Chapters 22.800 – 22.808 and any other provisions applicable to the facilities, as now and hereafter in effect, (2) implement the terms of the drainage control plan required by the SMC and (3) inform all future purchasers, successors and assigns of the existence of the drainage control facilities and other elements of the drainage control plan, the limitations of the drainage control facilities, and of the requirement for the facilities' continued inspection and maintenance; and

The obligations of Grantor and each of Grantor's heirs, successors and assigns under this Memorandum of Drainage Control shall terminate when that person, sells, devises or transfers the Property, or his or her interest therein, unless the obligation arises out of a claim of negligence or intentional act of that person. Further, recording of this Memorandum of Drainage Control as required herein shall satisfy the obligations to inform under subsection (3) above.

The Grantor, on behalf of Grantor and Grantor's heirs, successors and assigns, hereby grants permission for authorized representatives of the City of Seattle to enter onto the Property for inspection, monitoring, correction or abatement of conditions related to the Property's drainage control plan, drainage control facilities, Chapters SMC 22.800 – 22.808 or any other SMC provision applicable to drainage control, as now and hereafter in effect; and

The Grantor, on behalf of Grantor and Grantor's heirs, successors and assigns, (1) agrees and acknowledges that the City is not responsible for the adequacy or performance of the drainage control plan or the drainage control facilities, (2) agrees to accept any and all risks of harm, loss, or damage related to the drainage control plan or the drainage control facilities and (3) hereby waives any right to assert any and all present and future claims against the City, whether known or unknown, for any harm, loss or damage occurring either on or off the Property, related to the drainage control plan, the drainage control facilities, or drainage or erosion on the Property, except only for such harm, damages and losses that directly result from the sole negligence of the City.

This Memorandum of Drainage Control shall be recorded in the real estate records of the Office of Records and Elections of King County, Washington. If any provision of this Memorandum is held invalid, the remainder of the Memorandum is not affected.

Memorandum of Drainage Control--4



**SIGNATURES, ACKNOWLEDGEMENTS AND NOTARY**  
**(INDIVIDUAL—attach more pages if needed)**

Dated: \_\_\_\_\_

State of Washington )  
 ) ss  
County of \_\_\_\_\_ )

\_\_\_\_\_  
Owner/Grantor

I certify that I know or have satisfactory evidence that \_\_\_\_\_ is the person who appeared before me, and said person acknowledged that he/she signed this instrument and acknowledged it to be his/her free and voluntary act for the uses and purposes mentioned in the instrument.

\_\_\_\_\_  
Printed Name

Date: \_\_\_\_\_

\_\_\_\_\_  
Address

NOTARY PUBLIC in and for the State of  
Washington  
Residing at \_\_\_\_\_  
My commission expires: \_\_\_\_\_  
PRINT NAME: \_\_\_\_\_



Use this space for Notary Seal

Dated: \_\_\_\_\_

County of \_\_\_\_\_ ) ss  
 )

\_\_\_\_\_  
Owner/Grantor

I certify that I know or have satisfactory evidence that \_\_\_\_\_ is the person who appeared before me, and said person acknowledged that he/she signed this instrument and acknowledged it to be his/her free and voluntary act for the uses and purposes mentioned in the instrument.

\_\_\_\_\_  
Printed Name

Date: \_\_\_\_\_

\_\_\_\_\_  
Address

NOTARY PUBLIC in and for the State of  
Washington  
Residing at \_\_\_\_\_  
My commission expires: \_\_\_\_\_  
PRINT NAME: \_\_\_\_\_



Use this space for Notary Seal

State of Washington )

Memorandum of Drainage Control—Page No. \_\_\_\_\_

**(CORPORATE OWNER, PARTNERSHIP OWNER, LIMITED LIABILITY COMPANY  
OWNER/OTHER LEGAL ENTITY OWNER—attach more pages if needed)**

Date: \_\_\_\_\_

State of Washington )  
 )ss  
County of \_\_\_\_\_ )

\_\_\_\_\_  
Owner/Grantor

I certify that I know or have satisfactory evidence that \_\_\_\_\_ is the person who appeared before me, and said person acknowledged that he/she signed this instrument, on oath stated that he/she was authorized to execute the instrument and acknowledged it as the \_\_\_\_\_ (type of authority, e.g., partner, trustee, title of officer, personal representative, guardian, attorney in fact for a principal, etc.) of \_\_\_\_\_ (name of owner/entity on behalf of whom instrument was executed), to be the free and voluntary act of such party for the uses and purposes mentioned in the instrument.

\_\_\_\_\_  
Printed Name

\_\_\_\_\_  
Address

Date: \_\_\_\_\_

By \_\_\_\_\_

NOTARY PUBLIC in and for the State of  
Washington  
Residing at \_\_\_\_\_  
My commission expires: \_\_\_\_\_  
PRINT NAME: \_\_\_\_\_

\_\_\_\_\_  
Printed Name

Its \_\_\_\_\_



Use this space for Notary Seal

Date: \_\_\_\_\_

State of Washington )  
 )ss  
County of \_\_\_\_\_ )

\_\_\_\_\_  
Owner/Grantor

I certify that I know or have satisfactory evidence that \_\_\_\_\_ is the person who appeared before me, and said person acknowledged that he/she signed this instrument, on oath stated that he/she was authorized to execute the instrument and acknowledged it as the \_\_\_\_\_ (type of authority, e.g., partner, trustee, title of officer, personal representative, guardian, attorney in fact for a principal, etc.) of \_\_\_\_\_ (name of owner/entity on behalf of whom instrument was executed), to be the free and voluntary act of such party for the uses and purposes mentioned in the instrument.

\_\_\_\_\_  
Printed Name

\_\_\_\_\_  
Address

Date: \_\_\_\_\_

By \_\_\_\_\_

NOTARY PUBLIC in and for the State of  
Washington  
Residing at \_\_\_\_\_  
My commission expires: \_\_\_\_\_  
PRINT NAME: \_\_\_\_\_

\_\_\_\_\_  
Printed Name

Its \_\_\_\_\_



Use this space for Notary Seal

## **Appendix I-G3**

---

Maintenance Agreement, Non-Residential Stormwater Facilities



(CORPORATE VERSION)

AGREEMENT TO MAINTAIN  
STORMWATER FACILITIES AND TO IMPLEMENT A  
POLLUTION SOURCE CONTROL PLAN  
BY AND BETWEEN \_\_\_\_\_  
(HEREINAFTER "THE LOCAL GOVERNMENT") AND  
\_\_\_\_\_, AND  
ITS HEIRS, SUCCESSORS, OR ASSIGNS  
(HEREINAFTER "OWNER")

The upkeep and maintenance of stormwater facilities and the implementation of pollution source control best management practices (BMPs) is essential to the protection of water resources in \_\_\_\_\_. All property owners are expected to conduct business in a manner that promotes environmental protection. This Agreement contains specific provisions with respect to maintenance of stormwater facilities and use of pollution source control BMPs. The authority to require maintenance and pollution source control is provided by ordinance.

LEGAL DESCRIPTION:

Whereas, Owner has constructed improvements, including but not limited to, buildings, pavement, and stormwater facilities on the property described above. In order to further the goals of the Local Government to ensure the protection and enhancement of Local Government's water resources, the Local Government and Owner hereby enter into this Agreement. The responsibilities of each party to this Agreement are identified below.

OWNER SHALL:

- (1) Implement the stormwater facility maintenance program included herein as Attachment "A".
- (2) Implement the pollution source control program included herein as Attachment "B".
- (3) Maintain a record (in the form of a log book) of steps taken to implement the programs referenced in (1) and (2) above. The log book shall be available for inspection by Local Government staff at Owner's business during normal business hours. The log book shall catalog the action taken, who took it, when it was done, how it was done, and any problems encountered or follow-on actions recommended. Maintenance items ("problems") listed in Attachment "A" shall be inspected on a monthly or more frequent basis as necessary. Owner is encouraged to photocopy the individual checklists in Attachment A and use them to complete its monthly inspections. These completed checklists would then, in combination, comprise the monthly log book.
- (4) Submit an annual report to the Local Government regarding implementation of the programs referenced in (1) and (2) above. The report must be submitted on or before May 15 of each calendar year and shall contain, at a minimum, the following:
  - (a) Name, address, and telephone number of the business, the person, or the firm responsible

for plan implementation, and the person completing the report.

(b) Time period covered by the report.

(c) A chronological summary of activities conducted to implement the programs referenced in (1) and (2) above. A photocopy of the applicable sections of the log book, with any additional explanation needed, shall normally suffice. For any activities conducted by paid parties not affiliated with Owner, include a copy of the invoice for services.

(d) An outline of planned activities for the next year.

THE LOCAL GOVERNMENT WILL, AS RESOURCES ALLOW:

- (1) Provide technical assistance to Owner in support of its operation and maintenance activities conducted pursuant to its maintenance and source control programs. Said assistance shall be provided upon request and at no charge to Owner.
- (2) Review the annual report and conduct occasional site visits to discuss performance and problems with Owner.
- (3) Review this agreement with Owner and modify it as necessary.

REMEDIES:

- (1) If the Local Government determines that maintenance or repair work is required to be done to the stormwater facility existing on the Owner property, the Stormwater Manual Administrator shall give Owner within which the drainage facility is located, and the person or agent in control of said property if different, notice of the specific maintenance and/or repair required. The Administrator shall set a reasonable time in which such work is to be completed by the persons who were given notice. If the above required maintenance and/or repair is not completed within the time set, written notice will be sent to the persons who were given notice stating the Local Government's intention to perform such maintenance and bill Owner for all incurred expenses. The Local Government may also adjust stormwater utility charges on the Owner's bill if required maintenance is not performed.
- (2) If at any time the Local Government determines that the existing system creates any imminent threat to public health or welfare, the Administrator may take immediate measures to remedy said threat. No notice to the persons listed in (1), above, shall be required under such circumstances.
- (3) The Owner grants authority to the Local Government for access to any and all stormwater system features for the purpose of inspection, and performing maintenance or repair as may become necessary under Remedies (1) and/or (2).
- (4) The persons listed in (1), above, shall assume all responsibility for the cost of any maintenance and for repairs to the stormwater facility. Such responsibility shall include reimbursement to the Local Government within 30 days of the receipt of the invoice for any such work performed. Overdue payments will require payment of interest at the current legal rate for liquidated judgments. If legal action ensues, any costs or fees incurred by the Local Government will be borne by the parties responsible for said reimbursements.
- (5) The owner hereby grants to the Local Government a lien against the above-described property

in an amount equal to the cost incurred by the Local Government to perform the maintenance or repair work described herein.

This Agreement is intended to protect the value and desirability of the real property described above and to benefit all the citizens of the Local Government. It shall run with the land and be binding on all parties having or acquiring from Owner or their successors any right, title, or interest in the property or any part thereof, as well as their title, or interest in the property or any part thereof, as well as their heirs, successors, and assigns. They shall inure to the benefit of each present or future successor in interest of said property or any part thereof, or interest therein, and to the benefit of all citizens of the Local Government.

Dated at \_\_\_\_\_, Washington, this \_\_\_\_\_ day of \_\_\_\_\_, \_\_\_\_\_.

OWNER

By: \_\_\_\_\_  
Authorized Agent for Owner  
\_\_\_\_\_

STATE OF WASHINGTON        )  
  ) ss  
COUNTY OF THURSTON

On this day and year above personally appeared before me, a Notary Public in and for the State of Washington duly commissioned and sworn, personally appeared \_\_\_\_\_, to me known to be the \_\_\_\_\_ of \_\_\_\_\_ and acknowledge the said instrument to be the free and voluntary act and deed of said corporation, for the uses and purposes therein mentioned, and on oath stated that \_\_\_\_\_ is authorized to execute the said instrument and that the seal affixed is the corporate seal of said corporation.

WITNESS my hand and official seal the day and year first above written.

\_\_\_\_\_  
Notary Public in and for the State of  
Washington, residing in \_\_\_\_\_  
My Commission Expires: \_\_\_\_\_

Dated at \_\_\_\_\_, Washington, this \_\_\_\_\_ day of \_\_\_\_\_, \_\_\_\_\_.

LOCAL GOVERNMENT

By: \_\_\_\_\_  
Authorized Agent for Local Government

STATE OF WASHINGTON )  
 ) ss  
COUNTY OF THURSTON )

On this day and year above personally appeared before me, \_\_\_\_\_, to me known to be acting as Authorized Agent for \_\_\_\_\_, a Municipal Corporation, who executed the foregoing instrument and acknowledged the said instrument to be the free and voluntary act and deed of said Municipal Corporation for the uses and purposes therein mentioned and on oath states he is authorized to execute the said instrument.

Given under my hand and official seal this \_\_\_\_\_ day of \_\_\_\_\_, \_\_\_\_\_.

\_\_\_\_\_  
Notary Public in and for the State of  
Washington, residing in \_\_\_\_\_  
My Commission Expires: \_\_\_\_\_

APPROVED AS TO FORM:

\_\_\_\_\_  
Local Government Attorney



## **Appendix I-G4**

---

Maintenance Agreement, Residential Stormwater Facilities



(RESIDENTIAL SUBDIVISION VERSION)

AGREEMENT TO MAINTAIN  
STORMWATER FACILITIES AND TO IMPLEMENT A  
POLLUTION SOURCE CONTROL PLAN  
BY AND BETWEEN \_\_\_\_\_  
(HEREINAFTER "THE LOCAL GOVERNMENT") AND  
\_\_\_\_\_, AND  
ITS HEIRS, SUCCESSORS, OR ASSIGNS  
(HEREINAFTER "OWNER")

The upkeep and maintenance of stormwater facilities and the implementation of pollution source control best management practices (BMPs) is essential to the protection of water resources in the Local Government's jurisdiction. All property owners are expected to conduct business in a manner that promotes environmental protection. This Agreement contains specific provisions with respect to maintenance of stormwater facilities and use of pollution source control BMPs. The authority to require maintenance and pollution source control is provided in ordinance.

LEGAL DESCRIPTION:

Whereas, Owner has constructed improvements, including but not limited to, buildings, pavement, and stormwater facilities on the property described above. In order to further the goals of the Local Government to ensure the protection and enhancement of Local Government's water resources, the Local Government and Owner hereby enter into this Agreement. The responsibilities of each party to this Agreement are identified below.

OWNER SHALL:

- (1) Implement the stormwater facility maintenance program included herein as Attachment "A".
- (2) Implement the pollution source control program included herein as Attachment "B".
- (3) Maintain a record (in the form of a log book) of steps taken to implement the programs referenced in (1) and (2) above. The log book shall be available for inspection by Local Government staff at Owner's business during normal business hours. The log book shall catalog the action taken, who took it, when it was done, how it was done, and any problems encountered or follow-on actions recommended. Maintenance items ("problems") listed in Attachment "A" shall be inspected on a monthly or more frequent basis as necessary. Owner is encouraged to photocopy the individual checklists in Attachment A and use them to complete its monthly inspections. These completed checklists would then, in combination, comprise the monthly log book.
- (4) Submit an annual report to the Local Government regarding implementation of the programs

referenced in (1) and (2) above. The report must be submitted on or before May 15 of each calendar year and shall contain, at a minimum, the following:

- (a) Name, address, and telephone number of the business, the person, or the firm responsible for plan implementation, and the person completing the report.
- (b) Time period covered by the report.
- (c) A chronological summary of activities conducted to implement the programs referenced in (1) and (2) above. A photocopy of the applicable sections of the log book, with any additional explanation needed, shall normally suffice. For any activities conducted by paid parties not affiliated with Owner, include a copy of the invoice for services.
- (d) An outline of planned activities for the next year.

THE LOCAL GOVERNMENT WILL, AS RESOURCES ALLOW:

- (1) Provide technical assistance to Owner in support of its operation and maintenance activities conducted pursuant to its maintenance and source control programs. Said assistance shall be provided upon request and at no charge to Owner.
- (2) Review the annual report and conduct occasional site visits to discuss performance and problems with Owner.
- (3) Review this agreement with Owner and modify it as necessary.

REMEDIES:

- (1) If the Local Government determines that maintenance or repair work is required to be done to the stormwater facility existing on the Owner property, the Stormwater Manual Administrator shall give Owner, and the person or agent in control of said property if different, notice of the specific maintenance and/or repair required. The Administrator shall set a reasonable time in which such work is to be completed by the persons who were given notice. If the above required maintenance and/or repair is not completed within the time set by the Administrator, written notice will be sent to the persons who were given notice stating the Local Government's intention to perform such maintenance and bill the owner for all incurred expenses. The Local Government may also adjust stormwater utility charges if required maintenance is not performed.
- (2) If at any time the Local Government determines that the existing system creates any imminent threat to public health or welfare, the Administrator may take immediate measures to remedy said threat. No notice to the persons listed in (1), above, shall be required under such circumstances.
- (3) The Owner grants authority to the Local Government for inspection, and access to any and all stormwater system features for the purpose of performing maintenance or repair as may become necessary under Remedies (1) and/or (2).
- (4) The Owner shall assume all responsibility for the cost of any maintenance and for repairs to the stormwater facility. Such responsibility shall include reimbursement to the Local

Government within 30 days of the receipt of the invoice for any such work performed. Overdue payments will require payment of interest at the current legal rate for liquidated judgments. If legal action ensues, any costs or fees incurred by the Local Government will be borne by the parties responsible for said reimbursements.

- (5) The Owner hereby grants to the Local Government a lien against the above-described property in an amount equal to the cost incurred by the Local Government to perform the maintenance or repair work described herein.

This Agreement is intended to protect the value and desirability of the real property described above and to benefit all the citizens of the Local Government. It shall run with the land and be binding on all parties having or acquiring from Owner or their successors any right, title, or interest in the property or any part thereof, as well as their title, or interest in the property or any part thereof, as well as their heirs, successors, and assigns. They shall inure to the benefit of each present or future successor in interest of said property or any part thereof, or interest therein, and to the benefit of all citizens of the Local Government.

Dated at \_\_\_\_\_, Washington, this \_\_\_\_\_ day of \_\_\_\_\_, \_\_\_\_\_.

OWNER

\_\_\_\_\_  
Authorized Agent for Owner

STATE OF WASHINGTON     )  
  ) ss  
COUNTY OF THURSTON)

On this day and year above personally appeared before me, \_\_\_\_\_  
\_\_\_\_\_ known to be the individual(s) described, and who executed the  
foregoing instrument and acknowledge that they signed the same as their free and voluntary act  
and deed for the uses and purposes therein mentioned.

Given under my hand and official seal this \_\_\_\_\_ day of \_\_\_\_\_, \_\_\_\_\_.

\_\_\_\_\_  
Notary Public in and for the  
State of Washington, residing in  
\_\_\_\_\_.

Dated at \_\_\_\_\_, Washington, this \_\_\_\_\_ day of \_\_\_\_\_, \_\_\_\_\_.

LOCAL GOVERNMENT

\_\_\_\_\_  
Authorized Agent for the Local Government

STATE OF WASHINGTON        )  
  ) ss  
COUNTY OF THURSTON)

On this day and year above personally appeared before me, \_\_\_\_\_, to me known to be the Authorized Agent for the Local Government, a Municipal Corporation, who executed the foregoing instrument and acknowledge the said instrument to be the free and voluntary act and deed of said Municipal Corporation for the uses and purposes therein mentioned and on oath states he is authorized to execute the said instrument.

Given under my hand and official seal this \_\_\_\_\_ day of \_\_\_\_\_, \_\_\_\_\_.

\_\_\_\_\_  
Notary Public in and for the  
State of Washington, residing in  
  
\_\_\_\_\_.

APPROVED AS TO FORM:

\_\_\_\_\_  
Local Government Attorney

When Recorded, Return To:

City of Tacoma  
Environmental Services / Science and Engineering  
747 Market Street Tacoma, WA 98402

**DOCUMENT TITLE: COVENANT AND EASEMENT  
PROJECT NAME**

**Grantor(s):  
DEVELOPER**

**Grantee:**  
CITY OF TACOMA, a Municipal Corporation

**Legal Description (abbreviated):**  
\*\*\*EXAMPLE\*\*\*

See Page 4, Exhibit "A", for Legal Description

**Reference Number(s):**  
City of Tacoma Short Plat No. xxxxxxxxx;  
City of Tacoma Work Order No. xxxxxxxxx;  
City of Tacoma Building Permit No. xxxxxxxxx

**Assessor's Parcel Number(s):**  
XX-XX-XX-XX

**COVENANT AND EASEMENT – PROJECT NAME**

WHEREAS DEVELOPER, hereinafter collectively referred to as the Grantor(s), owns the real property known as Project Name, located at \*\*\*insert address here\*\*\* (the “Subject Property”), which is more fully described herein; and

WHEREAS pursuant to Tacoma Municipal Code 12.08.090(D), as may be hereafter amended, a condition of developing the Subject Property requires that it have adequate stormwater drainage; and

WHEREAS pursuant to \_\_\_\_\_ approval, private storm drainage collection systems must be provided; and

WHEREAS Grantor(s) have/has chosen to install a private storm drainage system for the Subject Property, the location of which is legally described in Exhibit A, so as to proceed with \_\_\_\_\_ approval; and

WHEREAS such a private storm drainage system will require ongoing maintenance to ensure it operates as designed;

NOW THEREFORE, in consideration of the mutual benefits herein described, Grantor(s) hereby make the following Covenant which shall be recorded with the Pierce County Auditor encumbering the Subject Property (Assessor’s Parcel Number(s) xx-xx-xx-x-xxx).

(1) The Grantor(s) shall construct and maintain at his/her/their/its own cost, a private storm drainage system on the Subject Property, in accordance with the approved construction plans under City of Tacoma Short Plat No. XXXXXXXXXXXX. The private storm drainage system shall consist of storm drainage pipes, manholes, catch basins and various drainage facilities throughout the short plat including all drainage facilities located in private easements.

(2) It shall be the sole responsibility of the Grantor(s) and/or his/her/their/its successors-in-interest to maintain the private storm drainage system in its originally designed condition. Any damages caused by the failure of the system shall be the sole responsibility of the Grantor(s), owner(s) and/or his/her/their successor(s)-in-interest.

(3) This Covenant is made to ensure the proper maintenance of the storm drainage system. This Covenant shall run with the Subject Property and be binding upon the Grantor(s) and all successor(s)-in-interest. The Grantor(s) consent(s) to filing this Covenant with the Pierce County Auditor’s Office once it is executed.

(4) If the private storm drainage system is not maintained in accordance with the approved or as-built design, approved under City of Tacoma Work Short Plat No. XXXXXXXXXXXX incorporated herein by reference, the City may enter the Subject Property, inspect and repair the system, and assess reasonable costs for the work that may be charged against the owner of any beneficiary lot(s).





EXHIBIT A  
LEGAL DESCRIPTION

**\*\*EXAMPLE\*\***

When Recorded Return To:

City of Tacoma  
Public Works  
Real Property Services  
747 Market Street, Room 737  
Tacoma WA 98402-3769

**DOCUMENT TITLE: COVENANT AND EASEMENT**

\*\*\*\*\*

**Grantor(s):**

**Grantee:**

CITY OF TACOMA, a Municipal Corporation

**Legal Description (abbreviated):**

See pages 5 thru \_\_\_\_\_, Exhibit's "A" and "B", for full Legal Description

**Reference Number(s):**

City of Tacoma Work Order

**Assessor's Parcel Number(s):**

**COVENANT AND EASEMENT –Short Plat**

WHEREAS\*\*\*\*\* , hereinafter referred to as the Grantor, owns the properties on \*\*\*\*\*. hereinafter referred to as \*\*\*\*\* , which is more fully described in the attached and incorporated Exhibit A; and

WHEREAS in order to satisfy the requirements of TMC 12.08.090 (D), Grantor intends to construct a public bioretention facility located within the planting strip of the Fawcett Avenue right-of-way, for the benefit of the \*\*\*\*\*; and

WHEREAS in order to satisfy requirements set forth in TMC Chapter 9.17, 9.18, and 9.19, *abutting property owners* are responsible for the maintenance of the planting strip and will be responsible for ongoing maintenance of the proposed bioretention facility to ensure it operates as designed.

WHEREAS Grantor, and all successors in interest, of those certain Lots within the \*\*\*\*\* , (hereinafter collectively referred to as “Owner”), shall be obligated to maintain the public bioretention facility in accordance with this Covenant and Easement; and

WHEREAS the bioretention facility was designed by \*\*\*\*\*who also designed the public storm drainage system;

NOW THEREFORE, in consideration of the mutual benefits herein described, Grantor hereby makes the following Covenant which shall be recorded with the Pierce County Auditor under Parcel Number’s \*\*\*\*\*.

**COVENANT AND EASEMENT – \*\*\*\*\***

(1) The Grantor shall construct and maintain, at its own cost, a public storm drainage system within the right-of-way adjacent to the property legally described in Exhibit B (which is incorporated herein by this reference), and in accordance with the approved Work Order under City of Tacoma Permit Number \*\*\*\*\*

(2) The proposed bioretention facility in the right of way will be an asset of the City of Tacoma. However per Tacoma Municipal Code Chapter 9.17, 9.18, and 9.19, *abutting property owners* are responsible for the maintenance of the planting strip and will be responsible for maintenance of the proposed bioretention facility and Grantor hereby agrees to maintain the facility as outlined herein below.

Grantor shall:

- Weed and water the bioretention facility as necessary until the plants have become established,
- Remove leaves and debris blocking storm drains and pipes to prevent local flooding on an on-going basis,

- Keep sidewalks in front of homes clear of impediments to pedestrian access and safety, also on an on-going basis.

The City shall be responsible for:

- Regular monitoring and maintenance of the Natural Drainage System “hardware” – pipes, culverts, outlets, drains, and grates, and
- Providing emergency services and repairs.

(3) This Covenant is made to ensure the proper maintenance of the storm drainage system. It is the Grantor’s intent that the terms and conditions of this Covenant shall run with the land and be binding upon the Grantor(s) and all successor(s) in interest. The Grantor consents to the City filing this Covenant with the Pierce County Auditor’s Office once it is executed.

---

\*\*\*\*\*

STATE OF WASHINGTON )  
 ) ss  
COUNTY OF \_\_\_\_\_ )

I certify that I know or have satisfactory evidence that \*\*\*\*\* is the person who appeared before me, and said person acknowledged that he signed this instrument, on oath stated that he was authorized to execute the instrument and acknowledged it, as the owner of the property concerned in this agreement, to be his free and voluntary act for the uses and purposes mentioned in the instrument.

Dated this \_\_\_\_\_ day of \_\_\_\_\_, 2009

\_\_\_\_\_  
Notary Public in and for the  
State of Washington  
My Commission Expires \_\_\_\_\_

LEGAL DESCRIPTION APPROVED:

\_\_\_\_\_  
\*\*\*\*\*  
\*\*\*\*\*  
/Environmental Services

\_\_\_\_\_  
City Surveyor

APPROVED AS TO FORM:

\_\_\_\_\_  
Assistant City Attorney

**EXHIBIT A-- \*\*\*\*\***

**EXHIBIT B**

Legal Description



RECORDING REQUESTED BY AND  
WHEN RECORDED MAIL TO:

---

---

---

---

---

**RECORDING COVER SHEET**

**DECLARATION OF COVENANT AND GRANT OF EASEMENT**

Grantor: \_\_\_\_\_

Grantee: \_\_\_\_\_

Legal Description: \_\_\_\_\_

---

---

Additional Legal(s) on: \_\_\_\_\_

Assessor's Tax Parcel ID#: \_\_\_\_\_

---

---

**DECLARATION OF COVENANT AND GRANT OF EASEMENT  
For Stormwater Flow Control Best Management Practices**

IN CONSIDERATION of the following approved King County (check one of the following)

- residential building permit,  commercial building permit,  clearing and grading permit,
- subdivision permit, or  short subdivision permit for Application No. \_\_\_\_\_

relating to real property ("Property") legally described as follows:

---

---

---

---

The Grantor(s), the owner(s) in fee of the above described parcel of land, hereby covenants with King County, a political subdivision of the state of Washington its successors in interest and assigns ("King County"), that it will observe, consent to, and abide by the conditions and obligations set forth and described in Paragraphs 1 and 2 and 4 through 7 below with regard to the Property, and hereby grants an access easement on and to the Property to King County, for the purposes described in Paragraph 3 below. Grantor(s) hereby grants, covenants, and agrees as follows:

1. Owner(s) of the Property shall retain, uphold, and protect the stormwater management devices, features, pathways, limits, and restrictions, known as flow control best management practices ("Flow Control BMPs"), shown on the approved Flow Control BMP Site Plan for the Property attached hereto and incorporated herein as Exhibit A.

2. Owner(s) of the Property shall at their own cost, operate, maintain, and keep in good repair, the Property's Flow Control BMPs as described in the approved Design and Maintenance Details for each BMP attached hereto and incorporated herein as Exhibit B.

3. King County shall have a nonexclusive perpetual access easement on the Property in order to ingress and egress over the Property for the sole purposes of inspecting and monitoring the Property's Flow Control BMPs, and if applicable in accordance with the terms of Paragraph 4 below, performing any corrective work required to bring the Property's Flow Control BMPs into compliance with Title 9 of the King County Code.

4. If King County determines that maintenance, repair, restoration, and/or mitigation work is required to be done to the Flow Control BMPs and has not been performed by the Property owner(s), the Director of the Water and Land Resources Division of the King County Department of Natural Resources and Parks shall give notice to the Property owner (s) of the specific maintenance, repair, restoration, and/or mitigation work (Work) required pursuant to Title 9 of the King County Code. The Manager shall also set a reasonable time in which the Work is to be completed by the Property owner(s). If the Work is not completed within the time set by the Division Director, King County may perform the required Work. Written notice will be sent to the Property owner(s) stating King County's intention to perform the Work. Performance of the Work by King County will not commence until at least seven (7) days after such notice is mailed. If, within the sole discretion of the Water and Land Resources Division Director, there exists an imminent or present danger, the owner hereby waives the seven (7) day notice period and the Work will begin immediately.

5. The owner(s) of the Property shall assume all responsibility for the cost of any Work required to be done to the Flow Control BMPs. Such responsibility shall include reimbursement to King County within thirty (30) days of the receipt of the invoice for any such Work performed by King County in accordance with the terms of Paragraph 3 above. Overdue payments will require payment of interest at the current legal rate as liquidated damages. In the event that King County does not receive reimbursement within the required time frame, it may elect to place a lien on the

Property and act upon the lien in accordance with the terms and procedures specified in Chapter 23.40 of the King County Code, as amended from time to time. If legal action is taken to enforce the provisions of this Paragraph, the prevailing party is entitled to costs and attorney's fees.

6. Apart from performing routine landscape maintenance, the Property owner(s) is (are) hereby required to obtain written approval from the Water and Land Resources Division Manager of the King County Department of Natural Resources and Parks prior to performing any alterations or modifications to the Flow Control BMPs. Any notice or consent required to be given or otherwise provided for by the provisions of this Declaration of Covenant and Grant of Easement shall be effective upon personal delivery, or three (3) days after mailing by Certified Mail, return receipt requested, whichever occurs sooner.

7. This Declaration of Covenant and Grant of Easement is intended to promote the efficient and effective management of surface water drainage on the Property, and it shall inure to the benefit of all the citizens of King County, its successors and assigns. This Declaration of Covenant and Grant of Easement shall run with the land and be binding upon Grantor(s), and Grantor's (s') successors in interest and assigns.

8. This Declaration of Covenant and Grant of Easement may be terminated by execution of a written agreement by Grantor(s) and King County expressing their mutual agreement to terminate this Declaration of Covenant and Grant of Easement.

IN WITNESS WHEREOF, this Declaration of Covenant and Grant of Easement is executed

this \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_.

By \_\_\_\_\_

Its \_\_\_\_\_

By \_\_\_\_\_

Its \_\_\_\_\_

STATE OF WASHINGTON)

)SS

COUNTY OF KING )

On this \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_, before me, the undersigned, a Notary Public in and for the State of \_\_\_\_\_, duly commissioned and sworn personally appeared, to me known to be the individual described in and who executed the foregoing instrument, and acknowledged to me that he signed and sealed the said instrument as his free and voluntary act and deed for the uses and purposes therein mentioned.

WITNESS my hand and official seal hereto affixed the day and year in this certificate above written.

\_\_\_\_\_

Printed name

Notary Public in and for the State of Washington,  
residing at \_\_\_\_\_

My appointment expires \_\_\_\_\_



RECORDING REQUESTED BY AND  
WHEN RECORDED MAIL TO:

---

---

---

---

---

**DECLARATION OF COVENANT  
FOR INSPECTION AND MAINTENANCE OF STORMWATER  
FACILITIES AND BMPS**

Grantor: \_\_\_\_\_

Grantee: King County

Legal Description: \_\_\_\_\_

---

---

Additional Legal(s) on: \_\_\_\_\_

Assessor's Tax Parcel ID#: \_\_\_\_\_

IN CONSIDERATION of the approved King County \_\_\_\_\_ permit for application No. \_\_\_\_\_ relating to the real property ("Property") described above, the Grantor(s), the owner(s) in fee of that Property, hereby covenants(covenant) with King County, a political subdivision of the state of Washington and its municipal successors in interest and assigns ("King County" and "the County", or "its municipal successor"), that he/she(they) will observe, consent to, and abide by the conditions and obligations set forth and described in Paragraphs 1 through

10 below with regard to the Property, and hereby grants(grant) an easement as described in Paragraphs 2 and 3. Grantor(s) hereby grants(grant), covenants(covenant), and agrees(agree) as follows:

1. The Grantor(s) or his/her(their) successors in interest and assigns ("Owners") shall at their own cost, operate, maintain, and keep in good repair, the Property's stormwater facilities and best management practices ("BMPs") identified in the plans and specifications submitted to King County for the review and approval of permit(s) #: \_\_\_\_\_ . Stormwater facilities include pipes, swales, tanks, vaults, ponds, and other engineered structures designed to manage stormwater on the Property. Stormwater BMPs include dispersion and infiltration devices, native vegetated areas, permeable pavements, vegetated roofs, rainwater harvesting systems, reduced impervious surface coverage, and other measures designed to reduce the amount of stormwater runoff on the Property.

2. King County shall have the right to ingress and egress over those portions of the Property necessary to perform inspections of the stormwater facilities and BMPs and conduct other activities specified in this Declaration of Covenant and in accordance with King County Code ("KCC") 9.04.120 or relevant municipal successor's codes as applicable. This right of ingress and egress, right to inspect, and right to perform required maintenance or repair as provided for in Section 3 below, shall not extend over those portions of the Property shown in Exhibit "A."

3. If King County determines that maintenance or repair work is required to be done to any of the stormwater facilities or BMPs, the Director of the Water and Land Resources Division or its municipal successor in interest ("WLR") shall give notice of the specific maintenance and/or repair work required pursuant to KCC 9.04.120 or relevant municipal successor's codes as applicable. The Director shall also set a reasonable time in which such work is to be completed by the Owners. If the above required maintenance or repair is not completed within the time set by the Director, the County may perform the required maintenance or repair, and hereby is given access to the Property, subject to the exclusion in Paragraph 2 above, for such purposes. Written notice will be sent to the Owners stating the



County's intention to perform such work. This work will not commence until at least seven (7) days after such notice is mailed. If, within the sole discretion of the WLR Director, there exists an imminent or present danger, the seven (7) day notice period will be waived and maintenance and/or repair work will begin immediately.

4. If at any time King County reasonably determines that a stormwater facility or BMP on the Property creates any of the hazardous conditions listed in KCC 9.04.130 or relevant municipal successor's codes as applicable and herein incorporated by reference, the WLR Director or equivalent municipal successors official may take measures specified therein.

5. The Owners shall assume all responsibility for the cost of any maintenance or repair work completed by the County as described in Paragraph 3 or any measures taken by the County to address hazardous conditions as described in Paragraph 4. Such responsibility shall include reimbursement to the County within thirty (30) days of the receipt of the invoice for any such work performed. Overdue payments will require payment of interest at the current legal rate as liquidated damages. If legal action ensues, the prevailing party is entitled to costs or fees.

6. The Owners are hereby required to obtain written approval from the King County WLR Director prior to filling, piping, cutting, or removing vegetation (except in routine landscape maintenance) in open vegetated stormwater facilities (such as swales, channels, ditches, ponds, etc.), or performing any alterations or modifications to the stormwater facilities and BMPs referenced in this Declaration of Covenant.

7. Any notice or consent required to be given or otherwise provided for by the provisions of this Agreement shall be effective upon personal delivery, or three (3) days after mailing by Certified Mail, return receipt requested.

8. With regard to the matters addressed herein, this agreement constitutes the entire agreement between the parties, and supersedes all prior discussions, negotiations, and all agreements whatsoever whether oral or written.

9. This Declaration of Covenant is intended to protect the value and desirability of the real property described above, and shall inure to the benefit of all the citizens of King County and its municipal successors and assigns. This Declaration of Covenant shall run with the land and be binding upon Grantor(s), and Grantor's(s') successors in interest, and assigns.

10. This Declaration of Covenant may be terminated by execution of a written agreement by the Owners and King County or the municipal successor that is recorded by King County in its real property records.

IN WITNESS WHEREOF, this Declaration of Covenant for the Inspection and Maintenance of Stormwater Facilities and BMPs is executed this \_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_.

\_\_\_\_\_  
GRANTOR, owner of the Property

\_\_\_\_\_  
GRANTOR, owner of the Property

STATE OF WASHINGTON    )  
COUNTY OF KING        )ss.

On this day personally appeared before me:

\_\_\_\_\_, to me known to be the individual(s) described in and who executed the within and foregoing instrument and acknowledged that they signed the same as their free and voluntary act and deed, for the uses and purposes therein stated.

Given under my hand and official seal this \_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_.

\_\_\_\_\_  
\_\_\_\_\_  
Printed name  
Notary Public in and for the State of Washington,  
residing at

\_\_\_\_\_  
My appointment expires \_\_\_\_\_



## ***Drainage Facility Maintenance Covenant***

We, the owners and contract purchasers of the lands herein **platted** (Grantor), agree that the obligations of Grantor shall inure to the benefit of and be binding upon the heirs, successors, and assigns. Grantor agrees that this covenant touches and concerns the land described herein and shall run with the land.

Grantor by execution of this covenant acknowledges that the benefits of this covenant inure to Grantor, downstream property owners, and the general public, and that Snohomish County (County) as third-party beneficiary of this covenant has the right, but not the obligation, to enforce this covenant on behalf of downstream property owners and the general public. County requires this covenant to protect private and public property, private and public drainage infrastructure, and natural resources of downstream property owners and the general public.

Grantor, in consideration of the approval of this **subdivision**, hereby covenants to perform regular maintenance upon the drainage facilities installed, or to be installed, upon Grantor's property. Regular maintenance shall include, at a minimum, annual inspection of the stormwater drainage system. As applicable, the system shall include the stormwater conveyance system pipes, ditches, swales, and catch basins; stormwater flow regulation system detention ponds, vaults, pipes, retention ponds, flow regulation and control structures; infiltration systems and water quality control system.

The scope of this covenant and right of entry shall be adequate to provide for the access, inspection, and maintenance of the stormwater drainage system, and shall be subject to the following terms and conditions:

1. County shall have the perpetual right of entry across adjacent lands of the Grantor for purposes of inspecting, auditing, or conducting required maintenance of the drainage facility.

2. If County inspection determines that maintenance is not being performed, County shall endeavor to provide Grantor reasonable advance notification of the need to perform the maintenance and a reasonable opportunity for Grantor to perform it. In the event that Grantor fails to complete the required maintenance within a reasonable time period, County

shall have the right to perform or contract with others to perform it at the sole expense of the Grantor. If County in its sole discretion determines that an imminent or present danger exists, required maintenance and/or repair may begin immediately at Grantor's expense without prior notice to Grantor. In such event, County shall provide Grantor with a written statement and accounting of all work performed and the fees, charges, and expenses incurred in making such repairs. Grantor shall agree to reimburse County or pay County's vendors directly for all reasonable fees, charges, and expenses identified in County's statement.

3. If County is required to act as a result of Grantor's failure to comply with this covenant, County may remove any obstructions and/or interferences that in the sole opinion of County impair the operation of the drainage facility or the maintenance thereof. Grantor agrees to hold County, its officers, employees, and agents harmless from any and all claims, actions, suits, liability, loss, expenses, damages and judgments of any nature whatsoever, including costs and attorney's fees, incurred by the removal of vegetation or physical interference from the drainage facility.

4. When exercising the maintenance provisions of the covenant, in the event of nonpayment, County may bring suit to recover such costs, including attorney's fees, and upon obtaining a judgment, such amount shall become a lien against the property of Grantor as provided in RCW 4.56.190.

5. Grantor covenants that all of the owners, contract purchasers and lien holders of the property described herein have signed the dedication and/or declaration of this **subdivision**, that they have the right to grant this covenant on the property, and that the title to the property is free and clear of any encumbrances which would interfere with the ability to grant this covenant.

Return Address:  
Snohomish County Property Manager  
3000 Rockefeller Avenue  
Mail Stop 404  
Everett, WA 98201-4046  
PDS Reference PFN: \_\_\_\_\_

## Drainage Facility Maintenance Covenant

**Grantor(s)** hereinafter referred to as **Grantor**:

- 1.
- 2.
- 3.

**Grantee: Snohomish County**, hereinafter referred to as **County**, a Political Subdivision under the Laws of the State of Washington.

**Legal Description** of property encumbered by covenant:  
Abbreviated:

*(if applicable, insert lot, Block, Plat Name), and/or as described in Exhibit(s) “ “ (typically Exhibit A).*

Located in      *qtr./*      *qtr.* Sec.      Twp.      N., Rge.      E., W.M.

**Reference Number(s)** of documents assigned, released, or modified:

**Assessor’s Property Tax Parcel/Account Number(s)** of property(s) encumbered by the drainage covenant:

Grantor has a record interest in the property encumbered by the covenant and agrees that the obligations of Grantor shall inure to the benefit of and be binding upon the heirs, successors, and assigns. Grantor agrees that this covenant touches and concerns the land described in Exhibit \_\_\_\_\_ and shall run with the land.

Grantor by execution of this covenant acknowledges that the benefits of this covenant inure to Grantor, downstream property owners, and the general public, and that the County as third-party beneficiary of this covenant has the right, but not the obligation, to enforce this covenant on behalf of downstream property owners and the general public. The County requires this covenant to protect private and public property, private and public drainage infrastructure, and natural resources of downstream property owners and the general public.

Grantor in consideration of the approval of County development permit No. \_\_\_\_\_, relating to the real property described in Exhibit \_\_\_\_\_ and in consideration of other valuable consideration, receipt and sufficiency of which is hereby acknowledged, hereby covenants to perform regular maintenance upon the drainage facilities installed, or to be installed, upon Grantor's property. Regular maintenance shall include, at a minimum, annual inspection of the stormwater drainage system. As applicable, the system shall include the stormwater conveyance system pipes, ditches, swales, and catch basins; stormwater flow regulation system detention ponds, vaults, pipes, retention ponds, flow regulation and control structures; infiltration systems and water quality control system.

The scope of this covenant and right of entry shall be adequate to provide for the access, inspection, and maintenance of the stormwater drainage system, and shall be subject to the following terms and conditions:

1. The County shall have the perpetual right of entry across adjacent lands of the Grantor for purposes of inspecting, auditing, or conducting required maintenance of the drainage facility.

2. If County inspection determines that maintenance is not being performed, the County shall endeavor to provide Grantor reasonable advance notification of the need to perform the maintenance and a reasonable opportunity for the Grantor to perform it. In the event that Grantor fails to complete the required maintenance within a reasonable time period, the County shall have the right to perform or contract with others to perform it at the sole expense of the Grantor. If the County in its sole discretion determines that an



imminent or present danger exists, required maintenance and/or repair may begin immediately at Grantor's expense without prior notice to Grantor. In such event, the County shall provide Grantor with a written statement and accounting of all work performed and the fees, charges, and expenses incurred in making such repairs. Grantor shall agree to reimburse the County or pay the County's vendors directly for all reasonable fees, charges, and expenses identified in the County's statement.

3. If the County is required to act as a result of Grantor's failure to comply with this covenant, the County may remove any obstructions and/or interferences that in the sole opinion of the County impair the operation of the drainage facility or the maintenance thereof. Grantor agrees to hold the County, its officers, employees, and agents harmless from any and all claims, actions, suits, liability, loss, expenses, damages and judgments of any nature whatsoever, including costs and attorney's fees, incurred by the removal of vegetation or physical interference from the drainage facility.

4. When exercising the maintenance provisions of the covenant, in the event of nonpayment, the County may bring suit to recover such costs, including attorney's fees, and upon obtaining a judgment, such amount shall become a lien against the property of Grantor as provided in RCW 4.56.190.

5. Grantor covenants that the owners of the property described herein are the person or persons identified on page 1 of this covenant as Grantors, that they have the right to grant this covenant on the property, and that the title to the property is free and clear of any encumbrances which would interfere with the ability to grant this covenant.

Executed this \_\_\_\_\_ day of \_\_\_\_\_, \_\_\_\_\_

**Grantors:**

Signature(s): \_\_\_\_\_

Printed Name(s): \_\_\_\_\_

Title of Authorized Representative(s):  
(if signing on behalf of a corporation)  
\_\_\_\_\_

**Drainage Facility Maintenance Covenant**

**PFN** \_\_\_\_\_

Additional Signatures (if needed):

\_\_\_\_\_  
\_\_\_\_\_

Note: Signature(s) of Grantor(s) must be acknowledged by appropriate Notary Form.

Accepted and approved  
for Snohomish County:

\_\_\_\_\_ Date: \_\_\_\_\_  
Director  
Snohomish County  
Department of Planning and  
Development Services

**CONSENT TO AND APPROVAL OF  
DRAINAGE MAINTENANCE COVENANT**

\_\_\_\_\_ (*lender*), the current Beneficiary of a Deed of Trust recorded under AFN \_\_\_\_\_, records of Snohomish County, which deed of trust encumbers the real estate described in Exhibit \_\_\_\_\_ of the attached Drainage Maintenance Covenant, does hereby consent to the establishment of said covenant

Signed: \_\_\_\_\_

Title: \_\_\_\_\_

Date: \_\_\_\_\_

*REPRESENTATIVE ACKNOWLEDGMENT*

STATE OF WASHINGTON       )  
  ) ss  
COUNTY OF SNOHOMISH     )

I certify that I know or have satisfactory evidence that \_\_\_\_\_ is the person who appeared before me, and said person acknowledged that (he/she/they) signed this instrument, on oath stated that (he/she/they) was/were authorized to execute the instrument and acknowledged it as the \_\_\_\_\_ of \_\_\_\_\_ to be the free and voluntary act of such party for the uses and purposes mentioned in the instrument.

Dated: \_\_\_\_\_

Signature: \_\_\_\_\_  
(print name) \_\_\_\_\_

(Seal or stamp)

NOTARY PUBLIC IN AND FOR THE STATE OF WASHINGTON  
My appointment expires \_\_\_\_\_

*INDIVIDUAL ACKNOWLEDGMENT*

STATE OF WASHINGTON        )  
  ) ss  
COUNTY OF SNOHOMISH    )

I certify that I know or have satisfactory evidence that

\_\_\_\_\_  
is/are the person(s) who appeared before me, and said person(s) acknowl-  
edged that (he/she/they) signed this instrument and acknowledged it to be  
(his/her/their) free and voluntary act for the uses and purposes mentioned in  
the instrument.

Dated: \_\_\_\_\_

Signature: \_\_\_\_\_  
(print name) \_\_\_\_\_

(Seal or stamp)

NOTARY PUBLIC IN AND FOR THE STATE OF WASHINGTON  
My appointment expires \_\_\_\_\_

*REPRESENTATIVE ACKNOWLEDGMENT*

STATE OF WASHINGTON        )  
  ) ss  
COUNTY OF SNOHOMISH    )

I certify that I know or have satisfactory evidence that

\_\_\_\_\_ is the person  
who appeared before me, and said person acknowledged that (he/she/they)  
signed this instrument , on oath stated that (he/she/they) was/were authorized  
to execute the instrument and acknowledged it as the  
\_\_\_\_\_ of \_\_\_\_\_  
to be the free and voluntary act of such party for the uses and purposes  
mentioned in the instrument.

Dated: \_\_\_\_\_

Signature: \_\_\_\_\_  
(print name) \_\_\_\_\_

(Seal or stamp)

NOTARY PUBLIC IN AND FOR THE STATE OF WASHINGTON  
My appointment expires \_\_\_\_\_

## APPENDIX B


---

# Examples of Private Property Owner Education



# Pierce County

## Stormwater Maintenance Manual for Private Facilities



# 1.0 Introduction:

## Maintaining Your Stormwater Facilities

The intent of this stormwater maintenance manual is to assist private stormwater management system owners in performing proper maintenance of these facilities.

Stormwater management facilities consist of a series of collection and conveyance systems, detention systems, and treatment facilities. They are typically a combination of landscape and structural components that slow, filter, detain, or infiltrate stormwater runoff on-site after a rainfall event. Properly designed, installed and maintained stormwater management facilities protect water quality and reduce flooding.

Pierce County Code Section 17A.40.020 states that private property owners are responsible for maintaining stormwater management structures that they own. Owners should have a maintenance program that addresses every component of the stormwater system, to ensure the system does not lose its intended capability to manage stormwater. Pierce County's "Stormwater Management and Site Development Manual", (Ord. 2008-59s, Ord. 96-47) requires that owners of private stormwater management facilities applying for development after the effective date of the Stormwater Manual conduct routine and non-routine inspection and maintenance of their stormwater system and prepare an annual inspection report to be submitted to Pierce County on or before May 15.

Property owners with private systems constructed prior to the effective date of the *Stormwater Manual* are also required to maintain their stormwater facilities, but are not required to submit the annual inspection and maintenance report to Pierce County.

## 1.1 How to Apply this Manual

Private owners should review this manual for understanding of the general function of their stormwater management facilities. After determining the type of facilities associated with the owner's site, the owner should download or copy the checklists for each facility and utilize them in facility inspection and maintenance.

It is important to note that there may be more than one facility associated with an individual site. For example, your site may include catch basins, a detention pond, and a control [structure/flow restrictor](#). In this case, all three checklists should be utilized for inspection and maintenance.



## 1.2 Why Manage Stormwater Runoff?

When it rains or snows in urban areas, the stormwater runs off impervious surfaces (such as roofs and paved areas) instead of soaking into the ground. In the past stormwater runoff has mainly been directed into drains and pipes that carry it off-site for eventual discharge into a river or stream.

The past approach to stormwater management has a number of harmful effects:

- Impervious areas and residential lawns generate large volumes of runoff relatively quickly. The increased volume and rate of runoff can cause flooding and erosion of natural waterways, damage to roads and other manmade structures, and destroy natural wildlife habitat.
- The stormwater runoff picks up oil, pesticides, metals, chemicals, sediment, and other pollutants that harm water quality and fish habitat.
- During warm weather, the runoff absorbs heat from the impervious surfaces. This increases the temperature of the receiving waters, with negative impacts on fish and other aquatic life.
- Less water is able to infiltrate into the ground. This reduces groundwater recharge which reduces summer base flow in streams.

The current approach to stormwater management is for facilities to be designed to help mitigate for these negative effects of stormwater runoff by a combination of reducing or eliminating runoff, treatment of runoff, and/or retention or detention of runoff with a metered release through actions called “Best Management Practices”.

## 1.3 Frequently Asked Questions

1. **Q.** What are Best Management Practices (BMPs)?

**A.** BMPs are a series of actions that are designed to reduce stormwater pollution, prevent discharging contaminants to natural water bodies and reduce stormwater facility maintenance costs. These actions can take several different forms. Examples of these are:

Behavioral--For example, sweeping a driveway instead of hosing it into the storm drain.

Procedural--Such as implementing an inventory control program for hydraulic oil or other lubricants to identify changes in consumption. This type of program can be used to identify maintenance problems, and save the business owner money on equipment down-time and lubricant costs.

Structural--Such as building a roof over a production area, or installing an oil/water separator.

In general, behavioral and procedural type BMPs will cost the least to implement initially and may save money over time. Structural BMPs typically cost more to construct, operate, and maintain.

BMPs are separated into two broad categories, namely *source control* and *treatment BMPs*. As the name implies, source control BMPs prevent contaminants from entering stormwater runoff by controlling them at the source. Treatment BMPs are utilized to treat stormwater that is already contaminated. Most treatment BMPs require planning, designing, permitting, and construction, and none can remove 100% of the contaminants in stormwater. These factors, added to the typical expense of treatment BMPs, makes source control BMPs the preferred choice.

2. **Q.** There is a ditch in front of my home. Who is responsible for maintaining it?

**A.** If you are in a private development: you and your neighbors will have to maintain the drainage. If you are within a city's limits: contact your city's public works department. If you are not within a city's limits: storm drainage systems in public roads are maintained by the Transportation Division of Public Works and Utilities. The contact number for the Road Maintenance Division is (253)-798-6000. You can also use the online request system at the following URL; <http://www.co.pierce.wa.us/cfapps/secure/publicworks/request.cfm>

3. Q. What methods should we use to control unwanted pests and vegetation?

A. Pierce County encourages the use of an Integrated Pest Management (IPM) approach to control unwanted pests. Pests are any plant or animal life that adversely interferes with the function, safety, and aesthetics of the stormwater facility. IPM is a coordinated decision-making and action process that uses the most appropriate control methods and strategy in an environmentally and economically sound manner.

The IPM approach emphasizes physical, mechanical, cultural, and biological tactics to keep pests and vegetation problems low enough to limit or eliminate the use of chemical control. The major elements of IPM include:

- Preventing pest problems;
- Monitoring for the presence of pests and pest damage;
- Establishing a level of pest population that can be tolerated without being detrimental to the stormwater facilities function or aesthetics of the facility.
- Treating pest problems to reduce populations below those established levels by using the most environmentally sensitive and safe method to control the pest;
- Evaluating the effects and effectiveness of the pest treatment.

Monitoring of pest populations is key to successful IPM implementation. Pest problems are easier to control if the problem is discovered early. With IPM, pesticides are used only as a last resort in order to protect water quality and human health.

More information on IPM is available from the Washington State Department of Agriculture (<http://agr.wa.gov>) and the Washington State University/Pierce County Extension Service (<http://www.pierce.wa.wsu.edu>).

4. Q. There is tall grass and debris in the pond/creek near my house. Who takes care of this?

A. Publicly owned storm drainage ponds and some creeks are maintained by Surface Water Management. Call the Water Quality/ Flooding and Storm Drainage Line at 253-798-4274 to report your concern. Your call will be routed to a member of our maintenance team for inspection and the scheduling of a work crew if needed. Privately owned storm drain systems must be maintained by the property owner or homeowner's association.

5. Q. *t plants should we avoid planting?*

A. Non-native, invasive plants should not be planted. Early detection and control of these plants are important to prevent future maintenance problems and increased

maintenance costs. Some native plants, such as red alder (*Alnus rubra*), can increase maintenance costs due to leaf fall into the pond causing clogging problems. Additional plant species to avoid are: English ivy (*Hedera helix*), willow (*Salix* species), black cottonwood (*Populus balsamifera* spp. *trichocarpa*), Himalayan and evergreen blackberry (*Rubus discolor* and *laciniatus*), and cattails (*Typha*).

6. Q. *How can we make the stormwater facility more attractive?*

A. The Integrated Pond, a booklet produced by King County, provides information on Integrating stormwater facilities into attractive community spaces. This booklet provides information on planting appropriate vegetation around the facility to make it more attractive or to screen the facility. The booklet can be downloaded from King County's website at (<http://www.kingcounty.gov/environment/waterandland/stormwater/documents/integrated-pond.aspx>)

Pierce County recommends native plants be used around stormwater facilities. Native plants require less water once they are established, resist pests and diseases better, require less fertilizer and pesticides, and provide wildlife habitat.

Plants differ in their ability to cope with different soils, moisture levels, and sun exposure. When planting next to the stormwater facility, consider future maintenance requirements such as grass mowing and watering requirements. Avoid planting deciduous trees and shrubs adjacent to the facility as their falling leaves may cause blocking problems. Avoid plants with invasive root systems, such as willows, and plants that can blow over easily, such as Red alder and Cottonwood. See *The Integrated Pond* (King County) and the *Low Impact Development Technical Guidance Manual for Puget Sound – Appendices 1 and 3* at ([http://www.pierce.wsu.edu/Water\\_Quality/LID/LID\\_manual2005.pdf](http://www.pierce.wsu.edu/Water_Quality/LID/LID_manual2005.pdf)) for a list of native plants appropriate for stormwater facilities. Additional information on native plants can be found on the Washington Native Plant Society website at (<http://www.wnps.org/index.html>).

To reduce maintenance costs and prevent future water flow problems, it is not recommended to plant shrubs or trees in stormwater ponds below the maximum designed water level. Planting grass or low growing, non-invasive, native plants within the facility may be appropriate but it should be done cautiously so as to not interfere with the functions of the facility. Promptly replant any bare soil areas that could contribute sediments to the stormwater system or cause erosion of the facility.

7. Q. *We have a limited maintenance budget. What are the most important vegetation maintenance activities we should do?*

A. The inlets and outlets should be kept clear of vegetation and other potentially blocking material. The pond should not be allowed to become overgrown with noxious or invasive vegetation.

8. Q. Where do I find more information on the cost of stormwater maintenance?

A. Unit costs for common maintenance procedures can be found on the Stormwater Managers Resource Center (SMRC) website at:

[Stormwater Managers Resource Center \(SMRC\)](#)

9. Q. Can I get credit for maintaining my stormwater facility?

A. A properly maintained storm drainage system can significantly reduce your Surface Water Management Fee.

Credits to the Surface Water Management Fee can be received by meeting the requirements of Pierce County Code Section 11.02.050B.

For more information on receiving stormwater credits call (253) 798-4020.

10. Q. Why can't I dump used motor oil and other wastes into the stormwater inlet on my street?

A. Stormwater inlets lead to stormwater management systems that discharge to natural water bodies (e.g. lakes or stream) or to the groundwater. Excessive contaminants, such as motor oils dumped into the storm system, will create the need for more frequent maintenance and higher maintenance costs.

11. Q. I wash my own car, how can I be environmentally responsible?

A. The best option is to use a commercial car wash where the wash water is recycled and does not drain to the storm system. Improper disposal of wash water will increase the required maintenance frequency resulting in higher maintenance costs. The Pierce County Stormwater Pollution Prevention Manual provides Best Management Practices (BMPs) for washing vehicles on private property; see additional resources section in Chapter 5.

12. Q. Can you make the flooding go away?

A. Not once the flooding has started, but we might be able to help keep it from flooding again. We use input from residents to figure out the best solution to flood problems and to prioritize which projects get constructed first. During a flood, sand bags can be picked up at your local Fire District Headquarters. If a blocked pipe or ditch in the public system is the cause of your flooding, the Road Maintenance Shops may also help with cleaning them out.

County Road Maintenance Hot Line ..... (253) 798-6000  
Requests will be acted on within 24 hours or the next business day.

Water Quality/ Flood & Storm Drainage Complaints: ..... (253) 798-4274  
Report flooding and private property storm drainage concerns.

**13. Q.** Where do I find information on the West Nile virus?

**A.** West Nile virus is a mosquito-borne virus that can cause encephalitis (or meningitis in humans and animals. Preventing mosquito bites and reducing mosquito-breeding habitat around your home are the best ways to protect your family. You should empty containers that hold standing water, such as old tires, buckets, and planters. Also, change the water in your birdbaths, fountains, wading pools and animal troughs weekly, and clean out your rain gutters so that they drain properly.


For questions related to West Nile Virus, contact the Tacoma-Pierce County Health Department at (253) 798-6578

Poorly maintained private stormwater drainage facilities can increase breeding sites for mosquitoes in your community or property. Owners of private stormwater drainage facilities can request a courtesy inspection of their system to insure proper operation by contacting Pierce County Surface Water Management at (253) 798-2725.

## 3.25 Drywell

A drywell is a perforated, open-bottomed manhole used to infiltrate stormwater into the ground. Drywells temporarily store stormwater runoff during rain events. Drywells do not discharge to a downstream conveyance system or nearby surface water. Instead, drywells rely on the ability of the site's soils to absorb the stormwater into the ground.

While not the intended use, drywells trap sediment and some of the oily pollutants in runoff. They are more likely to fill with oily sediment in areas that lack swales or other treatment facilities. Fine oil sediment can clog drywells and lead to localized street flooding. Also, pollutants discharged into drywells can migrate into groundwater. Drywells were often installed in closed topographic depressions, areas with well drained soils, or areas having inadequate storm sewers. Often, drywells contain groundwater. Because drywells can be easily clogged and tend to concentrate pollutants in one place; pollution and sediment control practices should be used to protect them.



### 3.25 Drywell Checklist

Frequency	Drainage System Feature	Date				Problem	Conditions to Check For	Conditions That Should Exist
		✓	✓	✓	✓			
MONTHLY, STORM	General					Trash & Debris	Trash or debris (in the drywell) that exceeds 60 percent of the sump depth as measured from the bottom of basin to invert of the lowest pipe into or out of the drywell, but in no case less than a minimum of six inches clearance from the debris surface to the invert of the lowest pipe.	No trash or debris in the drywell.
MONTHLY	General					Contaminants and pollution	Any evidence of oil, gasoline, contaminants or other pollutants in or around facility.	Remove. (Coordinate removal and cleanup with local water quality agency).
MONTHLY	General					Cover damaged or difficult to remove	One maintenance person cannot remove lid after applying normal lifting pressure. Corrosion/deformation of cover. Intent is to keep cover from sealing off access to maintenance.	Cover can be removed and installed by one maintenance person.
MONTHLY	General					Cover not in place	Cover is missing or only partially in place. Any open manhole or catch basin requires maintenance.	Manhole or catch basin cover is closed.
MONTHLY	General					Does not dissipate stormwater	Does not dissipate stormwater	Replace or repair.
MONTHLY	General					Ladder damaged	Ladder is unsafe due to missing rungs, misalignment, not securely attached to structure wall, rust, cracks, corrosion, or sharp edges. Confined space warning sign is missing.	Ladder meets design standards. Allows maintenance person safe access. Replace sign warning of confined space entry requirements. Ladder and entry notification complies with OSHA standards.
ANNUAL	Structure					Structure damage	Maintenance/inspection personnel determine that drywell is not structurally sound.	Vault replaced or repairs made so that vault meets design specifications and is structurally sound.

### Drywell Checklist (Continued)



Frequency	Drainage System Feature	DANNUALte				Problem	Conditions to Check For	Conditions That Should Exist
		✓	✓	✓	✓			
ANNUAL	Structure					Structure Damage	Cracks wider than ½-inch at the joint of any inlet/outlet pipe or evidence of soil particles entering through the cracks.	Vault repaired so that no cracks exist wider than ¼-inch at the joint of the inlet/outlet pipe.
MONTHLY	General					Opening clogged	Openings are clogged, reducing capacity.	Water-jet clogged openings; or Convert existing, clogged drywell to a sediment trap and install a new drywell or drainage trench. To convert to a sediment trap, required are grouting holes, covering the base with concrete, and adding piping.
MONTHLY	General					Sediment	Sediment is greater than 1/3 of the distance between the base and the inlet pipe.	Remove. Do not allow sediment and water to discharge back into the storm sewer.
MONTHLY	General					Standing water	Standing water indicates the drywell is into the water table.	Rebuild drywell to prevent stormwater from going directly into groundwater.

If you are unsure whether a problem exists, please contact a Professional Engineer.

Comments:

Key:


(MONTHLY) Monthly from November through April.

(ANNUAL) Once in late summer (preferable September)

(STORM) After any major storm (use 1-inch in 24 hours as a guideline).

## 3.28 Infiltration Trench

A stormwater infiltration trench is a closed basin built by excavating below existing ground. Infiltration trenches temporarily store stormwater runoff during rain events. Infiltration trenches do not discharge to a downstream conveyance system or nearby surface water. Instead, infiltration trenches rely on the ability of the site's soils to absorb the stormwater into the ground.



### 3.28 Infiltration Trench Checklist

Frequency	Drainage System Feature	Date				Problem	Conditions to Check For	Conditions That Should Exist
		✓	✓	✓	✓			
MONTHLY	General					Contaminants and Pollution	Any evidence of oil, gasoline, contaminants or other pollutants in or around facility.	Remove.  (Coordinate removal and cleanup with local water quality response agency).
MONTHLY	General					Drainage Slow	Drainage Trench - decreased capacity that indicates slow drainage.	Verify facility design rate. Clean perforated drain pipe. Do not allow removed sediment and water to discharge back into the storm sewer.
MONTHLY	General					Sediment & Debris	Sediment depth is greater than 20% of pipe diameter.	Clean pipe and remove material.
MONTHLY	General					Trash & Debris	Trash or debris which is located immediately in front of the catch basin opening or is blocking inletting capacity of the basin by more than 10%.	No Trash or debris located immediately in front of catch basin or on grate opening.
MONTHLY	General					Trash & Debris	Trash or debris (in the basin) that exceeds 60 percent of the sump depth as measured from the bottom of basin to invert of the lowest pipe into or out of the basin, but in no case less than a minimum of six inches clearance from the debris surface to the invert of the lowest pipe.	No trash or debris in the trench.
MONTHLY	General					Trash & Debris	Trash or debris in any inlet or outlet pipe blocking more than 1/3 of its height.	Inlet and outlet pipes free of trash or debris.
MONTHLY	General					Trash & Debris	Dead animals or vegetation that could generate odors that could cause complaints or dangerous gases (e.g., methane).	No dead animals or vegetation present within the catch basin.

If you are unsure whether a problem exists, please contact a Professional Engineer.

Comments:

Key:

(MONTHLY) Monthly from November through April.


(ANNUAL) Once in late summer (preferable September)

(STORM) After any major storm (use 1-inch in 24 hours as a guideline).

### 3.31 Compost Amended Soils

Amending a soil with compost increases the soil’s permeability and water holding capacity, thereby delaying and often reducing the peak stormwater run-off flow rate, and decreasing irrigation water requirements. Amending soils will also enhance the lawn’s long-term aesthetics while reducing fertilizer and pesticide requirements.

**Surface Water Runoff Rate - Austrian Vineyard Data**  
**Municipal Solid Waste Compost Application**  
**30% Slope**



### 3.31 Compost Amended Soil

Frequency	Drainage System Feature	Date				Problem	Conditions to Check For	Conditions That Should Exist
		✓	✓	✓	✓			
ANNUAL	General Facility Requirements					Soil media (maintain high organic soil content)	Vegetation not fully covering ground surface.	Re-mulch landscape beds with 2-3 inches of mulch until the vegetation fully closes over the ground surface
Ongoing	General Facility Requirements					Soil media (maintain high organic soil content)	None. Preventative maintenance	Return leaf fall and shredded woody materials from the landscape to the site as mulch.
Ongoing	General Facility Requirements					Soil media (maintain high organic soil content)	None. Preventative maintenance	On turf areas, "grasscycle" (mulch-mow or leave the clippings) to build turf health
Ongoing	General Facility Requirements					Soil media (maintain high organic soil content)	None. Preventative maintenance	Avoiding broadcast use of pesticides (bug and weed killers) like "weed & feed," which damage the soil life.
ANNUAL	General Facility Requirements					Soil media (maintain high organic soil content)	None. Preventative maintenance	Where fertilization is needed (mainly turf and annual flower beds), a moderate fertilization program which relies on natural organic fertilizers (like compost) or slow release synthetic balanced fertilizers.
ANNUAL	General Facility Requirements					Compaction	Soils become waterlogged, do not appear to be infiltrating.	To remediate, aerate soil, till or further amend soil. If drainage is still slow, consider investigating alternative causes (e.g., high wet-season groundwater levels, low permeability soils). Also consider landuse and protection from compacting activities. If areas are turf, aerate compacted areas and top dress them with ¼-½ inch of compost to renovate them.
ANNUAL	General Facility Requirements					Erosion/scouring	Areas of potential erosion are visible.	Take steps to repair or prevent erosion. Identify and address the causes of erosion.
ANNUAL	General Facility Requirements					Grass/vegetation	Less than 75% of planted vegetation is healthy with a generally good appearance.	Take appropriate maintenance actions (e.g., remove/replace plants)

MONTHLY	General Facility Requirements				Noxious weeds	Listed noxious vegetation is present. See Pierce County noxious weed list.	By law, noxious weeds must be removed and disposed immediately. It is strongly encouraged that herbicides and pesticides not be used in order to protect water quality.
QUARTERLY	General Facility Requirements				Weeds	Weeds are present.	Remove and dispose of weed material. It is strongly encouraged that herbicides and pesticides not be used in order to protect water quality.

If you are unsure whether a problem exists, please contact a Professional Engineer.

Comments:

Key:

(MONTHLY) Monthly from November through April.

(ANNUAL) Once in late summer (preferable September)


(STORM) After any major storm (use 1-inch in 24 hours as a guideline).

(Biannually) Twice per year in the spring and fall

(Quarterly) 4 times per year

## 3.32 Pervious Pavement

Pervious paving allows water to infiltrate into layers of gravel placed below the paving and then into soil and groundwater below. By infiltrating most of the storm water on-site, the amount of water and pollution flowing into storm sewers and directly to rivers and streams is greatly reduced. This, in turn, protects water quality, maintains more stable base flows to streams, reduces flood peaks, and reduces stream bank erosion. With infiltration, groundwater is recharged and streams are replenished with cool, clean groundwater in a more natural way. Pervious paving is one component of Low Impact Development (LID).



## 3.32 Pervious Pavement

Frequency	Drainage System Feature	Date				Problem	Conditions to Check For	Conditions That Should Exist
		✓	✓	✓	✓			
BIANNUAL	Surface					Pervious asphalt or cement concrete	None. Maintenance to prevent clogging with fine sediment.	Use conventional street sweepers equipped with vacuums, water, and brushes or pressure washer to restore permeability. Vacuum or pressure wash the pavement two to three times annually.
Ongoing	Surface					Pervious asphalt or cement concrete	None. Maintenance to prevent clogging with fine sediment.	Prohibit use of sand and sealant application and protect from construction runoff.
ANNUAL	Surface					Pervious asphalt or cement concrete	Major cracks or trip hazards.	Fill with patching mixes. Large cracks and settlement may require cutting and replacing the pavement section.
As needed	Surface					Pervious asphalt or cement concrete	Utility cuts.	See utility restoration protocol on SPU NDS website.
BIANNUAL	Surface					Fallen leaves / debris	Fallen leaves or debris.	Remove/dispose.
BIANNUAL	Surface					Interlocking concrete paver blocks	Interlocking paving block missing or damaged.	Replace damaged paver block
ANNUAL	Surface					Interlocking concrete paver blocks	Settlement of surface.	May require resetting
BIANNUAL	Surface					Interlocking concrete paver blocks	Sediment or debris accumulation between paver blocks.	Remove/dispose
ANNUAL	Surface					Interlocking concrete paver blocks	Loss of void material between paver blocks.	Refill per manufacturer's recommendations.
Varies	Surface					Interlocking concrete paver blocks	Varied conditions.	Perform O&M per manufacturer's recommendations.
BIANNUAL	Surface					Open-celled paving grid with gravel	Sediment or debris accumulation in grid voids.	Remove/dispose
ANNUAL	Surface					Open-celled paving grid with gravel	Loss of soil and/or grass material in grid.	Refill and/or replant per manufacturer's recommendations.



Varies	Surface					Open-celled paving grid with gravel	Varied conditions.	Perform O&M per manufacturer's recommendations.
BIANNUAL	Surface					Open-celled paving grid with grass	Sediment or debris accumulation in grid voids.	Remove/dispose
ANNUAL	Surface					Open-celled paving grid with grass	Loss of soil and/or grass material in grid.	Refill and/or replant per manufacturer's recommendations.
Varies	Surface					Open-celled paving grid with grass	Varied conditions.	Perform O&M per manufacturer's recommendations.
BIANNUAL	Overflows and Emergency Spillways					Obstructions / debris	Obstructions or debris block 30% or more of outlet structure.	Remove/dispose
BIANNUAL	Overflows and Emergency Spillways					Erosion	Native soil is exposed or other signs of erosion damage are present.	Repair erosion and stabilize surface of spillway
Ongoing	Spill Prevention and Response					Spill prevention	Storage or use of potential contaminants in the vicinity of facility.	Exercise spill prevention measures whenever handling or storing potential contaminants
As needed	Spill Prevention and Response					Spill response	Release of pollutants. Call to report any spill to the the Wa Dept of Emergency Management 1-800-258-5990	Cleanup spills as soon as possible to prevent contamination of stormwater

If you are unsure whether a problem exists, please contact a Professional Engineer

Comments:

Key:

(MONTHLY) Monthly from November through April.

(ANNUAL) Once in late summer (preferable September)

(STORM) After any major storm (use 1-inch in 24 hours as a guideline).

(Biannually) Twice per year in the spring and fall

(Quarterly) 4 times per year

## 5.0 Developing a Maintenance Program

A stormwater maintenance program is essential to ensure that the facilities continue to function as designed to prevent possible flooding, property damage, water quality problems and expensive future repairs. The maintenance program consists of inspections and repairs as detailed in the maintenance checklists provided in Section 3.0.

Stormwater management facilities are most effective coupled with good housekeeping procedures. Good housekeeping includes educating facility users of proper storage and disposal of chemicals and potential pollutants, procedures for spill cleanup, proper use of fertilizers and other lawn care products, and maintenance of equipment to prevent release of pollutants to the stormwater system. Guidelines for establishing good housekeeping procedures (I.E. Source Control BMPs) and developing a training program to educate facility users can be found in the Pierce County Surface Water Management Webpage at Stormwater Pollution Prevention Manual located at:

<http://www.co.pierce.wa.us/swm>

### 5.1 Who Should Perform Maintenance Duties?

Private stormwater facility owners are responsible for ensuring that the facilities are maintained and continue to function as designed. Some activities such as litter removal and mowing can be effectively undertaken by facility owners, however, it is usually worth the cost to have a professional do the more difficult tasks. Filling eroded areas and soil disturbing activities, such as reseeding or re-planting vegetation are tasks that a professional landscaping firm should manage. If these tasks are not performed properly, erosion may occur resulting in accelerated sedimentation of stormwater facilities. Grading and sediment removal are tasks that are best left to professional contractors with the equipment and experience to safely perform the task and who are also able to identify potential problems early when it is most cost effective to make repairs or alterations.

## 5.2 Working with Maintenance Contractors

The following is a guideline for researching and choosing a qualified contractor to meet your maintenance needs.

Start your search for a contractor the right way - be informed. The information provided below will help you in your search for the right contractor for your job.

- Landscape maintenance contractors are typically capable of providing most routine maintenance for stormwater facilities. Special, non-routine maintenance may require an earthwork contractor or vactor company. Recently, several contractors have started specializing in stormwater facility maintenance. Private owners can choose to hire contractors when individual maintenance needs arise or enter into annual maintenance agreements where the contractor monitors and provides routine maintenance throughout the year as needed.
- Develop a list of potential contractors. Look in the Yellow Pages and/or ask friends, neighbors, relatives, and coworkers who they have used. Find out if their experiences were good or bad and why. Ask if they would use the contractor again.
- Ask contractors for references. Call your potential contractors and ask for a list of their customers or locations of completed jobs. Call references and ask whether they were satisfied with the job done, if the contractor kept to the agreed upon schedule, and whether they would hire the same contractor again.
- Ask to which trade associations the contractor belongs. Membership in a professional association is one sign the contractor recognizes the responsibilities of being a professional.
- Make sure to obtain and evaluate bids. Ask for a free written estimate of the work you want done. Be sure everyone is bidding on the same exact scope of work and including the exact materials you want. Be sure all quotes include everything you want and that there is a clear understanding of work to be performed by owner and work to be performed by contractor.
- Remember *"you get what you pay for."* A higher bid may be worth the price for better workmanship and contractor reliability.
- Make sure you understand the different types of bids you may receive. Be careful about hiring a contractor on an hourly time-and-materials, or cost-plus basis. Although the price may seem high at first, a fixed-price bid may give you the best protection and price. Also beware of "special deals," "demonstration projects," or *"a great deal from a friend of a friend."* Completely review and understand the contract prior to authorizing work.

### Questions to Ask Before Hiring a Contractor

- What experience, expertise and/or certification do you have? Do you specialize?
- Who will be doing the actual work: you personally, your employees, or subcontractors?
- Who will oversee the day-to-day job? (You may really like the contractor, but that person may not be the one performing or supervising the work.)
- How many other jobs will you be working on at the same time as mine? (If there are several, yours may not get the attention you want. On the other hand, the contractor's business may be large and he may be able to handle several jobs.)
- How long will the job take? What kind of mess, noise, and inconvenience should I expect? What problems may come up? (Asking questions before the job starts helps prevent surprises later.)
- Where will you dispose of material removed from storm drainage facilities? Is there an extra fee for contaminated materials?
- Does hiring this contractor feel right? (Use intuition - if you do not feel comfortable, find someone else.)
- Do I have rapport with this contractor? Am I confident in his expertise and ideas? Does he care about my concerns? Will he be reliable, keep his appointments, and return my telephone calls?
- Can I communicate with this person? Does he seem honest and forthright? (The contractor may be top-notch at the trade, but if the final product is not what you expected, you will not be happy.)
- Am I willing to be reasonable about unexpected costs that arise and to let my contractor make a profit?
- Am I ready for the unexpected, such as digging into solid rock, major replacement, etc.?
- Can I be flexible when the job takes longer than expected?
- Are my expectations so high that I will never be satisfied with my contractor?

## 5.3 How much will it Cost to Maintain a Stormwater Management System?

Specific maintenance costs depend on the characteristics of the facility, the site, and the area that contributes runoff to the facility. The general rule of thumb is that annual maintenance costs will be 5 to 10% of the facility's total capital cost. Routine, scheduled maintenance can help keep overall costs down by addressing problems before they require major attention.

Most of the routine maintenance measures recommended in the checklists (excluding major repair and replacement) are estimated to have an annual cost of \$200 to \$600 per acre of facility, above current landscape maintenance costs. Costs can vary depending on the types and level of maintenance practices used.

The cost and intensity of maintenance activities are usually higher during the two-year plant establishment period than after the facility has "settled in" after those first two years.

You need to determine how you will finance your maintenance needs. A healthy reserve should be put into place for both capital maintenance procedures (e.g., facility replacement and non-routine maintenance such as sediment removal, facility component repair or replacement, major replanting, or safety structure construction) and operating maintenance procedures (routine activities such as facility inspection, debris removal, and vegetation management).

The best recommendation is to establish a facility maintenance fund. For homeowner associations, this could be a portion of homeowner fees or a specific assessment. The fund should include:

- Ten percent of the facility's capital cost for annual routine maintenance per year.
- A percentage of the non-routine maintenance costs per year (i.e. for sediment removal, vegetation replacement) based on the frequency of removal. For example, if the facility needs mechanical sediment removal every 10 years, 10 percent of the total cost should be put aside each year.
- An additional 3 to 5% of the facility's capital cost per year for eventual facility replacement, based on the facility's life expectancy. Most of these facilities have a life expectancy of 25 to 50 years.

## 6.0 Additional Information/Resources

For more information on operation and maintenance of your stormwater management system contact:

Pierce County Department of Public Works and Utilities, Surface Water Management Division, (253) 798-2725

Or refer to information provided in the following resources:

Pierce County Stormwater Pollution Prevention Manual  
<http://www.co.pierce.wa.us/PC/services/home/environ/water/swm/sppman/>

King County Drainage Maintenance Standards for Commercial and Multifamily Drainage Facilities, 1997.  
<http://dnr.metrokc.gov/wlr/stormwater/DrainMaint.htm>

Puget Sound Shoreline Stewardship Guide Book,  
<http://dnr.metrokc.gov/wlr/watersheds/puget/puget-sound-guidebook.htm>

# Geotechnical Report

## Valley View Sub-division

Camas, Washington

Prepared for:  
Stan Firestone  
Vancouver, Washington  
30 April 2014  
Updated 1 May 2018



**Rapid**  
**Soil Solutions** LLC  
3915 SW Plum St  
Portland, OR  
503-816-3689

## TABLE OF CONTENTS

<b>1.0 GENERAL INFORMATION .....</b>	<b>3</b>
<b>2.0 SITE CONDITIONS.....</b>	<b>3</b>
2.1 Surface Conditions .....	3
2.2 Regional Geology .....	3
2.3 Field Explorations and Surfaces Conditions .....	4
2.3.1 Field Explorations .....	4
2.3.2 Surface Conditions .....	4
2.3.3 Groundwater .....	4
<b>3.0 GEOTECHNICAL DESIGN RECOMMENDATIONS .....</b>	<b>4</b>
3.1 Foundation.....	4
3.2 Retaining Walls .....	5
3.3 Seismic Design.....	6
3.4 Hazards.....	6
<b>4.0 CONSTRUCTION RECOMMENDATIONS .....</b>	<b>7</b>
4.1 Site Preparation .....	7
4.1.1 Proof Rolling.....	7
4.1.2 Wet Soil Conditions.....	8
4.2 Excavation .....	8
4.3 Structural Fills .....	8
4.3.1 Native Soils.....	8
4.3.2 Imported Granular Fill .....	8
4.3.3 Floor Slab and Base Rock Aggregate .....	9
4.4 Drainage .....	9
<b>5.0 CONSTRUCTION OBSERVATIONS .....</b>	<b>9</b>
<b>6.0 LIMITATIONS .....</b>	<b>9</b>

### SUPPORTING DATA

#### Appendix A - Figures

Figure 1 Location Plan

Figure 2 Site Plan

#### Appendix B – Laboratory data and Soil Logs



## 1.0 PROJECT AND SITE DESCRIPTIONS

### Introduction

Rapid Soil Solutions has prepared this Geotechnical Report to provide bearing capacity, roadway design values, soil parameters for earth work operations and installation of utilities for the 30 lot sub-division.

## 2.0 SITE CONDITIONS


### 2.1 Surface Conditions

The property is located in the Clark County Washington, accessed off of SE 40<sup>th</sup> Street. The site was cleared in past. The site was covered with tall grasses and weeds. See below site photo.



### 2.2 Regional Geology

The Camas Quadrangle developed in 2008 by Evarts and O'Connor maps the site as boring volcanic rock. However, the rock is far below the site and the site is cover with fine grained flood deposits.



## 2.3 Field Exploration and Subsurface Conditions

### 2.3.1 Field Explorations

Four (4) hand augur holes were excavated. The location of the augur holes are shown on Figure 2 in Appendix A. A registered professional engineer performed the excavation and logged the subsurface materials. Hand augur logs detailing materials encountered is in Appendix B. The logs were created using the Unified Soil Classification and Visual Manual Procedure (ASTM-D 2488).

### 2.3.1 Subsurface Conditions

The soil conditions were fine grained stiff damp sandy SILT. The soil conditions in all augur holes were consistent with each other and local geology map. Moistures ranged from 23.1 % to 28%.

### 2.3.2 Groundwater

No ground water was found during the explorations.

## 3.0 GEOTECHNICAL DESIGN RECOMMENDATIONS

### 3.1 Foundation Design

The building foundations may be installed on either engineered fill or firm native sub-grade that is found at a depth of about 0.5 feet. This depth may be locally variable and should be confirmed by a geotechnical engineer or their representative at the time of construction.

Continuous wall and isolated spread footings should be at least 16 and 24 inches wide, respectively. The bottom of exterior footings should be at least 16 inches below the lowest adjacent exterior grade. The bottom of interior footings should be at least 12 inches below the base of the floor slab.

Footings placed on engineered fill or firm native sub-grade should be designed for an allowable bearing capacity of 2,000 *pounds per square foot (psf)* by IBC 2012/2015 code. The recommended allowable bearing pressure can be doubled for short-term loads such as those resulting from wind or seismic forces.

Based on our analysis the total post-construction settlement is calculated to be less than 1 inch, with differential settlement of less than 0.5 inch over a 50-foot span for maximum column, perimeter footing loads of less than 100 kips and 6.0 kips per linear foot.

Lateral loads on footings can be resisted by passive earth pressure on the sides of the structures and by friction at the base of the footings. An allowable lateral bearing pressure of 150 *pounds per cubic foot (psf/f)* below grade may be used. Adjacent floor slabs, pavements or the upper 12-inch depth of adjacent, unpaved areas should not be

considered when calculating passive resistance. An angle of internal friction of 30 degrees can be used.

If construction is undertaken during periods of rain, then I recommend a 2-inch (or greater) layer of compacted, crushed rock be placed over the native soil. The silty soil is moisture sensitive. Meaning when dry it is firm and non-yielding but exposed to season rains it will lose its strength and need to be excavated and replaced with rock. See section 4.1.2 for wet weather conditions.

### **3.2 Retaining Walls**

The retaining wall design recommendations are based on the following assumptions: (1) the walls consist of conventional, cantilevered retaining walls; (2) the walls are less than 8 feet in height; (3) the backfill is drained; and (4) the backfill has a slope flatter than 4H: 1V. Re-evaluation of our recommendations will be required if the retaining wall design criteria for the project varies from these assumptions.

Unrestrained site walls that retain native soils should be designed to resist an active equivalent fluid unit weight of 35 pcf where supporting slopes are flatter than 4H: 1V. If retaining walls are restrained from rotation prior to being backfilled, the active equivalent fluid unit weight shall be increased to 50 pcf. For embedded building walls, a superimposed seismic lateral force should be calculated based on a dynamic force of  $5H^2$  pounds per lineal foot of wall, where H is the height of the wall in feet, and applied at 0.6H from the base of the wall. If other surcharges (e.g., slopes steeper than 4H:1V, foundations, vehicles, etc.) are located within a horizontal distance from the back of a wall equal to twice the height of the wall, then additional pressures will need to be accounted for in the wall design. Our office should be contacted for appropriate wall surcharges based upon the actual magnitude and configuration of the applied loads.

The wall footings should be designed in accordance with the guidelines provided in the “Foundation Design” section of this report.

These design parameters have been provided assuming that back-of-wall drains will be installed to prevent buildup of hydrostatic pressures behind all walls.

The backfill material placed behind the walls and extending a horizontal distance equal to at least half of the height of the retaining wall should consist of granular retaining wall backfill as specified in the “Structural Fill” section of this report.

The wall backfill should be compacted to a minimum of 92 percent of the maximum dry density, as determined by ASTM D1557. However, backfill located within a horizontal distance of 3 feet from the retaining walls should only be compacted to approximately 90 percent of the maximum dry density, as determined by ASTM D1557. Backfill placed within 3 feet of the wall should be compacted in lifts less than 6 inches thick using hand-operated tamping equipment (e.g., jumping jack or vibratory plate compactors). If flat work (e.g., sidewalks or pavements) will be placed atop the wall backfill, we recommend that the upper

2 feet of material be compacted to 92 percent of the maximum dry density, as determined by ASTM D1557.

A minimum 12-inch-wide zone of drain rock, extending from the base of the wall to within 6 inches of finished grade, should be placed against the back of all retaining walls. Perforated collector pipes should be embedded at the base of the drain rock. The drain rock should meet the requirements provided in the “Structural Fill” section of this report. The perforated collector pipes should discharge at an appropriate location away from the base of the wall. The discharge pipe(s) should not be tied directly into storm water drain systems, unless measures are taken to prevent backflow into the wall’s drainage system.

Settlements of up to 1 percent of the wall height commonly occur immediately adjacent to the wall as the wall rotates and develops active lateral earth pressures. Consequently, we recommend that construction of flat work adjacent to retaining walls be postponed at least 4 weeks after backfilling of the wall, unless survey data indicates that settlement is complete prior to that time.


### 3.3 Seismic Design Criteria

The seismic design criteria for this project USGS Earthquake Hazards Program. A summary of IBC 2012/2015 seismic design criterion below: using a Lat of 45.5909 and Long of -122.4650, site class D.

	<b>Short Period</b>	<b>1 Second</b>
Maximum Credible Earthquake Spectral Acceleration	Ss = 0.94	S1 = 0.38
Adjusted Spectral Acceleration	Sms = 1.05	Sm1 = 0.38
Design Spectral Response Acceleration Perimeters	Sds = 0.70	Sd1 = 0.42

### 3.4 Hazards

Slopes: The field reconnaissance on 27 March 2014 showed the steepest slopes are located in the southern end of the property. Here the slopes vary from less than 5% to 25% in the SE corner of the lot. See below figure from Clark County GIS mapping of the site.



Liquefaction: From the Liquefaction Susceptibility Map of Clark County, Washington

2004. The site has very little susceptibility.



### **Landslide Hazards**

RSS site reconnaissance on 27 March 2014 found no signs of land slide hazards. Site is covered with black berries, grasses. See site photo's of the slopes. Figure 3 shows the mapped landslides in Clark County as well as slope stability map of the Vancouver area. As well as IMS -43, this uses LIDAR to map landslides. LIDAR is a bare earth photo that shows landside and slow moving slopes as the lines on the map become fuzzy when the ground is moving. *There are no mapped slides on the project site. Figure 3 also lists the site has having little to no issues with liquefaction.*

From field reconnaissance RSS reviewed all the steep slopes surrounding the project site. There are no signs of slope instability, any sages, slumps or fan of debris from slides on the slopes in the SW corner of the property. There also no surface water features on the property. No seeps springs or other surface expressions of ground water were found when RSS was on site on 3/27/14.

## **4.0 CONSTRUCTION RECOMMENDATIONS**

### **4.1 Site Preparation**

Demolition should include removal of existing improvements throughout the project site. Underground utility lines, vaults, basement walls or tanks should be removed or grouted full if left in place. I recommend that soil disturbed during grubbing operations be removed to firm, undisturbed sub-grade. The excavations should then be backfilled with compacted structural fill. On this site only disturb the area in which can be covered with rock during the day. The moisture sensitive SILT soil when exposed to wet weather becomes soft and yielding. See wet weather conditions below.

#### **4.1.1 Proof Rolling**

Following stripping and prior to placing aggregate base course, pavement the exposed sub-grade should be evaluated by proof rolling. The sub-grade should be proof rolled to identify soft, loose, or unsuitable areas. Please give 24 hour notice to observe the proof rolling. Soft or loose zones identified during the field evaluation should be compacted to an unyielding condition or be excavated and

replaced with structural fill, as discussed in the *Structural Fill* section of this report.

#### **4.1.2 Wet Weather Conditions**

The near-surface soils will be difficult during or after extended wet periods or when the moisture content of the surface soil is more than a few percentage points above optimum. Soils that have been disturbed during site preparation activities, or soft or loose zones identified during probing or proof rolling, should be removed and replaced with compacted structural fill. Track-mounted excavating equipment will be required during wet weather. The imported granular material should be placed in one lift over the prepared, undisturbed sub-grade and compacted using a smooth drum, non-vibratory roller. Additionally, a geo-textile fabric should be placed as a barrier between the sub-grade and imported granular material in areas of repeated traffic.

#### **4.2 Excavation**

Subsurface conditions of accessible cleared areas of the project site show predominately sands, silty soil to the depth explored (4.0 feet). Excavations in the upper soils may be readily accomplished with conventional earthwork equipment with smooth and teeth faced bucket.

#### **4.3 Structural Fills**

Fills should be placed over sub-grade prepared in compliance with Section 4.1 of this report. Material used, as structural fill should be free of organic matter or other unsuitable materials and should meet specifications provided in WSDOT, depending upon the application. A discussion of these materials is in the following sections.

##### **4.3.1 Native Soils**

Native soil can be used for filling operations to raise the site grades for flat backyards. Compaction testing of native soils shall use a standard ASTM D698 proctor and achieve 95%. See lab results in appendix b. Compaction testing is required as per WSDOT every 18in of fill material. Native soils can only be used if they are within optimum moisture content.

##### **4.3.2 Imported Granular Fill**

Material meeting WSDOT 9.03.12(1) B or WSDOT 9.03.11 Imported granular material should be placed in lifts 8 to 12 inches and be compacted to at least 95% of the maximum dry density, as determined by ASTM D 698. Where imported granular material is placed over wet or soft soil sub-grades, we recommend that a geo-textile serve as a barrier between the sub-grade and imported granular material. Compaction testing is required as per WSDOT every 18in of fill material.

### **4.3.3 Floor Slab Base and Footing Base Aggregate**

Base aggregate for floor slabs should be clean, crushed rock or crushed gravel meeting WSDOT 9.03.12(1) B Class B Gravel Backfill for Foundations, if acceptable WSDOT 9.03.11 Recycled Portland Cement Concrete Rubble can be used. The imported granular material should be placed in lifts and compacted to at least 95% of the maximum dry density, as determined by ASTM D 698. Compaction testing is required as per WSDOT every 18in of fill material.

### **4.4 Surface and Subsurface Drainage Requirements**

The Contractor shall be made responsible for temporary drainage of surface water and groundwater as necessary to prevent standing water and/or erosion at the working surface. We recommend removing only the foliage necessary for construction to help minimize erosion. Slope the ground surface around the structures to create a minimum gradient of 2% away from the building foundations for a distance of at least 5 feet. Surface water should be directed away from all buildings into drainage swales or into a storm drainage system.

## **5.0 CONSTRUCTION OBSERVATIONS**

Satisfactory pavement and earthwork performance depends on the quality of construction. Sufficient monitoring of the activities of the contractor is a key part of determining that the work is completed in accordance with the construction drawings and specifications. I recommend that a geotechnical engineer observe general excavation, stripping, fill placement, and sub-grades in addition to base. Subsurface conditions observed during construction should be compared with those encountered during the subsurface explorations. Recognition of changed conditions requires experience. Therefore, qualified personnel should visit the site with sufficient frequency to detect whether subsurface conditions changes significantly from those anticipated.

## **6.0 LIMITATIONS**

This report has been prepared for the exclusive use of the addressee, and their architects and engineers for aiding in the design and construction of the proposed development. It is the addressee's responsibility to provide this report to the appropriate design professionals, building officials, and contractors to ensure correct implementation of the recommendations. The opinions, comments and conclusions presented in this report were based upon information derived from our literature review, field investigation, and laboratory testing. Conditions between, or beyond, our exploratory borings may vary from those encountered. Unanticipated soil conditions and seasonal soil moisture variations are commonly encountered and cannot be fully determined by merely taking soil samples or soil borings. Such variations may result in changes to our recommendations and may require that additional expenditures be made to attain a properly constructed project. Therefore, some contingency fund is recommended to accommodate such potential extra costs.

If there is more than 2years time between the submission of this report and the start of work at the site; if conditions have changed due to natural causes or construction operations at, or

adjacent to, the site; or, if the basic project scheme is significantly modified from that assumed, it is recommended this report be reviewed to determine the applicability of the conclusions and recommendations.

The work has been conducted in general conformance with the standard of care in the field of geotechnical engineering currently in practice in the Pacific Northwest for projects of this nature and magnitude. No warranty, express or implied, exists on the information presented in this report. By utilizing the design recommendations within this report, the addressee acknowledges and accepts the risks and limitations of development at the site, as outlined within the report.



## **APPENDIX A**

---




Figure 1 – Site locations



**Legend**







- Landslide Hazard Areas**
-  Areas of Historic or Active Landslide
  -  Areas of Potential Instability
  -  Areas of Older Landslide Debris
  -  Slopes > 15%
  -  Slopes > 25%

Figure 3 – Landslide hazards

Project site is clear of landslide hazards




**SLOPE STABILITY**  
**CLARK COUNTY WASHINGTON**  
**ALLEN FIKSDAL**  
**1975**



IMS-43

## **APPENDIX B**

---



7409 SW Tech Center Dr, #145  
 Tigard, OR 97223  
 phn: 503-443-3799  
 fax: 503-620-2748

**RAPID SOIL SOLUTIONS**  
**3915 SW PLUM STREET**  
**PORTLAND, OR 97219-6018**

PROJECT: RSS 2014 LAB SERVICES  
 LOCATION: VALLEY VIEW ESTATES  
 SAMPLE SOURCE: SEE BELOW

JOB NO: 14-4790  
 WORK ORDER NO: N/A  
 DATE SAMPLED: 4/18/14

**MECHANICAL SIEVE ANALYSIS**  
**GROUP SYMBOL, USCS (ASTM D-2487)**

Location & Depth	USCS	LL	PI	Silt or Clay	SAND								GRAVEL						COBBLES	Lab #
					Fine			Medium			Coarse		Fine			Coarse				
					#200	#100	#50	#40	#30	#16	#10	#8	#4	1/4"	3/8"	1/2"	3/4"	1"		

**PERCENT PASSING BY WEIGHT**

Location & Depth	USCS	LL	PI	#200	#100	#50	#40	#30	#16	#10	#8	#4	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	3"	6"	Lab #			
HA1@2'		27	3																					7267		
HA2@ 4'		28	9																						7267	

BORING	DEPTH	MC%
HA1@2'		25.9
HA2 @ 4'		28.0
HA3@ 4'		23.1
HA4@ 4'		24.9

REVIEWED BY *[Signature]* DE/fs


# #1

Surface Elevation: 414  
Boring Date: 4/23/14  
Boring Location: Camas, WA  
Drilling Method: Hand Augur

Date: 4/30/2014

File: D:\Users\Mia\Desktop\WIA WORK\2014\Reports\Report to end April\Happy Valley Dental Clinic\HA 1.log

SuperLog CivilTech Software, USA www.civiltech.com

Depth	Remarks	Moisture (%)	Dry Density	Blow Counts	Sample Type	Water Table
0						
						Top Soil
					ML	Damp, medium light brown, fine grained medium plastic SILT
1						
2	PI=3, LL=27 25.9					
					ML	End hand augur hole
3						
4						
5						
6						
7						

## LOG OF BORING

**Rapid Soil Solutions**

Valley View Sub-division  
Stan Firestone

Plate 1

# #2

Surface Elevation: 464  
Boring Date: 4/23/14  
Boring Location: Camas, WA  
Drilling Method: Hand Augur

SuperLog CivilTech Software, USA www.civiltech.com File: D:\Users\Wia\Desktop\WIA WORK\12014\Reports\Report to end April\Valley View\HA 2.log Date: 4/30/2014

Depth	Remarks	Moisture (%)	Dry Density	Blow Counts	Sample Type	Water Table
0						
						Top Soil
					ML	Damp, dark brown, fine grained medium plastic SILT
1						
					ML	Damp, dark to medium brown clayey SILT trace gray
2						
3						
4	28				ML	End hand augur hole
5						
6						
7						

## LOG OF BORING

# #3

Surface Elevation: 418  
Boring Date: 4/23/14  
Boring Location: Camas, WA  
Drilling Method: Hand Augur

SuperLog CivilTech Software, USA www.civiltech.com File: D:\Users\Mia\Desktop\WIA WORK\2014\Reports\Report to end April\Valley View\HA 3.log Date: 4/30/2014

Depth	Remarks	Moisture (%)	Dry Density	Blow Counts	Sample Type	Water Table
0						
					ML	Top Soil
						Damp, dark brown, fine grained medium plastic clayey SILT
1						
2						
3						
4	PS=9, LL=28	23.1			ML	End hand augur hole
5						
6						
7						

## LOG OF BORING



# #4

Surface Elevation: 448  
Boring Date: 4/23/14  
Boring Location: Camas, WA  
Drilling Method: Hand Augur

SuperLog CivilTech Software, USA www.civiltech.com File: D:\Users\Wia\Desktop\WIA WORK\12014\Reports\Report to end April\Valley View\HA 3.log Date: 4/30/2014

Depth	Remarks	Moisture (%)	Dry Density	Blow Counts	Sample Type	Water Table
0						
0					ML	Top Soil
0						Damp, dark brown, fine grained medium plastic clayey SILT
1						
2						
3						
4	23.1				ML	End hand augur hole
5						
6						
7						

## LOG OF BORING

**Rapid Soil Solutions**

Valley View Sub-division  
Stan Firestone


Plate 1

# Geotechnical Report

## Valley View Sub-division

Camas, Washington

Prepared for:  
Stan Firestone  
Vancouver, Washington  
30 April 2014  
Updated 1 May 2018  
Revised 2 August 2018



**Rapid**  
**Soil Solutions** LLC

3915 SW Plum St  
Portland, OR  
503-816-3689

## TABLE OF CONTENTS

<b>1.0 GENERAL INFORMATION .....</b>	<b>3</b>
<b>2.0 SITE CONDITIONS.....</b>	<b>3</b>
2.1 Surface Conditions .....	3
2.2 Regional Geology .....	3
2.3 Field Explorations and Surfaces Conditions .....	4
2.3.1 Field Explorations .....	4
2.3.2 Surface Conditions .....	4
2.3.3 Groundwater .....	4
<b>3.0 GEOTECHNICAL DESIGN RECOMMENDATIONS .....</b>	<b>4</b>
3.1 Foundation.....	4
3.2 Retaining Walls .....	5
3.3 Seismic Design.....	6
3.4 Hazards .....	6
<b>4.0 CONSTRUCTION RECOMMENDATIONS .....</b>	<b>7</b>
4.1 Site Preparation .....	7
4.1.1 Proof Rolling.....	7
4.1.2 Wet Soil Conditions.....	8
4.2 Excavation.....	8
4.3 Structural Fills .....	8
4.3.1 Native Soils.....	8
4.3.2 Imported Granular Fill .....	8
4.3.3 Floor Slab and Base Rock Aggregate .....	9
4.4 Drainage .....	9
<b>5.0 CONSTRUCTION OBSERVATIONS .....</b>	<b>9</b>
<b>6.0 LIMITATIONS .....</b>	<b>9</b>

### SUPPORTING DATA

#### Appendix A - Figures

Figure 1      Location Plan

Figure 2      Site Plan

#### Appendix B – Laboratory data and Soil Logs

## 1.0 PROJECT AND SITE DESCRIPTIONS

### Introduction

Rapid Soil Solutions has prepared this Geotechnical Report to provide bearing capacity, roadway design values, soil parameters for earth work operations and installation of utilities for the 36 lot sub-division.

## 2.0 SITE CONDITIONS


### 2.1 Surface Conditions

The property is located in the Clark County Washington, accessed off of SE 40<sup>th</sup> Street. The site was cleared in past. The site was covered with tall grasses and weeds. See below site photo.



### 2.2 Regional Geology

The Camas Quadrangle developed in 2008 by Evarts and O'Connor maps the site as boring volcanic rock. However, the rock is far below the site and the site is cover with fine grained flood deposits.



## 2.3 Field Exploration and Subsurface Conditions

### 2.3.1 Field Explorations

Four (4) hand augur holes were excavated. The location of the augur holes are shown on Figure 2 in Appendix A. A registered professional engineer performed the excavation and logged the subsurface materials. Hand augur logs detailing materials encountered is in Appendix B. The logs were created using the Unified Soil Classification and Visual Manual Procedure (ASTM-D 2488).

### 2.3.1 Subsurface Conditions

The soil conditions were fine grained stiff damp clayey SILT. The soil conditions in all augur holes were consistent with each other and local geology map. Moistures ranged from 23.1 % to 28%.

### 2.3.2 Groundwater

No ground water was found during the explorations.

## 3.0 GEOTECHNICAL DESIGN RECOMMENDATIONS

### 3.1 Foundation Design

*The building foundations may be installed on either engineered fill or firm native sub-grade that is found at a depth of about 0.5 feet.* This depth may be locally variable and should be confirmed by a geotechnical engineer or their representative at the time of construction.

Continuous wall and isolated spread footings should be at least 16 and 24 inches wide, respectively. The bottom of exterior footings should be at least 16 inches below the lowest adjacent exterior grade. The bottom of interior footings should be at least 12 inches below the base of the floor slab.

Footings placed on engineered fill or firm native sub-grade should be designed for an allowable bearing capacity of 2,000 *pounds per square foot (psf)* by IBC 2012/2015 code. The recommended allowable bearing pressure can be increased by 1/3 for short-term loads such as those resulting from wind or seismic forces.

Based on our analysis the total post-construction settlement is calculated to be less than 1 inch, with differential settlement of less than 0.5 inch over a 50-foot span for maximum column, perimeter footing loads of less than 100 kips and 6.0 kips per linear foot. Lateral loads on footings can be resisted by passive earth pressure on the sides of the structures and by friction at the base of the footings. An allowable lateral bearing pressure of 150 *pounds per cubic foot (psf/f)* below grade may be used. Adjacent floor slabs, pavements or the upper 12-inch depth of adjacent, unpaved areas should not be considered when calculating passive resistance. If construction is undertaken during periods of rain, then I

recommend a 2-inch (or greater) layer of compacted, crushed rock be placed over the native soil. The silty soil is moisture sensitive. Meaning when dry it is firm and non-yielding but exposed to season rains it will lose its strength and need to be excavated and replaced with rock. See section 4.1.2 for wet weather conditions.

### **3.2 Retaining Walls**

The retaining wall design recommendations are based on the following assumptions: (1) the walls consist of conventional, cantilevered retaining walls; (2) the walls are less than 8 feet in height; (3) the backfill is drained; and (4) the backfill has a slope flatter than 4H: 1V. Re-evaluation of our recommendations will be required if the retaining wall design criteria for the project varies from these assumptions.

Unrestrained site walls that retain native soils should be designed to resist an active equivalent fluid unit weight of 35 pcf where supporting slopes are flatter than 4H: 1V. If retaining walls are restrained from rotation prior to being backfilled, the active equivalent fluid unit weight shall be increased to 50 pcf. For embedded building walls, a superimposed seismic lateral force should be calculated based on a dynamic force of  $5H^2$  pounds per lineal foot of wall, where H is the height of the wall in feet, and applied at 0.6H from the base of the wall. If other surcharges (e.g., slopes steeper than 4H:1V, foundations, vehicles, etc.) are located within a horizontal distance from the back of a wall equal to twice the height of the wall, then additional pressures will need to be accounted for in the wall design. Our office should be contacted for appropriate wall surcharges based upon the actual magnitude and configuration of the applied loads.

The wall footings should be designed in accordance with the guidelines provided in the “Foundation Design” section of this report. These design parameters have been provided assuming that back-of-wall drains will be installed to prevent buildup of hydrostatic pressures behind all walls.

The backfill material placed behind the walls and extending a horizontal distance equal to at least half of the height of the retaining wall should consist of granular retaining wall backfill as specified in the “Structural Fill” section of this report.

The wall backfill should be compacted to a minimum of 92 percent of the maximum dry density, as determined by ASTM D1557. However, backfill located within a horizontal distance of 3 feet from the retaining walls should only be compacted to approximately 90 percent of the maximum dry density, as determined by ASTM D1557. Backfill placed within 3 feet of the wall should be compacted in lifts less than 6 inches thick using hand-operated tamping equipment (e.g., jumping jack or vibratory plate compactors). If flat work (e.g., sidewalks or pavements) will be placed atop the wall backfill, we recommend that the upper 2 feet of material be compacted to 92 percent of the maximum dry density, as determined by ASTM D1557.

A minimum 12-inch-wide zone of drain rock, extending from the base of the wall to within 6 inches of finished grade, should be placed against the back of all retaining walls. Perforated

collector pipes should be embedded at the base of the drain rock. The drain rock should meet the requirements provided in the “Structural Fill” section of this report. The perforated collector pipes should discharge at an appropriate location away from the base of the wall. The discharge pipe(s) should not be tied directly into storm water drain systems, unless measures are taken to prevent backflow into the wall’s drainage system.

Settlements of up to 1 percent of the wall height commonly occur immediately adjacent to the wall as the wall rotates and develops active lateral earth pressures. Consequently, we recommend that construction of flat work adjacent to retaining walls be postponed at least 4 weeks after backfilling of the wall, unless survey data indicates that settlement is complete prior to that time.


### 3.3 Seismic Design Criteria

The seismic design criteria for this project USGS Earthquake Hazards Program. A summary of IBC 2012/2015 seismic design criterion below: using a Lat of 45.5909 and Long of -122.4650, site class D.


	<b>Short Period</b>	<b>1 Second</b>
Maximum Credible Earthquake Spectral Acceleration	Ss = 0.94	S1 = 0.38
Adjusted Spectral Acceleration	Sms = 1.05	Sm1 = 0.38
Design Spectral Response Acceleration Perimeters	Sds = 0.70	Sd1= 0.42

### 3.4 Hazards

Slopes: The field reconnaissance on 27 March 2014 showed the steepest slopes are located in the southern end of the property. Here the slopes vary from less than 5% to 25% in the SE corner of the lot. See below figure from Clark County GIS mapping of the site.



Liquefaction: From the Liquefaction Susceptibility Map of Clark County, Washington 2004. The site has very little susceptibility.



**Landslide Hazards**

RSS site reconnaissance on 27 March 2014 found no signs of land slide hazards. Site is covered with black berries, grasses. See site photo’s of the slopes. Figure 3 shows the mapped landslides in Clark County as well as slope stability map of the Vancouver area. As well as IMS -43, this uses LIDAR to map landslides. LIDAR is a bare earth photo that shows landside and slow moving slopes as the lines on the map become fuzzy when the ground is moving. *There are no mapped slides on the project site. Figure 3 also lists the site has having little to no issues with liquefaction.*

From field reconnaissance RSS reviewed all the steep slopes surrounding the project site. There are no signs of slope instability, any sages, slumps or fan of debris from slides on the slopes in the SW corner of the property. There also no surface water features on the property. No seeps springs or other surface expressions of ground water were found when RSS was on site on 3/27/14.

RSS finds that the development of the site will not impart any geological hazards on the site as well as the surrounding areas.

**4.0 CONSTRUCTION RECOMMENDATIONS**

**4.1 Site Preparation**

Demolition should include removal of existing improvements throughout the project site. Underground utility lines, vaults, basement walls or tanks should be removed or grouted full if left in place. I recommend that soil disturbed during grubbing operations be removed to firm, undisturbed sub-grade. The excavations should then be backfilled with compacted structural fill. On this site only disturb the area in which can be covered with rock during the day. The moisture sensitive clayey SILT soil when exposed to wet weather becomes soft and yielding. See wet weather conditions below.

**4.1.1 Proof Rolling**

Following stripping and prior to placing aggregate base course, pavement the exposed sub-grade should be evaluated by proof rolling. The sub-grade should be proof rolled to identify soft, loose, or unsuitable areas. Please give 24 hour notice to observe the proof rolling. Soft or loose zones identified during the field



evaluation should be compacted to an unyielding condition or be excavated and replaced with structural fill, as discussed in the *Structural Fill* section of this report.

#### **4.1.2 Wet Weather Conditions**

The near-surface soils will be difficult during or after extended wet periods or when the moisture content of the surface soil is more than a few percentage points above optimum. Soils that have been disturbed during site preparation activities, or soft or loose zones identified during probing or proof rolling, should be removed and replaced with compacted structural fill. Track-mounted excavating equipment will be required during wet weather. The imported granular material should be placed in one lift over the prepared, undisturbed sub-grade and compacted using a smooth drum, non-vibratory roller. Additionally, a geo-textile fabric should be placed as a barrier between the sub-grade and imported granular material in areas of repeated traffic.

#### **4.2 Excavation**

Subsurface conditions of accessible cleared areas of the project site show predominately clayey SILT soil to the depth explored (4.0 feet). Excavations in the upper soils may be readily accomplished with conventional earthwork equipment with smooth and teeth faced bucket. See below sections regarding grading activities shown on the 4/9 of the preliminary grading plans by Sterling Design.

#### **4.3 Structural Fills**

Fills should be placed over sub-grade prepared in compliance with Section 4.1 of this report. Material used, as structural fill should be free of organic matter or other unsuitable materials and should meet specifications provided in WSDOT, depending upon the application. A discussion of these materials is in the following sections.

##### **4.3.1 Native Soils**

Native soil can be used for filling operations to raise the site grades for flat backyards. Compaction testing of native soils shall use a standard ASTM D698 proctor and achieve 95%. See lab results in appendix b. Compaction testing is required as per WSDOT every 18in of fill material. Native soils can only be used if they are within optimum moisture content. *Proposed stock pile of native soils is planned for NE corner of the site. Any stock piles shall have erosion control fences around them as well as covered for the wet weather if the project proceeds into the winter months.*

##### **4.3.2 Imported Granular Fill**

Material meeting WSDOT 9.03.12(1) B or WSDOT 9.03.11 Imported granular material should be placed in lifts 8 to 12 inches and be compacted to at least 95% of the maximum dry density, as determined by ASTM D 698. Where imported

granular material is placed over wet or soft soil sub-grades, we recommend that a geo-textile serve as a barrier between the sub-grade and imported granular material. Compaction testing is required as per WSDOT every 18in of fill material.

#### **4.3.3 Floor Slab Base and Footing Base Aggregate**

Base aggregate for floor slabs should be clean, crushed rock or crushed gravel meeting WSDOT 9.03.12(1) B Class B Gravel Backfill for Foundations, if acceptable WSDOT 9.03.11 Recycled Portland Cement Concrete Rubble can be used. The imported granular material should be placed in lifts and compacted to at least 95% of the maximum dry density, as determined by ASTM D 698. Compaction testing is required as per WSDOT every 18in of fill material.

#### **4.4 Surface and Subsurface Drainage Requirements**

The Contractor shall be made responsible for temporary drainage of surface water and groundwater as necessary to prevent standing water and/or erosion at the working surface. We recommend removing only the foliage necessary for construction to help minimize erosion. Slope the ground surface around the structures to create a minimum gradient of 2% away from the building foundations for a distance of at least 5 feet. Surface water should be directed away from all buildings into drainage swales or into a storm drainage system.

*RSS has reviewed the preliminary storm water plans by Sterling Design and find plans protect the water quality and don't proposed any geological hazards to the site.*

### **5.0 CONSTRUCTION OBSERVATIONS**

Satisfactory pavement and earthwork performance depends on the quality of construction. Sufficient monitoring of the activities of the contractor is a key part of determining that the work is completed in accordance with the construction drawings and specifications. I recommend that a geotechnical engineer observe general excavation, stripping, fill placement, and sub-grades in addition to base. Subsurface conditions observed during construction should be compared with those encountered during the subsurface explorations. Recognition of changed conditions requires experience. Therefore, qualified personnel should visit the site with sufficient frequency to detect whether subsurface conditions changes significantly from those anticipated.

### **6.0 LIMITATIONS**

This report has been prepared for the exclusive use of the addressee, and their architects and engineers for aiding in the design and construction of the proposed development. It is the addressee's responsibility to provide this report to the appropriate design professionals, building officials, and contractors to ensure correct implementation of the recommendations. The

opinions, comments and conclusions presented in this report were based upon information derived from our literature review, field investigation, and laboratory testing. Conditions between, or beyond, our exploratory borings may vary from those encountered. Unanticipated soil conditions and seasonal soil moisture variations are commonly encountered and cannot be fully determined by merely taking soil samples or soil borings. Such variations may result in changes to our recommendations and may require that additional expenditures be made to attain a properly constructed project. Therefore, some contingency fund is recommended to accommodate such potential extra costs.

If there is more than 2 years time between the submission of this report and the start of work at the site; if conditions have changed due to natural causes or construction operations at, or adjacent to, the site; or, if the basic project scheme is significantly modified from that assumed, it is recommended this report be reviewed to determine the applicability of the conclusions and recommendations.

The work has been conducted in general conformance with the standard of care in the field of geotechnical engineering currently in practice in the Pacific Northwest for projects of this nature and magnitude. No warranty, express or implied, exists on the information presented in this report. By utilizing the design recommendations within this report, the addressee acknowledges and accepts the risks and limitations of development at the site, as outlined within the report.

## **APPENDIX A**

---




Figure 1 – Site locations




Figure 2 – site plan with testing locations



**Legend**







- Landslide Hazard Areas**
-  Areas of Historic or Active Landslide
  -  Areas of Potential Instability
  -  Areas of Older Landslide Debris
  -  Slopes > 15%
  -  Slopes > 25%

Figure 3 – Landslide hazards

Project site is clear of landslide hazards



**SLOPE STABILITY  
CLARK COUNTY WASHINGTON  
ALLEN FIKSDAL  
1975**



IMS-43

## **APPENDIX B**

---





7409 SW Tech Center Dr, #145  
 Tigard, OR 97223  
 phn: 503-443-3799  
 fax: 503-620-2748

**RAPID SOIL SOLUTIONS**  
**3915 SW PLUM STREET**  
**PORTLAND, OR 97219-6018**

PROJECT: RSS 2014 LAB SERVICES  
 LOCATION: VALLEY VIEW ESTATES  
 SAMPLE SOURCE: SEE BELOW

JOB NO: 14-4790  
 WORK ORDER NO: N/A  
 DATE SAMPLED: 4/18/14

**MECHANICAL SIEVE ANALYSIS**  
**GROUP SYMBOL, USCS (ASTM D-2487)**

Location & Depth	USCS	LL	PI	Silt or Clay	SAND								GRAVEL						COBBLES	Lab #
					Fine			Medium			Coarse		Fine			Coarse				
					#200	#100	#50	#40	#30	#16	#10	#8	#4	1/4"	3/8"	1/2"	3/4"	1"		

**PERCENT PASSING BY WEIGHT**

Location & Depth	USCS	LL	PI	#200	#100	#50	#40	#30	#16	#10	#8	#4	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	3"	6"	Lab #			
HA1@2'		27	3																					7267		
HA2@ 4'		28	9																						7267	

BORING	DEPTH	MC%
HA1@2'		25.9
HA2 @ 4'		28.0
HA3@ 4'		23.1
HA4@ 4'		24.9

REVIEWED BY  DE/fs

# #1

Surface Elevation: 414  
Boring Date: 4/23/14  
Boring Location: Camas, WA  
Drilling Method: Hand Augur

Date: 4/30/2014

File: D:\Users\Wia\Desktop\WIA WORK\2014\Reports\Report to end April\Happy Valley Dental Clinic\HA 1.log

SuperLog CivilTech Software, USA www.civiltech.com

Depth	Remarks	Moisture (%)	Dry Density	Blow Counts	Sample Type	Water Table
0						
0					ML	Top Soil
0						Damp, medium light brown, fine grained medium plastic SILT
1						
2	PI=3, LL=27 25.9				ML	End hand augur hole
3						
4						
5						
6						
7						

## LOG OF BORING

**Rapid Soil Solutions**

Valley View Sub-division  
Stan Firestone

Plate 1

# #2

Surface Elevation: 464  
Boring Date: 4/23/14  
Boring Location: Camas, WA  
Drilling Method: Hand Augur

Date: 4/30/2014

File: D:\Users\Wia\Desktop\WIA WORK\12014\Reports\Report to end April\Valley View\HA 2.log

SuperLog CivilTech Software, USA www.civiltech.com

Depth	Remarks	Moisture (%)	Dry Density	Blow Counts	Sample Type	Water Table
0						
					ML	Top Soil
					ML	Damp, dark brown, fine grained medium plastic SILT
1						
					ML	Damp, dark to medium brown clayey SILT trace gray
2						
3						
4	28				ML	End hand augur hole
5						
6						
7						

## LOG OF BORING

**Rapid Soil Solutions**

Valley View Sub-division  
Stan Firestone

Plate 1

# #3

Surface Elevation: 418  
Boring Date: 4/23/14  
Boring Location: Camas, WA  
Drilling Method: Hand Augur

SuperLog CivilTech Software, USA www.civiltech.com File: D:\Users\Wia\Desktop\WIA WORK\2014\Reports\Report to end April\Valley View\HA 3.log Date: 4/30/2014

Depth	Remarks	Moisture (%)	Dry Density	Blow Counts	Sample Type	Water Table
0						
0					ML	Top Soil
0						Damp, dark brown, fine grained medium plastic clayey SILT
1						
2						
3						
4	PS = 9, LL = 28	23.1			ML	End hand augur hole
5						
6						
7						

## LOG OF BORING

**Rapid Soil Solutions**

Valley View Sub-division  
Stan Firestone

Plate 1

# #4

Surface Elevation: 448  
Boring Date: 4/23/14  
Boring Location: Camas, WA  
Drilling Method: Hand Augur

SuperLog CivilTech Software, USA www.civitech.com  
File: D:\Users\Wia\Desktop\WIA WORK\2014\Reports\Report to end April\Valley View\HA 3.log Date: 4/30/2014

Depth	Remarks	Moisture (%)	Dry Density	Blow Counts	Sample Type	Water Table
0						
					ML	Top Soil
						Damp, dark brown, fine grained medium plastic clayey SILT
1						
2						
3						
4	23.1				ML	End hand augur hole
5						
6						
7						

## LOG OF BORING

**Rapid Soil Solutions**

Valley View Sub-division  
Stan Firestone

Plate 1



Earth  
Engineers,  
Inc.

2411 Southeast 8<sup>th</sup> Avenue • Camas • WA 98607

Phone: 360-567-1806 • Fax: 360-253-8624

[www.earth-engineers.com](http://www.earth-engineers.com)

---

July 23, 2018

City of Camas  
616 Northeast 4<sup>th</sup> Avenue  
Camas, Washington 98607  
Attention: Lauren Hollenbeck, Senior Planner

Phone: 360-817-1568, ext. 4253  
E-mail: [lhollenbeck@cityofcamas.us](mailto:lhollenbeck@cityofcamas.us)

**Subject: Geotechnical Peer Review  
Proposed Valley View Subdivision  
Tax Lot 48 and 59  
20109 Southeast 40<sup>th</sup> Street, Camas, Washington  
EEI Report No. 18-132-1**

Dear Ms. Hollenbeck:

Per your request, **Earth Engineers, Inc. (EEI)** has completed a geotechnical review of the project referenced above.

## **PROJECT BACKGROUND INFORMATION**

Our understanding of the project is based on the following information that has been provided to us.

- **May 1, 2018 report by Rapid Soil Solutions (RSS) titled “Geotechnical Report, Valley View Sub-division, Camas, Washington.”** The report was performed for Stan Firestone. It was originally issued April 30, 2014 (we do not have a copy of that report) and the version we have is an updated report.
- **May 2018 drawing (Sheet 1 of 9, “Site Information”) by Sterling Design titled “Valley View Estates, A Preliminary Subdivision within in a portion of the Ne ¼ of Sec. 8, T1N., R3E., W.M., Clark County, Washington.”** This drawing shows a 36 lot subdivision development on the 9.26 acre property. There are also 8 designated tracts (A through H). Note that we have not been provided Sheets 2 through 9.

Briefly, we understand that the project consists of constructing a new residential subdivision, including streets and underground utilities on the property, which consists of 2 tax lots.

## **PURPOSE AND SCOPE OF SERVICES**

The purpose of our geotechnical review was to assess the documents provided to us and provide a professional opinion on whether the geotechnical reports by RSS meet the geotechnical standard of care and Camas Municipal Code (CMC) Chapter 16.59.060—Critical Area Report Requirements for Geologically Hazardous Areas. It is our understanding that this site qualifies as a geologically hazardous area due to its steep slopes.

## **REVIEW COMMENTS**

After reviewing the RRS report, we offer the following comments:

1. Section 16.59.060.C.1.b requires that the geotechnical site evaluation report include the following:
  - a. Proposed structures
  - b. Proposed grading
  - c. Areas proposed for storage of materials
  - d. Proposed storm drainage areas
  - e. Related project impacts which have potential to adversely affect the geologic hazard(s) present

It does not appear that the RSS report addresses the proposed grading, acceptable areas to store materials, and storm drainage areas. RSS should be provided the current grading and storm drainage plans and update their report accordingly.

2. RSS states the proposed project is a 30 lot subdivision. However, the drawing provided to us shows it is a 36 lot subdivision. We recommend RSS be given the opportunity to review the most current project drawings and update their report in order to make it clear that their report is for the currently proposed project.
3. The “Field Exploration and Subsurface Conditions” section of RSS’s January 23, 2018 report states that they encountered sandy silt in their hand auger borings. However, the boring logs describe the soils as silt and clayey silt. RSS should revise their report so that the soil descriptions in the text of the report and the boring logs are consistent and correct.
4. The “Foundation Design” section of the RSS report states that the allowable soil bearing pressure can be doubled for short-term loads such as those resulting from wind or seismic forces. We are familiar with a code allowance to increase the allowable soil bearing pressure by one-third, but not double. RSS should provide justification for this recommendation.
5. The “Hazards” section of the report states that they evaluated liquefaction and landslide hazards. The site was found to have very little susceptibility to liquefaction and no

mitigation recommendations were provided. The site was determined to not have risk to landslides.

6. With regard to general compliance with Camas Municipal Code (CMC) 16.59.060, it is our professional opinion that if the above listed items are satisfactorily addressed in a revised or supplemental report, then RSS will have met the intent of the code section.

Once RSS has responded to our comments, we will determine if there are any staff report conditions required from a geotechnical standpoint.

## LIMITATIONS

This report has been prepared for the exclusive use of the City of Camas for the specific application to the proposed Valley View Estates Subdivision project located on tax lots 48 and 59 in Camas, Washington. EEI does not authorize the use of the advice herein nor the reliance upon the report by third parties without prior written authorization by EEI.

The Geotechnical Engineer warrants that the findings, recommendations, specifications, or professional advice contained herein have been made in accordance with generally accepted professional geotechnical engineering practices in the local area. No other warranties are implied or expressed.


We appreciate the opportunity to perform this geotechnical engineering evaluation. If you have any questions pertaining to this report, or if we may be of further service, please contact Troy Hull at 360-567-1806 (office) or 360-903-2784 (cell).

Sincerely,  
**Earth Engineers, Inc.**



Troy Hull, P.E.  
Principal Geotechnical Engineer

Reviewed by:



Travis Willis, P.E.  
Principal Geotechnical Engineer





Earth  
Engineers,  
Inc.

2411 Southeast 8<sup>th</sup> Avenue • Camas • WA 98607

Phone: 360-567-1806 • Fax: 360-253-8624

[www.earth-engineers.com](http://www.earth-engineers.com)

---

August 6, 2018

City of Camas  
616 Northeast 4<sup>th</sup> Avenue  
Camas, Washington 98607  
Attention: Lauren Hollenbeck, Senior Planner

Phone: 360-817-1568, ext. 4253  
E-mail: [lhollenbeck@cityofcamas.us](mailto:lhollenbeck@cityofcamas.us)

**Subject: Geotechnical Peer Review #2  
Proposed Valley View Subdivision  
Tax Lots 48 and 59  
20109 Southeast 40<sup>th</sup> Street, Camas, Washington  
EEI Report No. 18-132-2**

Dear Ms. Hollenbeck:

Per your request, **Earth Engineers, Inc. (EEI)** has completed an updated geotechnical review of the project referenced above. EEI has previously issued a peer review report (dated July 23, 2018) for the Rapid Soil Solutions (RSS) geotechnical report dated May 1, 2018. Our previous peer review report recommended that RSS submit additional information.

#### **PROJECT BACKGROUND INFORMATION**

Our understanding of the project is based on the following information that has been provided to us.

- **May 1, 2018 report by RSS titled “Geotechnical Report, Valley View Sub-division, Camas, Washington.”** The report was performed for Stan Firestone. It was originally issued April 30, 2014 (we do not have a copy of that report) and the version we have is an updated report.
- **August 2, 2018 revised report by RSS titled “Geotechnical Report, Valley View Sub-division, Camas, Washington.”** This is a revision of the May 1, 2018 report referenced above that addresses the comments in our July 23 peer review report.
- **August 2, 2018 letter to Joel Sterling at Sterling Design summarizing the corrections/updates included in their August 2, 2018 geotechnical report.**

- **May 2018 drawing (Sheet 1 of 9, “Site Information”) by Sterling Design titled “Valley View Estates, A Preliminary Subdivision within in a portion of the Ne ¼ of Sec. 8, T1N., R3E., W.M., Clark County, Washington.”** This drawing shows a 36 lot subdivision development on the 9.26 acre property. There are also 8 designated tracts (A through H). Note that we have not been provided Sheets 2 through 9.

Briefly, we understand that the project consists of constructing a new residential subdivision, including streets and underground utilities on the property, which consists of 2 tax lots.

## **PURPOSE AND SCOPE OF SERVICES**

The purpose of our geotechnical review was to assess the documents provided to us and provide a professional opinion on whether the geotechnical reports by RSS meet the geotechnical standard of care and Camas Municipal Code (CMC) Chapter 16.59.060—Critical Area Report Requirements for Geologically Hazardous Areas. It is our understanding that this site qualifies as a geologically hazardous area due to its steep slopes.

## **REVIEW COMMENTS**

After reviewing the revised RSS report dated August 2, 2018, we find that the report has addressed all of our previous review comments and it also appears to comply with Camas Municipal Code (CMC) Chapter 16.59.060—Critical Area Report Requirements for Geologically Hazardous Areas. From a geotechnical standpoint, we are not recommending the City of Camas include any staff report conditions.

## **LIMITATIONS**

This report has been prepared for the exclusive use of the City of Camas for the specific application to the proposed Valley View Estates Subdivision project located on tax lots 48 and 59 in Camas, Washington. EEI does not authorize the use of the advice herein nor the reliance upon the report by third parties without prior written authorization by EEI.

The Geotechnical Engineer warrants that the findings, recommendations, specifications, or professional advice contained herein have been made in accordance with generally accepted professional geotechnical engineering practices in the local area. No other warranties are implied or expressed.


We appreciate the opportunity to perform this geotechnical engineering evaluation. If you have any questions pertaining to this report, or if we may be of further service, please contact Troy Hull at 360-567-1806 (office) or 360-903-2784 (cell).

Sincerely,  
**Earth Engineers, Inc.**

Reviewed by:



Troy Hull, P.E.  
Principal Geotechnical Engineer



Travis Willis, P.E.  
Principal Geotechnical Engineer

# **REPORT**

## **Valley View Estates Traffic Impact Study**

---

March 16, 2018

**H. Lee & Associates, PLLC**

**VALLEY VIEW ESTATES  
TRAFFIC IMPACT STUDY**



3/16/18

Prepared for:

Mr. Joel Stirling, P.E.  
Sterling Design, Inc.  
2208 E. Evergreen Boulevard  
Vancouver, WA 98661

Prepared by:

**H. Lee & Associates, PLLC  
P.O. Box 1849  
Vancouver, WA 98668  
(360) 727-3119**

March 16, 2018

# TABLE OF CONTENTS

SECTION I - STUDY SUMMARY .....	1
Introduction .....	1
Summary of Findings.....	2
SECTION II- EXISTING CONDITIONS.....	5
Site Condition and Adjacent Land Use .....	5
Transportation Facilities .....	5
Existing Traffic Volumes.....	6
Existing Level of Service.....	9
Accident History .....	10
Existing Public Transit Service.....	10
Non-Motorized Transportation .....	10
Planned Transportation Improvements.....	11
SECTION III - TRAFFIC IMPACT ANALYSIS.....	12
Analysis Methodology .....	12
2023 "Without Project" Traffic Volumes and Levels of Service.....	12
Development Plans .....	14
Trip Generation .....	15
Trip Distribution and Assignment .....	15
2023 "With Project" Traffic Volumes and Levels of Service .....	17
Corner Sight Distance .....	19
Lane Warrant Analysis .....	29
Conclusions .....	20
APPENDIX A	Traffic Counts & Speed Study
APPENDIX B	Existing Level of Service
APPENDIX C	Accident Data
APPENDIX D	In-Process Information
APPENDIX E	2023 "Without Project" Level of Service
APPENDIX F	2023 "With Project" Level of Service

## LIST OF FIGURES

Figure 1.	Site Vicinity Map.....	3
Figure 2.	Site Plan.....	4
Figure 3.	Existing Lane Configurations and Traffic Control.....	7
Figure 4.	Existing Traffic Volumes.....	8
Figure 5.	2023 “Without Project” Traffic Volumes.....	13
Figure 6.	Trip Distribution and Assignment .....	16
Figure 7.	2023 “With Project” Traffic Volumes.....	18

## LIST OF TABLES

Table 1.	Existing Levels of Service.....	9
Table 2.	Summary of Traffic Accident History in Study Area.....	10
Table 3.	2023 “Without Project” Levels of Service.....	14
Table 4.	Trip Generation Summary for Valley View Estates.....	15
Table 5.	2023 “With Project” Levels of Service.....	17

# SECTION I STUDY SUMMARY

## INTRODUCTION

This traffic impact analysis has been prepared to assess transportation impacts related to the proposed Valley View Estates subdivision. The project site is located at 20109 SE 40<sup>th</sup> Street in Camas, Washington and is comprised of tax lots 125646-000 and 125635-000. Figure 1 shows the project vicinity.

### Project Description

The proposed project will subdivide approximately 9.26 acres into 36 single-family detached lots. One single-family detached home exists on-site and will be demolished upon construction of the subdivision. Access to the proposed project will be from connections to SE 40<sup>th</sup> Street and NW Goodwin Street. Figure 2 shows the project site plan.

### Scope of Traffic Impact Study

The scope of the traffic impact study was developed from known City of Camas traffic study requirements. From these requirements, the following intersections were analyzed:

- NW Pacific Rim Boulevard/SE Payne Road/NW Lorenz Street
- NW Brady Road/NW 16<sup>th</sup> Avenue
- NW Brady Road/NW McIntosh Road
- SE Brady Road/SE Grand Ridge Drive
- SE 40<sup>th</sup> Street/Project Access

The remainder of this report presents the following analysis:

- Existing traffic conditions in the project study area.
- 2023 “Without Project” condition to establish the baseline condition by which the project impacts are determined.
- Trip generation estimates for the proposed development.
- 2023 “With Project” condition to determine project traffic impacts.



## SUMMARY OF FINDINGS

### Findings

The following are the findings from the traffic analysis:

- The proposed development is expected to generate 333 daily, 26 A.M. peak hour (7 in, 19 out), and 35 P.M. peak hour (22 in, 13 out) net new trips.
- All of the study area intersections are projected to meet the City of Camas' level of service standards in the 2023 "Without Project" and 2023 "With Project" condition.
- Turn lane warrants at the SE 40<sup>th</sup> Street/Project Access intersection were not conducted because a westbound left turn lane into the site will be constructed with the subdivision.
- Based on field measurements conducted by H. Lee & Associates, PLLC, the project access intersection should be able to meet the sight distance requirements as long as any vegetation within the sight distance triangles are properly maintained after construction and no obstructions are placed within the sight distance triangles that could impede a driver's vision. Because the access into the project site is not built, the corner sight distance should be re-verified in the final engineering/construction stages of development.

### Recommendations

- Based on the traffic impact analysis documented in this report, no physical, off-site mitigation would be needed.




FIGURE 1  
Site Vicinity Map





FIGURE 2  
Site Plan

## SECTION II EXISTING CONDITIONS

### SITE CONDITION AND ADJACENT LAND USE

One existing single-family detached home exists on-site and will be demolished upon construction of the subdivision.

### TRANSPORTATION FACILITIES

The following provides a description of the existing street system in the study area.

***SE Brady Road:*** SE Brady Road is a two-lane minor arterial roadway. A small section of sidewalk exists along the north side of the roadway east of SE Grand Ridge Drive. The posted speed limit is 40 mph.

***NW Brady Road:*** NW Brady Road is a two-lane minor arterial roadway north of NW 16<sup>th</sup> Avenue with a posted speed limit of 35 mph. Between NW 16<sup>th</sup> Avenue and NW McIntosh Road, NW Brady road is a two-lane collector roadway with intermittent sidewalks along both sides of the roadway and a posted speed limit of 35 mph. South of NW McIntosh Road, NW Brady Road is a two-lane minor arterial roadway and has a posted speed limit of 40 mph.

***SE Grand Ridge Drive:*** SE Grand Ridge Drive is a two-lane local roadway. Sidewalks exist along both sides of the roadway in developed areas. The posted speed limit is 25 mph.

***NW McIntosh Road:*** NW McIntosh Road is a two-lane collector roadway. Intermittent sidewalks exist along both sides of the roadway. The posted speed limit is 35 mph.

***NW Pacific Rim Boulevard:*** NW Pacific Rim Boulevard is a four lane minor arterial roadway with a center turn lane/median and additional turn lanes at major intersections. Sidewalks exist on both sides of the roadway. The posted speed limit is 40 mph.

***SE Payne Road:*** SE Payne Road is a two-lane minor arterial roadway. Sidewalks exist along the west side of the roadway. The posted speed limit is 35 mph.

***NW 16<sup>th</sup> Avenue:*** NW 16<sup>th</sup> Avenue is a two-to-three lane minor arterial roadway. Intermittent sidewalks exist along both sides of the roadway. The posted speed limit is 25 mph.

***SE 40<sup>th</sup> Street:*** SE 40<sup>th</sup> Street is a two-lane collector roadway. A detached non-motorized pedestrian pathway exists along the south side of the roadway. The posted speed limit is 35 mph.

The scope of the traffic impact study was developed from known City of Camas traffic study requirements. From these requirements, the following intersections were analyzed:

- NW Pacific Rim Boulevard/SE Payne Road
- NW Brady Road/NW 16<sup>th</sup> Avenue
- NW Brady Road/NW McIntosh Road
- SE Brady Road/SE Grand Ridge Drive
- SE 40<sup>th</sup> Street/Project Access

All of the study area intersections are unsignalized and stop sign controlled. Figure 3 shows the existing lane configurations and traffic control at these intersections.


## EXISTING TRAFFIC VOLUMES

A.M. and P.M. peak hour traffic counts were obtained at the study area intersections by HLA in June of 2017 and February 2018. Per the 2010 HCM<sup>1</sup>, peak 15-minute traffic volumes were multiplied by four (4) to arrive at the peak hour traffic volumes. With this methodology of developing peak hour traffic volumes, the peak hour factor (PHF) is set to 1.00 because the peaking has already occurred by multiplying the peak 15-minute traffic volume by four (4). The existing condition traffic volumes are presented in Figure 4. The existing traffic counts can be referenced in Appendix A.

A speed study along SE 40<sup>th</sup> Street was conducted between 5:00 P.M. on March 7, 2018 and 5:00 P.M. on March 8, 2018. The 85<sup>th</sup> percentile speed eastbound was 40 mph. The 85<sup>th</sup> percentile westbound was 42 mph. The data can be referenced in Appendix A.

---

<sup>1</sup> 2010 Highway Capacity Manual (HCM), Volume 3, Transportation Research Board, 2010, page 18-2 and 18-3.




**LEGEND**

NOT TO SCALE

-  Lane Usage
-  Traffic Signal
-  Stop Sign

**\*** Future 2023 Lane Configuration and Traffic Control

**FIGURE 3**  
 Existing Lane Configuration and Traffic Control



**LEGEND**

128/200

A.M./P.M. Peak Hour  
 Traffic Volume

**FIGURE 4**  
 Existing A.M. and P.M.  
 Peak Hour Traffic Volumes

## EXISTING LEVEL OF SERVICE

Based on the traffic volumes in Figure 4 and the existing lane configurations presented in Figure 3, peak hour traffic operations were analyzed at the study area intersections using the methodologies outlined in the 2010 Highway Capacity Manual (HCM). According to the HCM, there are six levels of service (LOS) by which the operational performance of an intersection may be described. These levels of service range between LOS "A" which indicates a relatively free-flowing condition and LOS "F" which indicates operational breakdown.

LOS D is the City of Camas' adopted level of service standard for arterial/collector intersections. For non-arterial/collector intersections, LOS C is the adopted level of service standard.

Existing A.M. and P.M. peak hour levels of service at the study area intersections are summarized in Table 1. As shown in Table 1, all of the study area intersections are operating within the acceptable levels of service standards or better in the existing condition.

**Table 1. Existing Levels of Service**

	A.M. Peak Hour		P.M. Peak Hour	
	LOS	Average Delay (sec)	LOS	Average Delay (sec)
<b>All-Way Stop Intersection</b>				
NW Brady Road/NW 16 <sup>th</sup> Avenue	B	14.0	B	13.0
<b>Unsignalized Intersection</b>				
NW Pacific Rim Boulevard/SE Payne Road/NW Lorenz Street				
Eastbound Left	A	7.6	A	9.4
Westbound Left	A	8.4	A	8.3
Northbound Approach	C	19.0	D	29.2
Southbound Approach	A	9.4	C	20.7
NW Brady Road/NW McIntosh Road				
Westbound Approach	B	14.9	C	16.4
Southbound Left	A	7.7	A	8.5
SE Brady Road/SE Grand Ridge Road				
Eastbound Left	A	8.6	A	8.2
Southbound Approach	B	12.8	B	13.5
SE 40 <sup>th</sup> Street/Project Access				
Westbound Left	A	0.0	A	0.0
Northbound Approach	A	0.0	A	0.0



## ACCIDENT HISTORY

Accident data was obtained from the Washington State Department of Transportation (WSDOT) for the five year and two month period between January 1, 2013 and February 28, 2018. The data includes total accidents and accidents by severity (i.e. fatal, injury or property damage only). This accident data is summarized in Table 2. Appendix C contains the accident data.

As shown in Table 2, none of the study area intersections have accident rates above 1.00 accidents per million entering vehicles. Accident rates above 1.00 accident per million entering vehicles do not necessarily indicate there is a safety problem, but it is an indicator that further analysis should be conducted. Intersections with accident rates of less than 1.00 accidents per million entering vehicles are considered acceptable and therefore no further analysis is required.

It should be noted that there was a fatality at the NW Brady Road/NW 16<sup>th</sup> Avenue intersection on July 30, 2017. The crash involved a passenger car and motorcycle. The cause of accident was due to the passenger car running the stop sign and the motorcycle exceeding reasonable safe speed.

**Table 2. Summary of Traffic Accident History in Study Area**

Intersection	Average Annual Accidents				acc/mev <sup>2</sup>
	PDO <sup>1</sup>	Injury	Fatal	Total	
NW Pacific Rim Boulevard/SE Payne Road/NW Lorenz St	1.2	0.6	0.0	1.8	0.28
NW Brady Road/NW 16 <sup>th</sup> Avenue	1.0	0.2	0.2	1.4	0.31
NW Brady Road/NW McIntosh Road	0.6	0.2	0.0	0.8	0.19
SE Brady Road/SE Grand Ridge Drive	0.4	0.0	0.0	0.4	0.09
SE 40 <sup>th</sup> Street/Project Access	0.0	0.0	0.0	0.0	0.00

<sup>1</sup> PDO = property damage only

<sup>2</sup> acc/mev = accidents per million entering vehicles

## EXISTING PUBLIC TRANSIT SERVICE

C-Tran provides public transit service in the City of Camas. Currently there are no routes that provide service adjacent to the project site. The closest route to the project site is Route #37 (Mill Plain/Fisher's), which is approximately 0.67 miles from the project site at the intersection of SE 192<sup>nd</sup> Avenue/SE 34<sup>th</sup> Street.

## NON-MOTORIZED TRANSPORTATION

There is a detached non-motorized pedestrian path along the south side of SE 40<sup>th</sup> Street directly adjacent to the project site.

## **PLANNED TRANSPORTATION IMPROVEMENTS**

There are seven known transportation improvement projects planned by the City of Camas in the project vicinity based on the City of Camas' 2018-2023 Six Year Transportation Program. These projects are listed below:

### ***NW Brady Road – NW 16<sup>th</sup> Avenue to NW 25<sup>th</sup> Avenue***

This project will widen the roadway and add bike lanes. Construction is anticipated to begin in 2019. This project has a priority number of 1.

### ***NW Pacific Rim Boulevard at SE Payne Road***

This project is the installation of a traffic signal. This project is in its design phase and has a priority number of 6.

### ***NW Brady Road at NW 16<sup>th</sup> Avenue***

This project is the installation of a traffic signal. This project is in its design phase and has a priority number of 7.

### ***NW 18<sup>th</sup> Avenue – NW Whitman Street to NW Brady Road***

This project will reconstruct the roadway and add bike lanes. Construction is anticipated to begin in 2022. This project has a priority number of 24.

### ***NW 18<sup>th</sup> Avenue – NW Whitman Street to West to City Limits***

This project will widen the roadway and add bike lanes. Construction is anticipated to begin in 2022. This project has a priority number of 25.

### ***NW Brady Road – NW McIntosh Road to West City Limits***

This project will improve bike and pedestrian facilities. Construction is anticipated to begin in 2023. The priority number for this project is 28.

### ***NW McIntosh Road – NW Brady Road to NW 11<sup>th</sup> Avenue***

This project will widen the roadway and add bike lanes. Construction is anticipated to begin in 2023. The priority number for this project is 32.

## **SECTION III TRAFFIC IMPACT ANALYSIS**

### **ANALYSIS METHODOLOGY**


The A.M. and P.M. peak hour traffic impacts generated by the proposed Valley View Estates were analyzed as follows:

- The 2023 “Without Project” traffic volumes were established as the future baseline condition for the traffic analysis and to define a baseline by which project impacts are determined. The 2023 “Without Project” condition traffic volumes were derived by using a 2.0 percent annual, compounded growth factor and adding traffic generated by “in process” developments. The “in-process” traffic volumes were obtained from the City of Camas staff
- A.M., P.M., and daily trip generation were estimated for the proposed development using the rates in "Trip Generation, 10<sup>th</sup> Edition," (Institute of Transportation Engineers, 2017).
- Trip distribution of site-generated traffic was developed from existing count information, previous traffic studies, locations of major employment centers, and logical travel paths to and from major travel corridors.
- Predicted A.M. and P.M. peak hour site-generated traffic from the proposed development was assigned to the roadway network and added to the 2023 “Without Project” traffic volumes to develop the 2023 “With Project” traffic volumes.

A detailed discussion of the methodology summarized above and the analysis results are contained in the remainder of this section.

### **2023 “WITHOUT PROJECT” TRAFFIC VOLUMES AND LEVELS OF SERVICE**

The 2023 “Without Project” condition was analyzed as the future baseline condition for the traffic analysis and to define a baseline by which project impacts are determined. The 2023 “Without Project” condition traffic volumes were derived by using a 2.0 percent annual, compounded growth factor and adding traffic generated by “in process” developments. The “in-process” traffic volumes were obtained from the City of Camas staff and can be referenced in Appendix D. Figure 5 shows the 2023 “Without Project” traffic volumes.



**LEGEND**

128/200

A.M./P.M. Peak Hour  
 Traffic Volume

**FIGURE 5**  
 2023 "Without Project"  
 A.M. and P.M. Peak Hour Traffic Volumes



Levels of service were calculated at the study area intersections with the 2023 “Without Project” traffic volumes shown in Figure 5 and the lane configurations shown earlier in Figure 3. Appendix E contains the level of service worksheets for the 2023 “Without Project” condition.

The 2023 “Without Project” A.M. and P.M. peak hour levels of service at the study area intersections are summarized in Table 3. As shown in Table 3, all of the study area intersections are projected to operate within the acceptable levels of service standards or better in the 2023 “Without Project” condition.

**Table 3. 2023 “Without Project” Levels of Service**

	A.M. Peak Hour		P.M. Peak Hour	
	LOS	Average Delay (sec)	LOS	Average Delay (sec)
<b>Signalized Intersection</b>				
NW Pacific Rim Boulevard/SE Payne Road/NW Lorenz Street	B	13.0	B	12.3
<b>All-Way Stop Intersection</b>				
NW Brady Road/NW 16 <sup>th</sup> Avenue	D	28.3	C	19.3
<b>Unsignalized Intersection</b>				
NW Brady Road/NW McIntosh Road				
Westbound Approach	C	22.5	C	24.6
Southbound Left	A	7.9	A	9.0
SE Brady Road/SE Grand Ridge Road				
Eastbound Left	A	9.0	A	8.4
Southbound Approach	B	14.6	C	15.6
SE 40 <sup>th</sup> Street/Project Access				
Westbound Left	A	0.0	A	0.0
Northbound Approach	A	0.0	A	0.0

## DEVELOPMENT PLANS

As previously stated, the proposed project will subdivide approximately 9.26 acres into 36 single-family detached lots. One single-family detached home exists on-site and will be demolished upon construction of the subdivision. Access to the proposed project will be from connections to SE 40<sup>th</sup> Street and NW Goodwin Street. As previously shown, Figure 2 shows the project site plan.

## TRIP GENERATION


Estimates of daily, A.M. peak hour, and P.M. peak hour trips generated by the proposed project were developed from rates published in “Trip Generation, 10<sup>th</sup> Edition” (Institute of Transportation Engineers, 2017). The proposed development is expected to generate 333 daily, 26 A.M. peak hour (7 in, 19 out), and 35 P.M. peak hour (28 in, 16 out) net new trips. Table 4 summarizes the project’s trip generation.

**Table 4. Trip Generation Summary for Valley View Estates Subdivision**

	Amount	Average Daily	A.M. Peak			P.M. Peak		
			In	Out	Total	In	Out	Total
Single-Family Detached Homes (ITE Code 210)								
Rate per dwelling Unit		9.52	0.19	0.56	0.75	0.63	0.37	1.00
Trips	36 units	343	7	20	27	23	13	36
Existing Single-Family Detached Home (ITE Code 210)								
Rate per dwelling Unit		9.52	0.19	0.56	0.75	0.63	0.37	1.00
Trips	1 unit	(10)	-	(1)	(1)	(1)	-	(1)
<b>Net Total Trips</b>		<b>333</b>	<b>7</b>	<b>19</b>	<b>26</b>	<b>22</b>	<b>13</b>	<b>35</b>

## TRIP DISTRIBUTION AND ASSIGNMENT

A generalized trip distribution for the A.M. and P.M. peak hour was developed from the existing traffic counts, previous traffic studies, locations of major employment centers, and logical travel paths to and from major travel corridors. Figure 6 shows the resulting trip distribution pattern and assignment of project-generated trips.



**LEGEND**

128/200

A.M./P.M. Peak Hour  
 Traffic Volume

10%

Peak Hour Trip Distribution

**FIGURE 6**  
 Trip Distribution and Assignment  
 Traffic Volumes

## 2023 “WITH PROJECT” TRAFFIC VOLUMES AND LEVELS OF SERVICE


The traffic volumes shown in Figures 5 and 6 were combined to arrive at the 2023 “With Project” A.M. and P.M. peak hour traffic volumes. Figure 7 shows these traffic volumes. Levels of service were calculated for the 2023 “With Project” condition based on the traffic volumes shown in Figure 7 and the lane configurations previously shown in Figure 3. Appendix F contains the level of service worksheets for the 2023 “With Project” condition.

The 2023 “With Project” A.M. and P.M. peak hour levels of service at the study area intersections are summarized in Table 5a. As shown in Table 5, all of the study area intersections are projected to operate within the acceptable levels of service standards in the 2023 “With Project” condition.

**Table 5. 2023 “With Project” Levels of Service**

Signalized Intersection	A.M. Peak Hour		P.M. Peak Hour	
	LOS	Average Delay (sec)	LOS	Average Delay (sec)
NW Pacific Rim Boulevard/SE Payne Road/NW Lorenz Street	B	13.0	B	12.3
<b>All-Way Stop Intersection</b>				
NW Brady Road/NW 16 <sup>th</sup> Avenue	D	28.4	C	19.4
<b>Unsignalized Intersection</b>				
NW Brady Road/NW McIntosh Road				
Westbound Approach	C	22.5	C	24.8
Southbound Left	A	7.9	A	9.0
SE Brady Road/SE Grand Ridge Road				
Eastbound Left	A	9.0	A	8.4
Southbound Approach	B	14.9	C	15.1
SE 40 <sup>th</sup> Street/Project Access				
Westbound Left	A	7.4	A	7.6
Northbound Approach	A	9.4	A	9.9





**LEGEND**

128/200

A.M./P.M. Peak Hour  
 Traffic Volume

**FIGURE 7**  
 2023 "With Project"  
 A.M. and P.M. Peak Hour Traffic Volumes

## **CORNER SIGHT DISTANCE**

The minimum corner sight distance was analyzed for the proposed Valley View Estates subdivision. The minimum corner sight distance required for the proposed SE 40<sup>th</sup> Street/Project Access intersection is based on the City of Camas' Design Standard Manual. Per the City of Camas' Design Standard Manual, public and private streets must comply with the sight distance requirements contained in the current "A Policy on Geometric Design on Highways and Streets," published by AASHTO (American Association of State Highway and Transportation Officials.) The most recent edition of this reference is the 2011 – 6<sup>th</sup> Edition.

From AASHTO, the following intersection sight distances are relevant to the project's site access intersection:

- Case B1 – left turn from minor road
- Case B2 – right turn from minor road
- Case F – left from major road

The required sight distance for Case B1 based on a posted speed limit of 35 mph along SE 40<sup>th</sup> Street is 390 feet. This requirement can be found in Table 9-6 of the "A Policy on Geometric Design on Highways and Streets," page 9-38.

The required sight distance for Case B2 based on a posted speed limit of 35 mph along SE 40<sup>th</sup> Street is 335 feet. This requirement can be found in Table 9-8 of the "A Policy on Geometric Design on Highways and Streets," page 9-41.

The required sight distance for Case F based on a posted speed limit of 35 mph along SE 40<sup>th</sup> Street is 285 feet. This requirement can be found in Table 9-14 of the "A Policy on Geometric Design on Highways and Streets," page 9-52.

The corner sight distance at the proposed SE 40<sup>th</sup> Street/Project Access intersection was field measured and compared to the minimum acceptable AASHTO standards described above. Based on field measurements conducted by H. Lee & Associates, PLLC, all of the AASHTO sight distance requirements can be met at the proposed SE 40<sup>th</sup> Street/Project Access intersection as long as any vegetation within the sight distance triangles is properly maintained and no obstructions that obscure the driver's sight distance are located within the sight distance triangles. Since the intersection is not yet built, the intersection corner sight distance should be re-verified at the final engineering stage of the project.

## **LANE WARRANT ANALYSIS**

Turn lane warrants at the SE 40<sup>th</sup> Street/Project Access intersection were not conducted because a westbound left turn lane into the site will be constructed with the subdivision.

## CONCLUSIONS

### Findings

The following are the findings from the traffic analysis:

- The proposed development is expected to generate 333 daily, 26 A.M. peak hour (7 in, 19 out), and 35 P.M. peak hour (22 in, 13 out) net new trips.
- All of the study area intersections are projected to meet the City of Camas' level of service standards in the 2023 "Without Project" and 2023 "With Project" condition.
- Turn lane warrants at the SE 40<sup>th</sup> Street/Project Access intersection were not conducted because a westbound left turn lane into the site will be constructed with the subdivision.
- Based on field measurements conducted by H. Lee & Associates, PLLC, the project access intersection should be able to meet the sight distance requirements as long as any vegetation within the sight distance triangles are properly maintained after construction and no obstructions are placed within the sight distance triangles that could impede a driver's vision. Because the access into the project site is not built, the corner sight distance should be re-verified in the final engineering/construction stages of development.

### Recommendations

- Based on the traffic impact analysis documented in this report, no physical, off-site mitigation would be needed.

**APPENDIX A**  
**TRAFFIC COUNTS & SPEED STUDY**

Intersection: NW Pacific Rim Boulevard/SE Payne Road/NW Lorenz Street  
 AM Peak Hour Turning Movement Volumes

Date: 06/22/17

Time	<u>SB</u>				<u>WB</u>				<u>NB</u>				<u>EB</u>				Total
	SBR	SBT	SBL	Trucks	WBR	WBT	WBL	Trucks	NBR	NBT	NBL	Trucks	EBR	EBT	EBL	Trucks	
<u>15 Minute Totals</u>																	
7:00 - 7:15 AM	3	0	1	0	0	51	0	1	1	0	13	1	4	141	0	0	214
7:15 - 7:30 AM	5	0	2	0	0	49	1	5	0	0	24	1	10	71	1	2	163
7:30 - 7:45 AM	5	0	0	0	1	43	0	0	5	0	21	0	8	88	2	3	173
7:45 - 8:00 AM	7	0	1	0	0	46	3	2	8	0	37	1	13	102	1	4	218
8:00 - 8:15 AM	5	0	1	0	0	46	6	0	5	0	20	0	10	69	1	1	163
8:15 - 8:30 AM	3	0	0	0	0	42	2	6	3	0	22	0	13	48	2	3	135
8:30 - 8:45 AM	3	2	1	1	0	50	3	2	6	0	42	2	11	50	2	6	170
8:45 - 9:00 AM	5	0	2	0	2	52	2	3	18	0	40	0	16	56	0	6	193
																<b>Peak 15 Total</b>	<b>218</b>
<u>Hourly Total by 15 minutes</u>																	
7:00 - 8:00 AM	20	0	4	0	1	189	4	8	14	0	95	3	35	402	4	9	768
7:15 - 8:15 AM	22	0	4	0	1	184	10	7	18	0	102	2	41	330	5	10	717
7:30 - 8:30 AM	20	0	2	0	1	177	11	8	21	0	100	1	44	307	6	11	689
7:45 - 8:45 AM	18	2	3	1	0	184	14	10	22	0	121	3	47	269	6	14	686
8:00 - 9:00 AM	16	2	4	1	2	190	13	11	32	0	124	2	50	223	5	16	661
Peak Hour 7:00 - 8:00 AM	20	0	4	0	1	189	4	8	14	0	95	3	35	402	4	9	768
Peak Hour Factor	0.75				0.95				0.61				0.76				0.88
Peak Hour % Trucks	0%				4%				3%				2%				
Peak 15 Min % Trucks	0%				4%				2%				3%				

Intersection: NW Pacific Rim Boulevard/SE Payne Road/NW Lorenz Street  
 PM Peak Hour Turning Movement Volumes

Date: 06/22/17

Time	<u>SB</u>				<u>WB</u>				<u>NB</u>				<u>EB</u>				Total
	SBR	SBT	SBL	Trucks	WBR	WBT	WBL	Trucks	NBR	NBT	NBL	Trucks	EBR	EBT	EBL	Trucks	
<u>15 Minute Totals</u>																	
4:00 - 4:15 PM	4	0	0	0	2	123	2	2	4	0	34	1	39	49	5	2	262
4:15 - 4:30 PM	3	0	0	0	2	102	4	2	1	0	31	0	46	61	3	1	253
4:30 - 4:45 PM	1	0	1	0	0	121	4	3	2	0	23	0	34	52	4	3	242
4:45 - 5:00 PM	1	0	1	0	1	87	0	1	0	0	32	0	50	53	2	2	227
5:00 - 5:15 PM	1	0	3	0	1	192	3	2	4	0	33	0	55	57	6	1	355
5:15 - 5:30 PM	6	0	1	0	5	123	3	1	11	0	29	0	46	79	9	1	312
5:30 - 5:45 PM	4	0	0	0	2	92	3	2	5	0	29	0	43	60	4	1	242
5:45 - 6:00 PM	1	0	0	0	0	60	7	0	5	1	33	1	49	43	3	1	202
																Peak 15 Total	355
<u>Hourly Total by 15 minutes</u>																	
4:00 - 5:00 PM	9	0	2	0	5	433	10	8	7	0	120	1	169	215	14	8	984
4:15 - 5:15 PM	6	0	5	0	4	502	11	8	7	0	119	0	185	223	15	7	1,077
4:30 - 5:30 PM	9	0	6	0	7	523	10	7	17	0	117	0	185	241	21	7	1,136
4:45 - 5:45 PM	12	0	5	0	9	494	9	6	20	0	123	0	194	249	21	5	1,136
5:00 - 6:00 PM	12	0	4	0	8	467	16	5	25	1	124	1	193	239	22	4	1,111
Peak Hour 4:30 - 5:30 PM	9	0	6	0	7	523	10	7	17	0	117	0	185	241	21	7	1,136
Peak Hour Factor	0.54				0.69				0.84				0.83				0.80
Peak Hour % Trucks	0%				1%				0%				2%				
Peak 15 Min % Trucks	0%				1%				0%				1%				

Intersection: NW Brady Road/NW 16th Avenue  
 AM Peak Hour Turning Movement Volumes

Date: 02/13/18

Time	<u>SB</u>				<u>WB</u>				<u>NB</u>				<u>EB</u>				Total
	SBR	SBT	SBL	Trucks	WBR	WBT	WBL	Trucks	NBR	NBT	NBL	Trucks	EBR	EBT	EBL	Trucks	
<u>15 Minute Totals</u>																	
7:00 - 7:15 AM	1	30	7	0	16	13	40	1	9	22	2	3	4	10	4	3	158
7:15 - 7:30 AM	2	39	8	1	25	8	53	2	13	24	0	4	0	7	4	0	183
7:30 - 7:45 AM	4	38	6	2	42	14	33	5	10	31	3	3	1	5	5	2	192
7:45 - 8:00 AM	8	31	18	0	25	17	36	1	12	35	5	1	7	9	9	1	212
8:00 - 8:15 AM	8	29	14	1	30	20	48	0	13	25	5	3	5	13	3	0	213
8:15 - 8:30 AM	7	27	6	2	27	15	41	4	16	23	7	5	1	5	1	0	176
8:30 - 8:45 AM	8	30	12	4	16	23	22	0	14	22	11	5	1	6	2	0	167
8:45 - 9:00 AM	17	22	11	1	18	43	21	2	6	15	32	2	21	35	20	7	261
																Peak 15 Total	261
<u>Hourly Total by 15 minutes</u>																	
7:00 - 8:00 AM	15	138	39	3	108	52	162	9	44	112	10	11	12	31	22	6	745
7:15 - 8:15 AM	22	137	46	4	122	59	170	8	48	115	13	11	13	34	21	3	800
7:30 - 8:30 AM	27	125	44	5	124	66	158	10	51	114	20	12	14	32	18	3	793
7:45 - 8:45 AM	31	117	50	7	98	75	147	5	55	105	28	14	14	33	15	1	768
8:00 - 9:00 AM	40	108	43	8	91	101	132	6	49	85	55	15	28	59	26	7	817
Peak Hour 8:00 - 9:00 AM	40	108	43	8	91	101	132	6	49	85	55	15	28	59	26	7	817
Peak Hour Factor	0.94				0.83				0.89				0.37				0.78
Peak Hour % Trucks	4%				2%				8%				6%				
Peak 15 Min % Trucks	2%				2%				4%				9%				

Intersection: NW Brady Road/NW 16th Avenue  
 PM Peak Hour Turning Movement Volumes

Date: 02/13/18

Time	<u>SB</u>				<u>WB</u>				<u>NB</u>				<u>EB</u>				Total
	SBR	SBT	SBL	Trucks	WBR	WBT	WBL	Trucks	NBR	NBT	NBL	Trucks	EBR	EBT	EBL	Trucks	
<u>15 Minute Totals</u>																	
4:00 - 4:15 PM	6	23	25	3	25	21	26	0	26	28	1	0	7	33	7	0	228
4:15 - 4:30 PM	7	36	27	0	20	19	9	0	23	41	4	0	7	28	7	0	228
4:30 - 4:45 PM	8	25	23	1	24	13	23	1	26	27	2	0	25	20	4	0	220
4:45 - 5:00 PM	2	29	22	0	22	13	15	0	34	24	3	0	7	24	4	0	199
5:00 - 5:15 PM	1	59	25	2	24	6	26	0	34	47	1	0	2	25	1	0	251
5:15 - 5:30 PM	4	42	23	0	17	8	15	0	36	43	0	1	3	28	1	0	220
5:30 - 5:45 PM	4	31	32	0	20	12	30	0	34	42	1	1	5	27	0	0	238
5:45 - 6:00 PM	6	25	21	1	30	20	22	1	43	44	2	0	1	24	5	0	243
																Peak 15 Total	251
<u>Hourly Total by 15 minutes</u>																	
4:00 - 5:00 PM	23	113	97	4	91	66	73	1	109	120	10	0	46	105	22	0	875
4:15 - 5:15 PM	18	149	97	3	90	51	73	1	117	139	10	0	41	97	16	0	898
4:30 - 5:30 PM	15	155	93	3	87	40	79	1	130	141	6	1	37	97	10	0	890
4:45 - 5:45 PM	11	161	102	2	83	39	86	0	138	156	5	2	17	104	6	0	908
5:00 - 6:00 PM	15	157	101	3	91	46	93	1	147	176	4	2	11	104	7	0	952
Peak Hour 5:00 - 6:00 PM	15	157	101	3	91	46	93	1	147	176	4	2	11	104	7	0	952
Peak Hour Factor	0.80				0.80				0.92				0.95				0.95
Peak Hour % Trucks	1%				0%				1%				0%				
Peak 15 Min % Trucks	2%				0%				0%				0%				



Intersection: NW Brady Road/NW McIntosh Road  
 AM Peak Hour Turning Movement Volumes

Date: 02/13/18

Time	<u>SB</u>				<u>WB</u>				<u>NB</u>				<u>EB</u>				Total
	SBR	SBT	SBL	Trucks	WBR	WBT	WBL	Trucks	NBR	NBT	NBL	Trucks	EBR	EBT	EBL	Trucks	
<u>15 Minute Totals</u>																	
7:00 - 7:15 AM	0	73	1	1	3	0	26	0	5	26	0	2	0	0	0	0	134
7:15 - 7:30 AM	0	101	0	0	4	0	27	1	8	31	0	5	0	0	0	0	171
7:30 - 7:45 AM	0	84	2	1	1	0	33	0	8	35	0	2	0	0	0	0	163
7:45 - 8:00 AM	0	82	1	2	1	0	34	0	12	48	0	3	0	0	0	0	178
8:00 - 8:15 AM	0	87	1	0	1	0	26	3	13	40	0	6	0	0	0	0	168
8:15 - 8:30 AM	0	71	2	1	2	0	29	0	7	38	0	5	0	0	0	0	149
8:30 - 8:45 AM	0	65	2	3	4	0	22	2	13	41	0	5	0	0	0	0	147
8:45 - 9:00 AM	0	75	2	3	7	0	35	0	9	28	0	3	0	0	0	0	156
																<b>Peak 15 Total</b>	<b>178</b>
<u>Hourly Total by 15 minutes</u>																	
7:00 - 8:00 AM	0	340	4	4	9	0	120	1	33	140	0	12	0	0	0	0	646
7:15 - 8:15 AM	0	354	4	3	7	0	120	4	41	154	0	16	0	0	0	0	680
7:30 - 8:30 AM	0	324	6	4	5	0	122	3	40	161	0	16	0	0	0	0	658
7:45 - 8:45 AM	0	305	6	6	8	0	111	5	45	167	0	19	0	0	0	0	642
8:00 - 9:00 AM	0	298	7	7	14	0	112	5	42	147	0	19	0	0	0	0	620
Peak Hour 7:15 - 8:15 AM	0	354	4	3	7	0	120	4	41	154	0	16	0	0	0	0	680
Peak Hour Factor		0.89				0.91				0.81				0.00			0.96
Peak Hour % Trucks		1%				3%				8%				0%			
Peak 15 Min % Trucks		2%				0%				5%				0%			

Intersection: NW Brady Road/NW McIntosh Road  
 PM Peak Hour Turning Movement Volumes

Date: 02/13/18

Time	<u>SB</u>				<u>WB</u>				<u>NB</u>				<u>EB</u>				Total
	SBR	SBT	SBL	Trucks	WBR	WBT	WBL	Trucks	NBR	NBT	NBL	Trucks	EBR	EBT	EBL	Trucks	
<u>15 Minute Totals</u>																	
4:00 - 4:15 PM	0	52	3	1	3	0	16	1	25	54	0	0	0	0	0	0	153
4:15 - 4:30 PM	0	48	4	0	4	0	11	2	27	66	0	0	0	0	0	0	160
4:30 - 4:45 PM	0	60	2	0	2	0	17	0	22	51	0	0	0	0	0	0	154
4:45 - 5:00 PM	0	47	1	0	2	0	13	0	37	66	0	1	0	0	0	0	166
5:00 - 5:15 PM	0	89	2	3	3	0	12	0	33	96	0	1	0	0	0	0	235
5:15 - 5:30 PM	0	48	6	1	2	0	13	0	21	81	0	1	0	0	0	0	171
5:30 - 5:45 PM	0	66	1	0	2	0	14	2	33	75	0	1	0	0	0	0	191
5:45 - 6:00 PM	0	49	2	2	2	0	29	0	31	100	0	1	0	0	0	0	213
																<b>Peak 15 Total</b>	<b>235</b>
<u>Hourly Total by 15 minutes</u>																	
4:00 - 5:00 PM	0	207	10	1	11	0	57	3	111	237	0	1	0	0	0	0	633
4:15 - 5:15 PM	0	244	9	3	11	0	53	2	119	279	0	2	0	0	0	0	715
4:30 - 5:30 PM	0	244	11	4	9	0	55	0	113	294	0	3	0	0	0	0	726
4:45 - 5:45 PM	0	250	10	4	9	0	52	2	124	318	0	4	0	0	0	0	763
5:00 - 6:00 PM	0	252	11	6	9	0	68	2	118	352	0	4	0	0	0	0	810
Peak Hour 5:00 - 6:00 PM	0	252	11	6	9	0	68	2	118	352	0	4	0	0	0	0	810
Peak Hour Factor		0.72				0.62				0.90				0.00			0.86
Peak Hour % Trucks		2%				3%				1%				0%			
Peak 15 Min % Trucks		3%				0%				1%				0%			

Intersection: SE Brady Road/SE Grand Ridge Drive  
 AM Peak Hour Turning Movement Volumes

Date: 02/13/18

Time	<u>SB</u>				<u>WB</u>				<u>NB</u>				<u>EB</u>				Total
	SBR	SBT	SBL	Trucks	WBR	WBT	WBL	Trucks	NBR	NBT	NBL	Trucks	EBR	EBT	EBL	Trucks	
<u>15 Minute Totals</u>																	
7:00 - 7:15 AM	22	0	4	0	0	98	0	1	0	0	0	0	0	26	7	3	157
7:15 - 7:30 AM	18	0	2	0	1	129	0	0	0	0	0	0	0	39	2	4	191
7:30 - 7:45 AM	21	0	1	0	0	119	0	1	0	0	0	0	0	47	0	3	188
7:45 - 8:00 AM	12	0	2	0	3	112	0	2	0	0	0	0	0	53	0	2	182
8:00 - 8:15 AM	5	0	0	0	1	107	0	3	0	0	0	0	0	51	3	1	167
8:15 - 8:30 AM	13	0	2	0	0	98	0	1	0	0	0	0	0	40	6	5	159
8:30 - 8:45 AM	18	0	1	0	2	85	0	3	0	0	0	0	0	53	5	8	164
8:45 - 9:00 AM	5	0	0	0	1	104	0	2	0	0	0	0	0	38	4	4	152
																<b>Peak 15 Total</b>	<b>191</b>
<u>Hourly Total by 15 minutes</u>																	
7:00 - 8:00 AM	73	0	9	0	4	458	0	4	0	0	0	0	0	165	9	12	718
7:15 - 8:15 AM	56	0	5	0	5	467	0	6	0	0	0	0	0	190	5	10	728
7:30 - 8:30 AM	51	0	5	0	4	436	0	7	0	0	0	0	0	191	9	11	696
7:45 - 8:45 AM	48	0	5	0	6	402	0	9	0	0	0	0	0	197	14	16	672
8:00 - 9:00 AM	41	0	3	0	4	394	0	9	0	0	0	0	0	182	18	18	642
Peak Hour 7:15 - 8:15 AM	56	0	5	0	5	467	0	6	0	0	0	0	0	190	5	10	728
Peak Hour Factor	0.69				0.91				0.00				0.90				0.95
Peak Hour % Trucks	0%				1%				0%				5%				
Peak 15 Min % Trucks	0%				0%				0%				10%				

Intersection: SE Brady Road/SE Grand Ridge Drive  
 PM Peak Hour Turning Movement Volumes

Date: 02/13/18

Time	<u>SB</u>				<u>WB</u>				<u>NB</u>				<u>EB</u>				Total
	SBR	SBT	SBL	Trucks	WBR	WBT	WBL	Trucks	NBR	NBT	NBL	Trucks	EBR	EBT	EBL	Trucks	
<u>15 Minute Totals</u>																	
4:00 - 4:15 PM	5	0	0	1	1	64	0	3	0	0	0	0	0	79	8	2	157
4:15 - 4:30 PM	10	0	2	1	0	55	0	2	0	0	0	0	0	86	14	1	167
4:30 - 4:45 PM	7	0	0	1	4	72	0	1	0	0	0	0	0	78	5	1	166
4:45 - 5:00 PM	8	0	4	0	2	55	0	1	0	0	0	0	0	89	9	0	167
5:00 - 5:15 PM	4	0	2	0	1	94	0	2	0	0	0	0	0	122	12	1	235
5:15 - 5:30 PM	15	0	2	0	3	61	0	1	0	0	0	0	0	94	15	1	190
5:30 - 5:45 PM	9	0	0	0	0	72	0	2	0	0	0	0	0	113	12	3	206
5:45 - 6:00 PM	6	0	3	0	3	75	0	2	0	0	0	0	0	124	19	2	230
																<b>Peak 15 Total</b>	<b>235</b>
<u>Hourly Total by 15 minutes</u>																	
4:00 - 5:00 PM	30	0	6	3	7	246	0	7	0	0	0	0	0	332	36	4	657
4:15 - 5:15 PM	29	0	8	2	7	276	0	6	0	0	0	0	0	375	40	3	735
4:30 - 5:30 PM	34	0	8	1	10	282	0	5	0	0	0	0	0	383	41	3	758
4:45 - 5:45 PM	36	0	8	0	6	282	0	6	0	0	0	0	0	418	48	5	798
5:00 - 6:00 PM	34	0	7	0	7	302	0	7	0	0	0	0	0	453	58	7	861
Peak Hour 5:00 - 6:00 PM	34	0	7	0	7	302	0	7	0	0	0	0	0	453	58	7	861
Peak Hour Factor	0.60				0.81				0.00				0.89				0.92
Peak Hour % Trucks	0%				2%				0%				1%				
Peak 15 Min % Trucks	0%				2%				0%				1%				

Intersection: SE 40th Street/Project Access  
 AM Peak Hour Turning Movement Volumes

Date: 02/13/18

Time	<u>SB</u>				<u>WB</u>				<u>NB</u>				<u>EB</u>				Total	
	SBR	SBT	SBL	Trucks	WBR	WBT	WBL	Trucks	NBR	NBT	NBL	Trucks	EBR	EBT	EBL	Trucks		
<u>15 Minute Totals</u>																		
7:00 - 7:15 AM	0	0	0	0	0	21	0	1	0	0	0	0	0	2	0	2	23	
7:15 - 7:30 AM	0	0	0	0	0	15	0	1	0	0	0	0	0	7	0	1	22	
7:30 - 7:45 AM	0	0	0	0	0	29	0	1	0	0	0	0	0	7	0	0	36	
7:45 - 8:00 AM	0	0	0	0	0	17	0	0	0	0	0	0	0	12	0	0	29	
8:00 - 8:15 AM	0	0	0	0	0	14	0	0	0	0	0	0	0	13	0	1	27	
8:15 - 8:30 AM	0	0	0	0	0	17	0	1	0	0	0	0	0	9	0	1	26	
8:30 - 8:45 AM	0	0	0	0	0	21	0	0	0	0	0	0	0	16	0	0	37	
8:45 - 9:00 AM	0	0	0	0	0	31	0	2	0	0	0	0	0	17	0	3	48	
																	Peak 15 Total	48
<u>Hourly Total by 15 minutes</u>																		
7:00 - 8:00 AM	0	0	0	0	0	82	0	3	0	0	0	0	0	28	0	3	110	
7:15 - 8:15 AM	0	0	0	0	0	75	0	2	0	0	0	0	0	39	0	2	114	
7:30 - 8:30 AM	0	0	0	0	0	77	0	2	0	0	0	0	0	41	0	2	118	
7:45 - 8:45 AM	0	0	0	0	0	69	0	1	0	0	0	0	0	50	0	2	119	
8:00 - 9:00 AM	0	0	0	0	0	83	0	3	0	0	0	0	0	55	0	5	138	
Peak Hour 8:00 - 9:00 AM	0	0	0	0	0	83	0	3	0	0	0	0	0	55	0	5	138	
Peak Hour Factor	0.00				0.67				0.00				0.81				0.72	
Peak Hour % Trucks	0%				4%				0%				9%					
Peak 15 Min % Trucks	0%				6%				0%				18%					

Intersection: SE 40th Street/Project Access  
 PM Peak Hour Turning Movement Volumes

Date: 02/13/18

Time	<u>SB</u>				<u>WB</u>				<u>NB</u>				<u>EB</u>				Total	
	SBR	SBT	SBL	Trucks	WBR	WBT	WBL	Trucks	NBR	NBT	NBL	Trucks	EBR	EBT	EBL	Trucks		
<u>15 Minute Totals</u>																		
4:00 - 4:15 PM	0	0	0	0	0	33	0	0	0	0	0	0	0	39	0	0	72	
4:15 - 4:30 PM	0	0	0	0	0	23	0	0	0	0	0	0	0	27	0	0	50	
4:30 - 4:45 PM	0	0	0	0	0	28	0	0	0	0	0	0	0	34	0	0	62	
4:45 - 5:00 PM	0	0	0	0	0	18	0	0	0	0	0	0	0	44	0	0	62	
5:00 - 5:15 PM	0	0	0	0	0	9	0	0	0	0	0	0	0	28	0	0	37	
5:15 - 5:30 PM	0	0	0	0	0	22	0	0	0	0	0	0	0	34	0	0	56	
5:30 - 5:45 PM	0	0	0	0	0	22	0	0	0	0	0	0	0	50	0	0	72	
5:45 - 6:00 PM	0	0	0	0	0	19	0	0	0	0	0	0	0	36	0	0	55	
																	Peak 15 Total	72
<u>Hourly Total by 15 minutes</u>																		
4:00 - 5:00 PM	0	0	0	0	0	102	0	0	0	0	0	0	0	144	0	0	246	
4:15 - 5:15 PM	0	0	0	0	0	78	0	0	0	0	0	0	0	133	0	0	211	
4:30 - 5:30 PM	0	0	0	0	0	77	0	0	0	0	0	0	0	140	0	0	217	
4:45 - 5:45 PM	0	0	0	0	0	71	0	0	0	0	0	0	0	156	0	0	227	
5:00 - 6:00 PM	0	0	0	0	0	72	0	0	0	0	0	0	0	148	0	0	220	
Peak Hour 4:00 - 5:00 PM	0	0	0	0	0	102	0	0	0	0	0	0	0	144	0	0	246	
Peak Hour Factor	0.00				0.77				0.00				0.82				0.85	
Peak Hour % Trucks	0%				0%				0%				0%					
Peak 15 Min % Trucks	0%				0%				0%				0%					

# H. LEE & ASSOCIATES, PLLC

P.O. Box 1849  
Vancouver, WA 98668

**Change These in File > Preferences > Titles**

SE 40th Street  
Between SE201st St and NW Deer Fern St

A to B WB	1	16	21	26	31	36	41	46	51	56	61	66	71	76	Total	Pace	Number
Start Time	15	20	25	30	35	40	45	50	55	60	65	70	75	999		Speed	in Pace
03/07/18	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
01:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
02:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
03:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
04:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
05:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
06:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
07:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
08:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
09:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
10:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
11:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
12 PM	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
13:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
14:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
15:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
16:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
17:00	0	0	0	0	14	22	15	7	0	0	0	0	0	0	58	34-43	37
18:00	1	0	0	3	21	22	14	2	0	0	0	0	0	0	63	31-40	43
19:00	1	0	0	4	21	32	10	1	1	0	0	0	0	0	70	31-40	53
20:00	0	0	0	1	6	15	6	1	0	0	0	0	0	0	29	31-40	21
21:00	0	0	0	1	7	8	1	1	0	0	0	0	0	0	18	31-40	15
22:00	0	0	0	1	2	1	0	0	0	0	0	0	0	0	4	25-34	3
23:00	0	0	0	0	0	1	2	0	0	0	0	0	0	0	3	35-44	3
Total	2	0	0	10	71	101	48	12	1	0	0	0	0	0	245		
Percent	0.8%	0.0%	0.0%	4.1%	29.0%	41.2%	19.6%	4.9%	0.4%	0.0%	0.0%	0.0%	0.0%	0.0%			
AM Peak Vol.																	
PM Peak Vol.	18:00			19:00	18:00	19:00	17:00	17:00	19:00						19:00		
	1			4	21	32	15	7	1						70		

# H. LEE & ASSOCIATES, PLLC

P.O. Box 1849  
Vancouver, WA 98668

[Change These in File > Preferences > Titles](#)

SE 40th Street  
Between SE201st St and NW Deer Fern St

A to B WB	1	16	21	26	31	36	41	46	51	56	61	66	71	76	Total	Pace	Number
Start Time	15	20	25	30	35	40	45	50	55	60	65	70	75	999		Speed	in Pace
03/08/18	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1	19-28	1
01:00	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	34-43	1
02:00	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1	24-33	1
03:00	0	0	0	0	0	2	0	0	1	0	0	0	0	0	3	30-39	2
04:00	0	0	1	1	1	1	1	0	0	0	0	0	0	0	5	36-45	2
05:00	0	0	0	1	3	8	5	3	0	0	0	0	0	0	20	35-44	13
06:00	0	0	0	2	5	15	5	2	0	0	0	0	0	0	29	36-45	20
07:00	0	0	0	5	11	36	19	2	1	0	0	0	0	0	74	36-45	55
08:00	0	0	0	7	22	44	24	1	0	0	0	0	0	0	98	35-44	68
09:00	2	0	0	6	19	41	26	7	0	0	0	0	0	0	101	36-45	67
10:00	5	1	1	1	14	22	7	2	0	0	0	0	0	0	53	31-40	36
11:00	0	0	1	7	19	20	14	2	0	0	0	0	0	0	63	31-40	39
12 PM	1	0	0	5	11	24	10	1	1	0	0	0	0	0	53	31-40	35
13:00	1	1	4	4	14	18	17	1	0	0	0	0	0	0	60	36-45	35
14:00	1	0	1	1	20	22	13	2	0	0	0	0	0	0	60	31-40	42
15:00	0	0	2	4	34	35	12	4	1	1	0	0	0	0	93	31-40	69
16:00	4	0	1	2	22	33	14	1	0	1	0	0	0	0	78	31-40	55
17:00	0	0	0	2	0	1	0	0	0	0	0	0	0	0	3	20-29	2
18:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
19:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
20:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
21:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
22:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
23:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
Total	14	2	11	49	196	322	168	28	4	2	0	0	0	0	796		
Percent	1.8%	0.3%	1.4%	6.2%	24.6%	40.5%	21.1%	3.5%	0.5%	0.3%	0.0%	0.0%	0.0%	0.0%			
AM Peak	10:00	10:00	04:00	08:00	08:00	08:00	09:00	09:00	03:00								09:00
Vol.	5	1	1	7	22	44	26	7	1								101
PM Peak	16:00	13:00	13:00	12:00	15:00	15:00	13:00	15:00	12:00	15:00							15:00
Vol.	4	1	4	5	34	35	17	4	1	1							93
Total	16	2	11	59	267	423	216	40	5	2	0	0	0	0	1041		
Percent	1.5%	0.2%	1.1%	5.7%	25.6%	40.6%	20.7%	3.8%	0.5%	0.2%	0.0%	0.0%	0.0%	0.0%			

15th Percentile : 31 MPH  
50th Percentile : 36 MPH  
85th Percentile : 42 MPH  
95th Percentile : 44 MPH

Stats  
10 MPH Pace Speed : 31-40 MPH  
Number in Pace : 690  
Percent in Pace : 66.3%  
Number of Vehicles > 55 MPH : 2  
Percent of Vehicles > 55 MPH : 0.2%  
Mean Speed(Average) : 37 MPH



# H. LEE & ASSOCIATES, PLLC

P.O. Box 1849  
Vancouver, WA 98668

[Change These in File > Preferences > Titles](#)

SE 40th Street  
Between SE201st St and NW Deer Fern St

B to A EB	1	16	21	26	31	36	41	46	51	56	61	66	71	76	Total	Pace Speed	Number in Pace
Start Time	15	20	25	30	35	40	45	50	55	60	65	70	75	999			
03/07/18	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
01:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
02:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
03:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
04:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
05:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
06:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
07:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
08:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
09:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
10:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
11:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
12 PM	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
13:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
14:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
15:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
16:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
17:00	0	0	<b>2</b>	<b>8</b>	<b>45</b>	<b>64</b>	<b>21</b>	<b>4</b>	<b>1</b>	0	0	0	0	0	<b>145</b>	31-40	109
18:00	<b>1</b>	0	<b>1</b>	<b>9</b>	37	41	<b>22</b>	1	0	0	0	0	0	0	112	31-40	78
19:00	1	0	0	7	39	30	11	2	<b>2</b>	0	0	0	0	0	92	31-40	69
20:00	0	0	0	5	19	18	10	0	<b>1</b>	0	0	0	0	0	53	31-40	37
21:00	0	0	1	3	17	21	6	2	0	0	0	0	0	0	50	31-40	38
22:00	0	0	0	2	2	5	2	1	0	0	0	0	0	0	12	36-45	7
23:00	0	0	0	0	1	4	3	1	0	0	0	0	0	0	9	35-44	7
Total	2	0	4	34	160	183	75	11	4	0	0	0	0	0	473		
Percent	0.4%	0.0%	0.8%	7.2%	33.8%	38.7%	15.9%	2.3%	0.8%	0.0%	0.0%	0.0%	0.0%	0.0%			
AM Peak Vol.																	
PM Peak Vol.	18:00		17:00	18:00	17:00	17:00	18:00	17:00	19:00						17:00		
	1		2	9	45	64	22	4	2						145		

# H. LEE & ASSOCIATES, PLLC

P.O. Box 1849  
Vancouver, WA 98668

Change These in File > Preferences > Titles

SE 40th Street  
Between SE201st St and NW Deer Fern St

B to A EB

Start Time	15	20	25	30	35	40	45	50	55	60	65	70	75	999	Total	Pace Speed	Number in Pace
03/08/18	0	0	0	0	0	1	1	0	0	0	0	0	0	0	2	34-43	2
01:00	0	0	0	0	2	0	0	0	0	0	0	0	0	0	2	25-34	2
02:00	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	34-43	1
03:00	0	0	0	0	0	2	0	0	0	0	0	0	0	0	2	30-39	2
04:00	0	0	0	0	0	1	0	0	0	0	0	0	0	0	1	29-38	1
05:00	0	0	0	0	1	0	0	0	0	0	0	0	0	0	1	24-33	1
06:00	0	0	0	3	3	3	0	1	0	0	0	0	0	0	10	31-40	6
07:00	1	0	0	3	7	15	0	0	0	0	0	0	0	0	26	31-40	22
08:00	2	0	0	7	19	21	6	1	0	0	0	0	0	0	56	31-40	40
09:00	2	1	0	6	19	16	9	4	0	0	0	0	0	0	57	31-40	35
10:00	1	0	4	10	14	21	10	1	0	0	0	0	0	0	61	31-40	35
11:00	0	0	2	7	19	29	11	2	0	0	0	0	0	0	70	31-40	48
12 PM	1	0	1	7	21	30	12	1	1	0	0	0	0	0	74	31-40	51
13:00	0	0	0	6	22	20	12	2	1	0	0	0	0	0	63	31-40	42
14:00	1	0	0	8	27	22	18	2	0	0	0	0	0	0	78	31-40	49
15:00	0	1	1	8	44	42	17	2	0	0	0	0	0	0	115	31-40	86
16:00	8	1	8	8	38	67	13	3	0	0	0	0	0	0	146	31-40	105
17:00	0	0	1	2	0	0	0	0	0	0	0	0	0	0	3	20-29	3
18:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
19:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
20:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
21:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
22:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
23:00	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
<b>Total</b>	16	3	17	75	236	290	110	19	2	0	0	0	0	0	768		
<b>Percent</b>	2.1%	0.4%	2.2%	9.8%	30.7%	37.8%	14.3%	2.5%	0.3%	0.0%	0.0%	0.0%	0.0%	0.0%			
<b>AM Peak</b>	08:00	09:00	10:00	10:00	08:00	11:00	11:00	09:00							11:00		
<b>Vol.</b>	2	1	4	10	19	29	11	4							70		
<b>PM Peak</b>	16:00	15:00	16:00	14:00	15:00	16:00	14:00	16:00	12:00						16:00		
<b>Vol.</b>	8	1	8	8	44	67	18	3	1						146		
<b>Total</b>	18	3	21	109	396	473	185	30	6	0	0	0	0	0	1241		
<b>Percent</b>	1.5%	0.2%	1.7%	8.8%	31.9%	38.1%	14.9%	2.4%	0.5%	0.0%	0.0%	0.0%	0.0%	0.0%			

15th Percentile : 30 MPH  
 50th Percentile : 35 MPH  
 85th Percentile : 40 MPH  
 95th Percentile : 44 MPH

Stats  
 10 MPH Pace Speed : 31-40 MPH  
 Number in Pace : 869  
 Percent in Pace : 70.0%  
 Number of Vehicles > 55 MPH : 0  
 Percent of Vehicles > 55 MPH : 0.0%  
 Mean Speed(Average) : 36 MPH

**APPENDIX B**

**EXISTING LEVEL OF SERVICE**

Lanes, Volumes, Timings

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	4	408	52	12	184	0	148	0	32	4	0	28
Future Volume (vph)	4	408	52	12	184	0	148	0	32	4	0	28
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Storage Length (ft)	115		0	135		0	220		0	30		0
Storage Lanes	1		0	1		0	0		0	0		0
Taper Length (ft)	25			25			25			25		
Lane Util. Factor	1.00	0.95	0.95	1.00	0.95	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.983						0.976				0.882
Flt Protected	0.950			0.950				0.961				0.994
Satd. Flow (prot)	1752	3445	0	1736	3471	0	0	1747	0	0	1666	0
Flt Permitted	0.950			0.950				0.961				0.994
Satd. Flow (perm)	1752	3445	0	1736	3471	0	0	1747	0	0	1666	0
Link Speed (mph)		40			40			35				25
Link Distance (ft)		1779			1191			1505				543
Travel Time (s)		30.3			20.3			29.3				14.8
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	3%	3%	3%	4%	4%	4%	2%	2%	2%	0%	0%	0%
Adj. Flow (vph)	4	408	52	12	184	0	148	0	32	4	0	28
Shared Lane Traffic (%)												
Lane Group Flow (vph)	4	460	0	12	184	0	0	180	0	0	32	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(ft)		12			12			0				0
Link Offset(ft)		0			0			0				0
Crosswalk Width(ft)		16			16			16				16
Two way Left Turn Lane												
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15		9	15		9	15		9	15		9
Sign Control		Free			Free			Stop				Stop

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	36.4%
Analysis Period (min)	15
	ICU Level of Service A

**Intersection**

Int Delay, s/veh 4.4

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↖	↕		↖	↕			↕			↕	
Traffic Vol, veh/h	4	408	52	12	184	0	148	0	32	4	0	28
Future Vol, veh/h	4	408	52	12	184	0	148	0	32	4	0	28
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	115	-	-	135	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	100	100	100	100	100	100	100	100	100	100	100	100
Heavy Vehicles, %	3	3	3	4	4	4	2	2	2	0	0	0
Mvmt Flow	4	408	52	12	184	0	148	0	32	4	0	28

Major/Minor	Major1	Major2	Minor1	Minor2
Conflicting Flow All	184	0	0	460
Stage 1	-	-	-	-
Stage 2	-	-	-	-
Critical Hdwy	4.16	-	-	4.18
Critical Hdwy Stg 1	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-
Follow-up Hdwy	2.23	-	-	2.24
Pot Cap-1 Maneuver	1381	-	-	1083
Stage 1	-	-	-	-
Stage 2	-	-	-	-
Platoon blocked, %	-	-	-	-
Mov Cap-1 Maneuver	1381	-	-	1083
Mov Cap-2 Maneuver	-	-	-	-
Stage 1	-	-	-	-
Stage 2	-	-	-	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	0.1	0.5	19	9.4
HCM LOS			C	A

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	434	1381	-	-	1083	-	-	855
HCM Lane V/C Ratio	0.415	0.003	-	-	0.011	-	-	0.037
HCM Control Delay (s)	19	7.6	-	-	8.4	-	-	9.4
HCM Lane LOS	C	A	-	-	A	-	-	A
HCM 95th %tile Q(veh)	2	0	-	-	0	-	-	0.1

Lanes, Volumes, Timings  
 2: NW Brady Road & NW 16th Street

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Volume (vph)	80	140	84	84	172	72	128	60	24	44	88	68
Future Volume (vph)	80	140	84	84	172	72	128	60	24	44	88	68
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.963			0.970			0.985			0.954	
Flt Protected		0.987			0.987			0.971			0.989	
Satd. Flow (prot)	0	1657	0	0	1783	0	0	1747	0	0	1758	0
Flt Permitted		0.987			0.987			0.971			0.989	
Satd. Flow (perm)	0	1657	0	0	1783	0	0	1747	0	0	1758	0
Link Speed (mph)		25			25			35			35	
Link Distance (ft)		1212			959			2307			902	
Travel Time (s)		33.1			26.2			44.9			17.6	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	9%	9%	9%	2%	2%	2%	4%	4%	4%	2%	2%	2%
Adj. Flow (vph)	80	140	84	84	172	72	128	60	24	44	88	68
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	304	0	0	328	0	0	212	0	0	200	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(ft)		0			0			0			0	
Link Offset(ft)		0			0			0			0	
Crosswalk Width(ft)		16			16			16			16	
Two way Left Turn Lane												
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15		9	15		9	15		9	15		9
Sign Control		Stop			Stop			Stop			Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	56.8%
ICU Level of Service	B
Analysis Period (min)	15

Intersection	
Intersection Delay, s/veh	14
Intersection LOS	B











Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	80	140	84	84	172	72	128	60	24	44	88	68
Future Vol, veh/h	80	140	84	84	172	72	128	60	24	44	88	68
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles, %	9	9	9	2	2	2	4	4	4	2	2	2
Mvmt Flow	80	140	84	84	172	72	128	60	24	44	88	68
Number of Lanes	0	1	0	0	1	0	0	1	0	0	1	0

Approach	EB	WB	NB	SB
Opposing Approach	WB	EB	SB	NB
Opposing Lanes	1	1	1	1
Conflicting Approach Left	SB	NB	EB	WB
Conflicting Lanes Left	1	1	1	1
Conflicting Approach Right	NB	SB	WB	EB
Conflicting Lanes Right	1	1	1	1
HCM Control Delay	14.7	15.1	13.1	12.3
HCM LOS	B	C	B	B

Lane	NBLn1	EBLn1	WBLn1	SBLn1
Vol Left, %	60%	26%	26%	22%
Vol Thru, %	28%	46%	52%	44%
Vol Right, %	11%	28%	22%	34%
Sign Control	Stop	Stop	Stop	Stop
Traffic Vol by Lane	212	304	328	200
LT Vol	128	80	84	44
Through Vol	60	140	172	88
RT Vol	24	84	72	68
Lane Flow Rate	212	304	328	200
Geometry Grp	1	1	1	1
Degree of Util (X)	0.373	0.499	0.527	0.34
Departure Headway (Hd)	6.328	5.905	5.781	6.124
Convergence, Y/N	Yes	Yes	Yes	Yes
Cap	568	614	626	586
Service Time	4.374	3.917	3.794	4.172
HCM Lane V/C Ratio	0.373	0.495	0.524	0.341
HCM Control Delay	13.1	14.7	15.1	12.3
HCM Lane LOS	B	B	C	B
HCM 95th-tile Q	1.7	2.8	3.1	1.5

Lanes, Volumes, Timings  
 3: NW Brady Road & NW McIntosh Road

03/06/2018

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	136	4	192	48	4	328
Future Volume (vph)	136	4	192	48	4	328
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.996		0.973			
Flt Protected	0.954				0.950	
Satd. Flow (prot)	1805	0	1761	0	1770	1863
Flt Permitted	0.954				0.950	
Satd. Flow (perm)	1805	0	1761	0	1770	1863
Link Speed (mph)	35		40			35
Link Distance (ft)	1524		727			2307
Travel Time (s)	29.7		12.4			44.9
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	0%	0%	5%	5%	2%	2%
Adj. Flow (vph)	136	4	192	48	4	328
Shared Lane Traffic (%)						
Lane Group Flow (vph)	140	0	240	0	4	328
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Right	Left	Left
Median Width(ft)	12		12			12
Link Offset(ft)	0		0			0
Crosswalk Width(ft)	16		16			16
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15	9		9	15	
Sign Control	Stop		Free			Free

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	31.7%
Analysis Period (min)	15
	ICU Level of Service A



**Intersection**

Int Delay, s/veh 3

Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	136	4	192	48	4	328
Future Vol, veh/h	136	4	192	48	4	328
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	0	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	5	5	2	2
Mvmt Flow	136	4	192	48	4	328

Major/Minor	Minor1	Major1	Major2
Conflicting Flow All	552	216	0
Stage 1	216	-	-
Stage 2	336	-	-
Critical Hdwy	6.4	6.2	-
Critical Hdwy Stg 1	5.4	-	-
Critical Hdwy Stg 2	5.4	-	-
Follow-up Hdwy	3.5	3.3	-
Pot Cap-1 Maneuver	498	829	-
Stage 1	825	-	-
Stage 2	728	-	-
Platoon blocked, %			
Mov Cap-1 Maneuver	496	829	-
Mov Cap-2 Maneuver	496	-	-
Stage 1	825	-	-
Stage 2	726	-	-

Approach	WB	NB	SB
HCM Control Delay, s	14.9	0	0.1
HCM LOS	B		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	502	1327
HCM Lane V/C Ratio	-	-	0.279	0.003
HCM Control Delay (s)	-	-	14.9	7.7
HCM Lane LOS	-	-	B	A
HCM 95th %tile Q(veh)	-	-	1.1	0

Lanes, Volumes, Timings

4: SE Brady Road /SE Brady Road & SE Grand Ridge Drive

03/06/2018



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	8	156	516	4	8	72
Future Volume (vph)	8	156	516	4	8	72
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.999		0.878	
Flt Protected		0.998			0.995	
Satd. Flow (prot)	0	1724	1898	0	1660	0
Flt Permitted		0.998			0.995	
Satd. Flow (perm)	0	1724	1898	0	1660	0
Link Speed (mph)		40	40		25	
Link Distance (ft)		978	3072		1011	
Travel Time (s)		16.7	52.4		27.6	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	10%	10%	0%	0%	0%	0%
Adj. Flow (vph)	8	156	516	4	8	72
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	164	520	0	80	0
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Left	Left	Right	Left	Right
Median Width(ft)		0	0		12	
Link Offset(ft)		0	0		0	
Crosswalk Width(ft)		16	16		16	
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15			9	15	9
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	39.0%
Analysis Period (min)	15
	ICU Level of Service A

**Intersection**

Int Delay, s/veh 1.4

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↕	↕		↕	
Traffic Vol, veh/h	8	156	516	4	8	72
Future Vol, veh/h	8	156	516	4	8	72
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	10	10	0	0	0	0
Mvmt Flow	8	156	516	4	8	72

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	520	0	690
Stage 1	-	-	518
Stage 2	-	-	172
Critical Hdwy	4.2	-	6.4
Critical Hdwy Stg 1	-	-	5.4
Critical Hdwy Stg 2	-	-	5.4
Follow-up Hdwy	2.29	-	3.5
Pot Cap-1 Maneuver	1007	-	414
Stage 1	-	-	602
Stage 2	-	-	863
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1007	-	410
Mov Cap-2 Maneuver	-	-	410
Stage 1	-	-	602
Stage 2	-	-	855

Approach	EB	WB	SB
HCM Control Delay, s	0.4	0	12.8
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	1007	-	-	-	542
HCM Lane V/C Ratio	0.008	-	-	-	0.148
HCM Control Delay (s)	8.6	0	-	-	12.8
HCM Lane LOS	A	A	-	-	B
HCM 95th %tile Q(veh)	0	-	-	-	0.5

Lanes, Volumes, Timings  
 5: Project Access & SE 40th Street/SE 40th Street

03/06/2018



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	68	0	0	124	0	0
Future Volume (vph)	68	0	0	124	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)		0	100		0	0
Storage Lanes		0	1		1	0
Taper Length (ft)			25		25	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt						
Flt Protected						
Satd. Flow (prot)	1610	0	1792	1792	1900	0
Flt Permitted						
Satd. Flow (perm)	1610	0	1792	1792	1900	0
Link Speed (mph)	40			40	25	
Link Distance (ft)	1480			1830	2017	
Travel Time (s)	25.2			31.2	55.0	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	18%	18%	6%	6%	0%	0%
Adj. Flow (vph)	68	0	0	124	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	68	0	0	124	0	0
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Left	Left	Right
Median Width(ft)	12			12	12	
Link Offset(ft)	0			0	0	
Crosswalk Width(ft)	16			16	16	
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)		9	15		15	9
Sign Control	Free			Free	Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	9.9%
Analysis Period (min)	15
	ICU Level of Service A

**Intersection**

Int Delay, s/veh 0

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↔		↔	↑	↔	
Traffic Vol, veh/h	68	0	0	124	0	0
Future Vol, veh/h	68	0	0	124	0	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	100	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	18	18	6	6	0	0
Mvmt Flow	68	0	0	124	0	0

Major/Minor	Major1	Major2	Minor1		
Conflicting Flow All	0	0	68	0	192
Stage 1	-	-	-	-	68
Stage 2	-	-	-	-	124
Critical Hdwy	-	-	4.16	-	6.4
Critical Hdwy Stg 1	-	-	-	-	5.4
Critical Hdwy Stg 2	-	-	-	-	5.4
Follow-up Hdwy	-	-	2.254	-	3.5
Pot Cap-1 Maneuver	-	-	1508	-	801
Stage 1	-	-	-	-	960
Stage 2	-	-	-	-	907
Platoon blocked, %	-	-	-	-	-
Mov Cap-1 Maneuver	-	-	1508	-	801
Mov Cap-2 Maneuver	-	-	-	-	801
Stage 1	-	-	-	-	960
Stage 2	-	-	-	-	907

Approach	EB	WB	NB
HCM Control Delay, s	0	0	0
HCM LOS			A

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	-	-	-	1508	-
HCM Lane V/C Ratio	-	-	-	-	-
HCM Control Delay (s)	0	-	-	0	-
HCM Lane LOS	A	-	-	A	-
HCM 95th %tile Q(veh)	-	-	-	0	-

Lanes, Volumes, Timings

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	24	228	220	12	768	4	132	0	16	12	0	4
Future Volume (vph)	24	228	220	12	768	4	132	0	16	12	0	4
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Storage Length (ft)	115		0	135		0	220		0	30		0
Storage Lanes	1		0	1		0	0		0	0		0
Taper Length (ft)	25			25			25			25		
Lane Util. Factor	1.00	0.95	0.95	1.00	0.95	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.926			0.999			0.985			0.966	
Flt Protected	0.950			0.950				0.957			0.964	
Satd. Flow (prot)	1787	3310	0	1787	3571	0	0	1791	0	0	1769	0
Flt Permitted	0.950			0.950				0.957			0.964	
Satd. Flow (perm)	1787	3310	0	1787	3571	0	0	1791	0	0	1769	0
Link Speed (mph)		40			40			35			25	
Link Distance (ft)		1779			1191			1505			543	
Travel Time (s)		30.3			20.3			29.3			14.8	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	1%	1%	1%	1%	1%	1%	0%	0%	0%	0%	0%	0%
Adj. Flow (vph)	24	228	220	12	768	4	132	0	16	12	0	4
Shared Lane Traffic (%)												
Lane Group Flow (vph)	24	448	0	12	772	0	0	148	0	0	16	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(ft)		12			12			0			0	
Link Offset(ft)		0			0			0			0	
Crosswalk Width(ft)		16			16			16			16	
Two way Left Turn Lane												
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15		9	15		9	15		9	15		9
Sign Control		Free			Free			Stop			Stop	

Intersection Summary

Area Type: Other

Control Type: Unsignalized

Intersection Capacity Utilization 37.8% ICU Level of Service A

Analysis Period (min) 15

**Intersection**

Int Delay, s/veh 3.5

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↖	↕		↖	↕			↕			↕	
Traffic Vol, veh/h	24	228	220	12	768	4	132	0	16	12	0	4
Future Vol, veh/h	24	228	220	12	768	4	132	0	16	12	0	4
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	115	-	-	135	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	100	100	100	100	100	100	100	100	100	100	100	100
Heavy Vehicles, %	1	1	1	1	1	1	0	0	0	0	0	0
Mvmt Flow	24	228	220	12	768	4	132	0	16	12	0	4

Major/Minor	Major1	Major2	Minor1	Minor2
Conflicting Flow All	772	0	0	448
Stage 1	-	-	-	-
Stage 2	-	-	-	-
Critical Hdwy	4.12	-	-	4.12
Critical Hdwy Stg 1	-	-	-	-
Critical Hdwy Stg 2	-	-	-	-
Follow-up Hdwy	2.21	-	-	2.21
Pot Cap-1 Maneuver	845	-	-	1116
Stage 1	-	-	-	-
Stage 2	-	-	-	-
Platoon blocked, %	-	-	-	-
Mov Cap-1 Maneuver	845	-	-	1116
Mov Cap-2 Maneuver	-	-	-	-
Stage 1	-	-	-	-
Stage 2	-	-	-	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	0.5	0.1	29.2	20.7
HCM LOS			D	C

Minor Lane/Major Mvmt	NBLn1	EBL	EBT	EBR	WBL	WBT	WBR	SBLn1
Capacity (veh/h)	293	845	-	-	1116	-	-	246
HCM Lane V/C Ratio	0.505	0.028	-	-	0.011	-	-	0.065
HCM Control Delay (s)	29.2	9.4	-	-	8.3	-	-	20.7
HCM Lane LOS	D	A	-	-	A	-	-	C
HCM 95th %tile Q(veh)	2.7	0.1	-	-	0	-	-	0.2

Lanes, Volumes, Timings  
2: NW Brady Road & NW 16th Street

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Volume (vph)	4	100	8	104	24	96	4	188	136	100	236	4
Future Volume (vph)	4	100	8	104	24	96	4	188	136	100	236	4
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.990			0.942			0.944			0.998	
Flt Protected		0.998			0.977			0.999			0.986	
Satd. Flow (prot)	0	1877	0	0	1749	0	0	1792	0	0	1833	0
Flt Permitted		0.998			0.977			0.999			0.986	
Satd. Flow (perm)	0	1877	0	0	1749	0	0	1792	0	0	1833	0
Link Speed (mph)		25			25			35			35	
Link Distance (ft)		1212			959			2307			902	
Travel Time (s)		33.1			26.2			44.9			17.6	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	0%	0%	0%	0%	0%	0%	0%	0%	0%	2%	2%	2%
Adj. Flow (vph)	4	100	8	104	24	96	4	188	136	100	236	4
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	112	0	0	224	0	0	328	0	0	340	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(ft)		0			0			0			0	
Link Offset(ft)		0			0			0			0	
Crosswalk Width(ft)		16			16			16			16	
Two way Left Turn Lane												
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15		9	15		9	15		9	15		9
Sign Control		Stop			Stop			Stop			Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	66.2%
ICU Level of Service	C
Analysis Period (min)	15



Intersection	
Intersection Delay, s/veh	13
Intersection LOS	B











Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	4	100	8	104	24	96	4	188	136	100	236	4
Future Vol, veh/h	4	100	8	104	24	96	4	188	136	100	236	4
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles, %	0	0	0	0	0	0	0	0	0	2	2	2
Mvmt Flow	4	100	8	104	24	96	4	188	136	100	236	4
Number of Lanes	0	1	0	0	1	0	0	1	0	0	1	0

Approach	EB	WB	NB	SB
Opposing Approach	WB	EB	SB	NB
Opposing Lanes	1	1	1	1
Conflicting Approach Left	SB	NB	EB	WB
Conflicting Lanes Left	1	1	1	1
Conflicting Approach Right	NB	SB	WB	EB
Conflicting Lanes Right	1	1	1	1
HCM Control Delay	10.6	12	12.9	14.4
HCM LOS	B	B	B	B

Lane	NBLn1	EBLn1	WBLn1	SBLn1
Vol Left, %	1%	4%	46%	29%
Vol Thru, %	57%	89%	11%	69%
Vol Right, %	41%	7%	43%	1%
Sign Control	Stop	Stop	Stop	Stop
Traffic Vol by Lane	328	112	224	340
LT Vol	4	4	104	100
Through Vol	188	100	24	236
RT Vol	136	8	96	4
Lane Flow Rate	328	112	224	340
Geometry Grp	1	1	1	1
Degree of Util (X)	0.474	0.19	0.356	0.519
Departure Headway (Hd)	5.204	6.097	5.728	5.492
Convergence, Y/N	Yes	Yes	Yes	Yes
Cap	689	585	625	653
Service Time	3.263	4.175	3.794	3.549
HCM Lane V/C Ratio	0.476	0.191	0.358	0.521
HCM Control Delay	12.9	10.6	12	14.4
HCM Lane LOS	B	B	B	B
HCM 95th-tile Q	2.6	0.7	1.6	3

Lanes, Volumes, Timings  
 3: NW Brady Road & NW McIntosh Road

03/06/2018

						
Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	48	12	384	132	8	356
Future Volume (vph)	48	12	384	132	8	356
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.973		0.965			
Flt Protected	0.962				0.950	
Satd. Flow (prot)	1778	0	1815	0	1752	1845
Flt Permitted	0.962				0.950	
Satd. Flow (perm)	1778	0	1815	0	1752	1845
Link Speed (mph)	35		40			35
Link Distance (ft)	1524		727			2307
Travel Time (s)	29.7		12.4			44.9
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	0%	0%	1%	1%	3%	3%
Adj. Flow (vph)	48	12	384	132	8	356
Shared Lane Traffic (%)						
Lane Group Flow (vph)	60	0	516	0	8	356
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Right	Left	Left
Median Width(ft)	12		12			12
Link Offset(ft)	0		0			0
Crosswalk Width(ft)	16		16			16
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15	9		9	15	
Sign Control	Stop		Free			Free

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	38.3%
Analysis Period (min)	15
	ICU Level of Service A

**Intersection**

Int Delay, s/veh 1.1

Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	↔		↔		↔	↔
Traffic Vol, veh/h	48	12	384	132	8	356
Future Vol, veh/h	48	12	384	132	8	356
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	0	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	1	1	3	3
Mvmt Flow	48	12	384	132	8	356

Major/Minor	Minor1	Major1	Major2		
Conflicting Flow All	822	450	0	0	516
Stage 1	450	-	-	-	-
Stage 2	372	-	-	-	-
Critical Hdwy	6.4	6.2	-	-	4.13
Critical Hdwy Stg 1	5.4	-	-	-	-
Critical Hdwy Stg 2	5.4	-	-	-	-
Follow-up Hdwy	3.5	3.3	-	-	2.227
Pot Cap-1 Maneuver	346	613	-	-	1045
Stage 1	647	-	-	-	-
Stage 2	702	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	343	613	-	-	1045
Mov Cap-2 Maneuver	343	-	-	-	-
Stage 1	647	-	-	-	-
Stage 2	697	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	16.4	0	0.2
HCM LOS	C		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	376	1045
HCM Lane V/C Ratio	-	-	0.16	0.008
HCM Control Delay (s)	-	-	16.4	8.5
HCM Lane LOS	-	-	C	A
HCM 95th %tile Q(veh)	-	-	0.6	0

Lanes, Volumes, Timings

4: SE Brady Road /SE Brady Road & SE Grand Ridge Drive

03/06/2018



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↔	↔		↔	
Traffic Volume (vph)	48	488	376	4	8	16
Future Volume (vph)	48	488	376	4	8	16
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.999		0.910	
Flt Protected		0.996			0.984	
Satd. Flow (prot)	0	1874	1861	0	1701	0
Flt Permitted		0.996			0.984	
Satd. Flow (perm)	0	1874	1861	0	1701	0
Link Speed (mph)		40	40		25	
Link Distance (ft)		978	3072		1011	
Travel Time (s)		16.7	52.4		27.6	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	1%	1%	2%	2%	0%	0%
Adj. Flow (vph)	48	488	376	4	8	16
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	536	380	0	24	0
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Left	Left	Right	Left	Right
Median Width(ft)		0	0		12	
Link Offset(ft)		0	0		0	
Crosswalk Width(ft)		16	16		16	
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15			9	15	9
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	61.7%
Analysis Period (min)	15
	ICU Level of Service B

**Intersection**

Int Delay, s/veh 0.7

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↕	↕		↕	
Traffic Vol, veh/h	48	488	376	4	8	16
Future Vol, veh/h	48	488	376	4	8	16
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	1	1	2	2	0	0
Mvmt Flow	48	488	376	4	8	16

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	380	0	0
Stage 1	-	-	-
Stage 2	-	-	-
Critical Hdwy	4.11	-	-
Critical Hdwy Stg 1	-	-	-
Critical Hdwy Stg 2	-	-	-
Follow-up Hdwy	2.209	-	-
Pot Cap-1 Maneuver	1184	-	-
Stage 1	-	-	-
Stage 2	-	-	-
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1184	-	-
Mov Cap-2 Maneuver	-	-	-
Stage 1	-	-	-
Stage 2	-	-	-

Approach	EB	WB	SB
HCM Control Delay, s	0.7	0	13.5
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	1184	-	-	-	449
HCM Lane V/C Ratio	0.041	-	-	-	0.053
HCM Control Delay (s)	8.2	0	-	-	13.5
HCM Lane LOS	A	A	-	-	B
HCM 95th %tile Q(veh)	0.1	-	-	-	0.2

Lanes, Volumes, Timings  
 5: Project Access & SE 40th Street/SE 40th Street

03/06/2018



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	156	0	0	132	0	0
Future Volume (vph)	156	0	0	132	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)		0	100		0	0
Storage Lanes		0	1		1	0
Taper Length (ft)			25		25	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt						
Flt Protected						
Satd. Flow (prot)	1900	0	1900	1900	1900	0
Flt Permitted						
Satd. Flow (perm)	1900	0	1900	1900	1900	0
Link Speed (mph)	40			40	25	
Link Distance (ft)	1480			1830	2017	
Travel Time (s)	25.2			31.2	55.0	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	0%	0%	0%	0%	0%	0%
Adj. Flow (vph)	156	0	0	132	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	156	0	0	132	0	0
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Left	Left	Right
Median Width(ft)	12			12	12	
Link Offset(ft)	0			0	0	
Crosswalk Width(ft)	16			16	16	
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)		9	15		15	9
Sign Control	Free			Free	Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	11.5%
Analysis Period (min)	15
	ICU Level of Service A

**Intersection**

Int Delay, s/veh 0

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↔		↔	↔	↔	
Traffic Vol, veh/h	156	0	0	132	0	0
Future Vol, veh/h	156	0	0	132	0	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	100	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	156	0	0	132	0	0

Major/Minor	Major1	Major2	Minor1		
Conflicting Flow All	0	0	156	0	288
Stage 1	-	-	-	-	156
Stage 2	-	-	-	-	132
Critical Hdwy	-	-	4.1	-	6.4
Critical Hdwy Stg 1	-	-	-	-	5.4
Critical Hdwy Stg 2	-	-	-	-	5.4
Follow-up Hdwy	-	-	2.2	-	3.5
Pot Cap-1 Maneuver	-	-	1436	-	707
Stage 1	-	-	-	-	877
Stage 2	-	-	-	-	899
Platoon blocked, %	-	-	-	-	-
Mov Cap-1 Maneuver	-	-	1436	-	707
Mov Cap-2 Maneuver	-	-	-	-	707
Stage 1	-	-	-	-	877
Stage 2	-	-	-	-	899

Approach	EB	WB	NB
HCM Control Delay, s	0	0	0
HCM LOS			A

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	-	-	-	1436	-
HCM Lane V/C Ratio	-	-	-	-	-
HCM Control Delay (s)	0	-	-	0	-
HCM Lane LOS	A	-	-	A	-
HCM 95th %tile Q(veh)	-	-	-	0	-

**APPENDIX C**  
**ACCIDENT DATA**





February 22, 2018

Grant Stonex  
H. Lee & Associates, PLLC  
PO Box 1849  
Vancouver WA 98668

Dear Mr. Stonex:

In accordance with the Public Records Act, RCW 42.56, this letter acknowledges receipt of your request for records dated February 12, 2018 (Request Number PDR-18-0562).

We have prepared a history of officer reported crashes that occurred *at or in the vicinity of* the following intersections and road segment in the City of Camas for the period of 1/1/2013 – *available 2018*.

- 34th St / Pacific Rim Blvd @ Lorenz St / Payne Rd
- Brady Rd @ 16th Ave
- Brady Rd @ McIntosh Rd
- Brady Rd @ Grand Ridge Dr.
- Payne Rd / 40th St / 18th Ave from 201st Ave to Deerfern St

Federal law 23 United States Code Section 409 governs use of the data you requested. Under this law, data maintained for purposes of evaluating potential highway safety enhancements:

*“ . . . shall not be subject to discovery or admitted into evidence in a federal or state court proceeding or considered for other purposes in any action for damages arising from any occurrence at a location mentioned or addressed in such reports, surveys, schedules, lists, or data.”* [Emphasis added.]

Public Disclosure Request PDR-18-0562

February 22, 2018

Page 2

The Washington State Department of Transportation (WSDOT) is releasing this data to you with the understanding that you will not use this data contrary to the restrictions in Section 409, which means you will not use this data in discovery or as evidence at trial in any action for damages against the WSDOT, the State of Washington, or any other jurisdiction involved in the locations mentioned in the data. If you should attempt to use this data in an action for damages against WSDOT, the State of Washington, or any other jurisdiction involved in the locations mentioned in the data, these entities expressly reserve the right, under Section 409, to object to the use of the data, including any opinions drawn from the data.

With this package, your request for records is complete and closed.

If you have any further questions you may contact me at 360-570-2464.

Sincerely,

A handwritten signature in blue ink that reads "Julie Brown". The signature is written in a cursive, flowing style.

Julie Brown

Transportation Planning Technician 3

Transportation Data, GIS & Modeling Office




OFFICER REPORTED CRASHES THAT OCCURRED at OR in the vicinity of THE FOLLOWING INTERSECTIONS & ROAD SEGMENT IN THE CITY OF CAMAS  
 34th ST / PACIFIC RIM BLVD @ LORENZ ST/ PAYNE RD  
 BRADY RD @ 16th AVE  
 BRADY RD @ MCINTOSH RD  
 BRADY RD @ GRAND RIDGE DR.  
 PAYNE RD / 40th ST / 18th AVE FROM 201st AVE TO DEERFERN ST

01/01/2013 - available 2018  
 Under 23 U.S. Code § 409 and 23 U.S. Code § 148, safety data, reports, surveys, schedules, lists compiled or collected for the purpose of identifying, evaluating, or planning the safety enhancement of potential crash sites, hazardous roadway conditions, or railway-highway crossings are not subject to discovery or admitted into evidence in a Federal or State court proceeding or considered for other purposes in any action for damages arising from any occurrence at a location mentioned or addressed in such reports, surveys, schedules, lists, or data.

JURISDICTION	PRIMARY TRAFFICWAY	BLOCK NUMBER	INTERSECTING TRAFFICWAY	DIET FROM REF POINT	M or FT	COMP DIR FROM REF POINT	REFERENCE POINT NAME	MILEPOST	A / B	REPORT NUMBER	DATE	TIME	MOST SEVERE INJURY TYPE	# INJURY	# FATAL	# PROPERTY DAMAGE	VEHICLE 1 TYPE	VEHICLE 2 TYPE	JUNCTION RELATIONSHIP	WEATHER	ROADWAY SURFACE CONDITION	LIGHTING CONDITION	FIRST COLLISION TYPE / OBJECT STRUCK	VEHICLE 1 ACTION	VEHICLE 2 ACTION	VEHICLE 1 COMPASS DIRECTION FROM	VEHICLE 1 COMPASS DIRECTION TO	VEHICLE 2 COMPASS DIRECTION FROM	VEHICLE 2 COMPASS DIRECTION TO	MV DRIVER CONTRIBUTING CIRCUMSTANCE 1 (UNIT 1)	MV DRIVER CONTRIBUTING CIRCUMSTANCE 2 (UNIT 1)	MV DRIVER CONTRIBUTING CIRCUMSTANCE 3 (UNIT 1)	MV DRIVER CONTRIBUTING CIRCUMSTANCE 1 (UNIT 2)	MV DRIVER CONTRIBUTING CIRCUMSTANCE 2 (UNIT 2)	MV DRIVER CONTRIBUTING CIRCUMSTANCE 3 (UNIT 2)	FIRST IMPACT LOCATION (City, County & Misc. Trafficways - 2010 forward)	WA STATE PLANE SOUTH - 2010 FORWARD	WA STATE PLANE SOUTH - 2010 FORWARD			
City Street	SE BRADY RD	20300		203	F	W	SE GRAND RIDGE DR			376554	#####	21:36	No Apparent Injury	0	0	1	0	Pickup/Panel Truck or Vanette under 10,000 lb		Not at Intersection and Not Related	Overcast	Dry	Dark-No Street Lights	Metal Sign Post	Going Straight Ahead		West	East										Past the Outside Shoulder of Primary Trafficway	#####	#####	
City Street	SE PAYNE RD		NW PACIFIC RIM BLVD							3673292	#####	09:15	No Apparent Injury	0	0	2	0	Passenger Car	Pickup/Panel Truck or Vanette under 10,000 lb	At Intersection and Related	Clear or Partly Cloudy	Dry	Daylight	Entering at angle	Making Left Turn	Going Straight Ahead	South	West	West	East	Did Not Grant RW to Vehicle				Other				Past the Outside Shoulder of Primary Trafficway	#####	#####
City Street	SE PAYNE ST	4000	SE 201ST ST							3766646	#####	00:15	No Apparent Injury	0	0	1	0	Passenger Car		At Intersection and Related	Raining	Wet	Dark-Street Lights On	Metal Sign Post	Making Right Turn		North	Southwest				Unknown Driver Distraction							Past the Outside Shoulder of Primary Trafficway	#####	#####

**APPENDIX D**  
**IN-PROCESS INFORMATION**

Figure 9: Weekday Peak Hour Traffic Volumes Generated By Parker Village







Generated Site Traffic



	In	Out
AM Peak	9	33
PM Peak	34	19



N  
Drawing Not To Scale

- Traffic Signal 
- Stop Sign 
- Proposed Site 
- Proposed Roadway 
- AM(PM) Peak Hour Volumes


OR04.093.T01 Parker Village



Site-Generated Trips  
Weekday AM and PM Peak Hours  
Camas, Washington

Figure  
6

H:\projects\160000 - Kate's Woods\TIA\kgv\figs\20160705\_Report.dwg Jun 16, 2016 3:57pm - llyala Layout Tab: Figure 6





Site-Generated Trips  
 Weekday AM and PM Peak Hours  
 Camas, Washington


Figure  
 6

H:\p\16115639 - McIntosh Road PRD\mgs\fig15633\_Fig6.dwg Mar 10, 2017 - 3:32pm - hpcuser Layout Tab: Figure 6












1. SR-14 EB Ramp @ SE 192nd Ave.



2. SR-14 WB Ramp @ SE 192nd Ave.




3. SE Brady Rd. @ SE 192nd Ave.




4. Site Access @ SE 192nd Ave.




5. SE 192nd Ave. @ SE 34th St.




6. NW Brady Rd. @ McIntosh Rd.




7. NW Brady Rd. @ NW 16th Av.




8. Pacific Rim Blvd. @ Parker St.




9. Site Access @ SE Brady Rd.



10. Site Access @ SE Brady Rd.



11. Site Access @ SE Brady Rd.



**LEGEND**

- Traffic Signal
- Stop Sign
- Lane Configuration
- Future Project Access

- Study Intersection
- AM (PM) - Peak Hour Traffic Volumes

**DKS**

No Scale

**Site-Generated Traffic Volumes Weekday AM & PM Peak Hours**

*Columbia Palisades*

**APPENDIX E**

**2023 “WITHOUT PROJECT” LEVEL OF SERVICE**

Lanes, Volumes, Timings

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	5	474	63	117	264	0	169	0	85	5	0	32
Future Volume (vph)	5	474	63	117	264	0	169	0	85	5	0	32
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Storage Length (ft)	115		0	135		0	220		0	30		0
Storage Lanes	1		0	1		0	1		0	1		0
Taper Length (ft)	25			25			25			25		
Lane Util. Factor	1.00	0.95	0.95	1.00	0.95	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.982						0.850				0.850
Flt Protected	0.950			0.950			0.950			0.950		
Satd. Flow (prot)	1752	3442	0	1736	3471	0	1770	1583	0	1805	1615	0
Flt Permitted	0.589			0.295			0.489			0.702		
Satd. Flow (perm)	1087	3442	0	539	3471	0	911	1583	0	1334	1615	0
Right Turn on Red			Yes			Yes			Yes			Yes
Satd. Flow (RTOR)		16						450			538	
Link Speed (mph)		40			40			35			25	
Link Distance (ft)		1779			1191			1505			543	
Travel Time (s)		30.3			20.3			29.3			14.8	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	3%	3%	3%	4%	4%	4%	2%	2%	2%	0%	0%	0%
Adj. Flow (vph)	5	474	63	117	264	0	169	0	85	5	0	32
Shared Lane Traffic (%)												
Lane Group Flow (vph)	5	537	0	117	264	0	169	85	0	5	32	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(ft)		12			12			12			12	
Link Offset(ft)		0			0			0			0	
Crosswalk Width(ft)		16			16			16			16	
Two way Left Turn Lane												
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15		9	15		9	15		9	15		9
Number of Detectors	1	2		1	2		1	2		1	2	
Detector Template	Left	Thru		Left	Thru		Left	Thru		Left	Thru	
Leading Detector (ft)	20	100		20	100		20	100		20	100	
Trailing Detector (ft)	0	0		0	0		0	0		0	0	
Detector 1 Position(ft)	0	0		0	0		0	0		0	0	
Detector 1 Size(ft)	20	6		20	6		20	6		20	6	
Detector 1 Type	Cl+Ex	Cl+Ex		Cl+Ex	Cl+Ex		Cl+Ex	Cl+Ex		Cl+Ex	Cl+Ex	
Detector 1 Channel												
Detector 1 Extend (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Detector 1 Queue (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Detector 1 Delay (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Detector 2 Position(ft)		94			94			94			94	
Detector 2 Size(ft)		6			6			6			6	
Detector 2 Type		Cl+Ex			Cl+Ex			Cl+Ex			Cl+Ex	
Detector 2 Channel												
Detector 2 Extend (s)		0.0			0.0			0.0			0.0	
Turn Type	pm+pt	NA		pm+pt	NA		pm+pt	NA		pm+pt	NA	
Protected Phases	7	4		3	8		5	2		1	6	

Lanes, Volumes, Timings

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Permitted Phases	4			8			2			6		
Detector Phase	7	4		3	8		5	2		1	6	
Switch Phase												
Minimum Initial (s)	5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0	
Minimum Split (s)	9.5	22.5		9.5	22.5		9.5	22.5		9.5	22.5	
Total Split (s)	11.0	31.0		16.0	36.0		17.0	32.0		11.0	26.0	
Total Split (%)	12.2%	34.4%		17.8%	40.0%		18.9%	35.6%		12.2%	28.9%	
Maximum Green (s)	6.5	26.5		11.5	31.5		12.5	27.5		6.5	21.5	
Yellow Time (s)	3.5	3.5		3.5	3.5		3.5	3.5		3.5	3.5	
All-Red Time (s)	1.0	1.0		1.0	1.0		1.0	1.0		1.0	1.0	
Lost Time Adjust (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Total Lost Time (s)	4.5	4.5		4.5	4.5		4.5	4.5		4.5	4.5	
Lead/Lag	Lead	Lag		Lead	Lag		Lead	Lag		Lead	Lag	
Lead-Lag Optimize?	Yes	Yes		Yes	Yes		Yes	Yes		Yes	Yes	
Vehicle Extension (s)	3.0	3.0		3.0	3.0		3.0	3.0		3.0	3.0	
Recall Mode	None	None		None	None		None	Min		None	Min	
Walk Time (s)		7.0			7.0			7.0			7.0	
Flash Dont Walk (s)		11.0			11.0			11.0			11.0	
Pedestrian Calls (#/hr)		0			0			0			0	
Act Effct Green (s)	18.7	14.7		23.5	22.0		18.0	15.8		10.4	6.3	
Actuated g/C Ratio	0.36	0.29		0.46	0.43		0.35	0.31		0.20	0.12	
v/c Ratio	0.01	0.54		0.27	0.18		0.34	0.11		0.02	0.05	
Control Delay	8.4	19.4		10.1	10.9		15.9	0.3		14.4	0.1	
Queue Delay	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Total Delay	8.4	19.4		10.1	10.9		15.9	0.3		14.4	0.1	
LOS	A	B		B	B		B	A		B	A	
Approach Delay		19.3			10.6			10.7			2.1	
Approach LOS		B			B			B			A	

Intersection Summary

Area Type: Other

Cycle Length: 90

Actuated Cycle Length: 51.4

Natural Cycle: 65

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 0.54

Intersection Signal Delay: 14.2


Intersection LOS: B

Intersection Capacity Utilization 48.9%

ICU Level of Service A

Analysis Period (min) 15

Splits and Phases: 1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard



Queues

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018























Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Group Flow (vph)	5	537	117	264	169	85	5	32
v/c Ratio	0.01	0.54	0.27	0.18	0.34	0.11	0.02	0.05
Control Delay	8.4	19.4	10.1	10.9	15.9	0.3	14.4	0.1
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	8.4	19.4	10.1	10.9	15.9	0.3	14.4	0.1
Queue Length 50th (ft)	1	81	21	24	38	0	1	0
Queue Length 95th (ft)	5	132	46	62	91	0	8	0
Internal Link Dist (ft)		1699		1111		1425		463
Turn Bay Length (ft)	115		135		220		30	
Base Capacity (vph)	505	1952	570	2201	604	1106	364	1057
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.01	0.28	0.21	0.12	0.28	0.08	0.01	0.03

Intersection Summary

# HCM 2010 Signalized Intersection Summary

## 1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	5	474	63	117	264	0	169	0	85	5	0	32
Future Volume (veh/h)	5	474	63	117	264	0	169	0	85	5	0	32
Number	7	4	14	3	8	18	5	2	12	1	6	16
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Adj Sat Flow, veh/h/ln	1845	1845	1900	1827	1827	1900	1863	1863	1900	1900	1900	1900
Adj Flow Rate, veh/h	5	474	63	117	264	0	169	0	85	5	0	32
Adj No. of Lanes	1	2	0	1	2	0	1	1	0	1	1	0
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Percent Heavy Veh, %	3	3	3	4	4	4	2	2	2	0	0	0
Cap, veh/h	482	866	115	440	1243	0	493	0	346	328	0	184
Arrive On Green	0.01	0.28	0.28	0.09	0.36	0.00	0.11	0.00	0.22	0.01	0.00	0.11
Sat Flow, veh/h	1757	3113	412	1740	3563	0	1774	0	1583	1810	0	1615
Grp Volume(v), veh/h	5	266	271	117	264	0	169	0	85	5	0	32
Grp Sat Flow(s),veh/h/ln	1757	1752	1772	1740	1736	0	1774	0	1583	1810	0	1615
Q Serve(g_s), s	0.1	5.7	5.7	1.9	2.3	0.0	3.4	0.0	1.9	0.1	0.0	0.8
Cycle Q Clear(g_c), s	0.1	5.7	5.7	1.9	2.3	0.0	3.4	0.0	1.9	0.1	0.0	0.8
Prop In Lane	1.00		0.23	1.00		0.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	482	488	493	440	1243	0	493	0	346	328	0	184
V/C Ratio(X)	0.01	0.55	0.55	0.27	0.21	0.00	0.34	0.00	0.25	0.02	0.00	0.17
Avail Cap(c_a), veh/h	730	1057	1069	745	2489	0	800	0	991	583	0	791
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	1.00	1.00	1.00	0.00	1.00	0.00	1.00	1.00	0.00	1.00
Uniform Delay (d), s/veh	11.3	13.5	13.5	9.4	9.8	0.0	13.0	0.0	14.2	17.0	0.0	17.6
Incr Delay (d2), s/veh	0.0	1.0	1.0	0.3	0.1	0.0	0.4	0.0	0.4	0.0	0.0	0.4
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	0.0	2.9	2.9	0.9	1.1	0.0	1.7	0.0	0.9	0.1	0.0	0.4
LnGrp Delay(d),s/veh	11.3	14.4	14.5	9.7	9.9	0.0	13.4	0.0	14.5	17.1	0.0	18.0
LnGrp LOS	B	B	B	A	A		B		B	B		B
Approach Vol, veh/h		542			381			254				37
Approach Delay, s/veh		14.4			9.8			13.8				17.9
Approach LOS		B			A			B				B
Timer	1	2	3	4	5	6	7	8				
Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	4.8	14.1	8.3	16.7	9.4	9.5	4.8	20.2				
Change Period (Y+Rc), s	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5				
Max Green Setting (Gmax), s	6.5	27.5	11.5	26.5	12.5	21.5	6.5	31.5				
Max Q Clear Time (g_c+l1), s	2.1	3.9	3.9	7.7	5.4	2.8	2.1	4.3				
Green Ext Time (p_c), s	0.0	0.6	0.1	4.5	0.2	0.6	0.0	5.0				
<b>Intersection Summary</b>												
HCM 2010 Ctrl Delay			13.0									
HCM 2010 LOS			B									



Lanes, Volumes, Timings  
 2: NW Brady Road & NW 16th Street

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Volume (vph)	102	165	101	110	211	80	159	82	29	52	138	106
Future Volume (vph)	102	165	101	110	211	80	159	82	29	52	138	106
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.963			0.973			0.985			0.952	
Flt Protected		0.986			0.986			0.971			0.991	
Satd. Flow (prot)	0	1655	0	0	1787	0	0	1747	0	0	1757	0
Flt Permitted		0.986			0.986			0.971			0.991	
Satd. Flow (perm)	0	1655	0	0	1787	0	0	1747	0	0	1757	0
Link Speed (mph)		25			25			35			35	
Link Distance (ft)		1212			959			2307			902	
Travel Time (s)		33.1			26.2			44.9			17.6	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	9%	9%	9%	2%	2%	2%	4%	4%	4%	2%	2%	2%
Adj. Flow (vph)	102	165	101	110	211	80	159	82	29	52	138	106
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	368	0	0	401	0	0	270	0	0	296	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(ft)		0			0			0			0	
Link Offset(ft)		0			0			0			0	
Crosswalk Width(ft)		16			16			16			16	
Two way Left Turn Lane												
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15		9	15		9	15		9	15		9
Sign Control		Stop			Stop			Stop			Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	70.7%
ICU Level of Service	C
Analysis Period (min)	15

Intersection	
Intersection Delay, s/veh	28.3
Intersection LOS	D

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	102	165	101	110	211	80	159	82	29	52	138	106
Future Vol, veh/h	102	165	101	110	211	80	159	82	29	52	138	106
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles, %	9	9	9	2	2	2	4	4	4	2	2	2
Mvmt Flow	102	165	101	110	211	80	159	82	29	52	138	106
Number of Lanes	0	1	0	0	1	0	0	1	0	0	1	0

Approach	EB	WB	NB	SB
Opposing Approach	WB	EB	SB	NB
Opposing Lanes	1	1	1	1
Conflicting Approach Left	SB	NB	EB	WB
Conflicting Lanes Left	1	1	1	1
Conflicting Approach Right	NB	SB	WB	EB
Conflicting Lanes Right	1	1	1	1
HCM Control Delay	30.5	34.7	22	22.5
HCM LOS	D	D	C	C

Lane	NBLn1	EBLn1	WBLn1	SBLn1
Vol Left, %	59%	28%	27%	18%
Vol Thru, %	30%	45%	53%	47%
Vol Right, %	11%	27%	20%	36%
Sign Control	Stop	Stop	Stop	Stop
Traffic Vol by Lane	270	368	401	296
LT Vol	159	102	110	52
Through Vol	82	165	211	138
RT Vol	29	101	80	106
Lane Flow Rate	270	368	401	296
Geometry Grp	1	1	1	1
Degree of Util (X)	0.594	0.761	0.811	0.623
Departure Headway (Hd)	7.916	7.443	7.281	7.579
Convergence, Y/N	Yes	Yes	Yes	Yes
Cap	454	486	497	474
Service Time	5.995	5.468	5.306	5.657
HCM Lane V/C Ratio	0.595	0.757	0.807	0.624
HCM Control Delay	22	30.5	34.7	22.5
HCM Lane LOS	C	D	D	C
HCM 95th-tile Q	3.8	6.6	7.7	4.2

Lanes, Volumes, Timings  
 3: NW Brady Road & NW McIntosh Road

03/06/2018



Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	194	26	231	71	13	420
Future Volume (vph)	194	26	231	71	13	420
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.984		0.968			
Flt Protected	0.958				0.950	
Satd. Flow (prot)	1791	0	1752	0	1770	1863
Flt Permitted	0.958				0.950	
Satd. Flow (perm)	1791	0	1752	0	1770	1863
Link Speed (mph)	35		40			35
Link Distance (ft)	1524		727			2307
Travel Time (s)	29.7		12.4			44.9
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	0%	0%	5%	5%	2%	2%
Adj. Flow (vph)	194	26	231	71	13	420
Shared Lane Traffic (%)						
Lane Group Flow (vph)	220	0	302	0	13	420
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Right	Left	Left
Median Width(ft)	12		12			12
Link Offset(ft)	0		0			0
Crosswalk Width(ft)	16		16			16
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15	9		9	15	
Sign Control	Stop		Free			Free

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	41.1%
Analysis Period (min)	15
	ICU Level of Service A

HCM 2010 TWSC  
 3: NW Brady Road & NW McIntosh Road

03/06/2018

Intersection						
Int Delay, s/veh	5.3					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	194	26	231	71	13	420
Future Vol, veh/h	194	26	231	71	13	420
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	0	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	5	5	2	2
Mvmt Flow	194	26	231	71	13	420

Major/Minor	Minor1	Major1	Major2		
Conflicting Flow All	713	267	0	0	302
Stage 1	267	-	-	-	-
Stage 2	446	-	-	-	-
Critical Hdwy	6.4	6.2	-	-	4.12
Critical Hdwy Stg 1	5.4	-	-	-	-
Critical Hdwy Stg 2	5.4	-	-	-	-
Follow-up Hdwy	3.5	3.3	-	-	2.218
Pot Cap-1 Maneuver	401	777	-	-	1259
Stage 1	782	-	-	-	-
Stage 2	649	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	397	777	-	-	1259
Mov Cap-2 Maneuver	397	-	-	-	-
Stage 1	782	-	-	-	-
Stage 2	642	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	22.5	0	0.2
HCM LOS	C		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	421	1259
HCM Lane V/C Ratio	-	-	0.523	0.01
HCM Control Delay (s)	-	-	22.5	7.9
HCM Lane LOS	-	-	C	A
HCM 95th %tile Q(veh)	-	-	2.9	0

Lanes, Volumes, Timings

4: SE Brady Road /SE Brady Road & SE Grand Ridge Drive

03/06/2018



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	9	196	629	4	9	79
Future Volume (vph)	9	196	629	4	9	79
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.999		0.879	
Flt Protected		0.998			0.995	
Satd. Flow (prot)	0	1724	1898	0	1662	0
Flt Permitted		0.998			0.995	
Satd. Flow (perm)	0	1724	1898	0	1662	0
Link Speed (mph)		40	40		25	
Link Distance (ft)		978	3072		1011	
Travel Time (s)		16.7	52.4		27.6	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	10%	10%	0%	0%	0%	0%
Adj. Flow (vph)	9	196	629	4	9	79
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	205	633	0	88	0
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Left	Left	Right	Left	Right
Median Width(ft)		0	0		12	
Link Offset(ft)		0	0		0	
Crosswalk Width(ft)		16	16		16	
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15			9	15	9
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	45.4%
Analysis Period (min)	15
	ICU Level of Service A

**Intersection**

Int Delay, s/veh 1.5

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↕	↕		↕	
Traffic Vol, veh/h	9	196	629	4	9	79
Future Vol, veh/h	9	196	629	4	9	79
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	10	10	0	0	0	0
Mvmt Flow	9	196	629	4	9	79

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	633	0	845
Stage 1	-	-	631
Stage 2	-	-	214
Critical Hdwy	4.2	-	6.4
Critical Hdwy Stg 1	-	-	5.4
Critical Hdwy Stg 2	-	-	5.4
Follow-up Hdwy	2.29	-	3.5
Pot Cap-1 Maneuver	913	-	336
Stage 1	-	-	534
Stage 2	-	-	826
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	913	-	332
Mov Cap-2 Maneuver	-	-	332
Stage 1	-	-	534
Stage 2	-	-	817

Approach	EB	WB	SB
HCM Control Delay, s	0.4	0	14.6
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	913	-	-	-	463
HCM Lane V/C Ratio	0.01	-	-	-	0.19
HCM Control Delay (s)	9	0	-	-	14.6
HCM Lane LOS	A	A	-	-	B
HCM 95th %tile Q(veh)	0	-	-	-	0.7

Lanes, Volumes, Timings  
 5: Project Access & SE 40th Street/SE 40th Street

03/06/2018



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	75	0	0	137	0	0
Future Volume (vph)	75	0	0	137	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)		0	100		0	0
Storage Lanes		0	1		1	0
Taper Length (ft)			25		25	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt						
Flt Protected						
Satd. Flow (prot)	1610	0	1792	1792	1900	0
Flt Permitted						
Satd. Flow (perm)	1610	0	1792	1792	1900	0
Link Speed (mph)	40			40	25	
Link Distance (ft)	1480			1830	2017	
Travel Time (s)	25.2			31.2	55.0	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	18%	18%	6%	6%	0%	0%
Adj. Flow (vph)	75	0	0	137	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	75	0	0	137	0	0
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Left	Left	Right
Median Width(ft)	12			12	12	
Link Offset(ft)	0			0	0	
Crosswalk Width(ft)	16			16	16	
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)		9	15		15	9
Sign Control	Free			Free	Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	10.5%
Analysis Period (min)	15
	ICU Level of Service A

**Intersection**

Int Delay, s/veh 0

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↔		↔	↑	↔	
Traffic Vol, veh/h	75	0	0	137	0	0
Future Vol, veh/h	75	0	0	137	0	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	100	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	18	18	6	6	0	0
Mvmt Flow	75	0	0	137	0	0

Major/Minor	Major1	Major2	Minor1		
Conflicting Flow All	0	0	75	0	212 75
Stage 1	-	-	-	-	75 -
Stage 2	-	-	-	-	137 -
Critical Hdwy	-	-	4.16	-	6.4 6.2
Critical Hdwy Stg 1	-	-	-	-	5.4 -
Critical Hdwy Stg 2	-	-	-	-	5.4 -
Follow-up Hdwy	-	-	2.254	-	3.5 3.3
Pot Cap-1 Maneuver	-	-	1499	-	781 992
Stage 1	-	-	-	-	953 -
Stage 2	-	-	-	-	895 -
Platoon blocked, %	-	-	-	-	-
Mov Cap-1 Maneuver	-	-	1499	-	781 992
Mov Cap-2 Maneuver	-	-	-	-	781 -
Stage 1	-	-	-	-	953 -
Stage 2	-	-	-	-	895 -

Approach	EB	WB	NB
HCM Control Delay, s	0	0	0
HCM LOS			A

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	-	-	-	1499	-
HCM Lane V/C Ratio	-	-	-	-	-
HCM Control Delay (s)	0	-	-	0	-
HCM Lane LOS	A	-	-	A	-
HCM 95th %tile Q(veh)	-	-	-	0	-



Lanes, Volumes, Timings

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	27	313	249	36	895	5	150	0	42	14	0	5
Future Volume (vph)	27	313	249	36	895	5	150	0	42	14	0	5
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Storage Length (ft)	115		0	135		0	220		0	30		0
Storage Lanes	1		0	1		0	1		0	1		0
Taper Length (ft)	25			25			25			25		
Lane Util. Factor	1.00	0.95	0.95	1.00	0.95	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.934			0.999			0.850				0.850
Flt Protected	0.950			0.950			0.950			0.950		
Satd. Flow (prot)	1787	3338	0	1787	3571	0	1805	1615	0	1805	1615	0
Flt Permitted	0.194			0.389			0.499			0.730		
Satd. Flow (perm)	365	3338	0	732	3571	0	948	1615	0	1387	1615	0
Right Turn on Red			Yes			Yes			Yes			Yes
Satd. Flow (RTOR)		249			1			548			229	
Link Speed (mph)		40			40			35			25	
Link Distance (ft)		1779			1191			1505			543	
Travel Time (s)		30.3			20.3			29.3			14.8	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	1%	1%	1%	1%	1%	1%	0%	0%	0%	0%	0%	0%
Adj. Flow (vph)	27	313	249	36	895	5	150	0	42	14	0	5
Shared Lane Traffic (%)												
Lane Group Flow (vph)	27	562	0	36	900	0	150	42	0	14	5	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(ft)		12			12			12			12	
Link Offset(ft)		0			0			0			0	
Crosswalk Width(ft)		16			16			16			16	
Two way Left Turn Lane												
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15		9	15		9	15		9	15		9
Number of Detectors	1	2		1	2		1	2		1	2	
Detector Template	Left	Thru		Left	Thru		Left	Thru		Left	Thru	
Leading Detector (ft)	20	100		20	100		20	100		20	100	
Trailing Detector (ft)	0	0		0	0		0	0		0	0	
Detector 1 Position(ft)	0	0		0	0		0	0		0	0	
Detector 1 Size(ft)	20	6		20	6		20	6		20	6	
Detector 1 Type	Cl+Ex	Cl+Ex		Cl+Ex	Cl+Ex		Cl+Ex	Cl+Ex		Cl+Ex	Cl+Ex	
Detector 1 Channel												
Detector 1 Extend (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Detector 1 Queue (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Detector 1 Delay (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Detector 2 Position(ft)		94			94			94			94	
Detector 2 Size(ft)		6			6			6			6	
Detector 2 Type		Cl+Ex			Cl+Ex			Cl+Ex			Cl+Ex	
Detector 2 Channel												
Detector 2 Extend (s)		0.0			0.0			0.0			0.0	
Turn Type	pm+pt	NA		pm+pt	NA		pm+pt	NA		pm+pt	NA	
Protected Phases	7	4		3	8		5	2		1	6	

Lanes, Volumes, Timings

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Permitted Phases	4		8				2		6			
Detector Phase	7	4	3		8	5		2	1		6	
Switch Phase												
Minimum Initial (s)	5.0	5.0	5.0		5.0	5.0		5.0	5.0		5.0	
Minimum Split (s)	9.5	22.5	9.5		22.5	9.5		22.5	9.5		22.5	
Total Split (s)	10.0	40.0	10.0		40.0	14.0		30.0	10.0		26.0	
Total Split (%)	11.1%	44.4%	11.1%		44.4%	15.6%		33.3%	11.1%		28.9%	
Maximum Green (s)	5.5	35.5	5.5		35.5	9.5		25.5	5.5		21.5	
Yellow Time (s)	3.5	3.5	3.5		3.5	3.5		3.5	3.5		3.5	
All-Red Time (s)	1.0	1.0	1.0		1.0	1.0		1.0	1.0		1.0	
Lost Time Adjust (s)	0.0	0.0	0.0		0.0	0.0		0.0	0.0		0.0	
Total Lost Time (s)	4.5	4.5	4.5		4.5	4.5		4.5	4.5		4.5	
Lead/Lag	Lead	Lag	Lead		Lag	Lead		Lag	Lead		Lag	
Lead-Lag Optimize?	Yes	Yes	Yes		Yes	Yes		Yes	Yes		Yes	
Vehicle Extension (s)	3.0	3.0	3.0		3.0	3.0		3.0	3.0		3.0	
Recall Mode	None	None	None		None	None		Min	None		Min	
Walk Time (s)	7.0		7.0		7.0		7.0		7.0		7.0	
Flash Dont Walk (s)	11.0		11.0		11.0		11.0		11.0		11.0	
Pedestrian Calls (#/hr)	0		0		0		0		0		0	
Act Effct Green (s)	22.3	20.6	22.3		20.6	16.6		14.8	10.2		6.1	
Actuated g/C Ratio	0.45	0.41	0.45		0.41	0.33		0.30	0.20		0.12	
v/c Ratio	0.08	0.37	0.08		0.61	0.32		0.05	0.04		0.01	
Control Delay	7.4	7.1	7.4		14.8	17.0		0.1	16.4		0.0	
Queue Delay	0.0	0.0	0.0		0.0	0.0		0.0	0.0		0.0	
Total Delay	7.4	7.1	7.4		14.8	17.0		0.1	16.4		0.0	
LOS	A	A	A		B	B		A	B		A	
Approach Delay	7.1		14.5		13.3		12.1					
Approach LOS	A		B		B		B					

Intersection Summary

Area Type: Other

Cycle Length: 90

Actuated Cycle Length: 49.9

Natural Cycle: 65

Control Type: Actuated-Uncoordinated

Maximum v/c Ratio: 0.61

Intersection Signal Delay: 11.9


Intersection LOS: B

Intersection Capacity Utilization 52.4%

ICU Level of Service A

Analysis Period (min) 15

Splits and Phases: 1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard



Queues

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018























Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Group Flow (vph)	27	562	36	900	150	42	14	5
v/c Ratio	0.08	0.37	0.08	0.61	0.32	0.05	0.04	0.01
Control Delay	7.4	7.1	7.4	14.8	17.0	0.1	16.4	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	7.4	7.1	7.4	14.8	17.0	0.1	16.4	0.0
Queue Length 50th (ft)	4	28	6	98	25	0	2	0
Queue Length 95th (ft)	13	72	16	196	93	0	16	0
Internal Link Dist (ft)		1699		1111		1425		463
Turn Bay Length (ft)	115		135		220		30	
Base Capacity (vph)	336	2502	455	2605	516	1152	334	890
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.08	0.22	0.08	0.35	0.29	0.04	0.04	0.01

Intersection Summary

# HCM 2010 Signalized Intersection Summary

## 1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	27	313	249	36	895	5	150	0	42	14	0	5
Future Volume (veh/h)	27	313	249	36	895	5	150	0	42	14	0	5
Number	7	4	14	3	8	18	5	2	12	1	6	16
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Adj Sat Flow, veh/h/ln	1881	1881	1900	1881	1881	1900	1900	1900	1900	1900	1900	1900
Adj Flow Rate, veh/h	27	313	249	36	895	5	150	0	42	14	0	5
Adj No. of Lanes	1	2	0	1	2	0	1	1	0	1	1	0
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Percent Heavy Veh, %	1	1	1	1	1	1	0	0	0	0	0	0
Cap, veh/h	340	787	612	461	1526	9	456	0	289	310	0	159
Arrive On Green	0.03	0.41	0.41	0.04	0.42	0.42	0.10	0.00	0.18	0.02	0.00	0.10
Sat Flow, veh/h	1792	1916	1489	1792	3644	20	1810	0	1615	1810	0	1615
Grp Volume(v), veh/h	27	291	271	36	439	461	150	0	42	14	0	5
Grp Sat Flow(s),veh/h/ln	1792	1787	1618	1792	1787	1878	1810	0	1615	1810	0	1615
Q Serve(g_s), s	0.4	5.8	6.0	0.6	9.6	9.6	3.6	0.0	1.1	0.4	0.0	0.1
Cycle Q Clear(g_c), s	0.4	5.8	6.0	0.6	9.6	9.6	3.6	0.0	1.1	0.4	0.0	0.1
Prop In Lane	1.00		0.92	1.00		0.01	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	340	734	665	461	748	786	456	0	289	310	0	159
V/C Ratio(X)	0.08	0.40	0.41	0.08	0.59	0.59	0.33	0.00	0.15	0.05	0.00	0.03
Avail Cap(c_a), veh/h	478	1247	1129	585	1247	1310	616	0	809	473	0	682
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00
Uniform Delay (d), s/veh	8.9	10.6	10.6	8.2	11.4	11.4	16.6	0.0	17.6	20.0	0.0	20.8
Incr Delay (d2), s/veh	0.1	0.3	0.4	0.1	0.7	0.7	0.4	0.0	0.2	0.1	0.0	0.1
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	0.2	2.9	2.7	0.3	4.8	5.0	1.8	0.0	0.5	0.2	0.0	0.1
LnGrp Delay(d),s/veh	9.0	10.9	11.0	8.3	12.1	12.1	17.0	0.0	17.9	20.1	0.0	20.8
LnGrp LOS	A	B	B	A	B	B	B		B	C		C
Approach Vol, veh/h		589			936			192				19
Approach Delay, s/veh		10.9			12.0			17.2				20.3
Approach LOS		B			B			B				C
Timer	1	2	3	4	5	6	7	8				
Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	5.4	13.6	6.5	25.4	9.5	9.5	6.1	25.8				
Change Period (Y+Rc), s	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5				
Max Green Setting (Gmax), s	5.5	25.5	5.5	35.5	9.5	21.5	5.5	35.5				
Max Q Clear Time (g_c+I1), s	2.4	3.1	2.6	8.0	5.6	2.1	2.4	11.6				
Green Ext Time (p_c), s	0.0	0.2	0.0	10.2	0.1	0.2	0.0	9.7				
<b>Intersection Summary</b>												
HCM 2010 Ctrl Delay			12.3									
HCM 2010 LOS			B									

Lanes, Volumes, Timings  
2: NW Brady Road & NW 16th Street

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Volume (vph)	15	115	13	124	30	109	8	246	159	112	283	13
Future Volume (vph)	15	115	13	124	30	109	8	246	159	112	283	13
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.988			0.944			0.948			0.996	
Flt Protected		0.995			0.977			0.999			0.986	
Satd. Flow (prot)	0	1868	0	0	1752	0	0	1799	0	0	1829	0
Flt Permitted		0.995			0.977			0.999			0.986	
Satd. Flow (perm)	0	1868	0	0	1752	0	0	1799	0	0	1829	0
Link Speed (mph)		25			25			35			35	
Link Distance (ft)		1212			959			2307			902	
Travel Time (s)		33.1			26.2			44.9			17.6	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	0%	0%	0%	0%	0%	0%	0%	0%	0%	2%	2%	2%
Adj. Flow (vph)	15	115	13	124	30	109	8	246	159	112	283	13
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	143	0	0	263	0	0	413	0	0	408	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(ft)		0			0			0			0	
Link Offset(ft)		0			0			0			0	
Crosswalk Width(ft)		16			16			16			16	
Two way Left Turn Lane												
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15		9	15		9	15		9	15		9
Sign Control		Stop			Stop			Stop			Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	81.1%
ICU Level of Service	D
Analysis Period (min)	15

Intersection	
Intersection Delay, s/veh	19.3
Intersection LOS	C

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	15	115	13	124	30	109	8	246	159	112	283	13
Future Vol, veh/h	15	115	13	124	30	109	8	246	159	112	283	13
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles, %	0	0	0	0	0	0	0	0	0	2	2	2
Mvmt Flow	15	115	13	124	30	109	8	246	159	112	283	13
Number of Lanes	0	1	0	0	1	0	0	1	0	0	1	0

Approach	EB	WB	NB	SB
Opposing Approach	WB	EB	SB	NB
Opposing Lanes	1	1	1	1
Conflicting Approach Left	SB	NB	EB	WB
Conflicting Lanes Left	1	1	1	1
Conflicting Approach Right	NB	SB	WB	EB
Conflicting Lanes Right	1	1	1	1
HCM Control Delay	12.9	15.6	20.6	22.6
HCM LOS	B	C	C	C

Lane	NBLn1	EBLn1	WBLn1	SBLn1
Vol Left, %	2%	10%	47%	27%
Vol Thru, %	60%	80%	11%	69%
Vol Right, %	38%	9%	41%	3%
Sign Control	Stop	Stop	Stop	Stop
Traffic Vol by Lane	413	143	263	408
LT Vol	8	15	124	112
Through Vol	246	115	30	283
RT Vol	159	13	109	13
Lane Flow Rate	413	143	263	408
Geometry Grp	1	1	1	1
Degree of Util (X)	0.678	0.281	0.48	0.701
Departure Headway (Hd)	5.91	7.062	6.575	6.184
Convergence, Y/N	Yes	Yes	Yes	Yes
Cap	607	506	544	583
Service Time	3.974	5.147	4.647	4.247
HCM Lane V/C Ratio	0.68	0.283	0.483	0.7
HCM Control Delay	20.6	12.9	15.6	22.6
HCM Lane LOS	C	B	C	C
HCM 95th-tile Q	5.2	1.1	2.6	5.6

Lanes, Volumes, Timings  
 3: NW Brady Road & NW McIntosh Road

03/06/2018



Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	80	19	477	204	17	424
Future Volume (vph)	80	19	477	204	17	424
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.974		0.960			
Flt Protected	0.961				0.950	
Satd. Flow (prot)	1778	0	1806	0	1752	1845
Flt Permitted	0.961				0.950	
Satd. Flow (perm)	1778	0	1806	0	1752	1845
Link Speed (mph)	35		40			35
Link Distance (ft)	1524		727			2307
Travel Time (s)	29.7		12.4			44.9
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	0%	0%	1%	1%	3%	3%
Adj. Flow (vph)	80	19	477	204	17	424
Shared Lane Traffic (%)						
Lane Group Flow (vph)	99	0	681	0	17	424
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Right	Left	Left
Median Width(ft)	12		12			12
Link Offset(ft)	0		0			0
Crosswalk Width(ft)	16		16			16
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15	9		9	15	
Sign Control	Stop		Free			Free

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	49.8%
Analysis Period (min)	15
	ICU Level of Service A

HCM 2010 TWSC  
 3: NW Brady Road & NW McIntosh Road

03/06/2018

Intersection						
Int Delay, s/veh	2.1					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	80	19	477	204	17	424
Future Vol, veh/h	80	19	477	204	17	424
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	0	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	1	1	3	3
Mvmt Flow	80	19	477	204	17	424

Major/Minor	Minor1	Major1	Major2		
Conflicting Flow All	1037	579	0	0	681
Stage 1	579	-	-	-	-
Stage 2	458	-	-	-	-
Critical Hdwy	6.4	6.2	-	-	4.13
Critical Hdwy Stg 1	5.4	-	-	-	-
Critical Hdwy Stg 2	5.4	-	-	-	-
Follow-up Hdwy	3.5	3.3	-	-	2.227
Pot Cap-1 Maneuver	258	519	-	-	907
Stage 1	564	-	-	-	-
Stage 2	641	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	253	519	-	-	907
Mov Cap-2 Maneuver	253	-	-	-	-
Stage 1	564	-	-	-	-
Stage 2	629	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	24.6	0	0.3
HCM LOS	C		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	281	907
HCM Lane V/C Ratio	-	-	0.352	0.019
HCM Control Delay (s)	-	-	24.6	9
HCM Lane LOS	-	-	C	A
HCM 95th %tile Q(veh)	-	-	1.5	0.1



Lanes, Volumes, Timings

4: SE Brady Road /SE Brady Road & SE Grand Ridge Drive

03/06/2018



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	53	602	447	4	9	18
Future Volume (vph)	53	602	447	4	9	18
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.999		0.910	
Flt Protected		0.996			0.984	
Satd. Flow (prot)	0	1874	1861	0	1701	0
Flt Permitted		0.996			0.984	
Satd. Flow (perm)	0	1874	1861	0	1701	0
Link Speed (mph)		40	40		25	
Link Distance (ft)		978	3072		1011	
Travel Time (s)		16.7	52.4		27.6	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	1%	1%	2%	2%	0%	0%
Adj. Flow (vph)	53	602	447	4	9	18
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	655	451	0	27	0
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Left	Left	Right	Left	Right
Median Width(ft)		0	0		12	
Link Offset(ft)		0	0		0	
Crosswalk Width(ft)		16	16		16	
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15			9	15	9
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	71.7%
Analysis Period (min)	15
	ICU Level of Service C

**Intersection**

Int Delay, s/veh 0.8

**Movement** EBL EBT WBT WBR SBL SBR

Lane Configurations		↕	↕		↕	
Traffic Vol, veh/h	53	602	447	4	9	18
Future Vol, veh/h	53	602	447	4	9	18
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	1	1	2	2	0	0
Mvmt Flow	53	602	447	4	9	18

**Major/Minor** Major1 Major2 Minor2

Conflicting Flow All	451	0	-	0	1157	449
Stage 1	-	-	-	-	449	-
Stage 2	-	-	-	-	708	-
Critical Hdwy	4.11	-	-	-	6.4	6.2
Critical Hdwy Stg 1	-	-	-	-	5.4	-
Critical Hdwy Stg 2	-	-	-	-	5.4	-
Follow-up Hdwy	2.209	-	-	-	3.5	3.3
Pot Cap-1 Maneuver	1115	-	-	-	219	614
Stage 1	-	-	-	-	647	-
Stage 2	-	-	-	-	492	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	1115	-	-	-	203	614
Mov Cap-2 Maneuver	-	-	-	-	203	-
Stage 1	-	-	-	-	647	-
Stage 2	-	-	-	-	457	-

**Approach** EB WB SB

HCM Control Delay, s	0.7	0	15.6
HCM LOS			C

**Minor Lane/Major Mvmt** EBL EBT WBT WBR SBLn1

Capacity (veh/h)	1115	-	-	-	367
HCM Lane V/C Ratio	0.048	-	-	-	0.074
HCM Control Delay (s)	8.4	0	-	-	15.6
HCM Lane LOS	A	A	-	-	C
HCM 95th %tile Q(veh)	0.1	-	-	-	0.2

Lanes, Volumes, Timings  
 5: Project Access & SE 40th Street/SE 40th Street

03/06/2018



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	172	0	0	146	0	0
Future Volume (vph)	172	0	0	146	0	0
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)		0	100		0	0
Storage Lanes		0	1		1	0
Taper Length (ft)			25		25	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt						
Flt Protected						
Satd. Flow (prot)	1900	0	1900	1900	1900	0
Flt Permitted						
Satd. Flow (perm)	1900	0	1900	1900	1900	0
Link Speed (mph)	40			40	25	
Link Distance (ft)	1480			1830	2017	
Travel Time (s)	25.2			31.2	55.0	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	0%	0%	0%	0%	0%	0%
Adj. Flow (vph)	172	0	0	146	0	0
Shared Lane Traffic (%)						
Lane Group Flow (vph)	172	0	0	146	0	0
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Left	Left	Right
Median Width(ft)	12			12	12	
Link Offset(ft)	0			0	0	
Crosswalk Width(ft)	16			16	16	
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)		9	15		15	9
Sign Control	Free			Free	Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	12.4%
Analysis Period (min)	15
	ICU Level of Service A

**Intersection**

Int Delay, s/veh 0

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↔		↔	↔	↔	↔
Traffic Vol, veh/h	172	0	0	146	0	0
Future Vol, veh/h	172	0	0	146	0	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	100	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	172	0	0	146	0	0

Major/Minor	Major1	Major2	Minor1		
Conflicting Flow All	0	0	172	0	318
Stage 1	-	-	-	-	172
Stage 2	-	-	-	-	146
Critical Hdwy	-	-	4.1	-	6.4
Critical Hdwy Stg 1	-	-	-	-	5.4
Critical Hdwy Stg 2	-	-	-	-	5.4
Follow-up Hdwy	-	-	2.2	-	3.5
Pot Cap-1 Maneuver	-	-	1417	-	679
Stage 1	-	-	-	-	863
Stage 2	-	-	-	-	886
Platoon blocked, %	-	-	-	-	-
Mov Cap-1 Maneuver	-	-	1417	-	679
Mov Cap-2 Maneuver	-	-	-	-	679
Stage 1	-	-	-	-	863
Stage 2	-	-	-	-	886

Approach	EB	WB	NB
HCM Control Delay, s	0	0	0
HCM LOS			A

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	-	-	-	1417	-
HCM Lane V/C Ratio	-	-	-	-	-
HCM Control Delay (s)	0	-	-	0	-
HCM Lane LOS	A	-	-	A	-
HCM 95th %tile Q(veh)	-	-	-	0	-

**APPENDIX F**

**2023 “WITH PROJECT” LEVEL OF SERVICE**

Lanes, Volumes, Timings

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	5	474	64	118	264	0	172	0	87	5	0	32
Future Volume (vph)	5	474	64	118	264	0	172	0	87	5	0	32
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Storage Length (ft)	115		0	135		0	220		0	30		0
Storage Lanes	1		0	1		0	1		0	1		0
Taper Length (ft)	25			25			25			25		
Lane Util. Factor	1.00	0.95	0.95	1.00	0.95	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.982						0.850				0.850
Flt Protected	0.950			0.950			0.950			0.950		
Satd. Flow (prot)	1752	3442	0	1736	3471	0	1770	1583	0	1805	1615	0
Flt Permitted	0.589			0.294			0.489			0.701		
Satd. Flow (perm)	1087	3442	0	537	3471	0	911	1583	0	1332	1615	0
Right Turn on Red			Yes			Yes			Yes			Yes
Satd. Flow (RTOR)		17						450				536
Link Speed (mph)		40			40			35				25
Link Distance (ft)		1779			1191			1505				543
Travel Time (s)		30.3			20.3			29.3				14.8
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	3%	3%	3%	4%	4%	4%	2%	2%	2%	0%	0%	0%
Adj. Flow (vph)	5	474	64	118	264	0	172	0	87	5	0	32
Shared Lane Traffic (%)												
Lane Group Flow (vph)	5	538	0	118	264	0	172	87	0	5	32	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(ft)		12			12			12				12
Link Offset(ft)		0			0			0				0
Crosswalk Width(ft)		16			16			16				16
Two way Left Turn Lane												
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15		9	15		9	15		9	15		9
Number of Detectors	1	2		1	2		1	2		1	2	
Detector Template	Left	Thru		Left	Thru		Left	Thru		Left	Thru	
Leading Detector (ft)	20	100		20	100		20	100		20	100	
Trailing Detector (ft)	0	0		0	0		0	0		0	0	
Detector 1 Position(ft)	0	0		0	0		0	0		0	0	
Detector 1 Size(ft)	20	6		20	6		20	6		20	6	
Detector 1 Type	Cl+Ex	Cl+Ex		Cl+Ex	Cl+Ex		Cl+Ex	Cl+Ex		Cl+Ex	Cl+Ex	
Detector 1 Channel												
Detector 1 Extend (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Detector 1 Queue (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Detector 1 Delay (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Detector 2 Position(ft)		94			94			94				94
Detector 2 Size(ft)		6			6			6				6
Detector 2 Type		Cl+Ex			Cl+Ex			Cl+Ex				Cl+Ex
Detector 2 Channel												
Detector 2 Extend (s)		0.0			0.0			0.0				0.0
Turn Type	pm+pt	NA		pm+pt	NA		pm+pt	NA		pm+pt	NA	
Protected Phases	7	4		3	8		5	2		1	6	

Lanes, Volumes, Timings

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018




Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Permitted Phases	4		8			2		6				
Detector Phase	7	4		3	8		5	2		1	6	
Switch Phase												
Minimum Initial (s)	5.0	5.0		5.0	5.0		5.0	5.0		5.0	5.0	
Minimum Split (s)	9.5	22.5		9.5	22.5		9.5	22.5		9.5	22.5	
Total Split (s)	11.0	31.0		16.0	36.0		17.0	32.0		11.0	26.0	
Total Split (%)	12.2%	34.4%		17.8%	40.0%		18.9%	35.6%		12.2%	28.9%	
Maximum Green (s)	6.5	26.5		11.5	31.5		12.5	27.5		6.5	21.5	
Yellow Time (s)	3.5	3.5		3.5	3.5		3.5	3.5		3.5	3.5	
All-Red Time (s)	1.0	1.0		1.0	1.0		1.0	1.0		1.0	1.0	
Lost Time Adjust (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Total Lost Time (s)	4.5	4.5		4.5	4.5		4.5	4.5		4.5	4.5	
Lead/Lag	Lead	Lag		Lead	Lag		Lead	Lag		Lead	Lag	
Lead-Lag Optimize?	Yes	Yes		Yes	Yes		Yes	Yes		Yes	Yes	
Vehicle Extension (s)	3.0	3.0		3.0	3.0		3.0	3.0		3.0	3.0	
Recall Mode	None	None		None	None		None	Min		None	Min	
Walk Time (s)		7.0			7.0			7.0			7.0	
Flash Dont Walk (s)		11.0			11.0			11.0			11.0	
Pedestrian Calls (#/hr)		0			0			0			0	
Act Effct Green (s)	18.7	14.8		23.5	22.0		18.0	15.8		10.4	6.4	
Actuated g/C Ratio	0.36	0.29		0.46	0.43		0.35	0.31		0.20	0.12	
v/c Ratio	0.01	0.54		0.27	0.18		0.34	0.11		0.02	0.05	
Control Delay	8.4	19.4		10.2	10.9		16.0	0.3		14.4	0.1	
Queue Delay	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Total Delay	8.4	19.4		10.2	10.9		16.0	0.3		14.4	0.1	
LOS	A	B		B	B		B	A		B	A	
Approach Delay		19.3			10.6			10.7			2.1	
Approach LOS		B			B			B			A	

Intersection Summary

Area Type:	Other
Cycle Length:	90
Actuated Cycle Length:	51.5
Natural Cycle:	65
Control Type:	Actuated-Uncoordinated
Maximum v/c Ratio:	0.54
Intersection Signal Delay:	14.2
Intersection LOS:	B
Intersection Capacity Utilization:	49.1%
ICU Level of Service:	A
Analysis Period (min):	15

Splits and Phases: 1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard



Queues

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Group Flow (vph)	5	538	118	264	172	87	5	32
v/c Ratio	0.01	0.54	0.27	0.18	0.34	0.11	0.02	0.05
Control Delay	8.4	19.4	10.2	10.9	16.0	0.3	14.4	0.1
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	8.4	19.4	10.2	10.9	16.0	0.3	14.4	0.1
Queue Length 50th (ft)	1	81	21	25	39	0	1	0
Queue Length 95th (ft)	5	132	46	62	93	0	8	0
Internal Link Dist (ft)		1699		1111		1425		463
Turn Bay Length (ft)	115		135		220		30	
Base Capacity (vph)	505	1951	569	2198	604	1105	363	1056
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.01	0.28	0.21	0.12	0.28	0.08	0.01	0.03





















Intersection Summary



# HCM 2010 Signalized Intersection Summary

## 1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	5	474	64	118	264	0	172	0	87	5	0	32
Future Volume (veh/h)	5	474	64	118	264	0	172	0	87	5	0	32
Number	7	4	14	3	8	18	5	2	12	1	6	16
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Adj Sat Flow, veh/h/ln	1845	1845	1900	1827	1827	1900	1863	1863	1900	1900	1900	1900
Adj Flow Rate, veh/h	5	474	64	118	264	0	172	0	87	5	0	32
Adj No. of Lanes	1	2	0	1	2	0	1	1	0	1	1	0
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Percent Heavy Veh, %	3	3	3	4	4	4	2	2	2	0	0	0
Cap, veh/h	481	864	116	439	1243	0	495	0	348	326	0	183
Arrive On Green	0.01	0.28	0.28	0.09	0.36	0.00	0.11	0.00	0.22	0.01	0.00	0.11
Sat Flow, veh/h	1757	3106	417	1740	3563	0	1774	0	1583	1810	0	1615
Grp Volume(v), veh/h	5	267	271	118	264	0	172	0	87	5	0	32
Grp Sat Flow(s),veh/h/ln	1757	1752	1771	1740	1736	0	1774	0	1583	1810	0	1615
Q Serve(g_s), s	0.1	5.7	5.8	2.0	2.3	0.0	3.4	0.0	2.0	0.1	0.0	0.8
Cycle Q Clear(g_c), s	0.1	5.7	5.8	2.0	2.3	0.0	3.4	0.0	2.0	0.1	0.0	0.8
Prop In Lane	1.00		0.24	1.00		0.00	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	481	488	493	439	1243	0	495	0	348	326	0	183
V/C Ratio(X)	0.01	0.55	0.55	0.27	0.21	0.00	0.35	0.00	0.25	0.02	0.00	0.17
Avail Cap(c_a), veh/h	728	1053	1065	742	2480	0	797	0	988	581	0	788
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	1.00	1.00	1.00	0.00	1.00	0.00	1.00	1.00	0.00	1.00
Uniform Delay (d), s/veh	11.3	13.5	13.6	9.5	9.8	0.0	13.0	0.0	14.2	17.1	0.0	17.7
Incr Delay (d2), s/veh	0.0	1.0	1.0	0.3	0.1	0.0	0.4	0.0	0.4	0.0	0.0	0.4
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	0.0	2.9	2.9	1.0	1.1	0.0	1.7	0.0	0.9	0.1	0.0	0.4
LnGrp Delay(d),s/veh	11.3	14.5	14.5	9.8	9.9	0.0	13.5	0.0	14.6	17.1	0.0	18.1
LnGrp LOS	B	B	B	A	A		B		B	B		B
Approach Vol, veh/h		543			382			259				37
Approach Delay, s/veh		14.5			9.9			13.8				18.0
Approach LOS		B			A			B				B
Timer	1	2	3	4	5	6	7	8				
Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	4.8	14.2	8.3	16.8	9.5	9.5	4.8	20.3				
Change Period (Y+Rc), s	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5				
Max Green Setting (Gmax), s	6.5	27.5	11.5	26.5	12.5	21.5	6.5	31.5				
Max Q Clear Time (g_c+l1), s	2.1	4.0	4.0	7.8	5.4	2.8	2.1	4.3				
Green Ext Time (p_c), s	0.0	0.6	0.1	4.5	0.2	0.6	0.0	5.0				
<b>Intersection Summary</b>												
HCM 2010 Ctrl Delay			13.0									
HCM 2010 LOS			B									

Lanes, Volumes, Timings  
2: NW Brady Road & NW 16th Street

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Volume (vph)	102	166	101	110	211	80	159	82	29	52	138	106
Future Volume (vph)	102	166	101	110	211	80	159	82	29	52	138	106
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.963			0.973			0.985			0.952	
Flt Protected		0.986			0.986			0.971			0.991	
Satd. Flow (prot)	0	1655	0	0	1787	0	0	1747	0	0	1757	0
Flt Permitted		0.986			0.986			0.971			0.991	
Satd. Flow (perm)	0	1655	0	0	1787	0	0	1747	0	0	1757	0
Link Speed (mph)		25			25			35			35	
Link Distance (ft)		1212			959			2307			902	
Travel Time (s)		33.1			26.2			44.9			17.6	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	9%	9%	9%	2%	2%	2%	4%	4%	4%	2%	2%	2%
Adj. Flow (vph)	102	166	101	110	211	80	159	82	29	52	138	106
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	369	0	0	401	0	0	270	0	0	296	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(ft)		0			0			0			0	
Link Offset(ft)		0			0			0			0	
Crosswalk Width(ft)		16			16			16			16	
Two way Left Turn Lane												
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15		9	15		9	15		9	15		9
Sign Control		Stop			Stop			Stop			Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	70.7%
Analysis Period (min)	15
	ICU Level of Service C

Intersection	
Intersection Delay, s/veh	28.4
Intersection LOS	D

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	102	166	101	110	211	80	159	82	29	52	138	106
Future Vol, veh/h	102	166	101	110	211	80	159	82	29	52	138	106
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles, %	9	9	9	2	2	2	4	4	4	2	2	2
Mvmt Flow	102	166	101	110	211	80	159	82	29	52	138	106
Number of Lanes	0	1	0	0	1	0	0	1	0	0	1	0

Approach	EB	WB	NB	SB
Opposing Approach	WB	EB	SB	NB
Opposing Lanes	1	1	1	1
Conflicting Approach Left	SB	NB	EB	WB
Conflicting Lanes Left	1	1	1	1
Conflicting Approach Right	NB	SB	WB	EB
Conflicting Lanes Right	1	1	1	1
HCM Control Delay	30.7	34.8	22	22.5
HCM LOS	D	D	C	C

Lane	NBLn1	EBLn1	WBLn1	SBLn1
Vol Left, %	59%	28%	27%	18%
Vol Thru, %	30%	45%	53%	47%
Vol Right, %	11%	27%	20%	36%
Sign Control	Stop	Stop	Stop	Stop
Traffic Vol by Lane	270	369	401	296
LT Vol	159	102	110	52
Through Vol	82	166	211	138
RT Vol	29	101	80	106
Lane Flow Rate	270	369	401	296
Geometry Grp	1	1	1	1
Degree of Util (X)	0.594	0.763	0.812	0.624
Departure Headway (Hd)	7.922	7.447	7.287	7.585
Convergence, Y/N	Yes	Yes	Yes	Yes
Cap	454	487	497	474
Service Time	6.003	5.473	5.311	5.664
HCM Lane V/C Ratio	0.595	0.758	0.807	0.624
HCM Control Delay	22	30.7	34.8	22.5
HCM Lane LOS	C	D	D	C
HCM 95th-tile Q	3.8	6.6	7.8	4.2

Lanes, Volumes, Timings  
 3: NW Brady Road & NW McIntosh Road

03/06/2018



Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	194	26	231	72	13	420
Future Volume (vph)	194	26	231	72	13	420
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.984		0.968			
Flt Protected	0.958				0.950	
Satd. Flow (prot)	1791	0	1752	0	1770	1863
Flt Permitted	0.958				0.950	
Satd. Flow (perm)	1791	0	1752	0	1770	1863
Link Speed (mph)	35		40			35
Link Distance (ft)	1524		727			2307
Travel Time (s)	29.7		12.4			44.9
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	0%	0%	5%	5%	2%	2%
Adj. Flow (vph)	194	26	231	72	13	420
Shared Lane Traffic (%)						
Lane Group Flow (vph)	220	0	303	0	13	420
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Right	Left	Left
Median Width(ft)	12		12			12
Link Offset(ft)	0		0			0
Crosswalk Width(ft)	16		16			16
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15	9		9	15	
Sign Control	Stop		Free			Free

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	41.1%
Analysis Period (min)	15
	ICU Level of Service A

**Intersection**

Int Delay, s/veh 5.3

Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	194	26	231	72	13	420
Future Vol, veh/h	194	26	231	72	13	420
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	0	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	5	5	2	2
Mvmt Flow	194	26	231	72	13	420

Major/Minor	Minor1	Major1	Major2		
Conflicting Flow All	713	267	0	0	303
Stage 1	267	-	-	-	-
Stage 2	446	-	-	-	-
Critical Hdwy	6.4	6.2	-	-	4.12
Critical Hdwy Stg 1	5.4	-	-	-	-
Critical Hdwy Stg 2	5.4	-	-	-	-
Follow-up Hdwy	3.5	3.3	-	-	2.218
Pot Cap-1 Maneuver	401	777	-	-	1258
Stage 1	782	-	-	-	-
Stage 2	649	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	397	777	-	-	1258
Mov Cap-2 Maneuver	397	-	-	-	-
Stage 1	782	-	-	-	-
Stage 2	642	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	22.5	0	0.2
HCM LOS	C		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	421	1258
HCM Lane V/C Ratio	-	-	0.523	0.01
HCM Control Delay (s)	-	-	22.5	7.9
HCM Lane LOS	-	-	C	A
HCM 95th %tile Q(veh)	-	-	2.9	0

Lanes, Volumes, Timings

4: SE Brady Road /SE Brady Road & SE Grand Ridge Drive

03/06/2018



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	13	196	629	4	10	90
Future Volume (vph)	13	196	629	4	10	90
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.999		0.878	
Flt Protected		0.997			0.995	
Satd. Flow (prot)	0	1722	1898	0	1660	0
Flt Permitted		0.997			0.995	
Satd. Flow (perm)	0	1722	1898	0	1660	0
Link Speed (mph)		40	40		25	
Link Distance (ft)		978	3072		1011	
Travel Time (s)		16.7	52.4		27.6	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	10%	10%	0%	0%	0%	0%
Adj. Flow (vph)	13	196	629	4	10	90
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	209	633	0	100	0
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Left	Left	Right	Left	Right
Median Width(ft)		0	0		12	
Link Offset(ft)		0	0		0	
Crosswalk Width(ft)		16	16		16	
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15			9	15	9
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	46.1%
Analysis Period (min)	15
	ICU Level of Service A

**Intersection**

Int Delay, s/veh 1.7

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↶	↷		↶	
Traffic Vol, veh/h	13	196	629	4	10	90
Future Vol, veh/h	13	196	629	4	10	90
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	10	10	0	0	0	0
Mvmt Flow	13	196	629	4	10	90

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	633	0	853
Stage 1	-	-	631
Stage 2	-	-	222
Critical Hdwy	4.2	-	6.4
Critical Hdwy Stg 1	-	-	5.4
Critical Hdwy Stg 2	-	-	5.4
Follow-up Hdwy	2.29	-	3.5
Pot Cap-1 Maneuver	913	-	332
Stage 1	-	-	534
Stage 2	-	-	820
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	913	-	327
Mov Cap-2 Maneuver	-	-	327
Stage 1	-	-	534
Stage 2	-	-	807

Approach	EB	WB	SB
HCM Control Delay, s	0.6	0	14.9
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	913	-	-	-	463
HCM Lane V/C Ratio	0.014	-	-	-	0.216
HCM Control Delay (s)	9	0	-	-	14.9
HCM Lane LOS	A	A	-	-	B
HCM 95th %tile Q(veh)	0	-	-	-	0.8

Lanes, Volumes, Timings  
 5: Project Access & SE 40th Street/SE 40th Street

03/06/2018



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Volume (vph)	75	2	1	137	5	2
Future Volume (vph)	75	2	1	137	5	2
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)		0	100		0	0
Storage Lanes		0	1		1	0
Taper Length (ft)			25		25	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.996				0.961	
Flt Protected			0.950		0.966	
Satd. Flow (prot)	1604	0	1703	1792	1764	0
Flt Permitted			0.950		0.966	
Satd. Flow (perm)	1604	0	1703	1792	1764	0
Link Speed (mph)	40			40	25	
Link Distance (ft)	1480			1830	2017	
Travel Time (s)	25.2			31.2	55.0	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	18%	18%	6%	6%	0%	0%
Adj. Flow (vph)	75	2	1	137	5	2
Shared Lane Traffic (%)						
Lane Group Flow (vph)	77	0	1	137	7	0
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Left	Left	Right
Median Width(ft)	12			12	12	
Link Offset(ft)	0			0	0	
Crosswalk Width(ft)	16			16	16	
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)		9	15		15	9
Sign Control	Free			Free	Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	17.2%
Analysis Period (min)	15
	ICU Level of Service A



**Intersection**

Int Delay, s/veh 0.4

**Movement** EBT EBR WBL WBT NBL NBR

Lane Configurations						
Traffic Vol, veh/h	75	2	1	137	5	2
Future Vol, veh/h	75	2	1	137	5	2
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	100	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	18	18	6	6	0	0
Mvmt Flow	75	2	1	137	5	2

**Major/Minor** Major1 Major2 Minor1

Conflicting Flow All	0	0	77	0	215	76
Stage 1	-	-	-	-	76	-
Stage 2	-	-	-	-	139	-
Critical Hdwy	-	-	4.16	-	6.4	6.2
Critical Hdwy Stg 1	-	-	-	-	5.4	-
Critical Hdwy Stg 2	-	-	-	-	5.4	-
Follow-up Hdwy	-	-	2.254	-	3.5	3.3
Pot Cap-1 Maneuver	-	-	1497	-	778	991
Stage 1	-	-	-	-	952	-
Stage 2	-	-	-	-	893	-
Platoon blocked, %	-	-	-	-	-	-
Mov Cap-1 Maneuver	-	-	1497	-	777	991
Mov Cap-2 Maneuver	-	-	-	-	777	-
Stage 1	-	-	-	-	952	-
Stage 2	-	-	-	-	892	-

**Approach** EB WB NB

HCM Control Delay, s	0	0.1	9.4
HCM LOS			A

**Minor Lane/Major Mvmt** NBLn1 EBT EBR WBL WBT

Capacity (veh/h)	828	-	-	1497	-
HCM Lane V/C Ratio	0.008	-	-	0.001	-
HCM Control Delay (s)	9.4	-	-	7.4	-
HCM Lane LOS	A	-	-	A	-
HCM 95th %tile Q(veh)	0	-	-	0	-

Lanes, Volumes, Timings

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	27	313	253	38	895	5	152	0	43	14	0	5
Future Volume (vph)	27	313	253	38	895	5	152	0	43	14	0	5
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Storage Length (ft)	115		0	135		0	220		0	30		0
Storage Lanes	1		0	1		0	1		0	1		0
Taper Length (ft)	25			25			25			25		
Lane Util. Factor	1.00	0.95	0.95	1.00	0.95	0.95	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.933			0.999			0.850			0.850	
Flt Protected	0.950			0.950			0.950			0.950		
Satd. Flow (prot)	1787	3335	0	1787	3571	0	1805	1615	0	1805	1615	0
Flt Permitted	0.194			0.386			0.499			0.729		
Satd. Flow (perm)	365	3335	0	726	3571	0	948	1615	0	1385	1615	0
Right Turn on Red			Yes			Yes			Yes			Yes
Satd. Flow (RTOR)		253			1			548			229	
Link Speed (mph)		40			40			35			25	
Link Distance (ft)		1779			1191			1505			543	
Travel Time (s)		30.3			20.3			29.3			14.8	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	1%	1%	1%	1%	1%	1%	0%	0%	0%	0%	0%	0%
Adj. Flow (vph)	27	313	253	38	895	5	152	0	43	14	0	5
Shared Lane Traffic (%)												
Lane Group Flow (vph)	27	566	0	38	900	0	152	43	0	14	5	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(ft)		12			12			12			12	
Link Offset(ft)		0			0			0			0	
Crosswalk Width(ft)		16			16			16			16	
Two way Left Turn Lane												
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15		9	15		9	15		9	15		9
Number of Detectors	1	2		1	2		1	2		1	2	
Detector Template	Left	Thru		Left	Thru		Left	Thru		Left	Thru	
Leading Detector (ft)	20	100		20	100		20	100		20	100	
Trailing Detector (ft)	0	0		0	0		0	0		0	0	
Detector 1 Position(ft)	0	0		0	0		0	0		0	0	
Detector 1 Size(ft)	20	6		20	6		20	6		20	6	
Detector 1 Type	Cl+Ex	Cl+Ex		Cl+Ex	Cl+Ex		Cl+Ex	Cl+Ex		Cl+Ex	Cl+Ex	
Detector 1 Channel												
Detector 1 Extend (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Detector 1 Queue (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Detector 1 Delay (s)	0.0	0.0		0.0	0.0		0.0	0.0		0.0	0.0	
Detector 2 Position(ft)		94			94			94			94	
Detector 2 Size(ft)		6			6			6			6	
Detector 2 Type		Cl+Ex			Cl+Ex			Cl+Ex			Cl+Ex	
Detector 2 Channel												
Detector 2 Extend (s)		0.0			0.0			0.0			0.0	
Turn Type	pm+pt	NA		pm+pt	NA		pm+pt	NA		pm+pt	NA	
Protected Phases	7	4		3	8		5	2		1	6	

Lanes, Volumes, Timings

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018




Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Permitted Phases	4		8				2		6			
Detector Phase	7	4	3		8	5		2	1		6	
Switch Phase												
Minimum Initial (s)	5.0	5.0	5.0		5.0	5.0		5.0	5.0		5.0	
Minimum Split (s)	9.5	22.5	9.5		22.5	9.5		22.5	9.5		22.5	
Total Split (s)	10.0	40.0	10.0		40.0	14.0		30.0	10.0		26.0	
Total Split (%)	11.1%	44.4%	11.1%		44.4%	15.6%		33.3%	11.1%		28.9%	
Maximum Green (s)	5.5	35.5	5.5		35.5	9.5		25.5	5.5		21.5	
Yellow Time (s)	3.5	3.5	3.5		3.5	3.5		3.5	3.5		3.5	
All-Red Time (s)	1.0	1.0	1.0		1.0	1.0		1.0	1.0		1.0	
Lost Time Adjust (s)	0.0	0.0	0.0		0.0	0.0		0.0	0.0		0.0	
Total Lost Time (s)	4.5	4.5	4.5		4.5	4.5		4.5	4.5		4.5	
Lead/Lag	Lead	Lag	Lead		Lag	Lead		Lag	Lead		Lag	
Lead-Lag Optimize?	Yes	Yes	Yes		Yes	Yes		Yes	Yes		Yes	
Vehicle Extension (s)	3.0	3.0	3.0		3.0	3.0		3.0	3.0		3.0	
Recall Mode	None	None	None		None	None		Min	None		Min	
Walk Time (s)	7.0		7.0		7.0		7.0		7.0		7.0	
Flash Dont Walk (s)	11.0		11.0		11.0		11.0		11.0		11.0	
Pedestrian Calls (#/hr)	0		0		0		0		0		0	
Act Effct Green (s)	22.3	20.6	22.3		20.6	16.6		14.8	10.2		6.1	
Actuated g/C Ratio	0.45	0.41	0.45		0.41	0.33		0.30	0.20		0.12	
v/c Ratio	0.08	0.37	0.08		0.61	0.32		0.05	0.04		0.01	
Control Delay	7.4	7.1	7.5		14.8	17.1		0.1	16.4		0.0	
Queue Delay	0.0	0.0	0.0		0.0	0.0		0.0	0.0		0.0	
Total Delay	7.4	7.1	7.5		14.8	17.1		0.1	16.4		0.0	
LOS	A	A	A		B	B		A	B		A	
Approach Delay	7.1		14.5		13.3		12.1					
Approach LOS	A		B		B		B					

Intersection Summary

Area Type: Other  
 Cycle Length: 90  
 Actuated Cycle Length: 49.9  
 Natural Cycle: 65  
 Control Type: Actuated-Uncoordinated  
 Maximum v/c Ratio: 0.61  
 Intersection Signal Delay: 11.8  
 Intersection LOS: B  
 Intersection Capacity Utilization 54.2%  
 ICU Level of Service A  
 Analysis Period (min) 15

Splits and Phases: 1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard



Queues

1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018























Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Group Flow (vph)	27	566	38	900	152	43	14	5
v/c Ratio	0.08	0.37	0.08	0.61	0.32	0.05	0.04	0.01
Control Delay	7.4	7.1	7.5	14.8	17.1	0.1	16.4	0.0
Queue Delay	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Delay	7.4	7.1	7.5	14.8	17.1	0.1	16.4	0.0
Queue Length 50th (ft)	4	28	6	98	25	0	2	0
Queue Length 95th (ft)	13	72	17	196	94	0	16	0
Internal Link Dist (ft)		1699		1111		1425		463
Turn Bay Length (ft)	115		135		220		30	
Base Capacity (vph)	336	2501	453	2605	516	1152	334	890
Starvation Cap Reductn	0	0	0	0	0	0	0	0
Spillback Cap Reductn	0	0	0	0	0	0	0	0
Storage Cap Reductn	0	0	0	0	0	0	0	0
Reduced v/c Ratio	0.08	0.23	0.08	0.35	0.29	0.04	0.04	0.01

Intersection Summary

# HCM 2010 Signalized Intersection Summary

## 1: SE Payne Road/NW Lorenz Street & NW Pacific Rim Boulevard

03/06/2018

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	27	313	253	38	895	5	152	0	43	14	0	5
Future Volume (veh/h)	27	313	253	38	895	5	152	0	43	14	0	5
Number	7	4	14	3	8	18	5	2	12	1	6	16
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Adj Sat Flow, veh/h/ln	1881	1881	1900	1881	1881	1900	1900	1900	1900	1900	1900	1900
Adj Flow Rate, veh/h	27	313	253	38	895	5	152	0	43	14	0	5
Adj No. of Lanes	1	2	0	1	2	0	1	1	0	1	1	0
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Percent Heavy Veh, %	1	1	1	1	1	1	0	0	0	0	0	0
Cap, veh/h	340	778	614	460	1526	9	457	0	290	309	0	158
Arrive On Green	0.03	0.41	0.41	0.04	0.42	0.42	0.10	0.00	0.18	0.02	0.00	0.10
Sat Flow, veh/h	1792	1902	1502	1792	3644	20	1810	0	1615	1810	0	1615
Grp Volume(v), veh/h	27	294	272	38	439	461	152	0	43	14	0	5
Grp Sat Flow(s),veh/h/ln	1792	1787	1616	1792	1787	1878	1810	0	1615	1810	0	1615
Q Serve(g_s), s	0.4	5.9	6.1	0.6	9.7	9.7	3.6	0.0	1.1	0.4	0.0	0.1
Cycle Q Clear(g_c), s	0.4	5.9	6.1	0.6	9.7	9.7	3.6	0.0	1.1	0.4	0.0	0.1
Prop In Lane	1.00		0.93	1.00		0.01	1.00		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	340	731	661	460	748	786	457	0	290	309	0	158
V/C Ratio(X)	0.08	0.40	0.41	0.08	0.59	0.59	0.33	0.00	0.15	0.05	0.00	0.03
Avail Cap(c_a), veh/h	477	1243	1125	580	1243	1306	615	0	807	472	0	681
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00
Uniform Delay (d), s/veh	9.0	10.7	10.7	8.3	11.4	11.4	16.6	0.0	17.6	20.1	0.0	20.8
Incr Delay (d2), s/veh	0.1	0.4	0.4	0.1	0.7	0.7	0.4	0.0	0.2	0.1	0.0	0.1
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	0.2	2.9	2.8	0.3	4.9	5.1	1.8	0.0	0.5	0.2	0.0	0.1
LnGrp Delay(d),s/veh	9.1	11.0	11.1	8.3	12.2	12.1	17.0	0.0	17.9	20.2	0.0	20.9
LnGrp LOS	A	B	B	A	B	B	B		B	C		C
Approach Vol, veh/h		593			938			195				19
Approach Delay, s/veh		11.0			12.0			17.2				20.4
Approach LOS		B			B			B				C
Timer	1	2	3	4	5	6	7	8				
Assigned Phs	1	2	3	4	5	6	7	8				
Phs Duration (G+Y+Rc), s	5.4	13.7	6.6	25.4	9.6	9.5	6.1	25.9				
Change Period (Y+Rc), s	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5				
Max Green Setting (Gmax), s	5.5	25.5	5.5	35.5	9.5	21.5	5.5	35.5				
Max Q Clear Time (g_c+l1), s	2.4	3.1	2.6	8.1	5.6	2.1	2.4	11.7				
Green Ext Time (p_c), s	0.0	0.2	0.0	10.3	0.1	0.2	0.0	9.7				
<b>Intersection Summary</b>												
HCM 2010 Ctrl Delay			12.3									
HCM 2010 LOS			B									

Lanes, Volumes, Timings  
 2: NW Brady Road & NW 16th Street

03/06/2018



Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Volume (vph)	15	116	13	124	31	109	8	246	159	112	283	13
Future Volume (vph)	15	116	13	124	31	109	8	246	159	112	283	13
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Frt		0.988			0.944			0.948			0.996	
Flt Protected		0.995			0.977			0.999			0.986	
Satd. Flow (prot)	0	1868	0	0	1752	0	0	1799	0	0	1829	0
Flt Permitted		0.995			0.977			0.999			0.986	
Satd. Flow (perm)	0	1868	0	0	1752	0	0	1799	0	0	1829	0
Link Speed (mph)		25			25			35			35	
Link Distance (ft)		1212			959			2307			902	
Travel Time (s)		33.1			26.2			44.9			17.6	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	0%	0%	0%	0%	0%	0%	0%	0%	0%	2%	2%	2%
Adj. Flow (vph)	15	116	13	124	31	109	8	246	159	112	283	13
Shared Lane Traffic (%)												
Lane Group Flow (vph)	0	144	0	0	264	0	0	413	0	0	408	0
Enter Blocked Intersection	No	No	No	No	No	No	No	No	No	No	No	No
Lane Alignment	Left	Left	Right	Left	Left	Right	Left	Left	Right	Left	Left	Right
Median Width(ft)		0			0			0			0	
Link Offset(ft)		0			0			0			0	
Crosswalk Width(ft)		16			16			16			16	
Two way Left Turn Lane												
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15		9	15		9	15		9	15		9
Sign Control		Stop			Stop			Stop			Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	81.2%
ICU Level of Service	D
Analysis Period (min)	15

**Intersection**

Intersection Delay, s/veh	19.4
Intersection LOS	C

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	15	116	13	124	31	109	8	246	159	112	283	13
Future Vol, veh/h	15	116	13	124	31	109	8	246	159	112	283	13
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles, %	0	0	0	0	0	0	0	0	0	2	2	2
Mvmt Flow	15	116	13	124	31	109	8	246	159	112	283	13
Number of Lanes	0	1	0	0	1	0	0	1	0	0	1	0

Approach	EB	WB	NB	SB
Opposing Approach	WB	EB	SB	NB
Opposing Lanes	1	1	1	1
Conflicting Approach Left	SB	NB	EB	WB
Conflicting Lanes Left	1	1	1	1
Conflicting Approach Right	NB	SB	WB	EB
Conflicting Lanes Right	1	1	1	1
HCM Control Delay	13	15.7	20.7	22.7
HCM LOS	B	C	C	C

Lane	NBLn1	EBLn1	WBLn1	SBLn1
Vol Left, %	2%	10%	47%	27%
Vol Thru, %	60%	81%	12%	69%
Vol Right, %	38%	9%	41%	3%
Sign Control	Stop	Stop	Stop	Stop
Traffic Vol by Lane	413	144	264	408
LT Vol	8	15	124	112
Through Vol	246	116	31	283
RT Vol	159	13	109	13
Lane Flow Rate	413	144	264	408
Geometry Grp	1	1	1	1
Degree of Util (X)	0.679	0.283	0.483	0.702
Departure Headway (Hd)	5.921	7.07	6.583	6.194
Convergence, Y/N	Yes	Yes	Yes	Yes
Cap	607	505	544	579
Service Time	3.986	5.157	4.655	4.26
HCM Lane V/C Ratio	0.68	0.285	0.485	0.705
HCM Control Delay	20.7	13	15.7	22.7
HCM Lane LOS	C	B	C	C
HCM 95th-tile Q	5.2	1.2	2.6	5.6

Lanes, Volumes, Timings  
 3: NW Brady Road & NW McIntosh Road

03/06/2018



Lane Group	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Volume (vph)	81	19	477	204	17	424
Future Volume (vph)	81	19	477	204	17	424
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.974		0.960			
Flt Protected	0.961				0.950	
Satd. Flow (prot)	1778	0	1806	0	1752	1845
Flt Permitted	0.961				0.950	
Satd. Flow (perm)	1778	0	1806	0	1752	1845
Link Speed (mph)	35		40			35
Link Distance (ft)	1524		727			2307
Travel Time (s)	29.7		12.4			44.9
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	0%	0%	1%	1%	3%	3%
Adj. Flow (vph)	81	19	477	204	17	424
Shared Lane Traffic (%)						
Lane Group Flow (vph)	100	0	681	0	17	424
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Right	Left	Left
Median Width(ft)	12		12			12
Link Offset(ft)	0		0			0
Crosswalk Width(ft)	16		16			16
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15	9		9	15	
Sign Control	Stop		Free			Free

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	49.8%
Analysis Period (min)	15
	ICU Level of Service A



HCM 2010 TWSC  
 3: NW Brady Road & NW McIntosh Road

03/06/2018

Intersection						
Int Delay, s/veh	2.1					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	81	19	477	204	17	424
Future Vol, veh/h	81	19	477	204	17	424
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	0	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	1	1	3	3
Mvmt Flow	81	19	477	204	17	424

Major/Minor	Minor1	Major1	Major2		
Conflicting Flow All	1037	579	0	0	681
Stage 1	579	-	-	-	-
Stage 2	458	-	-	-	-
Critical Hdwy	6.4	6.2	-	-	4.13
Critical Hdwy Stg 1	5.4	-	-	-	-
Critical Hdwy Stg 2	5.4	-	-	-	-
Follow-up Hdwy	3.5	3.3	-	-	2.227
Pot Cap-1 Maneuver	258	519	-	-	907
Stage 1	564	-	-	-	-
Stage 2	641	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	253	519	-	-	907
Mov Cap-2 Maneuver	253	-	-	-	-
Stage 1	564	-	-	-	-
Stage 2	629	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	24.8	0	0.3
HCM LOS	C		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	280	907
HCM Lane V/C Ratio	-	-	0.357	0.019
HCM Control Delay (s)	-	-	24.8	9
HCM Lane LOS	-	-	C	A
HCM 95th %tile Q(veh)	-	-	1.6	0.1

Lanes, Volumes, Timings

4: SE Brady Road /SE Brady Road & SE Grand Ridge Drive

03/06/2018



Lane Group	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Volume (vph)	66	602	447	5	9	26
Future Volume (vph)	66	602	447	5	9	26
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt			0.999		0.900	
Flt Protected		0.995			0.987	
Satd. Flow (prot)	0	1872	1861	0	1688	0
Flt Permitted		0.995			0.987	
Satd. Flow (perm)	0	1872	1861	0	1688	0
Link Speed (mph)		40	40		25	
Link Distance (ft)		978	3072		1011	
Travel Time (s)		16.7	52.4		27.6	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	1%	1%	2%	2%	0%	0%
Adj. Flow (vph)	66	602	447	5	9	26
Shared Lane Traffic (%)						
Lane Group Flow (vph)	0	668	452	0	35	0
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Left	Left	Right	Left	Right
Median Width(ft)		0	0		12	
Link Offset(ft)		0	0		0	
Crosswalk Width(ft)		16	16		16	
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)	15			9	15	9
Sign Control		Free	Free		Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	72.5%
Analysis Period (min)	15
	ICU Level of Service C

**Intersection**

Int Delay, s/veh 0.9

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↕	↕		↕	
Traffic Vol, veh/h	66	602	447	5	9	26
Future Vol, veh/h	66	602	447	5	9	26
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	1	1	2	2	0	0
Mvmt Flow	66	602	447	5	9	26

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	452	0	0 1184 450
Stage 1	-	-	- 450 -
Stage 2	-	-	- 734 -
Critical Hdwy	4.11	-	- 6.4 6.2
Critical Hdwy Stg 1	-	-	- 5.4 -
Critical Hdwy Stg 2	-	-	- 5.4 -
Follow-up Hdwy	2.209	-	- 3.5 3.3
Pot Cap-1 Maneuver	1114	-	- 211 613
Stage 1	-	-	- 647 -
Stage 2	-	-	- 478 -
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1114	-	- 192 613
Mov Cap-2 Maneuver	-	-	- 192 -
Stage 1	-	-	- 647 -
Stage 2	-	-	- 435 -

Approach	EB	WB	SB
HCM Control Delay, s	0.8	0	15.1
HCM LOS			C

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	1114	-	-	-	392
HCM Lane V/C Ratio	0.059	-	-	-	0.089
HCM Control Delay (s)	8.4	0	-	-	15.1
HCM Lane LOS	A	A	-	-	C
HCM 95th %tile Q(veh)	0.2	-	-	-	0.3

Lanes, Volumes, Timings  
 5: Project Access & SE 40th Street/SE 40th Street

03/06/2018



Lane Group	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	→		↵	↑	↵	
Traffic Volume (vph)	172	6	2	146	3	2
Future Volume (vph)	172	6	2	146	3	2
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900
Storage Length (ft)		0	100		0	0
Storage Lanes		0	1		1	0
Taper Length (ft)			25		25	
Lane Util. Factor	1.00	1.00	1.00	1.00	1.00	1.00
Frt	0.995				0.946	
Flt Protected			0.950		0.971	
Satd. Flow (prot)	1890	0	1805	1900	1745	0
Flt Permitted			0.950		0.971	
Satd. Flow (perm)	1890	0	1805	1900	1745	0
Link Speed (mph)	40			40	25	
Link Distance (ft)	1480			1830	2017	
Travel Time (s)	25.2			31.2	55.0	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Heavy Vehicles (%)	0%	0%	0%	0%	0%	0%
Adj. Flow (vph)	172	6	2	146	3	2
Shared Lane Traffic (%)						
Lane Group Flow (vph)	178	0	2	146	5	0
Enter Blocked Intersection	No	No	No	No	No	No
Lane Alignment	Left	Right	Left	Left	Left	Right
Median Width(ft)	12			12	12	
Link Offset(ft)	0			0	0	
Crosswalk Width(ft)	16			16	16	
Two way Left Turn Lane						
Headway Factor	1.00	1.00	1.00	1.00	1.00	1.00
Turning Speed (mph)		9	15		15	9
Sign Control	Free			Free	Stop	

Intersection Summary

Area Type:	Other
Control Type:	Unsignalized
Intersection Capacity Utilization	19.4%
Analysis Period (min)	15
	ICU Level of Service A

**Intersection**

Int Delay, s/veh 0.2

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Vol, veh/h	172	6	2	146	3	2
Future Vol, veh/h	172	6	2	146	3	2
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	100	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	100	100	100	100	100	100
Heavy Vehicles, %	0	0	0	0	0	0
Mvmt Flow	172	6	2	146	3	2

Major/Minor	Major1	Major2	Minor1		
Conflicting Flow All	0	0	178	0	325
Stage 1	-	-	-	-	175
Stage 2	-	-	-	-	150
Critical Hdwy	-	-	4.1	-	6.4
Critical Hdwy Stg 1	-	-	-	-	5.4
Critical Hdwy Stg 2	-	-	-	-	5.4
Follow-up Hdwy	-	-	2.2	-	3.5
Pot Cap-1 Maneuver	-	-	1410	-	673
Stage 1	-	-	-	-	860
Stage 2	-	-	-	-	883
Platoon blocked, %	-	-	-	-	-
Mov Cap-1 Maneuver	-	-	1410	-	672
Mov Cap-2 Maneuver	-	-	-	-	672
Stage 1	-	-	-	-	860
Stage 2	-	-	-	-	882

Approach	EB	WB	NB
HCM Control Delay, s	0	0.1	9.9
HCM LOS			A

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	740	-	-	1410	-
HCM Lane V/C Ratio	0.007	-	-	0.001	-
HCM Control Delay (s)	9.9	-	-	7.6	-
HCM Lane LOS	A	-	-	A	-
HCM 95th %tile Q(veh)	0	-	-	0	-



Stan Firestone  
P.O. Box 61928  
Vancouver, Washington 98666

Re: SE 40<sup>th</sup> Street (Valley View Estates Subdivision) Wetland Determination Addendum

Dear Mr. Firestone,

Ecological Land Services, Inc. (ELS) prepared a wetland determination detailing onsite conditions at the Valley View Estates Subdivision (Clark County Parcel Numbers 125646-000, 125634-000, and 125635-000) in October 2007 (*Wetland Determination Report for the Southeast 40<sup>th</sup> Site*). Onsite wetland conditions have not changed since the 2007 site investigation; there are no wetlands onsite. This addendum addresses off-site conditions within 300 feet of the property boundaries and meets the requirement for a critical areas report pursuant to CMC 16.53.030 as described in the June 27, 2013 pre-application summary.

One wetland is located offsite to the southwest. The northern boundary of the wetland is approximately 120 feet from the southern property boundary. A residential subdivision is under construction in the buffer of the wetland. The wetland was rated based on observations from your property and aerial photography using the *Wetland Rating Form for Western Washington* (Hruby; attached). The wetland appears to be a Category IV slope wetland. The City of Camas assigns a maximum 50-foot regulatory buffer to Category IV wetlands.

The buffer of the offsite wetland is estimated to be 50 feet. Because the wetland boundary is approximately 120 feet from the property boundary, no wetlands or wetland buffers extend onto your property from offsite.

If you have any questions, please contact me at [lisa@eco-land.com](mailto:lisa@eco-land.com) or (360) 835-9082.

Sincerely,

Lisa F. Willis  
Professional Biologist

Figure 1

# Valley View Estates Subdivision Adjacent Wetlands



### Legend

- Parcels
- Roads**
- ~ Alley
- ~ Arterial
- ~ DNR
- ~ DNR (Private Land)
- ~ Driveway
- ~ Interstate
- ~ Interstate Ramp
- ~ Primary Arterial
- ~ Private Roads
- ~ Private Roads w/o Names
- ~ Public Roads
- ~ SR Ramp
- ~ State Route
- ~ 2 Foot Contours
- Waterbodies
- Rural Centers
- City Boundaries
- Urban Growth Boundaries
- County Boundary

0 350 700 1050 ft.

Map center: 1137196, 99654



Scale: 1:3,735

This map was generated by Clark County's "Maps Online" website. Clark County does not warrant the accuracy, reliability or timeliness of any information on this map, and shall not be held liable for losses caused by using this information.

Wetland rating based on observations from the project site and aerial photography using the Wetland Rating Form for Western Washington (revised)

Wetland name or number \_\_\_\_\_

**WETLAND RATING FORM – WESTERN WASHINGTON**

Version 2 – Updated July 2006 to increase accuracy and reproducibility among users

Updated Oct 2008 with new WDFW definitions for priority habitats

Name of wetland (if known): Offsite Date of site visit: 10/3/13

Rated by M.McGraw Trained by Ecology? Yes  No  Date of Training: 2006

SECTION: 8 TOWNSHIP: 1N RANGE: 3E Is S/T/R in Appendix D? Yes  No

Map of wetland unit: **Figure 1** Estimated size **unknown**

**SUMMARY OF RATING**

**Category based on FUNCTIONS provided by wetland**

I  II  III  IV

Category I = Score >=70  
Category II = Score 51-69  
Category III = Score 30-50  
Category IV = Score < 30

Score for Water Quality Functions	<b>8</b>
Score for Hydrologic Functions	<b>2</b>
Score for Habitat Functions	<b>9</b>
<b>TOTAL Score for functions</b>	<b>19</b>

**Category based on SPECIAL CHARACTERISTICS of wetland**

I  II  Does not Apply

**Final Category** (choose the “highest” category from above)

**IV**

**Summary of basic information about the wetland unit**

Wetland Unit has Special Characteristics		Wetland HGM Class used for Rating	
Estuarine	<input type="checkbox"/>	Depressional	<input type="checkbox"/>
Natural Heritage Wetland	<input type="checkbox"/>	Riverine	<input type="checkbox"/>
Bog	<input type="checkbox"/>	Lake-fringe	<input type="checkbox"/>
Mature Forest	<input type="checkbox"/>	Slope	<input checked="" type="checkbox"/>
Old Growth Forest	<input type="checkbox"/>	Flats	<input type="checkbox"/>
Coastal Lagoon	<input type="checkbox"/>	Freshwater Tidal	<input type="checkbox"/>
Interdunal	<input type="checkbox"/>		
None of the above	<input type="checkbox"/>	Check if unit has multiple HGM classes present	<input type="checkbox"/>

**Does the wetland being rated meet any of the criteria below?**



Wetland name or number \_\_\_\_\_

If you answer YES to any of the questions below you will need to protect the wetland according to the regulations regarding the special characteristics found in the wetland.

<b>Check List for Wetlands That May Need Additional Protection (in addition to the protection recommended for its category)</b>	<b>YES</b>	<b>NO</b>
SP1. <i>Has the wetland been documented as a habitat for any Federally listed Threatened or Endangered <b>animal</b> or <b>plant</b> species (T/E species)?</i> For the purposes of this rating system, "documented" means the wetland is on the appropriate state or federal database.	<input type="checkbox"/>	<input checked="" type="checkbox"/>
SP2. <i>Has the wetland unit been documented as habitat for any State listed Threatened or Endangered <b>animal</b> species?</i> For the purposes of this rating system, "documented" means the wetland is on the appropriate state database. Note: Wetlands with State listed plant species are categorized as Category 1 Natural Heritage Wetlands (see p. 19 of data form).	<input type="checkbox"/>	<input checked="" type="checkbox"/>
SP3. <i>Does the wetland contain individuals of Priority species listed by the WDFW for the state?</i>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
SP4. <i>Does the wetland have a local significance in addition to its functions?</i> For example, the wetland has been identified in the Shoreline Master Program, the Critical Areas Ordinance, or in a local management plan as having special significance.	<input type="checkbox"/>	<input checked="" type="checkbox"/>

*To complete the next part of the data sheet you will need to determine the Hydrogeomorphic Class of the wetland being rated.*

The hydrogeomorphic classification groups wetlands into those that function in similar ways. This simplifies the questions needed to answer how well the wetland functions. The Hydrogeomorphic Class of a wetland can be determined using the key below. See p. 24 for more detailed instructions on classifying wetlands.

## Classification of Wetland Units in Western Washington

**If the hydrologic criteria listed in each question do not apply to the entire unit being rated, you probably have a unit with multiple HGM classes. In this case, identify which hydrologic criteria in questions 1-7 apply, and go to Question 8.**

1. Are the water levels in the entire unit usually controlled by tides (i.e. except during floods)?

NO – go to 2     YES – the wetland class is **Tidal Fringe**

If yes, is the salinity of the water during periods of annual low flow below 0.5 ppt (parts per thousand)?  YES – **Freshwater Tidal Fringe**     NO – **Saltwater Tidal Fringe (Estuarine)**

*If your wetland can be classified as a Freshwater Tidal Fringe use the forms for **Riverine** wetlands. If it is Saltwater Tidal Fringe it is rated as an **Estuarine** wetland.* Wetlands that were called estuarine in the first and second editions of the rating system are called Salt Water Tidal Fringe in the Hydrogeomorphic Classification. Estuarine wetlands were categorized separately in the earlier editions, and this separation is being kept in this revision. To maintain consistency between editions, the term “Estuarine” wetland is kept. Please note, however, that the characteristics that define Category I and II estuarine wetlands have changed (see p.    ).

2. The entire wetland unit is flat and precipitation is the only source (>90%) of water to it. Groundwater and surface water runoff are NOT sources of water to the unit.

NO – go to 3     YES – The wetland class is **Flats**

If your wetland can be classified as a “Flats” wetland, use the form for **Depressional** wetlands.

3. Does the wetland **meet both** of the following criteria?

- The vegetated part of the wetland is on the shores of a body of open water (without any vegetation on the surface) at least 20 acres (8 ha) in size;
- At least 30% of the open water area is deeper than 6.6 ft (2 m)?

NO – go to 4     YES – The wetland class is **Lake-fringe (Lacustrine Fringe)**

4. Does the wetland **meet all** of the following criteria?

- The wetland is on a slope (*slope can be very gradual*),
- The water flows through the wetland in one direction (unidirectional) and usually comes from seeps. It may flow subsurface, as sheetflow, or in a swale without distinct banks.
- The water leaves the wetland **without being impounded?**

NOTE: *Surface water does not pond in these type of wetlands except occasionally in very small and shallow depressions or behind hummocks (depressions are usually <3ft diameter and less than 1 foot deep).*

NO - go to 5     YES – The wetland class is **Slope**

5. Does the entire wetland unit **meet all** of the following criteria?

- The unit is in a valley, or stream channel, where it gets inundated by overbank flooding

Wetland name or number \_\_\_\_\_

from that stream or river

The overbank flooding occurs at least once every two years.

*NOTE: The riverine unit can contain depressions that are filled with water when the river is not flooding.*

NO - go to 6     YES - The wetland class is **Riverine**

6. Is the wetland in a topographic depression in which water ponds, or is saturated to the surface, at some time during the year. *This means that any outlet, if present, is higher than the interior of the wetland.*

NO - go to 7     YES - The wetland class is **Depressional**

7. Is the entire wetland located in a very flat area with no obvious depression and no overbank flooding? The unit does not pond surface water more than a few inches. The unit seems to be maintained by high groundwater in the area. The wetland may be ditched, but has no obvious natural outlet.

NO - go to 8     YES - The wetland class is **Depressional**

8. Your wetland unit seems to be difficult to classify and probably contains several different HGM classes. For example, seeps at the base of a slope may grade into a riverine floodplain, or a small stream within a depressional wetland has a zone of flooding along its sides. **GO BACK AND IDENTIFY WHICH OF THE HYDROLOGIC REGIMES DESCRIBED IN QUESTIONS 1-7 APPLY TO DIFFERENT AREAS IN THE UNIT** (make a rough sketch to help you decide). Use the following table to identify the appropriate class to use for the rating system if you have several HGM classes present within your wetland. *NOTE: Use this table only if the class that is recommended in the second column represents 10% or more of the total area of the wetland unit being rated. If the area of the class listed in column 2 is less than 10% of the unit; classify the wetland using the class that represents more than 90% of the total area.*

<i>HGM Classes within the wetland unit being rated</i>	<i>HGM Class to Use in Rating</i>
Slope + Riverine	Riverine
Slope + Depressional	Depressional
Slope + Lake-fringe	Lake-fringe
Depressional + Riverine along stream within boundary	Depressional
Depressional + Lake-fringe	Depressional
Salt Water Tidal Fringe and any other class of freshwater wetland	Treat as ESTUARINE under wetlands with special characteristics

If you are unable still to determine which of the above criteria apply to your wetland, or you have more than 2 HGM classes within a wetland boundary, classify the wetland as **Depressional** for the rating.

<b>D Depressional and Flats Wetlands</b>		<b>Points</b> (only 1 score per box)
<b>WATER QUALITY FUNCTION – Indicators that the wetland unit functions to improve water quality</b>		
<b>D</b>	<b>D 1. Does the wetland have the <u>potential</u> to improve water quality?</b>	(see p.38)
<b>D</b>	<p>D 1.1 Characteristics of surface water flows out of the wetland:</p> <p>Unit is a depression with no surface water leaving it (no outlet) points = 3</p> <p>Unit has an intermittently flowing, OR highly constricted, permanently flowing outlet points = 2</p> <p>Unit has an unconstricted, or slightly constricted, surface outlet (<i>permanently flowing</i>) points = 1</p> <p>Unit is a “flat” depression (Q. 7 on key), or in the Flats class, with permanent surface outflow <b>and no obvious natural outlet</b> and/or outlet is a man-made ditch points = 1</p> <p>(if ditch is not permanently flowing treat unit as “intermittently flowing”)</p> <p style="text-align: right;">Provide photo or drawing</p>	Figure _____
<b>D</b>	<p>D 1.2 The soil 2 inches below the surface (or duff layer) is clay or organic (<i>use NRCS definitions</i>)</p> <p>YES points = 4</p> <p>NO points = 0</p>	
<b>D</b>	<p>D 1.3 Characteristics of persistent vegetation (emergent, shrub, and/or forest Cowardin class):</p> <p>Wetland has persistent, ungrazed, vegetation &gt; = 95% of area points = 5</p> <p>Wetland has persistent, ungrazed, vegetation &gt; = 1/2 of area points = 3</p> <p>Wetland has persistent, ungrazed vegetation &gt; = 1/10 of area points = 1</p> <p>Wetland has persistent, ungrazed vegetation &lt;1/10 of area points = 0</p> <p style="text-align: right;">Map of Cowardin vegetation classes</p>	Figure _____
<b>D</b>	<p>D1.4 Characteristics of seasonal ponding or inundation.</p> <p><i>This is the area of the wetland that is ponded for at least 2 months, but dries out sometime during the year. Do not count the area that is permanently ponded. Estimate area as the average condition 5 out of 10 yrs.</i></p> <p>Area seasonally ponded is &gt; ½ total area of wetland points = 4</p> <p>Area seasonally ponded is &gt; ¼ total area of wetland points = 2</p> <p>Area seasonally ponded is &lt; ¼ total area of wetland points = 0</p> <p style="text-align: right;">Map of Hydroperiods</p>	Figure _____
<b>D</b>	<b>Total for D 1</b>	<i>Add the points in the boxes above</i>
<b>D</b>	<p><b>D 2. Does the wetland have the <u>opportunity</u> to improve water quality?</b></p> <p>Answer YES if you know or believe there are pollutants in groundwater or surface water coming into the wetland that would otherwise reduce water quality in streams, lakes or groundwater downgradient from the wetland? <i>Note which of the following conditions provide the sources of pollutants. A unit may have pollutants coming from several sources, but any single source would qualify as opportunity.</i></p> <p><input type="checkbox"/> Grazing in the wetland or within 150 ft</p> <p><input type="checkbox"/> Untreated stormwater discharges to wetland</p> <p><input type="checkbox"/> Tilled fields or orchards within 150 ft of wetland</p> <p><input type="checkbox"/> A stream or culvert discharges into wetland that drains developed areas, residential areas, farmed fields, roads, or clear-cut logging</p> <p><input type="checkbox"/> Residential, urban areas, golf courses are within 150 ft of wetland</p> <p><input type="checkbox"/> Wetland is fed by groundwater high in phosphorus or nitrogen</p> <p><input type="checkbox"/> Other _____</p> <p><input type="checkbox"/> YES multiplier is 2      <input type="checkbox"/> NO multiplier is 1</p>	(see p.44)
<b>D</b>	<b>TOTAL - Water Quality Functions</b>	<p>Multiply the score from D1 by D2</p> <p style="text-align: right;"><i>Add score to table on p. 1</i></p>





<b>R Riverine and Freshwater Tidal Fringe Wetlands</b>		<b>Points</b> (only 1 score per box)
<b>HYDROLOGIC FUNCTIONS - Indicators that wetland functions to reduce flooding and stream erosion</b>		
<b>R</b>	<b>R 3. Does the wetland have the <u>potential</u> to reduce flooding and erosion?</b>	(see p. 54)
<b>R</b>	<p>R 3.1 Characteristics of the overbank storage the wetland provides:  <i>Estimate the average width of the wetland perpendicular to the direction of the flow and the width of the stream or river channel (distance between banks). Calculate the ratio: (average width of unit)/(width of stream between banks).</i></p> <p>If the ratio is more than 20 points = 9                      If the ratio is between 10-20 points = 6                      If the ratio is 5- &lt;10 points = 4                      If the ratio is 1- &lt;5 points = 2                      If the ration is &lt;1 points = 1</p> <p><i>Aerial photo or map showing polygons of different vegetation types</i></p>	Figure __
<b>R</b>	<p>R 3.2 Characteristics vegetation that slow down water velocities during floods: <i>Treat large woody debris as "forest or shrub". Choose the points appropriate for the best description.</i></p> <p>Forest or shrub for &gt;1/3 area OR herbaceous plants &gt;2/3 area points = 7                      Forest or shrub &gt; 1/10 area OR herbaceous plants &gt;1/3 area points = 4                      Vegetation does not meet above criteria points = 0</p> <p><i>Aerial photo or map showing polygons of different vegetation types</i></p>	Figure __
<b>R</b>	<i>Add the points in the boxes above</i>	
<b>R</b>	<p><b>R 4. Does the wetland have the <u>opportunity</u> to reduce flooding and erosion?</b>                      Answer YES if the wetland is in a location in the watershed where the flood storage, or reduction in water velocity it provides helps protect downstream property and aquatic resources from flooding or excessive and/or erosive flows. <i>Note which of the following conditions apply.</i></p> <p><input type="checkbox"/> There are human structures and activities downstream (roads, buildings, bridges, farms) that can be damaged by flooding.  <input type="checkbox"/> There are natural resources downstream (e.g. salmon redds) that can be damaged by flooding  <input type="checkbox"/> Other _____</p> <p><i>(Answer NO if the major source of water to the wetland is controlled by a reservoir or the wetland is tidal fringe along the sides of a dike.)</i></p> <p><input type="checkbox"/> YES multiplier is 2    <input type="checkbox"/> NO multiplier is 1</p>	(see p. 57)           multiplier  _____
<b>R</b>	<b>TOTAL – Hydrologic Functions</b> Multiply the score from R3 by R4 <i>Add score to table on p. 1</i>	

**Comments**





<b>L Lake-Fringe Wetlands</b>		<b>Points</b> (only 1 score per box)
<b>HYDROLOGIC FUNCTIONS - Indicators that wetland unit functions to reduce shoreline erosion</b>		
<b>L</b>	<b>L 3. Does the wetland have the <u>potential</u> to reduce shoreline erosion?</b>	<i>(see p. 62)</i>
<b>L</b>	<p>L 3 Distance along shore and average width of Cowardin classes along the lakeshore (<b>do not</b> include aquatic bed): <i>(choose the highest scoring description that matches conditions in the wetland):</i></p> <p>&gt;<sup>3</sup>/<sub>4</sub> of distance is shrubs or forest at least 33 ft (10m) wide                      points = 6</p> <p>&gt;<sup>3</sup>/<sub>4</sub> of distance is shrubs or forest at least 6 ft. (2m) wide                      points = 4</p> <p>&gt;<sup>1</sup>/<sub>4</sub> of distance is shrubs or forest at least 33 ft (10m) wide                      points = 4</p> <p>Vegetation is at least 6 ft (2m) wide (any type except aquatic bed)              points = 2</p> <p>Vegetation is less than 6 ft (2m) wide (any type except aquatic bed)          points = 0</p> <p style="text-align: center;"><b>Aerial photo or map with Cowardin vegetation classes</b></p>	<b>Figure</b> ____
<b>L</b>	<i>Record the points from the box above</i>	
<b>L</b>	<p><b>L 4. Does the wetland unit have the <u>opportunity</u> to reduce erosion?</b></p> <p>Are there features along the shore which will be impacted if the shoreline erodes? <i>Note which of the following conditions apply.</i></p> <p><input type="checkbox"/> There are human structures and activities along the upland edge of the wetland (buildings, fields) that can be damaged by erosion.</p> <p><input type="checkbox"/> There are undisturbed natural resources along the upland edge of the wetland (e.g. mature forests other than wetland) that can be damaged by shoreline erosion</p> <p><input type="checkbox"/> Other _____</p> <p><input type="checkbox"/> <b>YES</b> multiplier is 2    <input type="checkbox"/> <b>NO</b> multiplier is 1</p>	<i>(see p. 63)</i>  multiplier  _____
<b>L</b>	<b>TOTAL – Hydrologic Functions</b> Multiply the score from L 3 by L 4 <i>Add score to table on p. 1</i>	

**Comments**




<b>S Slope Wetlands</b>		<b>Points</b> (only 1 score per box)
<b>HYDROLOGIC FUNCTIONS - Indicators that wetland unit functions to reduce flooding and stream erosion</b>		
<b>S</b>	<b>S 3. Does the wetland have the <u>potential</u> to reduce flooding and erosion?</b>	<i>(see p. 68)</i>
<b>S</b>	<p>S 3.1 Characteristics of vegetation that reduce the velocity of surface flows during storms.  <i>Choose the points appropriate for the description that best fit conditions in the wetland. (stems of plants should be thick enough (usually &gt; 1/8 in), or dense enough, to remain erect during surface flows)</i></p> <p>Dense, uncut, <b>rigid</b> vegetation covers &gt;90% of area of the wetland. points = 6            Dense, uncut, <b>rigid</b> vegetation &gt;1/2 area of wetland points = 3            Dense, uncut, <b>rigid</b> vegetation &gt;1/4 area of wetland points = 1            More than 3/4 of area is grazed, mowed, tilled or vegetation is not rigid points = 0</p>	<b>1</b>
<b>S</b>	<p>S 3.2 Characteristics of slope wetland that holds back small amounts of flood flows:            The slope wetland has small surface depressions that can retain water over at least 10% of its area.</p> <p>YES points = 2            NO points = 0</p>	<b>0</b>
<b>S</b>	<i>Add the points in the boxes above</i>	<b>1</b>
<b>S</b>	<p><b>S 4. Does the wetland have the <u>opportunity</u> to reduce flooding and erosion?</b>            Is the wetland in a landscape position where the reduction in water velocity it provides helps protect downstream property and aquatic resources from flooding or excessive and/or erosive flows? <i>Note which of the following conditions apply.</i></p> <p><input checked="" type="checkbox"/> Wetland has surface runoff that drains to a river or stream that has flooding problems  <input type="checkbox"/> Other _____</p> <p><i>Answer NO if the major source of water is controlled by a reservoir (e.g. wetland is a seep that is on the downstream side of a dam.)</i></p> <p><input checked="" type="checkbox"/> <b>YES</b> multiplier is 2    <input type="checkbox"/> <b>NO</b> multiplier is 1</p>	<i>(see p. 70)</i>  multiplier  <b>2</b>
<b>S</b>	<b>TOTAL - Hydrologic Functions</b> Multiply the score from S 3 by S 4 <i>Add score to table on p. 1</i>	<b>2</b>

**Comments**



**H 1.4 Interspersion of habitats** (see p. 76)

Decide from the diagrams below whether interspersion between Cowardin vegetation classes (described in H 1.1), or classes and unvegetated areas (can include open water or mudflats) is high, medium, low, or none.



NOTE: If you have four or more classes or three vegetation classes and open water the rating is always "high". Use map of Cowardin vegetation classes

Figure \_\_

1

**H 1.5 Special Habitat Features:** (see p. 77)

Check the habitat features that are present in the wetland. The number of checks is the number of points you put into the next column.

- Large, downed, woody debris within the wetland (>4in. diameter and 6 ft long).
- Standing snags (diameter at bottom >4 inches) in the wetland
- Undercut banks are present for at least 6.6 ft. (2m) and/or overhanging vegetation extends at least 3.3 ft (1m) over a stream (or ditch) in, or contiguous with the unit, for at least 33 ft (10m)
- Stable steep banks of fine material that might be used by beaver or muskrat for denning (>30 degree slope) OR signs of recent beaver activity are present (cut shrubs or trees that have not yet turned grey/brown)
- At least ¼ acre of thin-stemmed persistent vegetation or woody branches are present in areas that are permanently or seasonally inundated (structures for egg-laying by amphibians)
- Invasive plants cover less than 25% of the wetland area in each stratum of plants

Note: The 20% stated in early printings of the manual on page 78 is an error

1

**H 1. TOTAL Score** – potential for providing habitat  
Add the scores from H1.1, H1.2, H1.3, H1.4, H1.5

6

Comments:

<b>H 2. Does the wetland have the opportunity to provide habitat for many species?)</b>		
<p><b>H 2.1 Buffers (see p. 80)</b>  <i>Choose the description that best represents condition of buffer of wetland. The highest scoring criterion that applies to the wetland is to be used in the rating. See text for definition of "undisturbed."</i></p> <p><input type="checkbox"/> 100 m (330ft) of relatively undisturbed vegetated areas, rocky areas, or open water &gt;95% of circumference. No structures are within the undisturbed part of buffer. (relatively undisturbed also means no grazing, no landscaping, no daily human use) <b>Points = 5</b></p> <p><input type="checkbox"/> 100 m (330 ft) of relatively undisturbed vegetated areas, rocky areas, or open water &gt;50% circumference. <b>Points = 4</b></p> <p><input type="checkbox"/> 50 m (170ft) of relatively undisturbed vegetated areas, rocky areas, or open water &gt;95% circumference. <b>Points = 4</b></p> <p><input type="checkbox"/> 100 m (330ft) of relatively undisturbed vegetated areas, rocky areas, or open water &gt;25% circumference. <b>Points = 3</b></p> <p><input type="checkbox"/> 50 m (170ft) of relatively undisturbed vegetated areas, rocky areas, or open water for &gt; 50% circumference. <b>Points = 3</b></p> <p style="text-align: center;"><b>If buffer does not meet any of the three criteria above</b></p> <p><input checked="" type="checkbox"/> No paved areas (except paved trails) or buildings within 25 m (80ft) of wetland &gt; 95% circumference. Light to moderate grazing, or lawns are OK. <b>Points = 2</b></p> <p><input type="checkbox"/> No paved areas or buildings within 50m of wetland for &gt;50% circumference. Light to moderate grazing or lawns are OK <b>Points = 2</b></p> <p><input type="checkbox"/> Heavy grazing in buffer. <b>Points = 1</b></p> <p><input type="checkbox"/> Vegetated buffers are &lt;2m wide (6.6ft) for more than 95% of the circumference (e.g. tilled fields, paving, basalt bedrock extend to edge of wetland) <b>Points = 0</b></p> <p><input type="checkbox"/> Buffer does not meet any of the criteria above. <b>Points = 1</b></p> <p style="text-align: center;"><b>Aerial photo showing buffers</b></p>	<p>Figure ___</p> <p><b>2</b></p>	
<p><b>H 2.2 Corridors and Connections (see p. 81)</b></p> <p>H 2.2.1 Is the wetland part of a relatively undisturbed and unbroken vegetated corridor (either riparian or upland) that is at least 150 ft wide, has at least 30% cover of shrubs, forest or native undisturbed prairie, that connects to estuaries, other wetlands or undisturbed uplands that are at least 250 acres in size? (<i>dams in riparian corridors, heavily used gravel roads, paved roads, are considered breaks in the corridor</i>).</p> <p style="text-align: center;"><input type="checkbox"/> YES = <b>4 points</b> (go to H 2.3)      <input checked="" type="checkbox"/> NO = go to H 2.2.2</p> <p>H 2.2.2 Is the wetland part of a relatively undisturbed and unbroken vegetated corridor (either riparian or upland) that is at least 50ft wide, has at least 30% cover of shrubs or forest, and connects to estuaries, other wetlands or undisturbed uplands that are at least 25 acres in size? <b>OR</b> a <b>Lake-fringe</b> wetland, if it does not have an undisturbed corridor as in the question above?</p> <p style="text-align: center;"><input type="checkbox"/> YES = <b>2 points</b> (go to H 2.3)      <input checked="" type="checkbox"/> NO = H 2.2.3</p> <p>H 2.2.3 Is the wetland:</p> <p style="padding-left: 40px;">within 5 mi (8km) of a brackish or salt water estuary OR  within 3 mi of a large field or pasture (&gt;40 acres) OR  within 1 mi of a lake greater than 20 acres?</p> <p style="text-align: center;"><input type="checkbox"/> YES = <b>1 point</b>      <input checked="" type="checkbox"/> NO = <b>0 points</b></p>	<p><b>0</b></p>	

Total for page: 2

H 2.3 Near or adjacent to other priority habitats listed by WDFW (see new and complete descriptions of WDFW priority habitats, and the counties in which they can be found, in the PHS report <http://wdfw.wa.gov/hab/phslist.htm>)

Which of the following priority habitats are within 330ft (100m) of the wetland unit? *NOTE: the connections do not have to be relatively undisturbed.*

- Aspen Stands:** Pure or mixed stands of aspen greater than 0.4 ha (1 acre).
- Biodiversity Areas and Corridors:** Areas of habitat that are relatively important to various species of native fish and wildlife (*full descriptions in WDFW PHS report p. 152*).
- Herbaceous Balds:** Variable size patches of grass and forbs on shallow soils over bedrock.
- Old-growth/Mature forests:** (Old-growth west of Cascade crest) Stands of at least 2 tree species, forming a multi-layered canopy with occasional small openings; with at least 20 trees/ha (8 trees/acre) > 81 cm (32 in) dbh or > 200 years of age. (Mature forests) Stands with average diameters exceeding 53 cm (21 in) dbh; crown cover may be less than 100%; crown cover may be less than 100%; decay, decadence, numbers of snags, and quantity of large downed material is generally less than that found in old-growth; 80 - 200 years old west of the Cascade crest.
- Oregon white Oak:** Woodlands Stands of pure oak or oak/conifer associations where canopy coverage of the oak component is important (*fill descriptions in WLDFW PHS report p. 158*).
- Riparian:** The area adjacent to aquatic systems with flowing water that contains elements of both aquatic and terrestrial ecosystems which mutually influence each other.
- Westside Prairies:** Herbaceous, non-forested plant communities that can either take the form of a dry prairie or a wet prairie (*full descriptions in WDFW PHS report p. 161*).
- Instream:** The combination of physical, biological, and chemical processes and conditions that interact to provide functional life history requirements for instream fish and wildlife resources.
- Nearshore:** Relatively undisturbed nearshore habitats. These include Coastal Nearshore, Open Coast Nearshore, and Puget Sound Nearshore. (*full descriptions of habitats and the definition of relatively undisturbed are in WDFW report. ' pp. 167-169 and glossary in Appendix A*).
- Caves:** A naturally occurring cavity, recess, void, or system of interconnected passages under the earth in soils, rock, ice, or other geological formations and is large enough to contain a human.
- Cliffs:** Greater than 7.6 m (25 ft) high and occurring below 5000 ft.
- Talus:** Homogenous areas of rock rubble ranging in average size 0.15 - 2.0 m (0.5 - 6.5 ft), composed of basalt andesite, and/or sedimentary rock, including riprap slides and mine tailings. May be associated with cliffs.
- Snags and Logs:** Trees are considered snags if they are dead or dying and exhibit sufficient decay characteristics to enable cavity excavation/use by wildlife. Priority snags have a diameter at breast height of > 51 cm (20 in) in western Washington and are > 2 m (6.5 ft) in height. Priority logs are > 30 cm (12 in) in diameter at the largest end, and > 6 m (20 ft) long.

If wetland has **3 or more** priority habitats = **4 points**

If wetland has **2** priority habitats = **3 points**

If wetland has **1** priority habitat = **1 point**

No habitats = 0 points

*Note: All vegetated wetlands are by definition a priority habitat but are not included in this list. Nearby wetlands are addressed in question H 2.4)*

1

<p><b>H 2.4 Wetland Landscape</b> (<i>choose the <b>one</b> description of the landscape around the wetland that best fits</i>) (<i>see p. 84</i>)</p> <p><input type="checkbox"/> There are at least 3 other wetlands within ½ mile, and the connections between them are relatively undisturbed (light grazing between wetlands OK, as is lake shore with some boating, but connections should NOT be bisected by paved roads, fill, fields, or other development. <span style="float: right;">points = 5</span></p> <p><input type="checkbox"/> The wetland is Lake-fringe on a lake with little disturbance and there are 3 other lake-fringe wetlands within ½ mile <span style="float: right;">points = 5</span></p> <p><input type="checkbox"/> There are at least 3 other wetlands within ½ mile, BUT the connections between them are disturbed <span style="float: right;">points = 3</span></p> <p><input type="checkbox"/> The wetland is Lake-fringe on a lake <b>with</b> disturbance and there are 3 other lake-fringe wetlands within ½ mile <span style="float: right;">points = 3</span></p> <p><input type="checkbox"/> There is at least 1 wetland within ½ mile. <span style="float: right;">points = 2</span></p> <p><input checked="" type="checkbox"/> There are no wetlands within ½ mile. <span style="float: right;">points = 0</span></p>	<p><b>0</b></p>
<p><b>H 2. TOTAL Score</b> -opportunity for providing habitat <i>Add the scores in the column above</i></p>	<p><b>3</b></p>
<p>TOTAL for H 1 from page 14</p>	<p><b>6</b></p>
<p><b>Total Score for Habitat Functions</b> – add the points for H 1, H 2 and record the result on p. 1</p>	<p><b>9</b></p>



## CATEGORIZATION BASED ON SPECIAL CHARACTERISTICS

*Please determine if the wetland meets the attributes described below and circle the appropriate answers and Category.*

Wetland Type	Category
<p><i>Check off any criteria that apply to the wetland. Select the appropriate Category (from dropdown menu in Category column) when the appropriate criteria are met.</i></p>	
<p><b>SC 1.0 Estuarine wetlands (see p. 86)</b></p> <p>Does the wetland meet the following criteria for Estuarine wetlands?</p> <p><input type="checkbox"/> The dominant water regime is tidal,  <input type="checkbox"/> Vegetated, and  <input type="checkbox"/> With a salinity greater than 0.5 ppt.  <input type="checkbox"/> YES = Go to SC 1.1   <input checked="" type="checkbox"/> NO</p>	
<p>SC 1.1 Is the wetland within a National Wildlife Refuge, National Park, National Estuary Reserve, Natural Area Preserve, State Park or Educational, Environmental, or Scientific Reserve designated under WAC 332-30-151?</p> <p><input type="checkbox"/> YES = Category I                      <input checked="" type="checkbox"/> NO go to SC 1.2</p>	Cat. I
<p>SC 1.2 Is the wetland at least 1 acre in size and meets at least two of the following three conditions? YES = Category I NO = Category II</p> <p><input type="checkbox"/> The wetland is relatively undisturbed (has no diking, ditching, filling, cultivation, grazing, and has less than 10% cover of non-native plant species. If the non-native <i>Spartina</i> spp. are the only species that cover more than 10% of the wetland, then the wetland should be given a dual rating (I/II). The area of <i>Spartina</i> would be rated a Category II while the relatively undisturbed upper marsh with native species would be a Category I. Do not, however, exclude the area of <i>Spartina</i> in determining the size threshold of 1 acre.</p> <p><input type="checkbox"/> At least ¾ of the landward edge of the wetland has a 100 ft buffer of shrub, forest, or un-grazed or un-mowed grassland.</p> <p><input type="checkbox"/> The wetland has at least 2 of the following features: tidal channels, depressions with open water, or contiguous freshwater wetlands.</p>	Cat. I Cat. II  Dual rating  I/II

<p><b>SC 2.0 Natural Heritage Wetlands (see p. 87)</b>          Natural Heritage wetlands have been identified by the Washington Natural Heritage Program/DNR as either high quality undisturbed wetlands or wetlands that support state Threatened, Endangered, or Sensitive plant species.</p> <p>SC 2.1 Is the wetland being rated in a Section/Township/Range that contains a Natural Heritage wetland? (<i>this question is used to screen out most sites before you need to contact WNHP/DNR</i>)          S/T/R information from Appendix D <input type="checkbox"/> or accessed from WNHP/DNR web site <input checked="" type="checkbox"/></p> <p>YES <input type="checkbox"/> – contact WNHP/DNR (see p. 79) and go to SC 2.2      NO <input checked="" type="checkbox"/></p> <p>SC 2.2 Has DNR identified the wetland as a high quality undisturbed wetland or as or as a site with state threatened or endangered plant species?  <input type="checkbox"/> YES = Category I      <input type="checkbox"/> NO__ not in a Heritage Wetland</p>	<p>Cat. I</p>
<p><b>SC 3.0 Bogs (see p. 87)</b>          Does the wetland unit (<b>or part of the unit</b>) meet both the criteria for soils and vegetation in bogs? <i>Use the key below to identify if the wetland is a bog. If you answer yes you will still need to rate the wetland based on its functions.</i></p> <p>1. Does the unit have organic soil horizons (i.e. layers of organic soil), either peats or mucks, that compose 16 inches or more of the first 32 inches of the soil profile? (See Appendix B for a field key to identify organic soils)          Yes <input type="checkbox"/> - go to Q. 3      No <input checked="" type="checkbox"/> go to Q. 2</p> <p>2. Does the unit have organic soils, either peats or mucks that are less than 16 inches deep over bedrock, or an impermeable hardpan such as clay or volcanic ash, or that are floating on a lake or pond?          Yes <input type="checkbox"/> - go to Q. 3      No <input checked="" type="checkbox"/> - Is not a bog for purpose of rating</p> <p>3. Does the unit have more than 70% cover of mosses at ground level, AND other plants, if present, consist of the “bog” species listed in Table 3 as a significant component of the vegetation (more than 30% of the total shrub and herbaceous cover consists of species in Table 3)?          Yes <input type="checkbox"/> – Is a bog for purpose of rating      No <input type="checkbox"/> -go to Q. 4          NOTE: If you are uncertain about the extent of mosses in the understory you may substitute that criterion by measuring the pH of the water that seeps into a hole dug at least 16” deep. If the pH is less than 5.0 and the “bog” plant species in Table 3 are present, the wetland is a bog.</p> <p>4. Is the unit forested (&gt; 30% cover) with sitka spruce, subalpine fir, western red cedar, western hemlock, lodgepole pine, quaking aspen, Englemann’s spruce, or western white pine, WITH any of the species (or combination of species) on the bog species plant list in Table 3 as a significant component of the ground cover (&gt; 30% coverage of the total shrub/herbaceous cover)?          YES <input type="checkbox"/> = Category I      NO <input type="checkbox"/> Is not a bog for purpose of rating</p>	<p>Cat. I</p>

<p><b>SC 4.0 Forested Wetlands (see p. 90)</b>                  Does the wetland unit have at least 1 acre of forest that meets one of these criteria for the Department of Fish and Wildlife's forests as priority habitats? <i>If you answer yes you will still need to rate the wetland based on its functions.</i></p> <p><input type="checkbox"/> <b>Old-growth forests:</b> (west of Cascade crest) Stands of at least two tree species, forming a multi-layered canopy with occasional small openings; with at least 8 trees/acre (20 trees/hectare) that are at least 200 years of age OR have a diameter at breast height (dbh) of 32 inches (81 cm) or more.</p> <p>NOTE: The criterion for dbh is based on measurements for upland forests. Two-hundred year old trees in wetlands will often have a smaller dbh because their growth rates are often slower. The DFW criterion is and "OR" so old-growth forests do not necessarily have to have trees of this diameter.</p> <p><input type="checkbox"/> <b>Mature forests:</b> (west of the Cascade Crest) Stands where the largest trees are 80 – 200 years old OR have average diameters (dbh) exceeding 21 inches (53cm); crown cover may be less than 100%; decay, decadence, numbers of snags, and quantity of large downed material is generally less than that found in old-growth.</p> <p><input type="checkbox"/> YES = Category I      <input checked="" type="checkbox"/> NO not a forested wetland with special characteristics</p>	<p><b>Cat. I</b></p>
<p><b>SC 5.0 Wetlands in Coastal Lagoons (see p. 91)</b>                  Does the wetland meet all of the following criteria of a wetland in a coastal lagoon?</p> <p><input type="checkbox"/> The wetland lies in a depression adjacent to marine waters that is wholly or partially separated from marine waters by sandbanks, gravel banks, shingle, or, less frequently, rocks</p> <p><input type="checkbox"/> The lagoon in which the wetland is located contains surface water that is saline or brackish (&gt; 0.5 ppt) during most of the year in at least a portion of the lagoon (<i>needs to be measured near the bottom</i>)</p> <p><input type="checkbox"/> YES = Go to SC 5.1      NO <input checked="" type="checkbox"/> not a wetland in a coastal lagoon</p> <p><b>SC 5.1</b> Does the wetland meet all of the following three conditions?</p> <p><input type="checkbox"/> The wetland is relatively undisturbed (has no diking, ditching, filling, cultivation, grazing), and has less than 20% cover of invasive plant species (see list of invasive species on p. 74).</p> <p><input type="checkbox"/> At least ¾ of the landward edge of the wetland has a 100 ft buffer of shrub, forest, or un-grazed or un-mowed grassland.</p> <p><input type="checkbox"/> The wetland is larger than 1/10 acre (4350 square feet)</p> <p>YES <input type="checkbox"/> = Category I      NO <input type="checkbox"/> = Category II</p>	<p><b>Cat. I</b></p> <p><b>Cat. II</b></p>

<p><b>SC 6.0 Interdunal Wetlands (see p. 93)</b></p> <p>Is the wetland west of the 1889 line (also called the Western Boundary of Upland Ownership or WBUO)?</p> <p><input type="checkbox"/> YES = Go to SC 6.1      <input checked="" type="checkbox"/> NO -- not an interdunal wetland for rating</p> <p><i>If you answer yes you will still need to rate the wetland based on its functions.</i></p> <p>In practical terms that means the following geographic areas:</p> <ul style="list-style-type: none"> <li>• Long Beach Peninsula – lands west of SR103</li> <li>• Grayland-Westport- lands west of SR 105</li> <li>• Ocean Shores-Copalis- lands west of SR 115 and SR 109</li> </ul> <p>SC 6.1 Is the wetland one acre or larger, or is it in a mosaic of wetlands that is one acre or larger?</p> <p><input type="checkbox"/> YES = Category II      <input type="checkbox"/> NO go to SC 6.2</p> <p>SC 6.2 Is the wetland between 0.1 and 1 acre, or is it in a mosaic of wetlands that is between 0.1 and 1 acre,?</p> <p><input type="checkbox"/> YES = Category III</p>	<p></p> <p><b>Cat.II</b></p> <p><b>Cat.III</b></p>
<p><b>Category of wetland based on Special Characteristics</b></p> <p><i>Choose the "highest" rating if wetland falls into several categories, and record on p. 1.</i></p> <p>If you answered NO for all types enter "Not Applicable" on p. 1.</p>	<p><b>N/A</b></p>

**Comments**

USPS TRACKING#



9590 9402 3383 7227 1188 69



First-Class Mail  
Postage & Fees Paid  
USPS  
Permit No. G-10

United States  
Postal Service

• Sender: Please print your name, address, and ZIP+4® in this box•

*Warm  
Springs*

STERLING DESIGN, INC.  
2208 E. EVERGREEN BLVD.  
VANCOUVER, WA 98661

USPS TRACKING#



9590 9402 3383 7227 1188 76




First-Class Mail  
Postage & Fees Paid  
USPS  
Permit No. G-10

United States  
Postal Service

• Sender: Please print your name, address, and ZIP+4® in this box•

*Conuity*

STERLING DESIGN, INC.  
2208 E. EVERGREEN BLVD.  
VANCOUVER, WA 98661



USPS TRACKING#



9590 9402 3383 7227 1188 38




First-Class Mail  
Postage & Fees Paid  
USPS  
Permit No. G-10

United States  
Postal Service

• Sender: Please print your name, address, and ZIP+4® in this box•

*YAKAMA*

STERLING DESIGN, INC.  
2208 E. EVERGREEN BLVD.  
VANCOUVER, WA 98661



USPS TRACKING#



9590 9402 3383 7227 1188 52




First-Class Mail  
Postage & Fees Paid  
USPS  
Permit No. G-10

United States  
Postal Service

• Sender: Please print your name, address, and ZIP+4® in this box•

*umation*

STERLING DESIGN, INC.  
2208 E. EVERGREEN BLVD.  
VANCOUVER, WA 98661



## SENDER: COMPLETE THIS SECTION

- Complete items 1, 2, and 3.
- Print your name and address on the reverse so that we can return the card to you.
- Attach this card to the back of the mailpiece, or on the front if space permits.

## 1. Article Addressed to:

Neg Perce Trise  
P O Box 305  
LAPWAI ID 83540



9590 9402 3383 7227 1188 90

## 2. Article Number (Transfer from service label)

7018 0360 0001 0149 0561

PS Form 3811, July 2015 PSN 7530-02-000-9053

## COMPLETE THIS SECTION ON DELIVERY

## A. Signature

 Ashley [Signature]

 Agent  
 Addressee

## B. Received by (Printed Name)

Ashley [Signature]

## C. Date of Delivery

6-27-18

 D. Is delivery address different from item 1?  Yes  
 If YES, enter delivery address below:  No

## 3. Service Type

- |  |   |
|--|---|
| <input type="checkbox"/> Adult Signature                               | <input type="checkbox"/> Priority Mail Express®                     |
| <input type="checkbox"/> Adult Signature Restricted Delivery           | <input type="checkbox"/> Registered Mail™                           |
| <input checked="" type="checkbox"/> Certified Mail®                    | <input type="checkbox"/> Registered Mail Restricted Delivery        |
| <input type="checkbox"/> Certified Mail Restricted Delivery            | <input type="checkbox"/> Return Receipt for Merchandise             |
| <input type="checkbox"/> Collect on Delivery                           | <input type="checkbox"/> Signature Confirmation™                    |
| <input type="checkbox"/> Collect on Delivery Restricted Delivery       | <input type="checkbox"/> Signature Confirmation Restricted Delivery |
| <input type="checkbox"/> Insured Mail                                  |   |
| <input type="checkbox"/> Insured Mail Restricted Delivery (over \$500) |   |


Domestic Return Receipt

## SENDER: COMPLETE THIS SECTION

- Complete items 1, 2, and 3.
- Print your name and address on the reverse so that we can return the card to you.
- Attach this card to the back of the mailpiece, or on the front if space permits.

## 1. Article Addressed to:

Chinook Indian Nation  
P O Box 368  
La Center WA 98527



9590 9402 3383 7227 1188 21

## 2. Article Number (Transfer from service label)

7018 0360 0001 0149 0493

PS Form 3811, July 2015 PSN 7530-02-000-9053

## COMPLETE THIS SECTION ON DELIVERY

## A. Signature

 Lucy [Signature]

 Agent  
 Addressee

## B. Received by (Printed Name)

Lucy Anderson

## C. Date of Delivery

7/3/18

 D. Is delivery address different from item 1?  Yes  
 If YES, enter delivery address below:  No

## 3. Service Type

- |  |   |
|--|---|
| <input type="checkbox"/> Adult Signature                               | <input type="checkbox"/> Priority Mail Express®                     |
| <input type="checkbox"/> Adult Signature Restricted Delivery           | <input type="checkbox"/> Registered Mail™                           |
| <input checked="" type="checkbox"/> Certified Mail®                    | <input type="checkbox"/> Registered Mail Restricted Delivery        |
| <input type="checkbox"/> Certified Mail Restricted Delivery            | <input type="checkbox"/> Return Receipt for Merchandise             |
| <input type="checkbox"/> Collect on Delivery                           | <input type="checkbox"/> Signature Confirmation™                    |
| <input type="checkbox"/> Collect on Delivery Restricted Delivery       | <input type="checkbox"/> Signature Confirmation Restricted Delivery |
| <input type="checkbox"/> Insured Mail                                  |   |
| <input type="checkbox"/> Insured Mail Restricted Delivery (over \$500) |   |

Domestic Return Receipt

**RECIPIENT: COMPLETE THIS SECTION**

Complete items 1, 2, and 3.  
Print your name and address on the reverse so that we can return the card to you.  
Attach this card to the back of the mailpiece, or on the front if space permits.

Article Addressed to:  
Confederated Tribes  
Warm Springs  
PO Box 460  
Warm Springs OR 97761

Article Number (Transfer from service label)  
018 0360 0001 0149 0530

**COMPLETE THIS SECTION ON DELIVERY**

A. Signature  
X *Jennifer Doney*  Agent  Addressee

B. Received by (Printed Name)  
Jennifer Doney

C. Date of Delivery  
6/27/18

D. Is delivery address different from item 1?  Yes  
If YES, enter delivery address below:  No

3. Service Type  
 Adult Signature  Priority Mail Express®  
 Adult Signature Restricted Delivery  Registered Mail™  
 Certified Mail®  Registered Mail Restricted Delivery  
 Certified Mail Restricted Delivery  Return Receipt for Merchandise  
 Collect on Delivery  Signature Confirmation™  
 Collect on Delivery Restricted Delivery  Signature Confirmation Restricted Delivery  
 Insured Mail  Signature Confirmation Restricted Delivery (over \$500)  
 Insured Mail Restricted Delivery (over \$500)

Form 3811, July 2015 PSN 7530-02-000-9053

Domestic Return Receipt

**SENDER: COMPLETE THIS SECTION**

Complete items 1, 2, and 3.  
Print your name and address on the reverse so that we can return the card to you.  
Attach this card to the back of the mailpiece, or on the front if space permits.

1. Article Addressed to:  
Confederated Indian Tribe  
PO Box 2547  
Longview WA  
98632-8594

Article Number (Transfer from service label)  
7018 0360 0001 0149 0547

2. Article Number (Transfer from service label)  
7018 0360 0001 0149 0547

PS Form 3811, July 2015 PSN 7530-02-000-9053

**COMPLETE THIS SECTION ON DELIVERY**

A. Signature  
X *Cathy R...*  Agent  Addressee

B. Received by (Printed Name)  
Cathy R...

C. Date of Delivery  
6/27/18

D. Is delivery address different from item 1?  Yes  
If YES, enter delivery address below:  No

3. Service Type  
 Adult Signature  Priority Mail Express®  
 Adult Signature Restricted Delivery  Registered Mail™  
 Certified Mail®  Registered Mail Restricted Delivery  
 Certified Mail Restricted Delivery  Return Receipt for Merchandise  
 Collect on Delivery  Signature Confirmation™  
 Collect on Delivery Restricted Delivery  Signature Confirmation Restricted Delivery  
 Insured Mail  Signature Confirmation Restricted Delivery (over \$500)  
 Insured Mail Restricted Delivery (over \$500)

Form 3811, July 2015 PSN 7530-02-000-9053

Domestic Return Receipt

**RECIPIENT: COMPLETE THIS SECTION**

Complete items 1, 2, and 3.  
Print your name and address on the reverse so that we can return the card to you.  
Attach this card to the back of the mailpiece, or on the front if space permits.

Article Addressed to:  
Confederated Tribes &  
Band of the Yakima  
Indian Nation  
PO Box 151  
Oppenish WA 98948

Article Number (Transfer from service label)  
018 0360 0001 0149 0509

**COMPLETE THIS SECTION ON DELIVERY**

A. Signature  
X *Verni Benson*  Agent  Addressee

B. Received by (Printed Name)  
Verni Benson

C. Date of Delivery  
6/27/18

D. Is delivery address different from item 1?  Yes  
If YES, enter delivery address below:  No

3. Service Type  
 Adult Signature  Priority Mail Express®  
 Adult Signature Restricted Delivery  Registered Mail™  
 Certified Mail®  Registered Mail Restricted Delivery  
 Certified Mail Restricted Delivery  Return Receipt for Merchandise  
 Collect on Delivery  Signature Confirmation™  
 Collect on Delivery Restricted Delivery  Signature Confirmation Restricted Delivery  
 Insured Mail  Signature Confirmation Restricted Delivery (over \$500)  
 Insured Mail Restricted Delivery (over \$500)

Form 3811, July 2015 PSN 7530-02-000-9053

Domestic Return Receipt

**SENDER: COMPLETE THIS SECTION**

Complete items 1, 2, and 3.  
Print your name and address on the reverse so that we can return the card to you.  
Attach this card to the back of the mailpiece, or on the front if space permits.

1. Article Addressed to:  
Umatilla Indian Nation  
4641 Timine Way  
Pendleton OR 97801-9467

Article Number (Transfer from service label)  
7018 0360 0001 0149 0523

2. Article Number (Transfer from service label)  
7018 0360 0001 0149 0523

PS Form 3811, July 2015 PSN 7530-02-000-9053

**COMPLETE THIS SECTION ON DELIVERY**

A. Signature  
X *Alvany McKay*  Agent  Addressee

B. Received by (Printed Name)  
Alvany McKay

C. Date of Delivery  
6/28/18

D. Is delivery address different from item 1?  Yes  
If YES, enter delivery address below:  No

3. Service Type  
 Adult Signature  Priority Mail Express®  
 Adult Signature Restricted Delivery  Registered Mail™  
 Certified Mail®  Registered Mail Restricted Delivery  
 Certified Mail Restricted Delivery  Return Receipt for Merchandise  
 Collect on Delivery  Signature Confirmation™  
 Collect on Delivery Restricted Delivery  Signature Confirmation Restricted Delivery  
 Insured Mail  Signature Confirmation Restricted Delivery (over \$500)  
 Insured Mail Restricted Delivery (over \$500)

Form 3811, July 2015 PSN 7530-02-000-9053

Domestic Return Receipt

**SENDER: COMPLETE THIS SECTION**

- Complete items 1, 2, and 3.
- Print your name and address on the reverse so that we can return the card to you.
- Attach this card to the back of the mailpiece, or on the front if space permits.

1. Article Addressed to:

Confederate Tribes of  
Grande Ronde  
9615 Grande Ronde Rd  
Grande Ronde OR  
97347-9712



9590 9402 3383 7227 1188 45

2. Article Number (Transfer from service label)

7018 0360 0001 0149 0516

PS Form 3811, July 2015 PSN 7530-02-000-9053

**COMPLETE THIS SECTION ON DELIVERY**

A. Signature

*[Signature]*

- Agent
- Addressee

B. Received by (Printed Name)

*A WHITE*

C. Date of Delivery

*6/27/18*

D. Is delivery address different from item 1? If YES, enter delivery address below:

- Yes
- No

3. Service Type

- Adult Signature
- Adult Signature Restricted Delivery
- Certified Mail®
- Certified Mail Restricted Delivery
- Collect on Delivery
- Collect on Delivery Restricted Delivery
- Insured Mail
- Insured Mail Restricted Delivery (over \$500)
- Priority Mail Express®
- Registered Mail™
- Registered Mail Restricted Delivery
- Return Receipt for Merchandise
- Signature Confirmation™
- Signature Confirmation Restricted Delivery

Domestic Return Receipt

USPS TRACKING#



9590 9402 3383 7227 1188 45

United States  
Postal Service

\* Sender: Please print your name, address, and ZIP+4® in this box

*Grande Ronde*

STERLING DESIGN, INC.  
2208 E. EVERGREEN BLVD.  
VANCOUVER, WA 98661

First-Class I  
Postage & F  
USPS  
Permit No. C

**SENDER: COMPLETE THIS SECTION**

- Complete items 1, 2, and 3.
- Print your name and address on the reverse so that we can return the card to you.
- Attach this card to the back of the mailpiece, or on the front if space permits.

1. Article Addressed to:

SNOALWATERBAY TRIBE  
PO BOX 130  
TOKELAND WA 98590



9590 9402 3383 7227 1188 83

2. Article Number (Transfer from service label)

7018 0360 0001 0149 0554

PS Form 3811, July 2015 PSN 7530-02-000-9053

**COMPLETE THIS SECTION ON DELIVERY**

A. Signature

*[Signature]*

- Agent
- Addressee

B. Received by (Printed Name)

*Brandt Blushes*

C. Date of Delivery

D. Is delivery address different from item 1? If YES, enter delivery address below:

- Yes
- No

3. Service Type

- Adult Signature
- Adult Signature Restricted Delivery
- Certified Mail®
- Certified Mail Restricted Delivery
- Collect on Delivery
- Collect on Delivery Restricted Delivery
- Insured Mail
- Insured Mail Restricted Delivery (over \$500)
- Priority Mail Express®
- Registered Mail™
- Registered Mail Restricted Delivery
- Return Receipt for Merchandise
- Signature Confirmation™
- Signature Confirmation Restricted Delivery

Domestic Return Receipt

USPS TRACKING#



9590 9402 3383 7227 1188 83

United States  
Postal Service

\* Sender: Please print your name, address, and ZIP+4® in this box

*Snoalwater*

STERLING DESIGN, INC.  
2208 E. EVERGREEN BLVD.  
VANCOUVER, WA 98661

First-Class M  
Postage & Fe  
USPS  
Permit No. G-

431708





## Community Development Department

### Notice of Application

#### Valley View Estates Subdivision

File No. SUB18-02

**“NOTICE IS HEREBY GIVEN”** that an application for “Valley View Estates Subdivision” a 36 lot single-family detached residential subdivision development requesting preliminary plat approval was received on May 18, 2018, and deemed technically complete on July 6, 2018. A public hearing is required for the Subdivision, and will be scheduled at a later time. A separate public notice for the public hearing will be mailed to all property owners within 300-feet of the subject development and published in the Post Record.


**LOCATION:** The 9.26 acre site is zoned single-family residential (R-7.5) and located in the NE ¼ quarter of Section 8, Township 1 North, Range 3 East of the Willamette Meridian; Camas, WA. Parcel Number includes 125646-000, and 125635-000.

**APPLICATION MATERIALS:** The application included the following: project narrative; preliminary plan set; geotechnical report; traffic report; critical areas report; archaeological report\*; preliminary storm water report; State Environmental Policy Act (SEPA) checklist; and other required submittal documents. These documents are available for viewing at the Community Development Department (616 NE 4<sup>th</sup> Avenue, Camas, WA) during regular business hours Monday – Friday 8am-5pm.

**Questions/Comments:** For questions related to this application, please contact Lauren Hollenbeck, Senior Planner, at (360) 817-1568 ext. 4253 or by email at [communitydevelopment@cityofcamas.us](mailto:communitydevelopment@cityofcamas.us).

\*Consistent with RCW 42.56.300, Archaeological information is exempt from public disclosure.

**Excerpt from Preliminary Plat Application  
Valley View Subdivision (File #18-02)**



Published in the Post Record on July 12, 2018  
 Posted on bulletin boards at Camas City Hall and the Camas Library and on the City's website.  
 Mailed to property owners within 300-feet on July 11, 2018

Legal publication No. 610375

**COMMUNITY DEVELOPMENT DEPARTMENT**

616 NE 4<sup>th</sup> Avenue  
 Camas, WA 98607  
 www.ci.camass.wa.us

June 13, 2018

Joel Stirling  
 Sterling Design, Inc.  
 2208 E. Evergreen Blvd.  
 Vancouver, WA 98661

RE: Valley View Estates Subdivision (SUB18-02)

Dear Mr. Stirling,

Thank you for your application submittal for the Valley View Estates Subdivision. There are items that remain to be addressed with your application. The purpose of this letter is to inform you that the above application submitted on May 18, 2018, has been deemed incomplete in accordance with Camas Municipal Code (CMC) Section 18.55.130. You have 180 days from the date of application to submit the missing information pursuant to CMC 18.55.130.C. If the below requested information is submitted, staff will again verify whether the application is complete.

**Items necessary for completeness:**

1. The signature page submitted with the SEPA checklist is from an old form. The signature page should contain the language "under the penalty of perjury". The current SEPA checklist is on the city website. Please resign and resubmit (via email is ok).
2. Per CMC 17.11.030.B.13, a narrative addressing the preliminary plat approval criteria in CMC 17.11.030.D (1-10).
3. Per CMC 16.31.160, provide proof of mailing or emailing the archaeological predetermination report to the tribes.
4. The following information shall be addressed on the site and development plans pursuant to CMC 17.11.030.B.6:
  - a. The following standards in CMC Section 17.01.050 shall be included on the preliminary plat map:
    - i. Critical areas (i.e. streams and steep slopes) and existing buildings per CMC 17.01.050.A.2;
    - ii. Legal description of the boundaries per CMC 17.01.050.A.4;
    - iii. Tract C should be included as recreational open space per CMC 17.01.050.B.3.g;
  - c. Lines marking the boundaries of the existing lot(s) (any existing lot to be eliminated should be a dashed line and so noted). For example, is Tax Lot 48 proposed to be removed?
  - j. Provide recorded documents of the nature and extent of existing easements (i.e. 30-ft. easements adjacent to existing gravel road).
  - m. Location of any critical areas and critical area buffers (i.e. steep slopes) to indicate compliance with all applicable provisions of critical areas legislation.
5. Revise and resubmit the TIR to comply with the 2014 SWMMWW, not the 2005 SWMMWW manual.

**Other preliminary project issues noted by staff to be addressed:**

1. Do not reference Clark County Stormwater O&M Manual in your reports. Only reference the City of Camas and/or Ecology Stormwater Manuals.
2. Proposed retaining walls will need to comply with CMC 18.17.060.

Please note, additional comments will be provided during further review of your application. If you have any questions, please contact me at (360) 817-7253.

Respectfully,

A handwritten signature in black ink that reads "Lauren Hollenbeck". The signature is written in a cursive, flowing style.

Lauren Hollenbeck  
Senior Planner



**COMMUNITY DEVELOPMENT DEPARTMENT**

616 NE 4<sup>th</sup> Avenue  
Camas, WA 98607  
[www.ci.camass.wa.us](http://www.ci.camass.wa.us)

July 6th, 2018

Joel Sterling  
Sterling Design, Inc.  
2208 E. Evergreen Blvd.  
Vancouver, WA 98661  
Sent via email [Mail@SterlingDesign.biz](mailto:Mail@SterlingDesign.biz)

RE: Valley View Estates (SUB18-02)

Dear Joel Sterling,

The purpose of this letter is to inform you that the above application submitted on May 24<sup>th</sup>, 2018 has been deemed complete in accordance with Camas Municipal Code (CMC) Section 18.55.130. Staff will begin reviewing the application and contact you should we have questions/comments.

If you have any questions, please contact me at (360) 817-7253.

Respectfully,

A handwritten signature in black ink that reads "Lauren Hollenbeck". The signature is written in a cursive, flowing style.

Lauren Hollenbeck  
Senior Planner

Cc: Robert Maul, Planning Manager  
Anita Ashton, Engineering Project Manager

**COMMUNITY DEVELOPMENT DEPARTMENT**

616 NE 4<sup>th</sup> Avenue  
Camas, WA 98607  
www.ci.camass.wa.us

August 24, 2018

Joel Sterling  
Sterling Design, Inc.  
2208 E. Evergreen Blvd.  
Vancouver, WA 98661  
Sent via email [Mail@SterlingDesign.biz](mailto:Mail@SterlingDesign.biz)

RE: Valley View Estates (SUB18-02)

Dear Joel Sterling,

The below comments are based on the City's review (**except Engineering which will be provided at a later date**) of the Preliminary Plat application materials submitted May 18, 2018, revised materials resubmitted May 24 and June 25, 2018 for the Valley View Estates Subdivision:

1. Per the City Parks Manager, the T-21 trail designation was used in the 2006 PROS plan and has since changed to T-24 per the current 2014 Parks, Recreation and Open Space Plan.
2. Is the segment of the trail running east/west part of Tract C?
3. Lot 1 building envelope should be reduced to comply with the required 20-ft. building setback from the tract per CMC 17.19.030.D.6.d
4. Lot 30 building envelope may be extended per the 5-foot corner lot rear yard setback requirement pursuant to CMC 18.09.040.
5. Land inventory should be corrected on sheet 2 of 9. Site area and developed acreage should be the same. The infrastructure acreage should only include the stormwater tracts.
6. The setbacks table should also include "corner lot rear yard" on sheet 2 of 9.
7. Lots 1, 19, 23, 24, 26, 27 and 32: Walls in front yards cannot exceed 42-inches in height per CMC 18.17.050.C.2.
8. Provide a cross-section for the walls surrounding lots 24-26. Retaining walls shall comply with CMC 18.17.060.
9. Lots 1 and 2: A minimum 4 or 6-ft. wall is permitted per double frontage standards CMC17.19.030.D.6.b.ii.
10. Recommend landscaping on sides of entry into Tract G.
11. Submit proof of mailing archaeological predetermination report to tribes.

Please note, additional comments will be provided during further review of your application. If you have any questions, please contact me at (360) 817-7253.

Respectfully,

A handwritten signature in black ink that reads "Lauren Hollenbeck". The signature is written in a cursive, flowing style.

Lauren Hollenbeck  
Senior Planner

## Notice of Public Hearing

### Valley View Estate Subdivision

File No. SUB18-02

A public hearing for the “Valley View Estates Subdivision” will be held on **October 18<sup>th</sup>, 2018, at 5:00 p.m.** or soon thereafter, at City Hall, 616 NE 4<sup>th</sup> Avenue, Camas, WA.

The Valley View Estates Subdivision was submitted by Sterling Design, Inc. for the owner, Stan Firestone, on May 24<sup>th</sup>, 2018 and was deemed technically complete on July 6<sup>th</sup>, 2018. The applicant requests approval of a 36-lot subdivision. The proposed project is located at 20109 NE 40<sup>th</sup> Street, on 9.26 acres [*Tax Parcel: 125646-000, 125636-000*]. The project area is zoned Single-family Residential 7,500 (R-7.5).

**APPLICATION MATERIALS:** The Valley View Estates preliminary plat (subdivision) application included the following: Application form and fees; Developer GIS packet; Mailing Labels; Project Narrative; Preliminary Plans; Pre-Application meeting notes; SEPA checklist, Preliminary Storm water Plan and Report; Geotechnical Report; Traffic Study; Environmental Report; and Archaeological Predetermination\*. These documents are available for viewing at the Community Development Department (616 NE 4<sup>th</sup> Avenue, Camas, WA) during regular business hours Monday – Friday 8am-5pm.

**Participate:** All citizens are entitled to have equal access to the services, benefits and programs of the City of Camas. Please contact the City Clerk at (360) 834-6864 for special accommodations if needed. The City will provide translators for non-English speaking persons who request assistance at least three working days prior to a public meeting.

Public comments and questions are encouraged, and there are several opportunities available to interested citizens. *It is preferable that written comments be received two days prior to the public hearing, in order to be available with the online agenda and materials.* With that said, comments can also be accepted during the public hearing. The public hearing will follow the quasi-judicial process described within Camas Municipal Code §18.55.180. Comments related to this development may be submitted as follows: (1) In person by testifying at the public hearing; (2) by regular mail to Planning Division staff, Lauren Hollenbeck, Senior Planner, at the Camas City Hall, 616 NE 4<sup>th</sup> Avenue, Camas, WA 98607; (3) by email to: [communitydevelopment@cityofcamas.us](mailto:communitydevelopment@cityofcamas.us); or (4) by phone (360) 817-7253. **For questions related to this application, please contact Lauren Hollenbeck, Senior Planner, at (360) 817-7253 or [communitydevelopment@cityofcamas.us](mailto:communitydevelopment@cityofcamas.us).**

---

\*Consistent with RCW 42.56.300, Archaeological information is exempt from public disclosure.

Published in the Post Record on October 4, 2018 [Legal Publication # 43310]

Posted at Camas City Hall, Camas Library, City of Camas web site at: <http://www.cityofcamas.us>

Mailed to property owners within 300-feet on October 3, 2018







Date Published: October 4<sup>th</sup>, 2018

To Whom It May Concern:

Please find enclosed a Mitigated Determination of Non-Significance (MDNS) for the **Valley View Estates Subdivision (SEPA18-15)** that was issued pursuant to the State Environmental Policy Act (SEPA) Rules, Chapter 197-11, Washington Administrative Code. The enclosed review comments reflect evaluation of the environmental checklist by the lead agency as required by WAC 197-11-330(1)(a)(i).

The following materials were submitted with the initial application:

- Application Form*
- Narrative*
- Preliminary Plans*
- Mailing Labels*
- SEPA Checklist*
- Stormwater Plan and Report*
- Geotechnical Report*
- Traffic Impact Study*
- Archeological Pre-Determination Report*
- Environmental Report*

The application materials are available for review upon request from the Community Development Department.

Written comments may be submitted on this determination within fourteen (14) days of its issuance, after which the MDNS will be reconsidered in light of the comments received.

Please address all correspondence to:

City of Camas, SEPA Official  
Community Development Department  
616 NE Fourth Avenue  
Camas, Washington 98607  
[communitydevelopment@cityofcamas.us](mailto:communitydevelopment@cityofcamas.us)

Distribution:

Bureau of Indian Affairs  
C-Tran  
Camas School District  
Camas City Administrator, Peter Capell  
Camas Building Official, Bob Cunningham  
Camas Community Development Director, Phil Bourquin  
Camas Engineering Department Managers and Staff  
Camas Fire Department, Randy Miller  
Camas Finance Director, Cathy Huber Nickerson  
Camas Mayor and City Council Members  
Camas Parks and Recreation, Jerry Acheson  
Camas Parks Commission Chair, Randy Curtis  
Camas Hearings Examiner  
Camas Planning Manager and Staff  
Camas Police Chief, Mitch Lackey  
Camas Public Works Director, Steve Wall  
Camas Public Library, Connie Urquhart  
Camas-Washougal Post Record  
Chinook Indian Nation  
Cultural Resource Program, Cowlitz Indian Tribe  
Cultural Resource Program, Yakama Indian Nation  
Clark County Department of Environmental Services  
Clark County Public Works – Development Engineering Program  
Clark County Department of Transportation  
Clark County Natural Resources Council  
Clark Public Utilities  
Department of Ecology  
Department of Fish and Wildlife, Region 5  
Department of Natural Resources, SEPA Center  
Southwest Clean Air Agency  
US Army Corps of Engineers  
Vancouver-Clark Parks and Recreation  
Washington Office of Archaeology & Historic Preservation  
Washington State Department of Transportation  
Washington State Parks and Recreation Commission, Environmental Program  
Property Owners within 300 feet  
Joel Sterling



State Environmental Policy Act  
Mitigated Determination of Non-Significance

**CASE NO:** SEPA 18-15 Valley View Estates Subdivision

**APPLICANT:** Sterling Design, Inc.  
Joel Sterling  
2208 East Evergreen Blvd  
Vancouver, WA 98661

**REQUEST:** To subdivide 9.26 acres into 36 single-family residential lots

**Location:** 20109 SE 40<sup>th</sup> Street Camas, WA 98607.

**Legal Description:** The property is located in the NW ¼ of Section 8, Township 1 North, Range 3 East, of the Willamette Meridian; and described as tax parcels 125646-000 and 125635-000.

**SEPA Determination:** Mitigated Determination of Non-Significance (MDNS)

**Comment Deadline:** **Thursday, October 18<sup>th</sup>, 2018, at 5:00 p.m.**

As lead agency under the State Environmental Policy Act (SEPA) Rules [Chapter 197-11, Washington Administrative Code (WAC)], the City of Camas must determine if there are possible significant adverse environmental impacts associated with this proposal. The options include the following:

- DS = Determination of Significance (The impacts cannot be mitigated through conditions of approval and, therefore, requiring the preparation of an Environmental Impact Statement (EIS).
- MDNS = Mitigated Determination of Non-Significance (The impacts can be addressed through conditions of approval), or;
- DNS = Determination of Non-Significance (The impacts can be addressed by applying the Camas Municipal Code).

**Determination:**

**Mitigated Determination of Non-Significance (MDNS).** The City of Camas, as lead agency for review of this proposal, has determined that this proposal does not have a probable significant adverse impact on the environment. An Environmental Impact Statement (EIS) is not required under RCW 43.21C.030(2)(e). This decision was made after review of a completed environmental checklist, and other information on file with the City of Camas.

**Date of Publication & Comment Period:**

Publication date of this MDNS is **October 4<sup>th</sup>, 2018**, and is issued under WAC 197-11-350. The lead agency will not act on this proposal until the close of the 14-day comment period, which ends on **October 18<sup>th</sup>, 2018**. Comments may be sent by email to [communitydevelopment@cityofcamas.us](mailto:communitydevelopment@cityofcamas.us).

**SEPA Appeal Process:**

An appeal of any aspect of this decision, including the SEPA determination and any required mitigation, must be filed with the Community Development Department within fourteen (14) calendar days from the date of the decision notice. The letter of appeal should contain the following information.

1. The case number designated by the City of Camas and the name of the applicant; and,
2. The name and signature of each person or group (petitioners) and a statement showing that each petitioner is entitled to file an appeal as described under Title 16 of the Camas Municipal Code. If multiple parties file a single petition for review, the petition shall designate one party as the contact representative with the City Planner. All contact with the City Planner regarding the petition, including notice, shall be with this contact person.

The appeal request and appropriate fee of **\$369** must be submitted to the Community Development Department between 8:00 a.m., and 5:00 p.m., Monday through Friday, at the address listed below:

Appeal to the City of Camas SEPA Official  
Community Development Department  
616 NE Fourth Avenue  
Camas, Washington 98607

**Responsible Official:** Robert Maul (360) 817-1568

	<b>October 4<sup>th</sup>, 2018</b>
<b>Robert Maul, Planning Manager and Responsible Official</b>	<b>Date of publication</b>

## SEPA Mitigation Measures for Valley View Estates (SEPA18-15)

The following measures are based on general policies and regulatory provisions, which are consistent with Camas 2035, the city's comprehensive plan document, and with the Camas Municipal Code.


### B) ENVIRONMENTAL ELEMENTS

#### 1) Earth

- a. Clearing and grading including utility and road construction activities shall be allowed only from May 1st to October 1st of each year. The City may extend or shorten the dry season on a case-by-case basis depending on actual weather conditions.

#### 3) Water

- a. All on-site LID options and requirements, per Ecology's latest edition of the Stormwater Management for Western Washington, shall be incorporated into the project such that stormwater shall not leave the site unless it is determined that all LID measures are infeasible.
- b. Prior to final Engineering approval, stormwater runoff from adjacent properties to the east, Tax Lots 125645-000 and 125634-000, shall be addressed in order to alleviate potential impacts to Valley View lots.



# VALLEY VIEW ESTATES

A Preliminary Subdivision  
 within in a portion of the  
 NE 1/4 of Sec. 8,  
 T1N., R3E., W.M.  
 Clark County, Washington

PREPARED BY:  
 STERLING DESIGN, INC.  
 1000 1/2 ST. N.  
 WASHINGTON, WA 98040  
 TEL: (206) 441-1111  
 FAX: (206) 441-1112

**STERLING DESIGN, INC.**


Sheet Description:  
 COVER SHEET

Project:  
 VALLEY VIEW ESTATES  
 SUBDIVISION



**LEGEND**

[Symbol]	PROPOSED ZONING
[Symbol]	PROPOSED LOT LINE
[Symbol]	EXISTING BOUNDARY
[Symbol]	PROPOSED SANITARY SEWER LINE
[Symbol]	PROPOSED STORM SEWER LINE
[Symbol]	PROPOSED PROPANE GAS LINE
[Symbol]	PROPOSED RADIANT CENTERLINE
[Symbol]	EXISTING ELECTRIC
[Symbol]	EXISTING TELEPHONE LOCATE PAINT
[Symbol]	EXISTING WATER LOCATE PAINT
[Symbol]	EXISTING EDGE OF PAVED DRIVE/DRIVE
[Symbol]	EXISTING SANITARY SEWER LINE
[Symbol]	EXISTING STORM LINE
[Symbol]	EXISTING FENCE
[Symbol]	EXISTING GRAVEL DRIVEWAY
[Symbol]	PROPOSED GRAVEL DRIVEWAY (P)
[Symbol]	EXISTING OR EXISTING PLAN
[Symbol]	PROPOSED CONTROL BUT FENCE
[Symbol]	ALLEY PROTECTION
[Symbol]	PROPOSED SANITARY CLEANOUT
[Symbol]	PROPOSED FIRE HYDRANT
[Symbol]	8 IN. 1" WATER SERVICE
[Symbol]	PROPOSED MANHOLE
[Symbol]	PROPOSED STINGLE
[Symbol]	PROPOSED CATCH BASIN
[Symbol]	PROPOSED COMBINATION CURB VALET
[Symbol]	PROPOSED STABILIZER
[Symbol]	PROPOSED DRIVEWAY
[Symbol]	EXISTING UTILITY
[Symbol]	EXISTING TELEPHONE
[Symbol]	EXISTING STORM SEWER
[Symbol]	EXISTING CATCH BASIN
[Symbol]	EXISTING GAS MAIN
[Symbol]	EXISTING ELECTRICAL SERVICE BOX
[Symbol]	EXISTING SANITARY MANHOLE
[Symbol]	EXISTING SANITARY CLEANOUT
[Symbol]	EXISTING FIRE HYDRANT
[Symbol]	EXISTING WATER SERVICE
[Symbol]	EXISTING WATER VALVE
[Symbol]	PROPOSED STREET TREES BY S.C.
[Symbol]	PROPOSED STREET LIGHTS BY S.C.



**SHEET INDEX**

COVER SHEET	1
PROPOSED DEVELOPMENT PLAN	2
PRELIMINARY TOPOGRAPHIC & BOUNDARY SURVEY	3
PROPOSED GRADING PLAN	4
PROPOSED DRAINAGE CONTROL PLAN	5
PROPOSED STORMWATER MANAGEMENT PLAN	6
PROPOSED UTILIZATION PLAN	7
PROPOSED TRANSPORTATION PLAN	8
PROPOSED LANDSCAPE & LIVING PLAN	9

**SITE DATA:**  
 - TAX LOT(S): 59 & 48  
 - SERIAL NUMBER(S): 125646-000 & 125635-000  
 - SITE ADDRESS: 20109 SE 40TH STREET  
 - AREA: 9.26 ACRES  
 - ZONING: R-7.5  
 - COMPREHENSIVE PLAN: UL

**CITY OF CAMAS PRE-APPLICATION NUMBER: PA18-09**

**DESIGN & DEVELOPMENT TEAM**

<b>PROPERTY OWNER:</b> TIME PROPERTIES 1000 1/2 ST. N. WASHINGTON, WA 98040 (206) 441-1111 <a href="http://www.timeproperties.com">www.timeproperties.com</a>	<b>CIVIL ENGINEER/          LAND USE PLANNING:</b> STERLING DESIGN, INC. 1000 1/2 ST. N. WASHINGTON, WA 98040 (206) 441-1111 <a href="http://www.sterlingdesign.com">www.sterlingdesign.com</a>	<b>SURVEYOR:</b> MUNSTER & CLAYSON SURVEYING, INC. 2200 E. EVERETT BLVD. VACAVOON, WA 98641 (360) 544-5373 FAX: (360) 544-5410 <a href="http://www.mcsurveys.com">www.mcsurveys.com</a>
--	--	---

**RECORD PLANS:**  
 RECORD PLANS FOR "LACHAS" IS NO. 5788  
 A PHASE 5B 11 IS CONVEYED ON THE WESTERLY  
 SIDE OF N.E. 12th AVE APPROXIMATELY 250 FEET  
 NORTH OF THE INTERSECTION OF N.E. 15th AVE AND  
 14th STREET. ELEVATION = 254.85; CITY OF CAMAS DATA

**NOTE:**  
 Existing utilities shown are approximate only from utility  
 records and are shown as they are. The contractor shall verify  
 the location, depth, size and slope of any and all existing  
 utilities prior to construction. Services are not shown  
 at (00) 424-3555.

**SITE INFORMATION**

ALIGNMENT & FIELD DATA SURVEYED BY: CLAYTON SURVEYING, INC. (206) 584-8810	Date: 10/20/17
SCALE: 1" = 40'	Project Number: 255
DATE PLOTTED: 10/20/17	Drawn: JCS/JC
DATE CHECKED: 10/20/17	Checked: JCS/JC
DATE APPROVED: 10/20/17	Issued: 10/20/17
DATE: 10/20/17	Sheet: 1 of 9

# WETLAND DETERMINATION REPORT

FOR THE

## SOUTHEAST 40<sup>TH</sup> SITE

*Prepared for:*

Firestone Pacific Developing  
C/O Stan Firestone  
P.O. Box 61928  
Vancouver, WA 98666  
360-772-3445

*Prepared by:*


Ecological Land Services, Inc.  
1157 3<sup>rd</sup> Avenue, Suite 220  
Longview, WA 98632  
360-578-1371

**October 18, 2007**

## SIGNATURE PAGE

The information and data in this report were compiled and prepared under the supervision and direction of the undersigned.

  
Amanda Castro  
Biologist

  
Kelsey Woods  
Biologist

  
Andrea Aberle  
Biologist/ Project Manager



## **TABLE OF CONTENTS**

---

<b>INTRODUCTION</b> .....	<b>1</b>
<b>METHODS</b> .....	<b>1</b>
<b>VEGETATION</b> .....	<b>2</b>
<b>SOILS</b> .....	<b>2</b>
<b>HYDROLOGY</b> .....	<b>2</b>
<b>NATIONAL AND LOCAL WETLANDS INVENTORIES</b> .....	<b>3</b>
<b>CLARK COUNTY CRITICAL AREAS MAPPING</b> .....	<b>3</b>
<b>CONCLUSIONS</b> .....	<b>3</b>
<b>LIMITATIONS</b> .....	<b>4</b>
<b>REFERENCES</b> .....	<b>5</b>

### **APPENDIX A**

#### **Figures**

- Figure 1 Vicinity Map
- Figure 2 Site Map
- Figure 3 Soil Survey Map
- Figure 4 National Wetlands Inventory (NWI) Map
- Figure 5 Clark County Sensitive Areas
- Figure 6 DNR Stream Typing Map

### **APPENDIX B**

#### **Routine On-site Wetland Determination Data Forms**

## **INTRODUCTION**

Ecological Land Services, Inc. (ELS) has completed a wetland determination for Firestone Pacific Developing on an approximately 11-acre site located at 20305 S.E. 40<sup>th</sup> Street in the City of Camas, Clark County, Washington (Figure 1). The site consists of four parcels (tax parcel numbers 125646-000, 125645-000, 125634-000, and 125635-000) located in the Northwest 1/4 of Section 8, Township 1 North, Range 3 East of the Willamette Meridian. The site was investigated for the presence of critical areas on October 5, 2007 in accordance with Camas Municipal Code (CMC 16.50). The property boundaries have not been professionally surveyed.

## **SITE DESCRIPTION**

Much of the subject site is pastureland with a few scattered trees. Site topography generally slopes south and west, with the lowest point being a man-made ditch in the southwestern region of the site. A single family residence is located in the northwestern region of the site (Figure 2). Surrounding land uses include residential homes to the east and west, NE 40<sup>th</sup> Street to the north and a functionally isolated wetland to the south. The residence is accessed by a paved driveway from Southeast 40<sup>th</sup> Street and a gravel driveway off of 202<sup>nd</sup> Court. A private road, 202<sup>nd</sup> Court, bisects the property and runs the entire length of the property from north to south. An above-ground water conveyance pipe, located near the southern property boundary in the eastern parcel, transports water draining from a neighboring development to the east. The pipe is approximately 320 feet long on-site, extending from the eastern property boundary to 202<sup>nd</sup> Court.

## **METHODS**

The wetland determination completed by ELS followed the Routine Determination Method for delineating wetlands according to the U.S. Army Corps of Engineers, *Wetlands Delineation Manual* (Environmental Laboratory 1987) and the Washington State Department of Ecology, *Washington State Wetlands Identification and Delineation Manual* (1997).

The Routine Determination Method examines three parameters—vegetation, hydrology, and soils—to determine if wetlands exist in a given area. Hydrology is critical in determining what is wetland but is often difficult to assess because hydrologic conditions can change periodically (hourly, daily, or seasonally). Consequently, it is necessary to determine if hydrophytic vegetation and hydric soils are present, which would indicate that water is present for long enough duration to support a wetland plant community. By definition, wetlands are those areas that are inundated or saturated by surface or ground water at a frequency and duration sufficient to support, and that under normal circumstances do support, a prevalence of vegetation typically adapted for life in saturated soil conditions. Wetlands are regulated as “Waters of the United States” by the U.S. Army Corps of Engineers (USACE), as “Waters of the State” by the Department of Ecology (DOE), and locally by Clark County.

ELS evaluated the property for wetlands on October 5, 2007. Vegetation, hydrology, and soil data were collected from six test plots. Test plots were chosen randomly throughout the property in order to verify the absence of wetland hydrology, soils, and vegetation.

## VEGETATION

Dominant vegetation observed within the perimeter of test plots are listed below. The indicator status, following the common and scientific names, indicates how likely a species is to be found in wetlands. Listed from most-likely to least-likely to be found in wetlands, the categories are:

- **OBL** (obligate wetland) - occur almost always (estimated probability >99%) under natural conditions in wetlands.
- **FACW** (facultative wetland) - usually occur in wetlands (estimated probability 67%-99%), but occasionally found in non-wetlands.
- **FAC** (facultative) - equally likely to occur in wetlands or non-wetlands (estimated probability 34%-66%).
- **FACU** (facultative upland) - usually occur in non-wetlands (estimated probability 67%-99%), but occasionally found in wetlands (estimated probability 1%-33%).
- **UPL** (obligate upland) - occur almost always (estimated probability >99%) under natural conditions in non-wetlands.
- **NI** (no indicator) - insufficient data to assign to an indicator category.
- A positive (+) or negative (-) sign, when used with indicators, attempts to more-specifically define the frequency of occurrence in wetlands. The positive sign indicates "slightly more frequently found in wetlands: and the negative sign indicates "slightly less-frequently found in wetlands".

On-site vegetation included tall fescue (*Festuca arundinacea*, FAC-), velvet grass (*Holcus lanatus*, FAC), English plantain (*Plantago lanceolata* var. *lanceolata*, FAC), northern bentgrass (*Agrostis borealis*, FACU).

## SOILS

On-site soil types are mapped as Hesson clay loam, 0-8 percent slopes (HcB), Olympic stony clay loam, 3-30 percent slopes (OmE) and Powell silt loam, 8-20 percent slopes (PoD; Figure 3). Hesson clay loam is a well drained soil occurring on high ridges along mountain foot slopes. Olympic stony clay loam is a well drained soil that occurs on ridgetops, on long side slopes, and on short slopes along drainage. Powell silt loam is a somewhat poorly drained soil that occurs on long, smooth side slopes below ridges and on foot slopes (NRCS 2006). None of the soils mapped on-site by the NRCS are listed as hydric in Clark County.

Soils observed on-site generally agreed with the mapped soil series. No hydric soils were located on-site during site investigation.

Mapped hydric soils do not necessarily mean that the area is a wetland; hydrology, wetland vegetation, and hydric soils must all be present to classify an area as a wetland. Conversely, wetlands may be found in areas where the soils are not mapped as hydric.

## HYDROLOGY

Soils on the subject site did not display primary or secondary hydric soil indicators above 10 inches below ground surface (BGS) as described in the USACE 1987 Wetlands Delineation Manual. Significant redoximorphic features, including oxidized root channels and/or Iron or

Manganese concretions were not observed in test holes to a depth of 16 inches BGS. Site topography generally sloped to the south with few or no depressional areas to trap water. Mottles were observed in some test plots; however, they are likely relic due to the absence of evidence of recent hydrology in the form of oxidized channels of living roots.

A Type N (non fish-bearing) stream is mapped off-site to the south by Washington Department of Natural Resources Stream Type Mapping (Figure 6). As mapped, the stream originates off-site to the east from the current location of a single family residence. This discrepancy is likely due to a mapping error. An above-ground pipe was located on-site near the southern property boundary and drains beneath 202<sup>nd</sup> Court into a man-made ditch in the western region of the property. DNR Stream Type maps are created on a large scale and can be inaccurate due to a lack of ground-truthing. There is an adjacent wetland south of parcel 125635-000 with a functionally isolated buffer, due to the existing gravel road. No wetland buffer will extend onto the site.

### **NATIONAL AND LOCAL WETLANDS INVENTORIES**

The National Wetlands Inventory (NWI) map did not show any wetlands on or adjacent to the subject site. ELS agrees that no wetlands are located on-site (Figure 4). As a cautionary note, National Wetlands Inventory map information should be used with discretion because they are used to gather general wetland information about a regional area; therefore, they are limited in accuracy for smaller sites because of their large scale.

The Clark County Wetland Inventory maps does not show any wetlands on or adjacent to the subject site. ELS agrees no wetland were located on-site (Figure 5).

### **CLARK COUNTY CRITICAL AREAS MAPPING**

The Clark County Priority Species-Habitat map shows a Riparian Habitat Conservation Area designated within the buffer of the mapped stream (Figure 5). ELS does not concur with the location of the mapped stream as shown encroaching within the site boundary. It is possible that a type Ns stream is located south of the site; ELS has not conducted field reconnaissance outside the site boundaries.

### **CONCLUSIONS**

ELS found no jurisdictional wetlands on the subject site. The upland areas investigated were dominated by facultative (FAC) and facultative upland (FACU) herbaceous vegetation. There were no hydrologic indicators present within 10 inches BGS in the form of redoximorphic features, oxidized root channels, and/or concretions. The soils mapped and observed on-site were not hydric.

#### **Buffers**

No wetlands or streams are present on-site. The wetland and stream located south of the subject site are functionally isolated by a gravel road. CMC states that pre-existing roads are excluded from the buffer, terminating the buffer to the south (CMC 16.60.040 (B)(4)(b)(i)).

## **LIMITATIONS**

---

*We base the above listed determinations and conclusions on standard scientific methodology and best professional judgment. In our opinion, the conclusions should agree with local, state, and federal regulatory agencies. However, it should be considered a Preliminary Jurisdictional Determination and used at your own risk until it has been reviewed and approved in writing by the appropriate regulatory agencies.*

## REFERENCES

---

Camas Municipal Code. <http://bpc.iserver.net/codes/camas/index.htm>. Accessed October 2007.

Clark County Geographic Information System website. <http://gis.clark.wa.gov/applications/gishome/index.cfm>. Accessed October 2007.

Environmental Laboratory. 1987. Corps of Engineers Wetlands Delineation Manual. Technical Report Y-87-1. U.S. Army Waterways Experiment Station, Vicksburg, Mississippi.

Hruby, T. 2006. Washington State Wetland Rating System for Western Washington – Revised. Washington State Department of Ecology Publication #04-06-025.

Soils Conservation Service. 2006. Hydric Soils for Washington. Online document<[http://soils.usda.gov/soils\\_use/hydric/states/wa.htm](http://soils.usda.gov/soils_use/hydric/states/wa.htm)>. Accessed October 2007.

U.S.D.A. Natural Resources Conservation Service website for Clark County. Accessed October 2007. [http://www.or.nrcs.usda.gov/pnw\\_soil/washington/wa015.html](http://www.or.nrcs.usda.gov/pnw_soil/washington/wa015.html).

Washington State Department of Ecology. 1997. Washington State Wetlands Identification and Delineation Manual. Publication #96-94. Olympia, Washington.

## Appendix A

### Figures





9/5/2007 9:14 AM S:\Clark-WA\Camas\1543-Firestone\1543.02-SE 40th Street Site\1543.02-Figures\1543.02\_Figures\_101807.dwg maureenm



**LEGEND:**

- Site Boundary
- Parcel Boundary
- 125635-000 Parcel Number
- TP-1 ● Test Plot Location
- Above Ground Pipe
- Man-Made Ditch
- Existing Gravel Driveway

**NOTE:** Base map from Google Earth™, 2007.

**ECOLOGICAL LAND SERVICES, INC.**  
 1157 3rd Ave., Suite 220 Longview, WA 98632  
 (360) 578-1371 Fax: (360) 414-9305

DATE: 10/18/07  
 DWN: KLM  
 REQ. BY: AC  
 PRJ. MGR: AA  
 CHK:  
 APPR:  
 PROJ#: 1543.02

Figure 2  
**AERIAL SITE MAP**  
 SE 40th Street  
 Stan Firestone  
 City of Camas, Clark County, Washington  
 Section 8, Township 1N , Range 3E, W.M.

9/5/2007 9:14 AM S:\Clark-WA\Camas\1543-Firestone\1543.02-SE 40th Street Site\1543.02-Figures\1543.02-Figures\_10907.dwg kristin



- PoB - Powell silt loam, 0 to 8 percent slopes. Not hydric.
- PoD - Powell silt loam, 8 to 20 percent slopes. Not hydric.
- PoE - Powell silt loam, 20 to 30 percent slopes. Not hydric.
- HcB - Hesson clay loam, 8 to 20 percent slopes. Not hydric.
- OmE - Olympic stony clay loam, 3 to 30 percent slopes. Not hydric.

**NOTE:** Map provided on-line by NRCS at web address:  
[www.wa.nrcs.usda.gov/pnw\\_soil/wa\\_reports.html](http://www.wa.nrcs.usda.gov/pnw_soil/wa_reports.html)

 **ECOLOGICAL LAND SERVICES, INC.**  
 1157 3rd Ave., Suite 220 Longview, WA 98632  
 (360) 578-1371 Fax: (360) 414-9305

DATE: 10/9/07  
 DWN: KLM  
 REQ. BY: AC  
 PRJ. MGR: AA  
 CHK:  
 APPR:  
 PROJ.#: 1543.02

Figure 3  
 SOIL SURVEY MAP  
 SE 40th Street  
 Stan Firestone  
 City of Camas, Clark County, Washington  
 Section 8, Township 1N, Range 3E, W.M.

9/5/2007 9:14 AM S:\Clark-WA\Camas\1543-Firestone\1543.02-SE 40th Street Sital\1543.02-Figures\1543.02\_Figures\_101807.dwg kristin



No mapped wetlands indicated on site by US Fish & Wildlife Service.



**NOTES:**

1. Map provided on-line by US Fish & Wildlife Service at web address: <http://www.wetlandsfws.er.usgs.gov/NWI/index.html>
2. Map not to scale. Property boundary location and size is approximate.



1157 3rd Ave., Suite 220 Longview, WA 98632  
(360) 578-1371 Fax: (360) 414-9305

DATE: 10/18/07  
DWN: KLM  
REQ. BY: AC  
PRJ. MGR: AA  
CHK:  
APPR:  
PROJ.#: 1543.02

Figure 4  
NATIONAL WETLANDS INVENTORY MAP  
SE 40th Street  
Stan Firestone  
City of Camas, Clark County, Washington  
Section 8, Township 1N, Range 3E, W.M.

9/5/2007 9:14 AM S:\Clark-WA\Camas\1543-Firestone\1543.02-SE 40th Street Site\1543.02-Figures\1543.02-Figures\_101807.dwg maureenm

Clark County Wetland and Hydric Soils Inventory  
No Wetlands Mapped On-site



**SITE**



Clark County Species-Habitat



**SITE**



Clark County Topography



**SITE**



**NOTE:** Map provided on-line by Clark County, Washington at web address: <http://gis.clark.wa.gov/gishome/property>



**ECOLOGICAL LAND SERVICES, INC.**

1157 3rd Ave., Suite 220 Longview, WA 98632  
(360) 578-1371 Fax: (360) 414-9305

DATE: 10/18/07  
DWN: KLM  
REQ. BY: AC  
PRJ. MGR: AA  
CHK:  
APPR:  
PROJ.#: 1543.02

Figure 5  
SENSITIVE & HABITAT AREAS MAP  
SE 40th Street  
Stan Firestone  
City of Camas, Clark County, Washington  
Section 8, Township 1N, Range 3E, W.M.

9/5/2007 9:14 AM S:\Clark-WA\Camas\1543-Firestone\1543.02-SE 40th Street Site\1543.02-Figures\1543.02\_Figures\_10907.dwg kristin




SITE

No mapped streams indicated on site by Department of Natural Resources (DNR).

**LEGEND:**

 Stream Type, F, N, U



**NOTE:** Map provided on-line by Washington State Department of Natural Resources at web address: <http://www3.wadnr.gov/dnrapp5/website/fpars/viewer.htm>



**ECOLOGICAL LAND SERVICES, INC.**  
11 57 3rd Ave., Suite 220 Longview, WA 98632  
(360) 578-1371 Fax: (360) 414-9305

DATE: 10/10/07  
DWN: KLM  
REQ. BY: AC  
PRJ. MGR: AA  
CHK:  
APPR:  
PROJ.#: 1543.02

Figure 6  
DNR STREAM TYPING MAP  
SE 40th Street  
Stan Firestone  
City of Camas, Clark County, Washington  
Section 8, Township 1N, Range 3E, W.M.

## **Appendix B**

### **Routine On-site Wetland Determination Data Forms**



**ECOLOGICAL LAND SERVICES, INC.**

1157 3<sup>rd</sup> Avenue, Suite 220, Longview, Washington 98632  
 (360)578-1371 FAX (360)414-9305  
 DATA FORM - Routine Onsite Wetland Determination  
 1987 COE Wetlands Delineation Manual  
 1997 Washington State Delineation Manual

Project Site: SE 40 <sup>th</sup> St	Date: 10/5/07	Project #: 1543.02
Applicant/Owner: Stan Firestone	County/State: Clark, WA	
Test Plot Location: E of SE 202 <sup>nd</sup> Ct in southern region	Sec/Town/Range: S08, T1N, R3E	

Do normal circumstances exist at the site?	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Plot ID: TP1
Is the site significantly disturbed (atypical situation)?	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Community ID: --
Is the site a potential problem area?	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Transect ID: --

**VEGETATION** (Strata: tree, sapling, shrub, woody vine, herb)

Dominant Plant Species

Common Name	Scientific Name	Strata	% Cover	Indicator Status
1. Trailing blackberry*	<i>Rubus ursinus</i>	Herb	20	FACU
2. Tall fescue	<i>Festuca arundinacea</i>	Herb	10	FAC-
3. Velvet grass*	<i>Holcus lanatus</i>	Herb	20	FAC
4. Northern bentgrass*	<i>Agrostis borealis</i>	Herb	40	FACU
5. Canadian thistle	<i>Cirsium arvense</i>	Herb	10	FACU+
6.		-		-
7.		-		-
8.		-		-

Other species present: English plantain trace  
 % of dominant species OBL, FACW, FACW-, FAC+, FAC 33% (more than 50% required)  
 Remarks: \* = dominant species per the 50/20 rule.

Vegetation Criteria Met?  Yes  No

**HYDROLOGY**

Recorded data available?  Yes  No  
 Is it the growing season?  Yes  No  
 Is site inundated?  Yes  No

Depth of surface water: N/A  
 Depth to free water in pit: N/A  
 Depth to saturated soils: N/A

Type(s): --

Wetland Hydrology Indicators

<u>Primary Indicators</u> <input type="checkbox"/> Inundated <input type="checkbox"/> Saturated < 12 in. <input type="checkbox"/> Water Marks <input type="checkbox"/> Drift Lines <input type="checkbox"/> Sediment Deposits <input type="checkbox"/> Drainage Patterns in wetlands	<u>Secondary Indicators (2 required)</u> <input type="checkbox"/> Oxidized Root Channels < 12in. bgs <input type="checkbox"/> Local Soil Survey Data <input type="checkbox"/> Water Stained Leaves <input type="checkbox"/> FAC-Neutral Test <input type="checkbox"/> Other (Explain in remarks)
--	---

Hydrology Criteria Met?  Yes  No

Remarks:

**SOILS:**

Map Unit Name: Hesson clay loam (HcB)  
 (Series and Phase)  
 Taxonomy (Subgroup): Clayey, kaolinitic, mesic Xeric Palehumults

Field observations confirm mapped soil type?  Yes  No

Drainage Class:

<input type="checkbox"/> Excessively Drained
<input type="checkbox"/> Somewhat Excessively Drained
<input checked="" type="checkbox"/> Well Drained
<input type="checkbox"/> Moderately Well Drained
<input type="checkbox"/> Somewhat Poorly Drained
<input type="checkbox"/> Poorly Drained
<input type="checkbox"/> Very Poorly Drained

Profile Description

Depth (inches)	Horizon	Matrix color	Mottle Color	Mottle Abundance (few, common, many)	Mottle Size (fine, med, coarse)	Texture
0-12"	-	10YR 3/3	-	-	-	silt loam

Hydric Soil Indicators

<input type="checkbox"/> Histosol (-ists)	<input type="checkbox"/> Reducing Conditions	<input type="checkbox"/> Organic Streaking in Sandy Soils
<input type="checkbox"/> Histic Epipedon (8-16")	<input type="checkbox"/> Gleyed or Low Chroma Colors	<input type="checkbox"/> Organic Pans
<input type="checkbox"/> Sulfidic Odor	<input type="checkbox"/> Mn or Fe Concretions	<input type="checkbox"/> Listed on Local Hydric Soils List
<input type="checkbox"/> Aquic Moisture Regime	<input type="checkbox"/> High Organic Content in Layer of Sandy Soils	<input type="checkbox"/> Other (explain in remarks)

Remarks: charcoal observed throughout 0-12"

Soils Criteria Met?  Yes  No

**WETLAND DETERMINATION**

Hydrophytic Vegetation Dominant?  Yes  No  
 Wetland Hydrology Present?  Yes  No  
 Hydric Soil Present?  Yes  No

Remarks: Wetland criteria not met

Is test plot within a wetland?  Yes  No



# ECOLOGICAL LAND SERVICES, INC.

1157 3<sup>rd</sup> Avenue, Suite 220, Longview, Washington 98632  
 (360)578-1371 FAX (360)414-9305  
 DATA FORM – Routine Onsite Wetland Determination  
 1987 COE Wetlands Delineation Manual  
 1997 Washington State Delineation Manual

Project Site: SE 40 <sup>th</sup> St	Date: 10/5/07	Project #: 1543.02
Applicant/Owner: Stan Firestone	County/State: Clark, WA	
Test Plot Location: East Central of SE 202 <sup>nd</sup> Ct.	Sec/Town/Range: S08, T1N, R3E	

Do normal circumstances exist at the site?	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Plot ID: TP2
Is the site significantly disturbed (atypical situation)?	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Community ID: --
Is the site a potential problem area?	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Transect ID: --

**VEGETATION** (Strata: tree, sapling, shrub, woody vine, herb)

**Dominant Plant Species**

Common Name	Scientific Name	Strata	% Cover	Indicator Status
1. Velvet grass*	<i>Holcus lanatus</i>	Herb	50	FAC
2. Soft rush*	<i>Juncus effusus</i>	Herb	40	FACW
3. Evergreen blackberry*	<i>Rubus laciniatus</i>	Shrub	5	FACU
4. Himalayan blackberry*	<i>Rubus armeniacus</i>	Shrub	5	FACU
5.		-		-
6.		-		-
7.		-		-
8.		-		-

Other species present: Reed canary grass-trace, Canadian thistle-trace  
 % of dominant species OBL, FACW, FACW-, FAC+, FAC 50% (more than 50% required)  
 Remarks: \* = dominant species per the 50/20 rule.

Vegetation Criteria Met?  Yes  No

**HYDROLOGY**

Recorded data available?  Yes  No  
 Is it the growing season?  Yes  No  
 Is site inundated?  Yes  No

Depth of surface water: N/A  
 Depth to free water in pit: N/A  
 Depth to saturated soils: N/A

Type(s): --

**Wetland Hydrology Indicators**

<b>Primary Indicators</b>	<b>Secondary Indicators (2 required)</b>
<input type="checkbox"/> Inundated	<input type="checkbox"/> Oxidized Root Channels < 12in. bgs
<input type="checkbox"/> Saturated < 12 in.	<input type="checkbox"/> Local Soil Survey Data
<input type="checkbox"/> Water Marks	<input type="checkbox"/> Water Stained Leaves
<input type="checkbox"/> Drift Lines	<input type="checkbox"/> FAC-Neutral Test
<input type="checkbox"/> Sediment Deposits	<input type="checkbox"/> Other (Explain in remarks)
<input type="checkbox"/> Drainage Patterns in wetlands	

Hydrology Criteria Met?  Yes  No

Remarks:

**SOILS:**

Map Unit Name: Powell silt loam (PoB)  
 (Series and Phase)  
 Taxonomy (Subgroup): Fine silty, mixed, mesic Typic Fragiochrepts

Field observations confirm mapped soil type?  Yes  No

**Drainage Class:**

<input type="checkbox"/> Excessively Drained
<input type="checkbox"/> Somewhat Excessively Drained
<input type="checkbox"/> Well Drained
<input type="checkbox"/> Moderately Well Drained
<input checked="" type="checkbox"/> Somewhat Poorly Drained
<input type="checkbox"/> Poorly Drained
<input type="checkbox"/> Very Poorly Drained

**Profile Description**

Depth (inches)	Horizon	Matrix color	Mottle Color	Mottle Abundance (few, common, many)	Mottle Size (fine, med, coarse)	Texture
0-14"	-	10YR 3/4	10YR 4/6	common	medium	silt loam

**Hydric Soil Indicators**

<input type="checkbox"/> Histosol (-ists)	<input type="checkbox"/> Reducing Conditions	<input type="checkbox"/> Organic Streaking in Sandy Soils
<input type="checkbox"/> Histic Epipedon (8-16")	<input type="checkbox"/> Gleyed or Low Chroma Colors	<input type="checkbox"/> Organic Pans
<input type="checkbox"/> Sulfidic Odor	<input type="checkbox"/> Mn or Fe Concretions	<input type="checkbox"/> Listed on Local Hydric Soils List
<input type="checkbox"/> Aquic Moisture Regime	<input type="checkbox"/> High Organic Content in Layer of Sandy Soils	<input type="checkbox"/> Other (explain in remarks)

Remarks: charcoal observed throughout 0-14"

Soils Criteria Met?  Yes  No

**WETLAND DETERMINATION**

Hydrophytic Vegetation Dominant?  Yes  No  
 Wetland Hydrology Present?  Yes  No  
 Hydric Soil Present?  Yes  No

Remarks: Wetland criteria not met

Is test plot within a wetland?  Yes  No





**ECOLOGICAL LAND SERVICES, INC.**

1157 3<sup>rd</sup> Avenue, Suite 220, Longview, Washington 98632  
 (360)578-1371 FAX (360)414-9305  
 DATA FORM – Routine Onsite Wetland Determination  
 1987 COE Wetlands Delineation Manual  
 1997 Washington State Delineation Manual

Project Site: SE 40 <sup>th</sup> St.	Date: 10/5/07	Project #: 1543.02
Applicant/Owner: Stan Firestone	County/State: Clark, WA	
Test Plot Location: Northeast of SE 202nd Ct.	Sec/Town/Range: S08, T1N, R3E	

Do normal circumstances exist at the site?	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Plot ID: TP3
Is the site significantly disturbed (atypical situation)?	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Community ID: --
Is the site a potential problem area?	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Transect ID: --

**VEGETATION** (Strata: tree, sapling, shrub, woody vine, herb)

**Dominant Plant Species**

Common Name	Scientific Name	Strata	% Cover	Indicator Status
1. Tall fescue*	<i>Festuca arundinacea</i>	Herb	100	FAC-
2.		-		-
3.		-		-
4.		-		-
5.		-		-
6.		-		-
7.		-		-
8.		-		-

Other species present: velvet grass trace  
 % of dominant species OBL, FACW, FACW-, FAC+, FAC 0% (more than 50% required)  
 Remarks: \* = dominant species per the 50/20 rule.

Vegetation Criteria Met?  Yes  No

**HYDROLOGY**

Recorded data available?  Yes  No  
 Is it the growing season?  Yes  No  
 Is site inundated?  Yes  No

Depth of surface water: N/A  
 Depth to free water in pit: N/A  
 Depth to saturated soils: N/A

Type(s): --

**Wetland Hydrology Indicators**

**Primary Indicators**

- Inundated
- Saturated < 12 in.
- Water Marks
- Drift Lines
- Sediment Deposits
- Drainage Patterns in wetlands

**Secondary Indicators (2 required)**

- Oxidized Root Channels < 12in. bgs
- Local Soil Survey Data
- Water Stained Leaves
- FAC-Neutral Test
- Other (Explain in remarks)

Hydrology Criteria Met?  Yes  No

Remarks:

**SOILS:**

Map Unit Name: Powell silt loam (PoB)  
 (Series and Phase)  
 Taxonomy (Subgroup): Fine silty, mixed, mesic Typic Fragiochrepts

Field observations confirm mapped soil type?  Yes  No

**Drainage Class:**

- Excessively Drained
- Somewhat Excessively Drained
- Well Drained
- Moderately Well Drained
- Somewhat Poorly Drained
- Poorly Drained
- Very Poorly Drained

**Profile Description**

Depth (inches)	Horizon	Matrix color	Mottle Color	Mottle Abundance (few, common, many)	Mottle Size (fine, med, coarse)	Texture
0-15"	-	10YR 3/2	-	-	-	silt loam
15-16"	-	10YR 4/3	10YR 4/6	common	medium	silt loam

**Hydric Soil Indicators**

- Histosol (-ists)
- Histic Epipedon (8-16")
- Sulfidic Odor
- Aquic Moisture Regime
- Reducing Conditions
- Gleyed or Low Chroma Colors
- Mn or Fe Concretions
- High Organic Content in Layer of Sandy Soils
- Organic Streaking in Sandy Soils
- Organic Pans
- Listed on Local Hydric Soils List
- Other (explain in remarks)

Remarks: charcoal observed throughout 0-16"

Soils Criteria Met?  Yes  No

**WETLAND DETERMINATION**

Hydrophytic Vegetation Dominant?  Yes  No  
 Wetland Hydrology Present?  Yes  No  
 Hydric Soil Present?  Yes  No

Remarks: Wetland criteria not met

Is test plot within a wetland?  Yes  No



# ECOLOGICAL LAND SERVICES, INC.

1157 3<sup>rd</sup> Avenue, Suite 220, Longview, Washington 98632  
 (360)578-1371 FAX (360)414-9305  
 DATA FORM - Routine Onsite Wetland Determination  
 1987 COE Wetlands Delineation Manual  
 1997 Washington State Delineation Manual

Project Site: SE 40 <sup>th</sup> St	Date: 10/5/07	Project #: 1543.02
Applicant/Owner: Stan Firestone	County/State: Clark, WA	
Test Plot Location: Northwest of SE 202 <sup>nd</sup> Ct	Sec/Town/Range: S08, T1N, R3E	

Do normal circumstances exist at the site?	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Plot ID: TP4
Is the site significantly disturbed (atypical situation)?	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Community ID: --
Is the site a potential problem area?	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Transect ID: --

**VEGETATION** (Strata: tree, sapling, shrub, woody vine, herb)

**Dominant Plant Species**

Common Name	Scientific Name	Strata	% Cover	Indicator Status
1. Himalayan blackberry	<i>Rubus armeniacus</i>	Shrub	5	FACU
2. English hawthorne*	<i>Crataegus monogyna</i>	Shrub	40	FAC
3. Tall fescue	<i>Festuca arundinacea</i>	Herb	10	FAC-
4. Northern bentgrass*	<i>Agrostis borealis</i>	Herb	75	FACU
5. Lance-leaf plantain	<i>Plantago lanceolata</i>	Herb	10	FAC
6.		-		-
7.		-		-
8.		-		-

Other species present:  
 % of dominant species OBL, FACW, FACW-, FAC+, FAC 50% (more than 50% required)  
 Remarks: \* = dominant species per the 50/20 rule.

Vegetation Criteria Met?  Yes  No

**HYDROLOGY**

Recorded data available?  Yes  No  
 Is it the growing season?  Yes  No  
 Is site inundated?  Yes  No

Depth of surface water: N/A  
 Depth to free water in pit: N/A  
 Depth to saturated soils: N/A

Type(s): --

**Wetland Hydrology Indicators**

<b>Primary Indicators</b> <input type="checkbox"/> Inundated <input type="checkbox"/> Saturated < 12 in. <input type="checkbox"/> Water Marks <input type="checkbox"/> Drift Lines <input type="checkbox"/> Sediment Deposits <input type="checkbox"/> Drainage Patterns in wetlands	<b>Secondary Indicators (2 required)</b> <input type="checkbox"/> Oxidized Root Channels < 12in. bgs <input type="checkbox"/> Local Soil Survey Data <input type="checkbox"/> Water Stained Leaves <input type="checkbox"/> FAC-Neutral Test <input type="checkbox"/> Other (Explain in remarks)
--	---

Hydrology Criteria Met?  Yes  No

Remarks:

**SOILS:**

Map Unit Name: Powell silt loam (PoB)  
 (Series and Phase)  
 Taxonomy (Subgroup): Fine silty, mixed, mesic Typic Fragiochrepts

Field observations confirm mapped soil type?  Yes  No

**Drainage Class:**

<input type="checkbox"/> Excessively Drained <input type="checkbox"/> Somewhat Excessively Drained <input type="checkbox"/> Well Drained <input type="checkbox"/> Moderately Well Drained <input checked="" type="checkbox"/> Somewhat Poorly Drained <input type="checkbox"/> Poorly Drained <input type="checkbox"/> Very Poorly Drained
--

**Profile Description**

Depth (inches)	Horizon	Matrix color	Mottle Color	Mottle Abundance (few, common, many)	Mottle Size (fine, med, coarse)	Texture
0-16"	-	10YR 3/3	-	-	-	silt loam

**Hydric Soil Indicators**

<input type="checkbox"/> Histosol (-ists) <input type="checkbox"/> Histic Epipedon (8-16") <input type="checkbox"/> Sulfidic Odor <input type="checkbox"/> Aquic Moisture Regime	<input type="checkbox"/> Reducing Conditions <input type="checkbox"/> Gleyed or Low Chroma Colors <input type="checkbox"/> Mn or Fe Concretions <input type="checkbox"/> High Organic Content in Layer of Sandy Soils	<input type="checkbox"/> Organic Streaking in Sandy Soils <input type="checkbox"/> Organic Pans <input type="checkbox"/> Listed on Local Hydric Soils List <input type="checkbox"/> Other (explain in remarks)
---	--	---

Remarks: charcoal observed throughout 0-12"

Soils Criteria Met?  Yes  No

**WETLAND DETERMINATION**

Hydrophytic Vegetation Dominant?  Yes  No  
 Wetland Hydrology Present?  Yes  No  
 Hydric Soil Present?  Yes  No

Remarks: Wetland criteria not met

Is test plot within a wetland?  Yes  No



# ECOLOGICAL LAND SERVICES, INC.

1157 3<sup>rd</sup> Avenue, Suite 220, Longview, Washington 98632  
 (360)578-1371 FAX (360)414-9305  
 DATA FORM - Routine Onsite Wetland Determination  
 1987 COE Wetlands Delineation Manual  
 1997 Washington State Delineation Manual

Project Site: SE 40 <sup>th</sup> St	Date: 10/5/07	Project #: 1543.02
Applicant/Owner: Stan Firestone	County/State: Clark, WA	
Test Plot Location: Northwest of SE 202 <sup>nd</sup> Ct.	Sec/Town/Range: S08, T1N, R3E	

Do normal circumstances exist at the site?	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Plot ID: TP5
Is the site significantly disturbed (atypical situation)?	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Community ID: --
Is the site a potential problem area?	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Transect ID: --

**VEGETATION** (Strata: tree, sapling, shrub, woody vine, herb)

**Dominant Plant Species**

Common Name	Scientific Name	Strata	% Cover	Indicator Status
1. Himalayan blackberry*	<i>Rubus armeniacus</i>	Shrub	15	FACU
2. Tall fescue	<i>Festuca arundinacea</i>	Herb	15	FAC-
3. Pearly everlasting	<i>Anaphalis margaritacea</i>	Herb	5	NI
4. Northern bentgrass*	<i>Agrostis borealis</i>	Herb	40	FACU
5. Lance-leaf plantain*	<i>Plantago lanceolata</i>	Herb	25	FAC
6.		-		-
7.		-		-
8.		-		-

Other species present:  
 % of dominant species OBL, FACW, FACW-, FAC+, FAC 33% (more than 50% required)  
 Remarks: \* = dominant species per the 50/20 rule.

Vegetation Criteria Met?  Yes  No

**HYDROLOGY**

Recorded data available?  Yes  No  
 Is it the growing season?  Yes  No  
 Is site inundated?  Yes  No

Depth of surface water: N/A  
 Depth to free water in pit: N/A  
 Depth to saturated soils: N/A

Type(s): --

**Wetland Hydrology Indicators**

<b>Primary Indicators</b> <input type="checkbox"/> Inundated <input type="checkbox"/> Saturated < 12 in. <input type="checkbox"/> Water Marks <input type="checkbox"/> Drift Lines <input type="checkbox"/> Sediment Deposits <input type="checkbox"/> Drainage Patterns in wetlands	<b>Secondary Indicators (2 required)</b> <input type="checkbox"/> Oxidized Root Channels < 12in. bgs <input type="checkbox"/> Local Soil Survey Data <input type="checkbox"/> Water Stained Leaves <input type="checkbox"/> FAC-Neutral Test <input type="checkbox"/> Other (Explain in remarks)
--	---

Hydrology Criteria Met?  Yes  No

Remarks:

**SOILS:**

Map Unit Name: Hesson clay loam (HcB)  
 (Series and Phase)  
 Taxonomy (Subgroup): Clayey, kaolinitic, mesic Xeric Palehumults

Field observations confirm mapped soil type?  Yes  No

**Drainage Class:**

<input type="checkbox"/> Excessively Drained
<input type="checkbox"/> Somewhat Excessively Drained
<input checked="" type="checkbox"/> Well Drained
<input type="checkbox"/> Moderately Well Drained
<input type="checkbox"/> Somewhat Poorly Drained
<input type="checkbox"/> Poorly Drained
<input type="checkbox"/> Very Poorly Drained

**Profile Description**

Depth (inches)	Horizon	Matrix color	Mottle Color	Mottle Abundance (few, common, many)	Mottle Size (fine, med, coarse)	Texture
0-10"	-	10YR 3/3	-	-	-	silt loam
11-13"	-	10YR 4/4	-	-	-	silt loam

**Hydric Soil Indicators**

<input type="checkbox"/> Histosol (-ists)	<input type="checkbox"/> Reducing Conditions	<input type="checkbox"/> Organic Streaking in Sandy Soils
<input type="checkbox"/> Histic Epipedon (8-16")	<input type="checkbox"/> Gleyed or Low Chroma Colors	<input type="checkbox"/> Organic Pans
<input type="checkbox"/> Sulfidic Odor	<input type="checkbox"/> Mn or Fe Concretions	<input type="checkbox"/> Listed on Local Hydric Soils List
<input type="checkbox"/> Aquic Moisture Regime	<input type="checkbox"/> High Organic Content in Layer of Sandy Soils	<input type="checkbox"/> Other (explain in remarks)

Remarks: charcoal observed throughout 0-13"

Soils Criteria Met?  Yes  No

**WETLAND DETERMINATION**

Hydrophytic Vegetation Dominant?  Yes  No  
 Wetland Hydrology Present?  Yes  No  
 Hydric Soil Present?  Yes  No

Remarks: Wetland criteria not met

Is test plot within a wetland?  Yes  No



**ECOLOGICAL LAND SERVICES, INC.**

1157 3<sup>rd</sup> Avenue, Suite 220, Longview, Washington 98632  
 (360)578-1371 FAX (360)414-9305  
 DATA FORM - Routine Onsite Wetland Determination  
 1987 COE Wetlands Delineation Manual  
 1997 Washington State Delineation Manual

<b>Project Site:</b> SE 40 <sup>th</sup> St	<b>Date:</b> 10/5/07	<b>Project #:</b> 1543.02
<b>Applicant/Owner:</b> Stan Firestone	<b>County/State:</b> Clark, WA	
<b>Test Plot Location:</b> Southwest of SE 202 <sup>nd</sup> Ct.	<b>Sec/Town/Range:</b> S08, T1N, R3E	

<b>Do normal circumstances exist at the site?</b>	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<b>Plot ID:</b> TP6
<b>Is the site significantly disturbed (atypical situation)?</b>	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	<b>Community ID:</b> --
<b>Is the site a potential problem area?</b>	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	<b>Transect ID:</b> --

**VEGETATION** (Strata: tree, sapling, shrub, woody vine, herb)

**Dominant Plant Species**

Common Name	Scientific Name	Strata	% Cover	Indicator Status
1. Soft rush	<i>Juncus effusus</i>	Herb	10	FACW
2. Tall fescue*	<i>Festuca arundinacea</i>	Herb	30	FAC-
3. Velvet grass*	<i>Holcus lanatus</i>	Herb	30	FAC
4. Northern bentgrass*	<i>Agrostis borealis</i>	Herb	30	FACU
5.		-		-
6.		-		-
7.		-		-
8.		-		-

Other species present: Robert's geranium trace  
 % of dominant species OBL, FACW, FACW-, FAC+, FAC 33% (more than 50% required)  
**Remarks:** \* = dominant species per the 50/20 rule.

Vegetation Criteria Met?  Yes  No

**HYDROLOGY**

Recorded data available?  Yes  No  
 Is it the growing season?  Yes  No  
 Is site inundated?  Yes  No

Depth of surface water: N/A  
 Depth to free water in pit: N/A  
 Depth to saturated soils: N/A

Type(s): --

**Wetland Hydrology Indicators**

<b>Primary Indicators</b>	<b>Secondary Indicators (2 required)</b>
<input type="checkbox"/> Inundated	<input type="checkbox"/> Oxidized Root Channels < 12in. hgs
<input type="checkbox"/> Saturated < 12 in.	<input type="checkbox"/> Local Soil Survey Data
<input type="checkbox"/> Water Marks	<input type="checkbox"/> Water Stained Leaves
<input type="checkbox"/> Drift Lines	<input type="checkbox"/> FAC-Neutral Test
<input type="checkbox"/> Sediment Deposits	<input type="checkbox"/> Other (Explain in remarks)
<input type="checkbox"/> Drainage Patterns in wetlands	

Hydrology Criteria Met?  Yes  No

**Remarks:**

**SOILS:**

Map Unit Name: Hesson clay loam (HcB)  
 (Series and Phase)  
 Taxonomy (Subgroup): Clayey, kaolinitic, mesic Xeric Palehumults

Field observations confirm mapped soil type?  Yes  No

**Drainage Class:**

<input type="checkbox"/> Excessively Drained
<input type="checkbox"/> Somewhat Excessively Drained
<input checked="" type="checkbox"/> Well Drained
<input type="checkbox"/> Moderately Well Drained
<input type="checkbox"/> Somewhat Poorly Drained
<input type="checkbox"/> Poorly Drained
<input type="checkbox"/> Very Poorly Drained

**Profile Description**

Depth (inches)	Horizon	Matrix color	Mottle Color	Mottle Abundance (few, common, many)	Mottle Size (fine, med, coarse)	Texture
0-16"	-	10YR 3/2	-	-	-	silt loam

**Hydric Soil Indicators**

<input type="checkbox"/> Histosol (-ists)	<input type="checkbox"/> Reducing Conditions	<input type="checkbox"/> Organic Streaking in Sandy Soils
<input type="checkbox"/> Histic Epipedon (8-16")	<input type="checkbox"/> Gleyed or Low Chroma Colors	<input type="checkbox"/> Organic Pans
<input type="checkbox"/> Sulfidic Odor	<input type="checkbox"/> Mn or Fe Concretions	<input type="checkbox"/> Listed on Local Hydric Soils List
<input type="checkbox"/> Aquic Moisture Regime	<input type="checkbox"/> High Organic Content in Layer of Sandy Soils	<input type="checkbox"/> Other (explain in remarks)

**Remarks:**


Soils Criteria Met?  Yes  No

**WETLAND DETERMINATION**

Hydrophytic Vegetation Dominant?  Yes  No  
 Wetland Hydrology Present?  Yes  No  
 Hydric Soil Present?  Yes  No

**Remarks:** Wetland criteria not met

Is test plot within a wetland?  Yes  No



**PROPERTY BOUNDARY LEGAL DESCRIPTION(s)**

**TAX LOT 48 (ASSESSORS PARCEL NUMBER 125635-000):**

That parcel of land located in a portion of the Joel Knight D.L.C. No. 41 and in a portion of the Northwest Quarter of the Northeast Quarter and the Northeast Quarter of Section 8, Township 1 North, Range 3 East, Willamette Meridian, City of Camas, Clark County, Washington, described as follows:

BEGINNING at the Northwest corner of the Plat of "Breckenridge" as recorded in Book 311 of Plats, at Page 715, Clark County, Washington, plat records;

Thence South 89°29'23" East, along the North line of said Plat of "Breckenridge" for a distance of 95.97 feet;

Thence leaving said North line, North 04°25'46" East, parallel with the West line of the Joel Knight D.L.C. No. 41, for a distance of 62.70 feet;

Thence North 39°16'12" East, for a distance of 114.49 feet to the beginning of a 96.00 foot radius non-tangent curve to the left;

Thence along the arc of a 96.00 foot radius non-tangent curve to the right, for an arc distance of 20.15 feet, through a central angle of 12°01'29", the radius of which bears North 39°16'12" East, the long chord of which bears North 44°43'03" West, for a chord distance of 20.11 feet;

Thence South 39°16'12" West, for a distance of 123.30 feet;

Thence North 89°29'23" West, parallel with the North line of said Plat of "Breckenridge", for a distance of 75.68 feet to the West line of the Joel Knight D.L.C. No. 41;

Thence South 04°25'46" West, along said West line, for a distance of 70.00 feet to the POINT OF BEGINNING;

CONTAINING: 9,000 square feet of land, more or less.

**TAX LOT 59 (ASSESSORS PARCEL NUMBER 125646-000):**

That parcel of land located in a portion of the Joel Knight D.L.C. No. 41 and in a portion of the Northwest Quarter of the Northeast Quarter and the Northeast Quarter of Section 8, Township 1 North, Range 3 East, Willamette Meridian, City of Camas, Clark County, Washington, described as follows:

BEGINNING at the Northeast corner of the Plat of "Breckenridge" as recorded in Book 311 of Plats, at Page 715, Clark County, Washington, plat records;

Thence North 89°29'23" West, along the North line of said Plat of "Breckenridge", for a distance of 335.14 feet;

Thence continuing along said North line, South 04°25'46" West, for a distance of 9.20 feet;

Thence continuing along said North line, North 89°29'23" West, for a distance of 197.07 feet;

Thence leaving said North line, North 04°25'46" East, for a distance of 62.70 feet;

Thence North 39°16'12" East, for a distance of 114.49 feet to the beginning of a 96.00 foot radius non-tangent curve to the right;

Thence along the arc of a 96.00 foot radius non-tangent curve to the right, for an arc distance of 20.15 feet, through a central angle of 12°01'29", the radius of which bears North 39°16'12" East, the long chord of which bears North 44°43'03" West, for a chord distance of 20.11 feet;

Thence South 39°16'12" West, for a distance of 123.30 feet;

Thence North 89°29'23" West, for a distance of 75.68 feet to the West line of the Joel Knight D.L.C. No. 41;

Thence North 04°25'46" East, along the West line of said Joel Knight D.L.C. No. 41, for a distance of 659.58 feet to the South Right of Way line of SE 40th Street and the beginning of a 220.99 foot radius non-tangent curve to the left;

Thence leaving said West line, along said South Right of Way line, along the arc of a 220.99 foot radius non-tangent curve to the left, for an arc distance of 40.96 feet, through a central angle of 10°37'07", the radius of which bears North 10°55'53" East, the long chord of which bears South 84°22'41" East, for a chord distance of 40.90 feet;

Thence continuing along said South Right of Way line, South 89°41'15" East, for a distance of 378.44 feet to the Northwest corner of Tax Lot 58, as described and recorded under Clark County, Washington, Auditor's File Number #4919758 D;

Thence leaving said South Right of Way line, South 04°25'46" West, along the West line of said Tax Lot 58, for a distance of 181.97 feet to the Southwest corner thereof;

Thence leaving said West line, South 89°41'15" East, along the South line of said Tax Lot 58, for a distance of 36.14 feet to the Northwest corner of Tax Lot 47 as described and recorded under Clark County, Washington, Auditor's File Number #5106393 D;

Thence leaving said South line, South 01°26'14" West, along the West line of said Tax Lot 47, for a distance of 70.01 feet to the Southwest corner thereof;

Thence leaving said West line, South 89°41'15" East, along the South line of said Tax Lot 47, for a distance of 128.57 feet to the Southeast

**PROPOSED DEVELOPMENT PLAN:**

**TOTAL LOTS: 36**  
**MINIMUM LOT AREA: 5,900 sq.ft.**  
**MAXIMUM LOT AREA: 9,000 sq.ft.**  
**AVERAGE LOT AREA: 7,042 sq.ft.**

TRACT PURPOSE	OWNED & AREA MAINTAINED
TRACT 'A' - LANDSCAPE	2,268 sf HOA
TRACT 'B' - ACCESS & UTILITY	1,541 sf HOA
TRACT 'C' - RECREATIONAL OPEN SPACE	13,438 sf CITY
TRACT 'D' - ACCESS & UTILITY	1,752 sf HOA
TRACT 'E' - STORM FACILITY	23,887 sf HOA
TRACT 'F' - STORM FACILITY	10,405 sf HOA
TRACT 'G' - ACCESS & UTILITY	2,630 sf HOA
TRACT 'H' - ACCESS & UTILITY	5,034 sf HOA
TRACT 'I' - LANDSCAPE & SIGNAGE	1,315 sf HOA

**LAND INVENTORY**

TOTAL SITE AREA: 9.26 ACRES  
 TOTAL DEVELOPED ACREAGE: 7.29 ACRES  
 TOTAL LOT AREA: 5.85 ACRES  
 TOTAL INFRASTRUCTURE ACREAGE: 2.79 ACRES  
 TOTAL TRACT AREA(MINUS STORM TRACTS): 0.61 ACRES  
 TOTAL ACREAGE OF CRITICAL AREAS: NONE  
 TOTAL ACREAGE OF REC. OPENSAPCE 0.31 ACRES

**SITE INFORMATION**

ALIGNMENT & FIELD DATA: MINISTER & GLAESER SURVEYING, INC. (360) 694-3313  
 SOIL TYPE(s): HYDROLOGIC GROUP: C AASHTO CLASSIFICATION: A-4  
 SOILS TESTING BY: RAPID SOIL SOLUTIONS (603) 816-3889 DATE: MARCH 2014  
 SITE LOCATION: CLARK COUNTY, WA APPROX. SURFACE ELEV.: 385'-468'  
 SITE AREA: 9.26 ACRES FILENAME: 288:/Preliminary.pro

TABLE 18.09.040  
 MINIMUM SETBACKS:

FRONT:	20'
SIDE STREET:	20'
SIDE INTERIOR:	5'
REAR:	25'
MAX. LOT COVERAGE:	40%
MAX. BLDG. HEIGHT:	35'

ALL PROPOSED BUILDING ENVELOPES ARE LARGE ENOUGH TO FIT A 40 FOOT X 40 FOOT BUILDING FOOT PRINT.

PREPARED BY:  
 STERLING DESIGN, INC.  
 2208 E EVERGREEN BLVD  
 WACONIA, WA 98601  
 (360) 758-1044  
 FAX (360) 758-1088  
 mailsterlingdesign@gmail.com

**STERLING DESIGN, INC.**

Sheet Description:  
**PROPOSED DEVELOPMENT PLAN**

Project:  
**VALLEY VIEW ESTATES SUBDIVISION**



Scale: AS SHOWN  
 Project Number: 288  
 Design/Drawn: JGS/BC  
 Drawing Date: OCT 2018  
 Sheet 2 of 9 Sheet(s)

NOTE:  
 Existing utilities shown are approximate only from utility records and as visible at the site. Contractor shall verify presence, location, depth, & slope of any and all existing utilities prior to construction. Contact One Call Concepts at (800) 424-5555.



## STAFF REPORT

### Valley View Estates Subdivision

File No. SUB18-02 (consolidated files: SEPA18-15, ARCH18-08, CA18-08)

*Type III*

Staff Report Date: October 11, 2018

---

<b>TO</b>	Hearings Examiner	<b>HEARING DATE</b>	October 18, 2018
<b>PROPOSAL</b>	To subdivide 9.2 acres into 36 detached single-family residential lots.		
<b>LOCATION</b>	The site is located at 20109 SE 40 <sup>th</sup> Street in the NE ¼ of Section 8, Township 1 North, Range 3 East, of the Willamette Meridian; and described as tax parcels 125646-000 and 125635-000.		
<b>APPLICANT</b>	Sterling Design, Inc. 2208 E. Evergreen Blvd. Vancouver, WA 98661	<b>CONTACT</b>	Joel Stirling (360) 759-1794
<b>APPLICATION SUBMITTED</b>	May 24, 2018; Resubmitted June 25, 2018	<b>APPLICATION COMPLETE</b>	July 6, 2018
<b>SEPA</b>	The City issued a SEPA Mitigated Determination of Non-significance (MDNS) October 4, 2018, with a comment and appeal period that ends on October 18, 2018. The SEPA MDNS was mailed to property owners October 3, 2018 and published in the Post Record on October 4, 2018. Legal publication #45510.		
<b>PUBLIC NOTICES</b>	Notice of Application was mailed to property owners within 300 feet of the site on July 11, 2018, and published in the Post Record on July 12, 2018. Legal publication #610375. Notice of public hearing was mailed to property owners within 300 feet of the site on October 3, 2018, and published in the Post Record October 4, 2018. Legal publication #43310.		

---

**APPLICABLE LAW:** The application was submitted on May 18, 2018 and the applicable codes are those codes that were in effect at the date of application. Camas Municipal Code (CMC) Title 16 Environment, Title 17 Land Development, and Title 18, specifically (but not limited to): Chapter 18.11 - Parking, Chapter 18.13 - Landscaping, Chapter 18.18 - Site Plan Review, Chapter 18.19 Design Review, and Chapter 18.55 Administrative Procedures.

# CONTENTS

<b>SUMMARY</b> .....	2
<b>FINDINGS</b> .....	2
<i>Title 16 Environment</i> .....	2
<i>Title 17 Land Development</i> .....	3
<b>PUBLIC COMMENTS</b> .....	14
<b>CONCLUSION</b> .....	14
<b>RECOMMENDATION</b> .....	15
<b>CONDITIONS OF APPROVAL</b> .....	15

## **SUMMARY**

Application has been made to the City of Camas for preliminary plat approval for a 36-lot single-family residential subdivision located at 20109 SE 40<sup>th</sup> Street in the R-7.5 single-family residential zone. The preliminary plat proposal would segregate 9.2 acres into 36 lots ranging in size from 5,900 square feet to 9,000 square feet. The proposal includes tracts for a trail, private access roads, parking, and stormwater detention facilities.

The subject property is bordered to the west by the Winchester Hills subdivision, which is located within unincorporated Clark County. The southwest corner of the site is abutted by City of Vancouver property planned for a mixed use development. To the south is the Breckenridge subdivision zoned single-family residential (R-7.5) and to the west is Knight Point subdivision zoned single-family residential (R-15) both within the City of Camas city limits. SE 40<sup>th</sup> Street and NW 18<sup>th</sup> Avenue abuts the site to the north. The road name changes approximately mid-way along the site’s frontage. The north side of SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue is the location of the Camas School District Pacific Rim Campus. The site is accessed from north via SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue and the south via NW Goodwin Street.

The site slopes downwards from 5% to 25% towards the SE corner of the parcel. The entire project site is open and grassy, with large areas of blackberries and a few scattered trees.

The proposed preliminary plat does or can comply with the applicable standards of the Camas Municipal Code (CMC) and Revised Code of Washington (RCW).

## **FINDINGS**

### *Title 16 Environment*

---

#### STATE ENVIRONMENTAL POLICY ACT (SEPA18-15)

#### CMC CHAPTER 16.07

---

A SEPA checklist was submitted and a Mitigated Determination of Non Significance (MDNS) was issued October 4, 2018 as the proposed development includes more than ten residential dwelling units per CMC 16.07.020.A.1. The mitigation measures identified in the SEPA MDNS will need to be complied with (See Exhibit 26). The comment and appeal period ends October 18, 2018. As of the writing of this staff report, no SEPA comments were received.

**FINDING:** Staff finds the mitigation measures identified in the SEPA MDNS will need to be complied with.

The applicant provided an archaeological predetermination report that is consistent with CMC 16.31.090. Based on the report, no further archaeological work is necessary at this time. The report and findings are not subject to the open public records act and as such, the city cannot disclose the results. A note should be added to the face of the final plat that includes inadvertent discovery language as required by the State Department of Archaeology & Historic Preservation.

**FINDING:** Staff finds if potential artifacts are discovered during the course of construction, work must immediately cease and both State Department of Archaeological and Historic Preservation and the City shall be notified.

**CMC Chapter 16.53 Wetlands and CMC 16.61 Fish and Wildlife Habitat Conservation Areas-**

Clark County GIS mapping identified the subject property with a stream along the southern boundary. The 2007 Wetland Determination Report prepared by Ecological Land Services, Inc. (ELS) did not concur with the location of the mapped stream within the site boundary based on ELS’s field investigation (See Exhibit 27). In 2013 a follow up on-site field investigation was performed by ELS, Inc. and confirmed the onsite wetland conditions have not changed; there are no wetlands onsite. A Category IV off-site wetland was identified but located approximately 120-feet south from the subject property boundary (See Exhibit 18).

**FINDING:** Staff finds the project to be developable based on the findings in the environmental reports.

**CMC Chapter 16.59.060(C) Geotechnical Evaluation and Assessment-**

Clark County GIS mapping identified the subject property within an area of geologically hazardous areas (i.e. steep slopes). As such, the applicant submitted a Geotechnical Report prepared by Rapid Soil Solutions (RSS) (revised August 2, 2018), which identified slopes up to 25% in the southeast corner of the property. At page 7 of the report, RSS found no signs of land slide hazards or slope stability during their site reconnaissance and concluded “the development of the site will not impact any geological hazards on the site as well as the surrounding areas” (See Exhibit 14). The City’s geotechnical consultant Earth Engineers, Inc. (EEI), performed a peer review of the geotechnical report and concurred the report is in compliance with CMC 16.59.060 (See Exhibits 15 & 16).

**FINDINGS:** Staff finds the property to be developable based on the findings and recommendations in the geotechnical report. The applicant should comply with the geotechnical report recommendations to minimize any potential hazards associated with construction.

*Title 17 Land Development*

**CMC Chapter 17.11.030(D) Criteria for Preliminary Plat Approval:**

*The hearings examiner decision on application for preliminary plat approval shall be based on the following criteria:*

- 1. The proposed subdivision is in conformance with the Camas Comprehensive Plan, Parks and Open Space Comprehensive Plan, Neighborhood Traffic Management Plan, and any other City adopted plans.**



### Comprehensive Plan

The subject property is designated as Single-Family Medium in the City's Comprehensive Plan, which includes the Single-Family Residential (R-7.5) zone designation. Citywide Housing Goal H-1 states, "Maintain the strength, vitality, and stability of all neighborhoods and promotes the development of a variety of housing choices that meet the needs of all members of the community." To facilitate alternative housing choices, affordable housing and ageing readiness within the City of Camas, accessory dwelling units (ADU's) are an allowed use within the residential zones under CMC 18.07.040 Table 2 and should not be precluded in CC&R's.

Further, Neighborhood Goal LU-3 states, "Create vibrant, stable and livable neighborhoods with a variety of housing choices that meet all stages in the life cycle and a range of affordability." The side building elevations on corner lots are highly visible from the street and should exhibit architectural variation similar to the front of the building façade, including landscaping, in order to avoid blank walls thereby supporting the city's goal of creating vibrant and livable neighborhoods in Camas.

The Natural Environment Comprehensive Plan Policy NE-1.7 states, "Limit clearing, grading, and soil disturbance outside building footprints in order to maintain the natural hydrologic functions of the site." Due to the steep slopes, multiple retaining walls are utilized throughout the site to create flat lots, and therefore site grading should be minimized to retain the natural contours of the land.

Overall, the 2035 City of Camas Comprehensive Plan supports the subdivision through a number of land use and transportation policies such as the following:

- LU Policy 1.3: Maintain compatible use and design with the surrounding built and natural environments when considering new development or redevelopment.
- LU Policy 1.4: Ensure the park and recreation opportunities are distributed equitably throughout the City and work to achieve park and continuous trail corridors from Green Mountain to the Columbia River.
- LU Policy 3.3: Encourage connectivity between neighborhoods (vehicular and pedestrian) to support citywide connectivity and pedestrian access.
- LU Policy 3.4: Camas residents are protective of the small-town ambiance and family-friendliness of the community. Discourage exclusive neighborhoods, privacy walls, and gated communities.
- LU Policy 3.5: Where neighborhoods adjoin natural areas or trails, ensure connections through neighborhoods to enhance access to recreation amenities.
- LU Goal 4: Develop an interconnected network of parks, trails, and open space to support wildlife corridors and natural resources and enhance the quality of life for Camas residents and visitors.
- LU Policy 4.3: Encourage regional trail connectivity and increased access throughout the City to support multi-modal transportation and physical activity.
- T Policy 1.3: Construct streets that are interconnected and avoid long cul-de-sacs or dead ends.
- T Policy 2.1: Enhance travel choices and provide pedestrian and bicycle routes designed especially for them, not simply along routes designed for cars. Route planning should seek shortcuts and other opportunities that give walking or biking advantages over the automobile.
- T Policy 2.5: Coordinate with schools and the community to designate safe pedestrian and bicycle routes between residential areas, schools and public facilities.

### Parks and Open Space Comprehensive Plan

The City of Camas adopted and updated the Parks, Recreation, and Open Space (PROS) plan in 2014. The subject site is located in an area identified by the PROS plan as requiring a trail connection, in particular the T-24 trail which connects to the north and south of the site. Per the PROS plan at page 4-5, "Proposed segments of the trail system are generalized to make connections or follow the direction of natural corridors. Final alignments are subject to change due to environmental conditions, development or alternate routes." Further, trails should be off-street as much as possible per Objective 4A of the PROS plan.

The applicant presented a conceptual trail connection to the Parks Ad Hoc Committee for feedback on July 25, 2018 and followed up with a site visit on July 31, 2018. The applicant and the Parks Ad Hoc Committee agreed the following general public accessible trail connection will be provided as shown on Preliminary Site Plan, Sheet 1 (Exhibit 4); a north-south trail through proposed Tract C connecting the existing T-24 trail alongside SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue to the sidewalk in NE Goodwin Street of the Breckenridge Subdivision development. The Parks Ad Hoc Committee further concurred the applicant should provide the following trail features; 1) landscaping along both sides of the trail 2) directional signage to the Breckenridge trail and a bench to be located near the intersection with NW Goodwin Street.

The placement of the trail should avoid the removal of existing healthy trees. The trail should be a 10-foot wide paved surface consistent with the existing T-24 trail located along the south side of SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue and to be constructed prior to final plat approval. Proposed Tract C will need to be owned and maintained by the City.

The T-24 trail is a 10-foot wide shared use trail for pedestrians and bicyclists. The applicant has not proposed any additional road widening that would allow for a separate bike lane on SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue. As such, staff finds that the applicant should extend the west end of the trail to match up with the existing curb and sidewalk on the east side of the intersection on SE 201<sup>st</sup> Avenue and SE 40<sup>th</sup> Street.

**FINDING:** Staff finds that as conditioned the applicant can and will provide an open space network and trail system consistent with the City's 2014 Parks, Recreation and Open Space Comprehensive Plan.

### Neighborhood Traffic Management Plan

The City has a Neighborhood Traffic Management Plan (NTM). The NTM plan identifies the need for installation of acceptable traffic calming features when a proposed development will create 700 Average Daily Trips (ADT) or more. The submitted Transportation Impact Study (TIS) from H. Lee & Associates, PLLC, dated March, 2018, found the project is expected to generate approximately 333 Average Daily Trips (ADT) with 36 new AM peak hour trips and 35 PM peak hour trips.

**FINDING:** Staff finds that this proposed project is not subject to the requirements for traffic calming as noted in the City's NTM plan.

### Traffic Impact Analysis

A Transportation Impact Study (TIS) was submitted by H. Lee & Associates, PLLC, dated March 16, 2018. The study assessed transportation impacts related to the proposed project located at 20109 SE 40<sup>th</sup> Street. The report evaluated existing traffic conditions in the study area; the 2035 "without project" condition in order to establish a baseline condition by which project impacts are determined; estimated trip generations; and the 2023 "with project" condition to determine project traffic impacts.

The findings in the TIS were as follows:

- The proposed development is expected to generate 333 daily, 26 AM peak hour (7 in, 19 out), and 35 PM peak hour (22 in, 13 out) net new trips.
- All the study area intersections are projected to meet the City of Camas' level of service standards in the 2023 "Without Project" and the 2023 "With Project" condition.
- Turn lane warrants at the SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Street project access intersection were not conducted because a westbound left-turn lane into the site will be constructed with the subdivision.
- Based on field measurements conducted by H. Lee & Associates, PLLC, the project access intersection should be able to meet the sight distance requirements as long as any vegetation within the sight distance triangles are properly maintained after construction and no obstructions are placed within the sight distance triangles that could impede a driver's vision. Because the access into the project site is not built, the corner sight distance should be re-verified in the final engineering/construction stages of development.
- Staff finds that the applicant should submit a sight distance analysis at the access to SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue prior to final approval of engineering plans.

Recommendations were as follows:

- Based on the traffic impact analysis, documented in the report, no physical, off-site mitigation would be needed.

**FINDINGS:** Staff finds that the applicant should provide a sight distance analysis at the SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue access prior to final approval of the engineering plans. The applicant will need to install a left-turn lane from NW 18<sup>th</sup> Avenue into the development site, per the TIA.

**2. Provisions have been made for water, storm drainage, erosion control and sanitary sewage disposal for the subdivision that are consistent with current standards and plans as adopted in the Camas Design Standard Manual.**

Water: There are three existing water mains located on the north, south, and southwest boundaries of the proposed project. There is an existing 12-inch ductile iron water main located in SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue located at the northern boundary, an existing 8-inch water main that is stubbed to the southern boundary from the Breckenridge subdivision, and an existing 12-inch water main that was recently stubbed to the southwest corner from the Columbia Palisades development. The applicant has proposed to install an 8-inch water main that is shown to connect to the southern and northern water mains.

Staff finds that the applicant should upsize the proposed 8-inch waterline to a 12-inch waterline from Columbia Palisades north to the 12-inch waterline located in SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue. This would provide for a looped system from SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue to Columbia Palisades. Staff supports the reducing to the proposed 8-inch waterline connection south to NW Goodwin Street. Water pressure from the 12-inch main located in SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue is sufficient to supply water to the 36 proposed lots.

The current water main design for Valley View indicates that a blowoff is proposed at the southwest end of the proposed thru road into Columbia Palisades. As part of the Columbia Palisades development, a 12-inch water main was installed and stubbed near the east end of the future road extension into the applicant's proposed development. Water for the Columbia Palisades development is provided by the City of Camas. Staff finds that the applicant should connect the proposed Valley View water system to the existing Columbia Palisades 12-inch waterline and work with the City's Utility Manager to evaluate water pressure and the potential need for a pressure reducing station.

Individual water services will be provided to each lot with meter boxes located in the proposed planter strips. Fire hydrants will also be installed in accordance with Camas Design Standards Manual (CDSM) and Fire Department requirements. Irrigation service(s) may also be installed to provide irrigation for landscaping needs of open space tracts, stormwater detention facilities, etc. Any irrigation meters proposed will be required to be privately maintained by the HOA and will require acceptable back flow prevention devices. The water lines, irrigation service(s), water services and fire hydrants will be located in both public and private streets that will serve the proposed lots.

Staff finds that the applicant will be conditioned to provide adequate access and utility easements to the City over the private street tracts at the time of final platting for the inspection, maintenance and operation of said public water lines.

The applicant will also be required to provide acceptable back flow device(s) (BFD) and yearly backflow testing for any private HOA irrigation service(s) proposed. Prior to occupancy of each home with an irrigation system, the builder should submit acceptable BFD testing for each irrigation meter installed and provide said testing results to the city.

**FINDINGS:** Staff finds that as conditioned the applicant can and will provide water system improvements consistent with the City's standards.

Storm Drainage:

[Stormwater Facilities]: The applicant is proposing to construct two detention ponds, Tract E located in the southwest corner and Tract F located in the southeast corner. Both facilities are bordered on all four sides with vertical retaining walls that range in height from 5-ft. to 20-ft. for the Tract E facility and 6-ft. to 12-ft. for the Tract F facility and include fencing on top of the walls as shown on the Preliminary Stormwater Plan, Sheet 6 (Exhibit 4). Access for both facilities is via a combination of a 12-ft. wide access road and ladders attached to the interior of the retaining walls. Ecology's Stormwater Maintenance Manual for Western Washington (SWMMWW), Volume III, section 3.2 has an option that allows deviating from the 25% vegetated slopes requirement and allows for storm facilities to have 100% of the perimeter to be vertical walls with the following requirements:

- a) Walls are constructed of reinforced concrete per Section 3.2.3, Material;
- b) A fence is provided along the top of the wall;
- c) The entire pond perimeter may be retaining walls ...;
- d) The design is stamped by a licensed engineer with structural expertise. If the entire pond is to be retaining walls, ladders should be provided on the walls for safety reasons.

Staff finds that the proposed design meets the guidelines as outlined in the 2014 SWMMWW. However, the facilities do not meet the guidelines as set forth in the Camas Stormwater Design Standards Manual.

The applicant has stated that the storm facility retaining walls will comply with CMC 18.17.060. However, the storm facility retaining walls do not meet the requirements of the Camas Stormwater Design Standards Manual, Chapter 4 for side slopes and setbacks.

Chapter 4.05, Side slopes states the following:

- 1. Interior side slopes shall be 3:1 or flatter, or constructed with retaining walls.
- 2. Exterior side slopes steeper than 3:1 are allowed if it is demonstrated that the facility can be adequately maintained. Long-term erosion control shall be provided and an approved maintenance plan is required.
- 3. Use of retaining walls in stormwater facilities taller than four feet requires approval of the Director. The height of the wall shall be measured from the bottom of the footing to the top of the wall.

4. The City may grant a deviation from the side slope standards when the Director determines that the safety, health, and welfare of the public will not be compromised.

Chapter 4.05, Setbacks states the following:

1. Per CMC 17.19.030.F from streets and accessory structures.
2. At least 10-feet from neighboring property lines.

The storm facility located on Tract E is proposing retaining walls that range in height from 5-ft. to 20-ft. and are located on the property lines along Lots 10-12 and Lot 21. These walls do not meet either the setback requirement for 10-feet from neighboring property line nor the side slope requirements for walls not exceeding 4-ft. in height.

The storm facility located on Tract F is proposing retaining walls that range in height from 6-ft. to 12-ft. The walls for this facility do not meet either the setback requirement for 10-feet from the neighboring property line nor the side slope requirements for walls not exceeding 4-ft. in height.

Staff finds that the storm facilities located on Tract E and Tract F be conditioned to meet the requirements of the Camas Stormwater Design Standards Manual, Chapter 4.05 Side Slopes and Setbacks, prior to final engineering plan approval.

Maintenance of the stormwater facilities is the responsibility of the HOA. Reasonable access for maintenance activities is to be provided, including 12-foot wide ramps for accessing inlet and outlet pipes. Staff finds that the applicant should provide reasonable accessibility for maintenance activities.

CMC 17.19.030.F.6 requires that storm drainage facilities be setback a minimum of 30-feet from any street or accessory structure and be landscaped in accordance with the Camas Design Standards Manual. The proposed storm facilities located in Tract E and Tract F meet the minimum setback requirement from the right-of-way, however the preliminary landscape plan does not indicate any landscaping on these tracts. Staff finds that the applicant should be required to include landscaping, screening, and fencing acceptable to the City prior to final engineering plan approval.

[Stormwater discharge]: The Knights Pointe subdivision, located on the east side of the proposed development, has historically had stormwater discharged into a series of 36-inch diameter storm pipe, that traveled overland across the Firestone property, and into a culvert, and then ultimately into the seasonal creek on the west side of Breckenridge. The applicant has proposed to construct an underground collection and conveyance system that will take the stormwater from Knights Pointe, route it around the southern end of the proposed development, thru a series of storm manholes, and discharge it into the seasonal creek that flows thru the wetlands along the western boundary of Breckenridge subdivision. Staff does not take exception to the proposed design as the pipe conveyance system mimics the existing route that the stormwater currently takes.

The applicant has stated that there aren't any wetlands on the property or immediately adjacent to the property. However, the stormwater from this development will discharge into a seasonal creek located within the off-site wetland approximately 160-ft. south of Tract E. The storm facilities located in Tracts E and F will both discharge into an existing stormwater manhole that is located at the northern boundary between the proposed development and Breckenridge. Staff finds that the applicant should provide documentation to the effect that any discharge of stormwater into wetlands, is to be consistent with Ecology's SWMMWW Appendix 1-D: Guidelines for Wetlands When Managing Stormwater criteria.

[Offsite Analysis]: The preliminary stormwater report, which was submitted by Joel Sterling on June 2018, discussed the offsite analysis that was performed. A site visit was conducted that followed the downstream flow route to a point in the receiving water, approximately ¼ mile from the site, in order to analyze existing conditions and potential impacts from this development. The proposed design

conveys all the stormwater from the site to a public storm manhole that was installed at the northern boundary of the Breckenridge subdivision. This portion of the Breckenridge conveyance system, then discharges into the seasonal creek that runs along the western boundary of Breckenridge. Per the offsite analysis, the stormwater flows from the proposed development will continue to follow historical flow routes and will not be rerouted to another drainage basin. Staff finds that the applicant should submit a final stormwater report (TIS) to the City for review and approval, prior to final engineering plan approval.

Stormwater facilities are to be owned and maintained by the HOA, with a right-of-entry granted to the City of Camas for inspections.

**FINDINGS:** Staff finds that as conditioned the applicant can and will make adequate provisions for stormwater control, detention, conveyance, and water quality treatment.

Erosion Control: Adequate erosion control measures can or will be provided during the site improvements contemplated for this subdivision in accordance with adopted city standards. The Erosion Sediment Control (ESC) plans will ultimately be submitted to the City for review and approval prior to any ground disturbance. The applicant will be required to provide an Erosion Control Bond, per CMC 17.21.050.B.3, prior to final approval engineering plan approval.

Additionally, the applicant will provide a copy of both their Stormwater Pollution Prevention Plan (SWPPP), which is a part of their application for their NPDES General Construction Stormwater Permit (GCSWP) that is required through the Washington State Department of Ecology for ground disturbances of over one acre, and their NPDES GCSWP, prior to approval of the engineering plans.

**FINDINGS:** Staff finds that adequate provisions for erosion control can or will be made.

Sanitary Sewage Disposal: The applicant is proposing to tie into the existing 8-inch PVC sanitary sewer system that was stubbed north from the Breckenridge development located south of the proposed development. The effluent flows from this development would be routed to the existing Grand Ridge pump station, located in the Grand Ridge subdivision, with the solids retained in individual tanks located on the individual lots. As such, staff finds that the applicant should be conditioned to perform a sewer basin analysis to quantify the existing and proposed sewer flows that will be conveyed to the existing pump station prior to final engineering approval.

Staff finds that the applicant should be conditioned to conduct a capacity analysis of the existing pump station that evaluates the existing flows from Grand Ridge, Breckenridge, and future Valley View flows. The analysis should include but not be limited to evaluation of pump sizes, pumping rates, and condition of existing structures, etc. The analysis is to evaluate the effects on the downstream facilities, from the Grand Ridge pump station to the Brady Road pump station and in to the STEP transmission main in NW Brady Road, to determine if there is adequate capacity to serve the existing and proposed new flows.

Staff finds that the applicant will be responsible for appropriate mitigation of any identified and necessary pump station or system upgrades to serve the proposed development.

The applicant is proposing the installation of a Septic Tank Effluent Filter (STEF) sewer system to serve the proposed lots. The system will consist of individual underground Roth STEF Tanks to be installed at the time of home construction on each lot. The tanks will retain the solids and the effluent will gravity flow out of the tank and into the STEF mainline where the flow will then be conveyed to the existing pump station. The City will maintain the individual STEF tank systems once home construction is completed. The individual lot owners will be responsible for the cost and installation of the individual systems at the time of home construction. A right-of-entry will also be granted to the City for the maintenance and repair of said STEF tanks.

Existing wells, septic tanks and septic drain fields: CMC 17.19.020 (A 3) requires abandonment of existing wells, septic tanks and septic drain fields. Existing water wells should be properly abandoned in accordance with State and County guidelines prior to final plat approval for the phase they may be located in.

**FINDINGS:** Staff finds that adequate provisions can or will be made as conditioned for water, storm drainage, erosion control and sanitary sewage disposal which are consistent with the Camas Municipal Code and the Camas Design Standard Manual.

**3. Provisions have been made for road, utilities, street lighting, street trees and other improvements that are consistent with the Six-Year Street Plan, the Camas Design Standards Manual and other State adopted standards and plans;**

Roads: The proposed development is located on the south side of the convergence between SE 40<sup>th</sup> Street and NW 18<sup>th</sup> Avenue. NW 18<sup>th</sup> Avenue / SE 40<sup>th</sup> Street is designated as an existing 2-lane collector. The applicant is proposing to extend a public road, currently un-improved SE 202<sup>nd</sup> Avenue, through the project in order to connect SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue to NW Goodwin Street to the south and Street 'E' to the southwest. Street 'E', at the southwest corner of the subject property is located within the City of Vancouver city limits. Street 'E' is a public road and constructed as part of the Columbia Palisades mixed use project.

The applicant is proposing public roads that would provide connectivity between the City of Vancouver's Columbia Palisades development, the City of Camas Breckenridge subdivision, and the Camas School District Pacific Rim Campus. The public street section proposed for the interior streets to the site, is consistent with the public street section 17.19.040.B.8 Table 17.19.040-2 Minimum Public Street Standards, which includes a 52-foot width right-of-way, a 28-foot paved surface, a 5-foot detached sidewalk on both sides with planter strips, and no parking restricted on one side. The proposed street section is the minimum allowable and requires approval from the City Engineer. The City Engineer supports the proposed street standards as shown.

NW 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue is classified as an existing 2-lane collector. As such, the minimum driveway setback from a collector road is 110-feet. A restricted access is required for Lots 1 and 36 to ensure that the driveway locations for these two lots meet or exceed the minimum access setback requirement.

Tracts B, D, and G are private streets providing access to four or less dwelling units. Per CMC 17.19.040.B.8 private streets are to meet the minimum private street standards per Table 17.19.040-2 with a 20-foot tract width and a 12-foot paved surface, optional sidewalk and no parking on both sides.

Staff finds that as a bike lane is not being constructed on SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue, the applicant should provide adequate improvements and necessary adjustments for the existing multi-use pedestrian trail (aka T-24). Improvements should include a 10-ft. minimum path width from the existing landing on the northeast corner of SE 201<sup>st</sup> Avenue east to the eastern boundary of the applicant's site. The existing 10-ft. wide path should be preserved to the extent possible.

The proposed street section for SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue does not meet the public street sections as indicated in Table 17.19.040-2. A half-street improvement is not proposed, however there is an existing 10-ft. wide multi-use pedestrian T-24 trail. A deviation from the public street standards in CMC 17.19.040 may be permitted with a recommendation from the City Engineer. The City Engineer supports the deviation.

Additionally, staff finds that the curb ramps at SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue and the site entrance should align both vertically and horizontally with the shared use path along SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue and shall meet Public Right-of-Way Accessibility Guidelines (PROWAG).

A Geotechnical investigation and analysis of the existing roadway (SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue) has not been provided. Staff finds that the applicant should provide a Geotechnical report with an analysis to determine if the existing street section meets the half-street improvement requirements of the Camas Design Standards Manual.

In accordance with the provisions of CMC 17.19.040 (A7) homes accessed from a private street require automatic fire sprinklers installed per NFPA 13D or 13R and the applicant will need to provide for adequate parking enforcement in the CC&R's at the time of final platting.

Utilities, Street Lighting, Street Trees, and Other Improvements:

[Street lighting]: LED Street lighting will be installed along all street frontages in accordance with the Camas Design Standards Manual (CDSM). Street light locations are to be shown on the construction plans. Draft electrical plans are to be submitted for review by the City prior to submittal to Clark Public Utilities.

[Street trees and Landscaping]: CMC 17.19.030 (F 1) requires one 2-inch diameter street tree in the planter strip of the right-of-way for each dwelling unit. The proposed street tree locations are shown on the Preliminary Landscape Plan, Sheet 9 (Exhibit 4) in compliance with this requirement. The applicant will also be required to provide acceptable fencing and landscaping behind lots 1-4 in accordance with CMC17.19.030.D.6 as further discussed under criterion 5 below. Additionally, prior to final engineering approval, the applicant is to show proposed driveway locations for each lot to ensure that street trees are not impacted.

The street tree plantings and other landscaping as discussed throughout this report, should be included on the landscaping plans with final engineering plan submittal for the site improvements. All landscaping should be installed or bonded for prior to final plat acceptance.

[Storm Facility Landscaping]: CMC 17.19.030.F.6 requires that storm drainage facilities be setback a minimum of 30-feet from any street or accessory structure and be landscaped in accordance with the Camas Design Standards Manual. The proposed storm facilities located in Tract E and Tract F meet the minimum setback requirement, however the preliminary landscape plan does not indicate any landscaping on these tracts. Staff finds the applicant should include on the final landscaping plans the landscaping and fencing for the stormwater facilities located on Tract E and Tract F.

[Parking]: The proposed average lot size falls below 7,400 square feet and as such, the applicant has provided 8 parking stalls within Tract F in compliance with this requirement in CMC 17.19.040.B.10.e. Subject to the requirements of CMC 18.13.060.A and E, parking areas are to be landscaped at all perimeters and provide a minimum 5-foot width of planting space.

**FINDING:** Staff finds that the applicant can or will make adequate provisions for roads, utilities, street lighting, street trees, and other improvements that are consistent with the six-year street plan, the Camas Design Standard Manual and other state adopted standards and plans.

**4. Provisions have been made for dedications, easements and reservations;**

The applicant's submittal does not include any of the proposed private easements for storm, sewer or water lines and does not show existing easements of record on adjacent parcels. The applicant should be required to provide said easements on the construction drawings and the final plat.



The applicant is proposing to provide an internal public road to serve the development, with private driveways/roadways that will provide access to several flag lots. Proposed Tracts B, D & G are identified as private roadways/driveways on the preliminary plat. Public water and sewer services will also be located within these private roadways, as such the applicant is proposing to provide a blanket access and utility maintenance easement over the proposed private roads to the City of Camas at the time of final platting.

The applicant will also be required to provide a right-of-entry to the city for inspection and maintenance of the individual S.T.E.F. systems.

Tract H provides access to tax lots 58 and 47, which are not part of this proposed development and should not be under the ownership of the homeowner's association of this subdivision. Prior to final plat approval, the applicant will need to accomplish one of the following: 1) Add a note to the final plat that the developer will own and maintain Tract H, 2) quit claim deed Tract H to the property owners of tax lots 58 and 47 or 3) submit to the city for review and approval a boundary line adjustment between Tract H and tax lots 58 and 47.

A homeowner's association (HOA) will be required and a copy of the CC&R's for the development will need to be submitted to the City for review and approval. Specifically, the applicant will need to make provisions in the CC&R's for ownership and maintenance of the storm drainage systems, fencing, walls, landscaping, irrigation, private roads, and tracts or easements outside of the City's right-of-way if applicable. Further, all necessary easements and dedications should be noted on the final plat.

**FINDING:** Staff finds that adequate provisions for dedications, easements and reservations can or will be made by the applicant at the time of final platting.

##### **5. The design, shape and orientation of the proposed lots are appropriate to the proposed use.**

Lot sizes: Proposed Tract C on the preliminary plat contains a proposed trail connection, which is identified on the Parks, Recreation, and Open Space (PROS) plan as the T-24 trail. The applicant has the ability to utilize the density transfer provisions per CMC 18.09.060.C when land is set aside in a tract that is approved as a recreational area (i.e. trails).

The density transfer provisions in the R-7.5 single-family residential zone requires a minimum lot size of 5,250 square feet and a maximum lot size of 9,000 square feet CMC 18.09.040 Table 1. As such, the proposed lots are between 5,900-9,000 square feet in size. Further, CMC 18.09.080.B requires new lots along the common property boundary needs to be the maximum size allowed of the zone designation with the development if adjacent to a lower density zone. In compliance with this requirement, lots 22-25 are 9,000 square feet in size as they abut the existing Knight Point subdivision which is located in a higher density residential zone (R-15).

Lot dimensions: The proposed lots meet the required minimum width of 60-feet and depth of 80-feet and density of the overall site is below the maximum allowed at 5.8 du/acre. CMC 18.09.040.C- Table 2 specifies that "Setbacks are based on average lot sizes (not zone specific)". The average lot size for the proposed development falls under the R-7.5 density range which requires a minimum 20-foot front yard setback, a 25-foot front minimum rear yard setback, a 5-foot minimum side yard and corner rear yard setback and a 20-foot minimum side yard flanking a street setback. A minimum 40x40 building envelope and building setbacks should be shown on the final plat.

Double-frontage lots: The preliminary plat proposed double frontage lots at Lots 1-4 adjacent to SE 40<sup>th</sup> Street. "Double Frontage lots shall be avoided" per CMC 17.19.030.D.6 except where the lots are adjacent to an arterial or collector; SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue is a Collector Road. Consistent with CMC 17.19.030.D.6.a, the applicant has provided a 10-ft. wide landscape tract (Tract A) along the rear

property lines of Lots 1-4. The landscape tract should include a minimum 2-inch caliper tree every thirty feet on center, three-foot tall shrubs that form a continuous screen and groundcover plants that fully cover the remainder of the landscaped area per CMC 17.19.030.D.6.a. A 4-foot sight obscuring fence or masonry wall should be located at the line that separates the lot from the 10-foot tract per CMC Figure 17.19-1 and include columns or physical indentations every fifty lineal feet per CMC 17.19.030.D.6.b. Subject to CMC 17.19.030.D.6.d, a 20-foot setback is required from the property line separating the lot from the tract. As such, Lot 1 building envelope should be reduced to comply with the required 20-foot building setback from the tract. The rear building elevations facing SW 40<sup>th</sup> Street should maintain the architectural design of the front building façade to avoid blank walls per CMC 17.09.030.D.6.c.

**FINDINGS:** The proposed lot sizes and dimensions conform to the density transfer provisions of the R-7.5 zone for single-family residential lots. Building envelopes and setbacks should be shown on the final plat. Lots 1-4 will need to comply with the development standards for double frontage lots in CMC 17.19.030.D.6(a-d).

**6. The subdivision complies with the relevant requirements of the Camas land development and zoning codes, and all other relevant local regulations;**

**CMC Section 17.19.030.A Environmental Regulations:**

Relates to the preservation of significant trees and states, *“In addition to meeting the requirement of CMC Chapter 18.31, Tree Regulations, every reasonable effort shall be made to preserve existing significant trees and vegetation, and integrate them into the land use design.”* CMC 18.31.080.B further states, *“To the extent practical, existing healthy significant trees shall be retained. Preservation of groups of significant trees, rather than individual trees shall be preferred.”* The applicant’s narrative states few scattered trees are located on the property but not significant trees as defined by CMC 18.31.080. However, the applicant should submit an arborist report and tree survey for City review and approval prior to engineering plan approval.

**CMC Section 15.50.090 Clearing and Grading Standards:**

CMC 15.50.090.A requires clearing and grading activities be conducted as to minimize potential adverse impacts to the vegetation, drainage and other natural features of the land. Clearing and grading should be conducted in a manner to preserve and enhance the city of Camas aesthetic character to include the preservation of unique landforms and natural features per CMC 15.50.090.E. Further, CMC 15.50.100.B requires the minimization of clearing and grading on slopes greater than 15%. Residential land development projects with steep slopes often include retaining walls for flatter lots. The proposed subdivision includes several walls up to 10-feet in height for lot design. To minimize clearing and grading and to further highlight the existing aesthetic landscape character of Camas, a revised clearing and grading plan should be submitted in compliance with CMC 18.17.060 *Retaining walls* prior to final engineering plan approval.

**FINDING:** As stated in the responses to criteria in this staff report and as conditioned herein, this proposal can or will meet all relevant codes, regulations, ordinances and other requirements as identified herein.

**7. Appropriate provisions are made to address all impacts identified by the transportation impact study;**

The applicant was notified by staff at the pre-application meeting that a Traffic Impact Study (TIS) would be required for this project. The applicant’s traffic engineer, Hann Lee & Associates, submitted a TIS with the application materials dated March 16, 2018.

The TIS indicated that adequate site distance was available at the site access points as long as any vegetation within the sight distance triangles are properly maintained after construction and no

obstructions are placed within the sight distance triangles that could impede a driver's vision. Additionally, all off site intersections within the study area were evaluated for, and met the Level of Service (LOS) standards in the 2013 "Without Project" and the 2023 "With Project" conditions. The study concluded that the area roadways will have adequate capacity for the proposed traffic that this development will generate.

Turn-lane warrants were not conducted at the project access intersection off SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue, as a left-turn lane into the project site will be designed prior to final engineering approval and constructed with this development.

Staff finds that there are no impacts needing mitigation associated with this developments traffic impacts to the area roadways based on the applicant's TIS.

See detailed comments under the approval criteria number 3 above, within this Section.

**8. Appropriate provisions for maintenance of commonly owned private facilities have been made;**

A Homeowner's Association will be required for this development including Conditions, Covenants, and Restrictions (CC&R's) to ensure there are adequate and appropriate measures in place for the perpetual maintenance of trails, fencing, landscaping, parking stalls, private roads and the stormwater detention/treatment systems.

**FINDING:** Staff find the applicant be required to place a note on the face of the plat that identifies the specific ownership and maintenance responsibilities for all tracts. The applicant should also submit to the City for review and approval a copy of the CC&R's.

**9. Appropriate provisions in accordance with RCW 58.17.110, are made for (a) the public health, safety, and general welfare, and (b)The public use and interest will be served by the platting of such subdivision and dedication;**

The applicant is proposing privately owned and maintained tracts for a public trail, landscaping, a stormwater facility and private roads. Furthermore, the applicant is providing adequate and appropriate utilities for stormwater, water, and sanitary sewer that will be dedicated to the public. The applicant will also provide sidewalks with the proposed street construction for adequate pedestrian mobility.

**FINDINGS:** As discussed throughout this report, staff finds that the subdivision can be conditioned to provide the appropriate provisions for public health, safety, general welfare, and assure safe walking conditions for pedestrians.

**10. The application and plans shall be consistent with the applicable regulations of the adopted comprehensive plans, shoreline master plan, state and local environmental acts and ordinances in accordance with RCW36.70B.030.**

**FINDINGS:** Staff concurs that the proposed subdivision can or will meet the requirements of RCW 58.17 and other applicable state and local laws that are in at the time of final platting. The final plat will be processed in accordance with the requirements of CMC 17.21.060.

## **PUBLIC COMMENTS**

As of the writing of this staff report, staff has not received written public comments.

## **CONCLUSION**

Based on the above findings and discussion provided in this staff report, staff concludes that Valley View Estates Subdivision (SUB18-02) should be approved, because it does comply with the applicable standards if all of the conditions of approval are met.

## RECOMMENDATION

Staff recommends APPROVAL of the preliminary plat of Valley View Estates Subdivision (SUB18-02) subject to the following conditions of approval *in addition to* the conditions of the SEPA (SEPA18-15) permit:

## CONDITIONS OF APPROVAL

### Standard Conditions:

1. All construction plans will be prepared in accordance with City of Camas standards. The plans will be prepared by a licensed civil engineer in Washington State and submitted to the City for review and approval.
2. A 3% construction plan review and inspection fee shall be required for this development. The fee will be based on an engineer's estimate or construction bid. The specific estimate will be submitted to the City's engineering department for review and approval. The fee will be paid prior to the construction plans being signed and released to the applicant. Under no circumstances will the applicant be allowed to begin construction prior to approval of the construction plans.
3. Existing water wells, septic tanks and septic drain fields shall be properly abandoned in accordance with State and County guidelines prior to final plat approval.
4. Any entrance structures or signs proposed or required for this project will be reviewed and approved by the City. All designs will be in accordance with applicable City codes. The maintenance of the entrance structure will be the responsibility of the homeowners.
5. The applicant will be responsible for ensuring that private utilities; underground power, telephone, gas, CATV, street lights, and associated appurtenances are installed.
6. A 6-foot private utility easement (PUE) shall be located outside of the right-of-way on public streets and outside of the tracts on private streets.
7. A draft street lighting plan shall be submitted for review prior to final plan submittal to Clark Public Utility.
8. The applicant will be required to purchase all permanent traffic control signs, street name signs, street lighting and traffic control markings and barriers for the improved subdivision.
9. A homeowner's association (HOA) will be required and a copy of the CC&R's for the development will need to be submitted to the City for review and approval. Specifically, the applicant will need to make provisions in the CC&R's for ownership and maintenance of the storm drainage systems, fencing, walls, landscaping, irrigation, private roads, and tracts or easements outside of the City's right-of-way if applicable. Further, all necessary easements and dedications should be noted on the final plat.
10. Final plat and final as-built construction drawing submittals shall meet the requirements of the CMC 17.11.060, CMC 17.01.050 and the Camas Design Standards Manual for engineering as-built submittals.
11. The applicant shall remove all temporary erosion prevention and sediment control measures from the site at the end of the two-year warranty period, unless otherwise directed by the Public Works Director.
12. Street names shall be reviewed and approved by the Building Department prior to final plat approval.

13. Building permits shall not be issued until this subdivision has been granted Final Acceptance and the final plat is recorded and approved by the Planning, Engineering, Building and Fire Departments.

**Special Conditions:**

14. The SEPA MDNS mitigation measures shall be complied with (SEPA18-15).
15. The applicant shall comply with the geotechnical report recommendations to minimize any potential hazards associated with construction.
16. Accessory dwelling units shall not be precluded from CC&R's.
17. On corner lots, the side façade elevation facing the street shall provide architectural variation similar with the front building façade. Additional landscaping shall be provided along the street side façade but shall not impede necessary vision clearance requirements.
18. The T-24 public access trail shall be generally located within Tract C as shown on the preliminary plat and installed in a manner to avoid the removal of existing healthy trees.
19. The applicant shall provide the following trail features:
  - A 10-foot wide trail with landscaping along both sides of the trail
  - Directional signage to the Breckenridge trail and a bench located near the intersection of NW Goodwin Street
20. The trail shall be constructed prior to final plat approval and owned and maintained by the City.
21. Prior to engineering plan approval, a sight distance analysis shall be provided at the SE 40th Street / NW 18th Avenue access.
22. The applicant shall install a left-turn lane from NW 18<sup>th</sup> Avenue into the development site per the TIA.
23. The applicant shall upsize the proposed 8-inch waterline to a 12-inch waterline from Columbia Palisades north to the 12-inch waterline located in SE 40th Street / NW 18th Avenue.
24. The applicant shall connect the proposed Valley View water system to the existing Columbia Palisades 12-inch waterline and work with the City's Utility Manager to evaluate water pressure and the potential need for a pressure reducing station.
25. The applicant shall provide adequate access and utility easements to the City over the private street tracts at the time of final platting for the inspection, maintenance and operation of said public water lines.
26. The applicant shall provide acceptable back flow device(s) (BFD) and yearly backflow testing for any private HOA irrigation service(s) proposed. Prior to occupancy of each home with an irrigation system, the builder shall submit acceptable BFD testing for each irrigation meter installed and provide said testing results to the city.
27. Prior to engineering plan approval, the storm facilities located on Tract E and Tract F shall meet the requirements of the Camas Stormwater Design Standards Manual, Chapter 4.05 Side Slopes and Setbacks.
28. The applicant shall provide reasonable accessibility for maintenance activities of the stormwater facilities.
29. The applicant shall provide documentation demonstrating compliance with Ecology's SWMMWW Appendix 1-D: Guidelines for Wetlands When Managing Stormwater criteria for any discharge of stormwater into the off-site wetlands.
30. Prior to engineering plan approval, the applicant shall submit a final stormwater report (TIS) to the City for review and approval.

31. Stormwater facilities shall be owned and maintained by the HOA, with a right-of-entry granted to the City of Camas for inspections.
32. Prior to final engineering approval, the applicant shall perform a sewer basin analysis to quantify the existing and proposed sewer flows that will be conveyed to the existing pump station.
33. The applicant shall conduct a capacity analysis of the existing pump station that evaluates the existing flows from Grand Ridge, Breckenridge, and future Valley View flows. The analysis shall include but not be limited to evaluation of pump sizes, pumping rates, and condition of existing structures, etc.
34. The applicant shall be responsible for appropriate mitigation of any identified and necessary pump station or system upgrades to serve the proposed development.
35. The individual lot owners shall be responsible for the cost and installation of the individual STEF systems at the time of home construction. A right-of-entry will also be granted to the City for the maintenance and repair of said STEF tanks.
36. A restricted access is required for Lots 1 and 36 to ensure that the driveway locations for these two lots meet or exceed the minimum 110-foot access setback requirement from a collector road.
37. The applicant shall provide adequate improvements and necessary adjustments for the existing multi-use T-24 trail alongside SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue to include:
  - a 10-ft. minimum path width from the existing landing on the northeast corner of SE 201st Avenue east to the eastern boundary of the applicant's site.
  - curb ramps at SE 40th Street / NW 18th Avenue and the site entrance that align both vertically and horizontally with the shared use path along SE 40th Street / NW 18th Avenue and shall meet Public Right-of-Way Accessibility Guidelines (PROWAG).
38. Prior to engineering plan approval, the applicant shall provide a Geotechnical report with an analysis to determine if the existing street section meets the half-street improvement requirements of the Camas Design Standards Manual.
39. Automatic fire sprinklers installed per NFPA 13D or 13R shall be required in all new residential structures.
40. Provisions for parking enforcement acceptable to the Fire Marshal shall be included in the CC&R's at the time of final platting.
41. Prior to the Building Department issuing a Certificate of Occupancy, street trees shall be located within the planter strip as approved on the final plat. Trees shall be a minimum of two-inch diameter at breast height.
42. Required trees shall be maintained in good health, and shall be promptly replaced (within six months) if damaged or in poor health, and a note to this effect shall be on the final plat document.
43. Prior to final engineering plan approval, the applicant shall submit a landscape plan for City review and approval that details the location, plant species, planting, irrigation and fencing notes and associated details for all required landscaping including but not limited to the stormwater facilities located on Tract E and F.
44. All landscaping shall be installed or bonded for prior to final plat acceptance.
45. Prior to final engineering approval, the applicant shall show proposed driveway locations for each lot to ensure that street trees are not impacted.
46. Off-street parking lot areas shall be landscaped at all perimeters and provide a minimum 5-foot width of planting space.

47. The applicant shall provide private easements for storm and, sewer and water lines. These easements shall be shown on the construction drawings and the final plat for recording.
48. The applicant shall grant an access and utility easement to the City of Camas for access, inspection and maintenance of the water and S.T.E.F. sanitary sewer systems.
49. Prior to final plat approval, the applicant shall accomplish one of the following: 1) add a note to the final plat that the developer will own and maintain Tract H, 2) quit claim deed Tract H to the property owners of tax lots 58 and 47 or 3) submit to the city for review and approval a boundary line adjustment application between Tract H and tax lots 58 and 47.
50. All building envelopes and setbacks shall be shown on the final plat.
51. Lots 1-4 shall comply with the development standards for double frontage lots in CMC 17.19.030.D.6(a-d).
52. Prior to engineering plan approval, the applicant shall submit the arborist report and tree survey for City review and approval.
53. Prior to engineering plan approval, a revised clearing and grading plan shall be submitted in compliance with CMC 18.17.060 *Retaining walls*.

#### **Proposed Plat Notes**

1. A homeowner's association (H.O.A) will be required for this development. Copies of the CC&R's shall be submitted and on file with the City of Camas.
2. The homeowner's association is responsible for maintaining all private roads and associated infrastructure in this subdivision, including but not limited to the pavement, curbs, sidewalks, landscaping, street lights and storm drainage utilities.
3. All costs associated with the installation of the step systems for individual lots will be the responsibility of said individual lot owners.
4. An access and utility maintenance easement is provided to the City over the private street tracts for the inspection, maintenance and operation of said public water lines.
5. A right of entry is hereby granted to the City of Camas for the repair and maintenance of the individual S.T.E.F systems located on the lots within the plat.
6. The following setbacks shall apply: Front yard 20-feet, Rear yard 25-feet, Side yard 5-feet, Corner rear yard 5-feet, Side yard flanking a street 20-feet.
7. No further short platting or subdividing will be permitted once the final plat has been recorded.
8. A final occupancy permit will not be issued by the Building Department until all subdivision improvements are completed and accepted by the City.
9. The lots in this subdivision are subject to traffic impact fees, school impact fees, and park/open space impact fees. Each new dwelling unit will be subject to the payment of appropriate impact fees at the time of building permit issuance or as otherwise provided by the city.
10. Prior to the Building Department issuing a Certificate of Occupancy, each lot shall install a minimum of one 2" caliper tree to be located in the planter strip as specified on the plat. Specified trees shall be maintained in good health, and damaged or dying trees shall be promptly replaced (within six months) by the homeowner.
11. Automatic fire sprinkler systems designed and installed in accordance with NFPA 13D are required in all structures.
12. Illegally parked vehicles may be subject to towing or other private parking enforcement measures in accordance with the provisions outlined in the HOA documents.

13. Should archaeological materials (e.g. cones, shell, stone tools, beads, ceramics, old bottles, hearth, etc.) be observed during project activities, all work in the immediate vicinity should stop and the State Department of Archaeology and Historic Preservation (360-586-3065), the City planning office, and the affected Tribe(s) should be contacted immediately. If any human remains are observed, all work should cease and the immediate area secured. Local law enforcement, the county medical examiner (360-397-8405), State Physical Anthropologist, Department of Archaeology and Historic Preservation (360-586-3534), the City planning office, and the affected Tribe(s) should be contacted immediately. Compliance with all applicable laws pertaining to archaeological resources (RCW 27.53, 27.44 and WAC 25-48) and human remains (RCW 68.50) is required. Failure to comply with this requirement could constitute a Class C Felony.
14. Prior to occupancy for each home with an irrigation system, the builder shall submit acceptable back flow device (BFD) testing for each irrigation meter installed and provide said testing results to the City.
15. A restricted access is required for Lots 1 and 36 to ensure that the driveway locations meet or exceed the minimum 110-foot access setback requirement from SE 40<sup>th</sup> Street / NW 18<sup>th</sup> Avenue.
16. Tract "A" is a landscape area to be owned and maintained by the homeowner's association.
17. Tract "C" is a public access trail to be owned and maintained by the City of Camas.
18. Tracts "B", "D" and "G" are hereby conveyed to the homeowner's association (HOA) upon the recording of this final plat for pedestrian and vehicle access and utilities. Parking shall not be allowed in the tracts. The HOA shall be responsible for the maintenance of the tract and the access improvements therein.
19. Tract "E" is a stormwater area to be owned and maintained by the homeowner's association (HOA). An easement for access and inspection shall be granted to the City of Camas with this plat.
20. Tract "F" is a parking area and stormwater area to be owned and maintained by the homeowner's association (HOA). An easement for access and inspection to the stormwater facility shall be granted to the City of Camas with this plat.
21. Tract "I" is a monument sign and landscape area to owned and maintained by the homeowner's association.



Valley View Estates Subdivision  
Public Hearing October 18th, 2018

Will storm water run off from Valley View Estates be addressed to alleviate potential impact to adjacent property to the west tax lot 12642-150

What existing tree's if any will be removed from the proposed Valley View Estates subdivision

Fir Tree on proposed T 24 along Tax Lot 126042-150 is dead, will it be removed prior to any weather that could potentially cause property damage. (Both tree's along the Failed septic system of the recently demolished home have died)

Requesting the existing Common Snowball Viburnum tree located on the fence line of Tax lot #12642-150 not to be removed and remain part of the landscape.

Will a fence be installed on both sides of the walk path/public access T 24 at tax Lots #126042-152 and 126042-150

Thank you,  
Don & Kris Good  
#126042-150

